



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM180700689902
Page: 1 of 16

TEST REPORT

Application No.: SZEM1807006899CR
Applicant: Gartner Studios, Inc
Address of Applicant: 220 East Myrtle Street, Stillwater, Minnesota 55082, United States.
Manufacturer: Dongguan DBK Energy Technology Co.,Ltd
Address of Manufacturer: No.51 Zhangshen Middle Road, Xuzhen Community, Zhangmutou Town, Dongguan City, Guangdong Province, P.R. China
Factory: Dongguan DBK Energy Technology Co.,Ltd
Address of Factory: No.51 Zhangshen Middle Road, Xuzhen Community, Zhangmutou Town, Dongguan City, Guangdong Province, P.R. China

Equipment Under Test (EUT):

EUT Name: Wireless Power Bank
Model No.: 38544
FCC ID: 2AQ7638544
Trade mark: MOTILE
Standard(s) : 47 CFR Part 18
Date of Receipt: 2018-08-10
Date of Test: 2018-08-16 to 2018-09-03
Date of Issue: 2018-09-06

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-09-06		Original

Authorized for issue by:			
		 _____ Leo Li /Project Engineer	
		 _____ Eric Fu /Reviewer	

2 Test Summary

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at Mains Terminals (150kHz-30MHz)	47 CFR Part 18	FCC OST/MP-5:1986	N/A	Pass
Radiated Emissions (9kHz-30MHz)	47 CFR Part 18	FCC OST/MP-5:1986	N/A	Pass

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 DETAILS OF E.U.T.	5
4.2 DESCRIPTION OF SUPPORT UNITS	5
4.3 MEASUREMENT UNCERTAINTY	6
4.4 TEST LOCATION	7
4.5 TEST FACILITY	7
4.6 DEVIATION FROM STANDARDS	7
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	7
5 EQUIPMENT LIST	8
6 RADIO SPECTRUM MATTER TEST RESULTS	9
6.1 CONDUCTED DISTURBANCE	9
6.1.1 <i>E.U.T. Operation</i>	9
6.1.2 <i>Test Setup Diagram</i>	9
6.1.3 <i>Measurement Procedure and Data</i>	9
6.2 RADIATED EMISSION	12
6.2.1 <i>E.U.T. Operation</i>	13
6.2.2 <i>Test Setup Diagram</i>	13
6.2.3 <i>Measurement Procedure and Data</i>	13
7 PHOTOGRAPHS	16
7.1 TEST SETUP	16
7.2 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	16

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 5V from USB port Input: DC 5V/2A Output: WPC: 5W(DC 5V/1A), 7.5W(DC 5V1.5A), 10W(DC 9V/1.1A) USB Port: USB-A*2 5V/2.1A Capacity: 10000mAh/37Wh
Operation frequency:	100.45-170.74kHz
Antenna type:	Inductive Loop Coil Antenna
Modulation type:	Load modulation
Remark:	This device has been tested in all load modes (5W, 7.5W, 10W) and the device has been tested with mobile phone built-in battery at level 5%, 50% and 90%. Then the worst case 10W load mode and 90% battery level is reported only.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	LeTV	EQ-248CN	16041847014
Load Resistor	SGS	BX7-14	REF. No.SEA3700
Load Resistor	SGS	N/A	REF. No.SEA0600
Micro USB Cable	PHILIPS	SWR2101	REF. No.SEA0700
Dummy Load	E-Charging	DC 5V/1A	N/A

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 2.84\text{dB}$
6	Conducted Spurious emissions	$\pm 0.75\text{dB}$
7	RF Radiated power	$\pm 4.5\text{dB}$ (below 1GHz) $\pm 4.8\text{dB}$ (above 1GHz)
8	Radiated Spurious emission test	$\pm 4.5\text{dB}$ (Below 1GHz) $\pm 4.8\text{dB}$ (Above 1GHz)
9	Temperature test	$\pm 1\text{ }^{\circ}\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1.5\%$
12	Time	$\pm 3\%$

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

Conducted disturbance					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ChangZhou ZhongYu	GB-88	SEM001-06	2017-05-10	2020-05-09
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2018-07-12	2019-07-11
LISN	Rohde & Schwarz	ENV216	SEM007-01	2017-09-27	2018-09-26
LISN	ETS-LINDGREN	3816/2	SEM007-02	2018-04-02	2019-04-01
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2018-04-02	2019-04-01

Radiated emission					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2018-03-31	2021-03-30
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2018-07-12	2019-07-11
EMI Test Receiver (9kHz-3GHz)	Rohde & Schwarz	ESR	SEM004-03	2018-04-02	2019-04-01
Trilog-Broadband Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-01-26	2019-01-25
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2018-04-13	2019-04-12
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2018-04-08	2019-04-07

6 Radio Spectrum Matter Test Results

6.1 Conducted disturbance

Test Requirement 47 CFR Part 18
Test Method: FCC OST/MP-5:1986
Limit:


Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

6.1.1 E.U.T. Operation


Operating Environment:
Temperature: 24.8 °C Humidity: 57.2 % RH Atmospheric Pressure: 1020 mbar
Pretest these modes to find the worst case:
d:Charging_Keep the battery of the EUT in charging mode and discharging via USB-A ports and WPC for load resistor.
e:Charge mode_Keep the battery of the EUT in charging and discharging via WPC for load resistor.
The worst case for final test:
d:Charging_Keep the battery of the EUT in charging mode and discharging via USB-A ports and WPC for load resistor.

6.1.2 Test Setup Diagram



6.1.3 Measurement Procedure and Data

Mode:d; Line:Live Line



Site : Shielding Room


Condition: Line

Job No. : 06899CR

Test mode: d

Freq	Cable	LISN	Read	Limit	Over	Remark
	MHz	dB	dB	dBuV	dBuV	
1	0.36	0.03	9.50	29.72	39.25	48.74 -9.49 Average
2	0.36	0.03	9.50	37.92	47.45	58.74 -11.29 QP
3	0.42	0.04	9.49	29.54	39.07	47.46 -8.39 Average
4	0.42	0.04	9.49	38.01	47.54	57.46 -9.92 QP
5	0.48	0.04	9.49	27.76	37.29	46.27 -8.98 Average
6	0.48	0.04	9.49	36.32	45.85	56.27 -10.42 QP
7	0.54	0.05	9.51	32.53	42.09	46.00 -3.91 Average
8	0.54	0.05	9.51	40.94	50.50	56.00 -5.50 QP
9	0.60	0.06	9.53	28.56	38.15	46.00 -7.85 Average
10	0.60	0.06	9.53	37.62	47.21	56.00 -8.79 QP
11	1.32	0.12	9.51	25.62	35.25	46.00 -10.75 Average
12	1.32	0.12	9.51	37.19	46.82	56.00 -9.18 QP

Mode: d; Line:Neutral Line



Site : Shielding Room

Condition: Neutral

Job No. : 06899CR

Test mode: d

Freq	Cable	LISN	Read	Limit	Over	Remark
	MHz	dB	dB	dBuV	dBuV	
1	0.36	0.03	9.58	29.84	39.45	48.74 -9.29 Average
2	0.36	0.03	9.58	38.08	47.69	58.74 -11.05 QP
3	0.42	0.04	9.59	30.03	39.66	47.46 -7.80 Average
4	0.42	0.04	9.59	38.55	48.18	57.46 -9.28 QP
5	0.48	0.04	9.60	29.08	38.72	46.32 -7.60 Average
6	0.48	0.04	9.60	37.55	47.19	56.32 -9.13 QP
7	0.54	0.05	9.61	32.28	41.94	46.00 -4.06 Average
8	0.54	0.05	9.61	41.09	50.75	56.00 -5.25 QP
9	0.60	0.06	9.62	30.34	40.02	46.00 -5.98 Average
10	0.60	0.06	9.62	38.90	48.58	56.00 -7.42 QP
11	1.38	0.12	9.63	26.11	35.86	46.00 -10.14 Average
12	1.38	0.12	9.63	37.05	46.80	56.00 -9.20 QP

6.2 Radiated emission

Test Requirement: 47 CFR Part 18
Test Method: FCC OST/MP-5:1986
Test Distance: 3m
Frequency Range: 9kHz-30MHz
Limit:

Equipment	Operating frequency	RF Power generated by equipment (watts)	Field strength limit (uV/m)	Distance (meters)
Any type unless otherwise specified	Any ISM frequency	Below 500	25	300
(miscellaneous).		500 or more	$25 \times \text{SQRT}(\text{power}/500)$	300 (1)
	Any non-ISM frequency	Below 500	15	300
		500 or more	$15 \times \text{SQRT}(\text{power}/500)$	300 (1)
Industrial heaters and RF stabilized arc	On or below 5,725 MHz	Any	10	1,600
welders.	Above 5,725 MHz	Any	(2)	(2)
Medical diathermy	Any ISM frequency	Any	25	300
	Any non-ISM frequency	Any	15	300
Ultrasonic	Below 490 kHz	Below 500	$2,400/F(\text{kHz})$	300
		500 or more	$2,400/F(\text{kHz}) \times$	300 (3)
			SQRT(power/500).	
	490 to 1,600 kHz	Any	$24,000/F(\text{kHz})$	30
	Above 1,600 kHz	Any	15	30
Induction cooking ranges	Below 90 kHz	Any	1,500	30 (4)
	On or above 90 kHz	Any	300	30 (4)

(1) Field strength may not exceed 10 $\mu\text{V}/\text{m}$ at 1600 meters. Consumer equipment operating below 1000 MHz is not permitted the increase in field strength otherwise permitted here for power over 500 watts.

(2) Reduced to the greatest extent possible.

(3) Field strength may not exceed 10 $\mu\text{V}/\text{m}$ at 1600 meters. Consumer equipment is not permitted the increase in field strength

(4) otherwise permitted here for over 500 watts.

Induction cooking ranges manufactured prior to February 1, 1980, shall be subject to the field strength limits for miscellaneous ISM equipment.

6.2.1 E.U.T. Operation

Operating Environment:


Temperature: 25 °C Humidity: 51 % RH Atmospheric Pressure: 1020 mbar

Pretest these modes to find the worst case:
a:Discharging mode_Keep the EUT in discharging mode via WPC for load resistors .


d:Charging_Keep the battery of the EUT in charging mode and discharging via USB-A ports and WPC for load resistor.

e:Charge mode_Keep the battery of the EUT in charging and discharging via WPC for load resistor.

The worst case for final test:
e:Charge mode_Keep the battery of the EUT in charging and discharging via WPC for load resistor.

6.2.2 Test Setup Diagram**6.2.3 Measurement Procedure and Data**


Mode e:
9kHz-150kHz



Condition: 3m
Job No. : 06899CR
Test Mode: e

Freq	Cable	Ant	Preamp	Read	Limit	Over		
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	0.05	0.12	12.38	32.31	69.16	49.35	63.52	-14.17
2	0.10	0.05	11.98	32.68	66.43	45.78	63.52	-17.74
3 pp	0.15	0.06	11.71	32.67	80.01	59.11	63.52	-4.41

Mode e:
150kHz-30MHz



Condition: 3m
Job No. : 06899CR
Test Mode: a

Freq	Cable	Ant	Preamp	Read	Limit	Over		
	Loss	Factor	Factor	Level			Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	0.15	0.07	11.70	32.67	80.47	59.57	63.52	-3.95
2	0.44	0.11	11.75	32.66	68.49	47.69	63.52	-15.83
3	1.93	0.33	12.09	32.65	48.88	28.65	63.52	-34.87

Remark:

1 This product belongs to any non-ISM frequency equipment, the field strength limit is 15uV/m at 300 meter
2 Limit: $20\log(15\mu\text{V}/\text{m})+20\log(300/3)=23.52+40=63.52\text{dBuV/m}$ at 3 meter

7 Photographs

7.1 Test Setup

Refer to setup photos.

7.2 EUT Constructional Details (EUT Photos)

Refer to external and internal photos.

- End of the Report -