



FCC RF EXPOSURE REPORT

Applicant	:	Globe Electric Company Inc.
Address of Applicant	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8
Manufacturer	:	Satellite Electronic(Zhong shan)Ltd.
Address of Manufacturer	:	No.8, Chuang Ye Road, Torch Development Zone, Zhongshan, Guangdong, China.
Equipment under Test	:	304 Remote Control
Model No.	:	GE37062TX
FCC ID	:	2AQUQGE37623TX
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE24041012-2E01
Issue Date	:	2024/04/30
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd.
Address of Laboratory	:	Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

Test report declares.....	3
1. General Information	5
1.1. Description of equipment	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation for FCC	6

Test Report Declare

Applicant	:	Globe Electric Company Inc.
Address of Applicant	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8
Equipment under Test	:	304 Remote Control
Model No.	:	GE37062TX
Manufacturer	:	Satellite Electronic(Zhong shan)Ltd.
Address of Manufacturer	:	No.8, Chuang Ye Road, Torch Development Zone, Zhongshan, Guangdong, China.

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No.:	DDT-RE24041012-2E01		
Date of Receipt:	2024/04/11	Date of Test:	2024/04/11 ~ 2024/04/29

Prepared By:



Johnson Huang/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/04/30	

1. General Information

1.1. Description of equipment

EUT Name	:	304 Remote Control
Model Number	:	GE37062TX
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	DC 3V by lithium battery
Operation Frequency	:	304.25 MHz
Modulation	:	ASK
Antenna Type	:	PCB

1.2. Assess laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No.17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Estimation Result

Worse case is as below: [304.25 MHz, -24.41 dBm, (0.0036 mW) output power]

PK Output Power=70.79dB_{UV}/m@3m-95.2=-24.41dBm

Please refer to the test report "DDT-RE24041012-2E01"

$(0.0036/5) \cdot [\sqrt{0.30425(\text{GHz})}] = 0.0004 < 3.0 \text{ for 1-g SAR}$

Then SAR evaluation is not required.

END OF REPORT