

RF Exposure Evaluation**Limit**

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Table 1-Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

Evaluation Method

$$\text{Transmission formula: } P_d = (\text{Pout} * G) / (4 * \pi * R^2)$$

Where

Pd = power density in mW/cm², Pout = output power to antenna in mW, G = gain of antenna in linear scale; $\pi = 3.1416$, R = distance between observation point and center of the radiator in cm

Conducted Power Results & Manufacturing tolerance

Specification	Operating Mode	Conducted Peak Output Power (dBm)	Target (dBm)	Tolerance \pm (dB)
2.4GWIFI	802.11b	16.30	15.5	1
	802.11g	16.25	15.5	1
	802.11n(HT20)	16.29	15.5	1
	802.11n(HT40)	15.97	15	1
BLE	GFSK	6.32	5.5	1

Evaluation Results

Spec.	Operating Mode	Antenna Distance (cm)	Conducted Output Power		Gain of antenna in linear scale	Power Density (mW /cm ²)	Limit (mW /cm ²)	Result
			dBm	mW				
2.4GWIFI	802.11b	20	16.5	44.67	1.00	0.009	1	PASS
	802.11g	20	16.5	44.67	1.00	0.009	1	PASS
	802.11n(HT20)	20	16.5	44.67	1.00	0.009	1	PASS
	802.11n(HT40)	20	16	39.81	1.00	0.008	1	PASS
BLE	GFSK	20	6.5	4.47	1.00	0.001	1	PASS

Remark:

1. Output power including tune up tolerance;
2. The maximum 2.4G antenna gain is 0dBi
3. The exposure safety distance is 20cm.

Simulation Transmission

EUT can only work in 2.4GWIFI+BLE mode

The formula of calculated the Simulation Transmission MPE is:

CPD1/LPD1+CPD2/LPD2+.....etc.<1

CPD=Calculation Maximum Power Denisty

Mode	Calculate	Limit	Result
2.4GWIFI+BLE mode	0.010	1	Pass

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE compliance per KDB 447498 v06.