

RF Exposure Evaluation**Limit**

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Table 1-Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

Evaluation Method

$$\text{Transmission formula: } P_d = (P_{\text{out}} * G) / (4 * \pi * R^2)$$

Where

Pd = power density in mW/cm², Pout = output power to antenna in mW, G = gain of antenna in linear scale;

$\pi = 3.1416$, R = distance between observation point and center of the radiator in cm

Conducted Power Results & Manufacturing tolerance

Specification	Operating Mode	Conducted Peak Output Power (dBm)	Target (dBm)	Tolerance \pm (dB)
2.4GWIFI	802.11b	14.14	13.5	1
	802.11g	17.00	16.5	1
	802.11n(HT20)	15.38	14.5	1
	802.11n(HT40)	15.13	14.5	1
BLE	GFSK	7.16	6.5	1

Evaluation Results

Spec.	Operating Mode	Antenna Distance (cm)	Conducted Output Power		Gain of antenna in linear scale	Power Density (mW /cm ²)	Limit (mW /cm ²)	Result
			dBm	mW				
2.4GWIFI	802.11b	20	14.5	28.18	0.79	0.004	1	PASS
	802.11g	20	17.5	56.23	0.79	0.009	1	PASS
	802.11n(HT20)	20	15.5	35.48	0.79	0.006	1	PASS
	802.11n(HT40)	20	15.5	35.48	0.79	0.006	1	PASS
BLE	GFSK	20	7.5	5.62	0.79	0.001	1	PASS

Remark:

1. *Output power including tune up tolerance;*
2. *The maximum 2.4G antenna gain is -1dBi*
3. *The exposure safety distance is 20cm.*

Simulation Transmission

EUT can only work in 2.4GWIFI+Ble mode

The formula of calculated the Simulation Transmission MPE is:

CPD1/LPD1+CPD2/LPD2+.....etc.<1

CPD=Calculation Maximum Power Denisty

Mode	Calculate	Limit	Result
2.4GWIFI+Ble mode	0.010	1	Pass

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE compliance per KDB 447498 v06.