



FCC TEST REPORT

FCC ID: 2AQURZW38M-V3

Product Name	:	SMART PLUG
Model Name	:	ZEN04 800LR, ZW38M
Brand Name	:	Minoston
Report No.	:	PTC23041905705E-FC01
Prepared for		
NIE-TECH Co., Ltd		
Jinlian commercial center 9001, Jinxiu road No.2, Changan Town,Dongguan City, GuangDongProv., CHINA		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China		



1 TEST RESULT CERTIFICATION

Applicant's name : NIE-TECH Co., Ltd
Address : Jinlian commercial center 9001, Jinxiu road No.2, Changan Town, Dongguan City, Guangdong Prov., CHINA
Manufacture's name : NIE-TECH Co., Ltd
Address : Jinlian commercial center 9001, Jinxiu road No.2, Changan Town, Dongguan City, Guangdong Prov., CHINA
Product name : SMART PLUG
Model name : ZEN04 800LR, ZW38M
Standards : FCC Part15 Subpart C, Paragraph 15.249
Test procedure : ANSI C63.10: 2013
Test Date : May. 15, 2023 to Jun. 14, 2023
Date of Issue : Jun. 14, 2023
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Simon Pu".

Simon Pu/ Engineer

Technical Manager:

A handwritten signature in black ink that appears to read "Ronnie Liu".

Ronnie Liu/ Manager



Contents

	Page
1 TEST RESULT CERTIFICATION	2
2 TEST SUMMARY	5
3 TEST FACILITY	6
4 GENERAL INFORMATION	7
4.1 GENERAL DESCRIPTION OF E.U.T.	7
4.2 TEST MODE	8
4.3 LIST OF CHANNELS	9
5 EQUIPMENT DURING TEST	10
5.1 EQUIPMENTS LIST	10
5.2 MEASUREMENT UNCERTAINTY	12
5.3 DESCRIPTION OF SUPPORT UNITS	13
6 TEST STANDARD AND LIMIT	14
6.1. TEST SETUP	14
6.2. TEST PROCEDURE	14
6.3. TEST DATA	15
7 . RADIATED EMISSION AND BAND EDGE	17
7.1. TEST STANDARD AND LIMIT	17
7.2. TEST SETUP	18
7.3. TEST PROCEDURE	19
7.4. TEST DATA	20
8. 20DB BANDWIDTH TEST	27
8.1. TEST STANDARD AND LIMIT	27
8.2. TEST SETUP	27
8.3. TEST PROCEDURE	27
8.4. TEST DATA	27
9. ANTENNA REQUIREMENT	29
9.1. TEST STANDARD AND REQUIREMENT	29
9.2. ANTENNA CONNECTED CONSTRUCTION	29
10 TEST PHOTO	30



Report No.: PTC23041905705E-FC01

11	EUT PHOTO	32
----	-----------------	----



2 Test Summary

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.249	Radiated Emission	PASS
15.215(c)	20dB Bandwidth	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		



Report No.: PTC23041905705E-FC01

3 TEST FACILITY

Precise Testing & Certification Co., Ltd.

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A

FCC Designation Number: CN1219



4 General Information

4.1 General Description of E.U.T.

Product Name	:	SMART PLUG
Model Name	:	ZEN04 800LR
Additional model	:	ZW38M
Model difference	:	Only the model names are different
Operating frequency	:	908.40MHz,908.42 MHz,916.00MHz
Numbers of Channels	:	3 Channels
Antenna Type	:	PCB antenna
Antenna Gain	:	-6.16 dBi
Type of Modulation	:	908.40MHz 908.42MHz 916.00MHz
Power supply	:	AC 120V/60Hz 15A
Hardware Version	:	1.0
Software Version	:	1.0



4.2 Test Mode

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Channel	Frequency (MHz)	Modulation
Mode 1	CH0	908.40	2FSK
Mode 2	CH1	908.42	2FSK
Mode 3	CH3	916.00	2GFSK

For Conducted Emission	
Final Test Mode	Description
Mode 1	CH0
Mode 2	CH1
Mode 3	CH2

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH0
Mode 2	CH1
Mode 3	CH2

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.



4.3 List of Channels

Channel	Frequency (MHz)	Modulation
CH0	908.40	2FSK
CH1	908.42	2FSK
CH2	916.00	2GFSK



5 Equipment During Test

5.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
MXG Signal Analyzer	Agilent	N9020A	SER MY5111038	10Hz-30GHz	Aug. 21, 2023
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Aug. 21, 2023
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Aug. 21, 2023
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Aug. 21, 2023

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Aug. 21, 2023
Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	Aug. 21, 2023
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Aug. 21, 2023
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	1MHz-1GHz	Aug. 21, 2023
Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	Aug. 21, 2023
Spectrum Analyzer	Agilent	E4407B	MY45109572	9KHz-40GHz	Aug. 21, 2023
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	1GHz-18GHz	Aug. 21, 2023
Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	1GHz-26.5GHz	Aug. 21, 2023
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-181	14GHz-40GHz	Aug. 21, 2023
Amplifier	SCHWARZBECK	BBV 9721	9721-205	18GHz-40GHz	Aug. 21, 2023
Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	Aug. 21, 2023
RF Cable	R&S	R204	R21X	1GHz-40GHz	Aug. 21, 2023



Report No.: PTC23041905705E-FC01

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Aug. 19, 2023
Artificial Mains Network	Rohde&Schwarz	ENV216	102453	9KHz-300MHz	Aug. 19, 2023
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz-300MHz	Aug. 19, 2023



5.2 Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
	:	Ur = 3.8 dB (Vertical)
Bandwidth	:	$\pm 1.5 \times 10^{-6}$
Conduction Uncertainty	:	Uc = 3.4 dB



Report No.: PTC23041905705E-FC01

5.3 Description of Support Units


Equipment	Model No.	Series No.
Incandescent lamp	N/A	N/A

6 Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

6.1. Test Setup



6.2. Test Procedure


The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test iSurpass Smart Gateway (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

6.3. Test Data

Test Mode: CH1
Power Source: AC 120V/60Hz
Polarization: LINE
Temp.(°C)/Hum.(%RH): 24.5°C/52%RH




Final Data List

NO.	Freq. [MHz]	QP Value	QP Limit	QP Margin	AV Value	AV Limit	AV Margin	Verdict
1	0.173	53.07	64.84	11.77	38.46	54.84	16.38	PASS
2	0.209	52.93	63.26	10.33	36.50	53.26	16.76	PASS
3	0.236	52.49	62.25	9.76	37.12	52.25	15.13	PASS
4	0.258	51.04	61.50	10.46	35.18	51.50	16.32	PASS
5	0.317	49.01	59.80	10.79	33.96	49.80	15.84	PASS
6	0.443	46.50	57.01	10.51	29.82	47.01	17.19	PASS



Test Mode: CH1
Power Source: AC 120V/60Hz
Polarization: NEUTRAL
Temp.(°C)/Hum.(%RH): 24.5°C/52%RH



Final Data List

NO.	Freq. [MHz]	QP Value	QP Limit	QP Margin	AV Value	AV Limit	AV Margin	Verdict
1	0.168	53.78	65.06	11.28	39.42	55.06	15.64	PASS
2	0.195	53.73	63.82	10.09	36.45	53.82	17.37	PASS
3	0.240	52.55	62.10	9.55	37.75	52.10	14.35	PASS
4	0.263	51.03	61.35	10.32	37.11	51.35	14.24	PASS
5	0.303	48.78	60.16	11.38	34.54	50.16	15.62	PASS
6	0.362	48.21	58.69	10.48	34.35	48.69	14.34	PASS

Note:1.All test mode have been tested. Only the worst case have been recorded in the report.

2.QP Margin[dB]= QP Limit[dBμV]- QP Value[dBμV], AV Margin[dB]= AV Limit[dBμV]- AV Value[dBμV].

7 . Radiated Emission and Band Edge

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz~1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz~30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Test Standard	FCC Part15 C Section 15.249					
Test Limit	Frequency (MHz)	Field Strength of fundamental ((millivolts /meter)	Field Strength of Harmonics (microvolts/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	902~928	50	-	94.0	Quasi-peak	3
		-	-	-	-	-

Remark:

(1) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

7.2. Test Setup

Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1 GHz





7.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.



7.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.


The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all the modes, and found the CH 01 channel which is the worst case, only the worst case is recorded in the report



Test Results (30~1000MHz)

Test Mode: CH1
 Power Source: AC 120V/60Hz
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 24.5°C/52%RH



Final Data List[QP]

NO.	Freq. [MHz]	QP Reading [dBμV/ m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	32.18	35.21	-18.22	16.99	40.00	23.01	Horizontal	PASS
2	60.07	28.49	-17.81	10.68	40.00	29.32	Horizontal	PASS
3	171.86	27.45	-16.44	11.01	43.50	32.49	Horizontal	PASS
4	196.84	42.17	-18.60	23.57	43.50	19.93	Horizontal	PASS
5	549.19	26.29	-9.40	16.89	46.00	29.11	Horizontal	PASS
6	941.80	26.12	-2.36	23.76	46.00	22.24	Horizontal	PASS


Test Results (30~1000MHz)

Test Mode: CH1

Power Source: AC 120V/60Hz

Polarization: Horizontal

Temp.(°C)/Hum.(%RH): 24.5°C/52%RH



Final Data List[QP]

NO.	Freq. [MHz]	QP Reading [dBμV/ m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	32.18	41.42	-18.22	23.20	40.00	16.80	Vertical	PASS
2	54.98	33.67	-17.89	15.78	40.00	24.22	Vertical	PASS
3	159.98	29.73	-15.85	13.88	43.50	29.62	Vertical	PASS
4	199.75	30.45	-18.82	11.63	43.50	31.87	Vertical	PASS
5	555.74	27.96	-9.31	18.65	46.00	27.35	Vertical	PASS
6	983.03	25.88	-1.72	24.16	54.00	29.84	Vertical	PASS

Note:1.All test mode have been tested. Only the worst case have been recorded in the report.
2.QP Margin[dB]= QP Limit[dBμV/m]- QP Value[dBμV/m], QP Value[dBμV/m]= QP Reading[dBμV]+ Factor[dB/m].



Test Frequency 1GHz-10GHz

CH0:

Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Level	Limits	Margin	Det.
(MHz)	Pol.	(dBuV)	(dB)	(dB/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Mode
1816.84	H	47.95	6.58	34.04	34.09	54.48	74	19.52	PK
1816.84	H	32.52	6.58	34.04	34.09	39.05	54	14.95	AV
2725.26	H	39.83	7.73	37.11	34.79	49.88	74	24.12	PK
2725.26	H	35.13	7.73	37.11	34.79	45.18	54	8.82	AV
1816.84	V	41.44	6.58	35.28	34.09	49.21	74	24.79	PK
1816.84	V	24.32	6.58	35.28	34.09	32.09	54	21.91	AV
2725.26	V	39.34	7.73	39.31	34.79	51.59	74	22.41	PK
2725.26	V	22.67	7.73	39.31	34.79	34.92	54	19.08	AV

Fundamental

Frequency	Antenna	Reading	Factor	Results	Limits	Det.
(MHz)	Pol.	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	Mode
908.40	H	87.16	3.01	90.17	94	QP
908.40	V	86.39	3.01	89.40	94	QP

Note: 1. The testing has been conformed to $10 \times 908.40 \text{ MHz} = 9084 \text{ MHz}$.

- All other emissions more than 30dB below the limit.
- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor
Margin=Limit-Emission Level



Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Level	Limits	Margin	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Mode
1816.84	H	46.00	6.58	34.04	34.09	52.53	74	21.47	PK
1816.84	H	30.14	6.58	34.04	34.09	36.67	54	17.33	AV
2725.26	H	42.34	7.73	37.11	34.79	52.39	74	21.61	PK
2725.26	H	33.20	7.73	37.11	34.79	43.25	54	10.75	AV
1816.84	V	41.13	6.58	35.28	34.09	48.90	74	25.10	PK
1816.84	V	25.41	6.58	35.28	34.09	33.18	54	20.82	AV
2725.26	V	38.70	7.73	39.31	34.79	50.95	74	23.05	PK
2725.26	V	24.91	7.73	39.31	34.79	37.16	54	16.84	AV

Fundamental

Frequency	Antenna	Reading	Factor	Results	Limits	Det.
(MHz)	Pol.	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	Mode
908.42	H	86.35	3.01	89.36	94	QP
908.42	V	86.59	3.01	89.6	94	QP

Note: 1. The testing has been conformed to $10 \times 908.42 \text{ MHz} = 9084.2 \text{ MHz}$.

2. All other emissions more than 30dB below the limit.

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Limit-Emission Level



CH2:

Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Level	Limits	Margin	Det.
(MHz)	Pol.	(dBuV)	(dB)	(dB/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Mode
1832.00	H	47.19	6.58	34.04	34.09	53.72	74	20.28	PK
1832.00	H	29.81	6.58	34.04	34.09	36.34	54	17.66	AV
2748.00	H	39.62	7.73	37.11	34.79	49.67	74	24.33	PK
2748.00	H	33.38	7.73	37.11	34.79	43.43	54	10.57	AV
1832.00	V	40.77	6.58	35.28	34.09	48.54	74	25.46	PK
1832.00	V	25.87	6.58	35.28	34.09	33.64	54	20.36	AV
2748.00	V	38.77	7.73	39.31	34.79	51.02	74	22.98	PK
2748.00	V	23.16	7.73	39.31	34.79	35.41	54	18.59	AV

Fundamental

Frequency	Antenna	Reading	Factor	Results	Limits	Det.
(MHz)	Pol.	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	Mode
916.00	H	87.06	3.01	90.07	94	QP
916.00	V	86.71	3.01	89.72	94	QP

Note: 1. The testing has been conformed to 10*916.00MHz=9160MHz.

2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor
Margin=Limit-Emission Level

**Spurious Emission in Restricted Band :**

Test Mode: Channel 908.4MHz							
Frequency (MHz)	Read Level (dBuV)	Corr. Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Detector
902.00	38.49	-2.97	35.52	46	-10.48	H	Peak
902.00	39.73	-2.97	36.76	46	-9.24	V	Peak

Test Mode: Channel 916MHz							
Frequency (MHz)	Read Level (dBuV)	Corr. Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Detector
928.00	38.88	-2.50	36.38	46	-9.62	H	Peak
928.00	36.55	-2.50	34.05	46	-11.95	V	Peak

Note:


1. Correction Factor = Antenna factor + Cable loss - Preamplifier.
2. Level = Read Level + Corr. Factor.
3. Over = Level - Limit.

8. 20dB Bandwidth Test

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.249
---------------	-----------------------------

8.2. Test Setup



8.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
 - RBW in the range of 1% to 5% of the OBW, $VBW \geq 3 \times RBW$,
 - Detector= Average
 - Trace mode= Max hold.
 - Sweep- auto couple.
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.


8.4. Test Data

Test Item	:	20dB Bandwidth	Test Mode	:	Mode 1
Test Voltage	:	AC 120/60Hz	Temperature	:	22.4°C
Test Result	:	PASS	Humidity	:	55%RH



Channel	Frequency (MHz)	20dB Bandwidth(kHz)	Result
CH0	908.40	85.02	PASS
CH1	908.42	66.16	PASS
CH2	916.00	113.4	PASS

Test Graphs:





9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2. Antenna Connected Construction

The antenna is a PCB antenna which permanently attached, and the best case gain of the antenna is -6.16 dBi. It complies with the standard requirement.

10 TEST PHOTO

CONDUCTED EMISSION TEST





RADIATED EMISSION TEST











11 EUT PHOTO


















*****THE END REPORT*****