

RF Exposure Evaluation Report

Product	: Arm-type Fully Automatic Digital Blood Pressure Monitor
Trade mark	: N/A
Model/Type reference	: DBP-62F6L, BM62
Serial Number	: N/A
Report Number	: EED32R81122602
FCC ID	: 2AQVU0070
Date of Issue	: Jul. 30, 2025
Test Standards	: 47 CFR Part 1.1307 47 CFR Part 1.1310 47 CFR Part 2.1091 47 CFR Part 2.1093 KDB 447498 D04 Interim General RF Exposure Guidance v01
Test result	: PASS

Prepared for:

JOYTECH HEALTHCARE CO., LTD.
No.365, Wuzhou Road, 311100 Hangzhou, Zhejiang Province,
PEOPLE'S REPUBLIC OF CHINA.

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Park, Zone 70, Bao'an District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Keven Tan.

Reviewed by:

Frazer. Li

Approved by:

Keven Tan

Date:

Jul. 30, 2025

Report Seal

Aaron Ma

Check No.: 5035040725

1 Contents

	Page
1 CONTENTS	2
2 GENERAL INFORMATION	3
2.1 CLIENT INFORMATION	3
2.2 GENERAL DESCRIPTION OF EUT	3
2.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	3
2.4 TEST LOCATION	4
2.5 DEVIATION FROM STANDARDS	4
2.6 ABNORMALITIES FROM STANDARD CONDITIONS	4
2.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
3 SAR EVALUATION	5
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
3.1.1 <i>Limits</i>	5
3.1.2 <i>Test Procedure</i>	5
3.1.3 <i>EUT RF Exposure Evaluation</i>	6

Report No. : EED32R81122602

Page 3 of 7

2 General Information

2.1 Client Information

Applicant:	JOYTECH HEALTHCARE CO., LTD.
Address of Applicant:	No.365, Wuzhou Road, 311100 Hangzhou, Zhejiang Province, PEOPLE'S REPUBLIC OF CHINA.
Manufacturer:	JOYTECH HEALTHCARE CO., LTD.
Address of Manufacturer:	No.365, Wuzhou Road, 311100 Hangzhou, Zhejiang Province, PEOPLE'S REPUBLIC OF CHINA.

2.2 General Description of EUT

Product Name:	Arm-type Fully Automatic Digital Blood Pressure Monitor
Model No.:	DBP-62F6L, BM62
Test Model No.:	DBP-62F6L
Trade mark:	N/A

2.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz
Modulation Type:	GFSK
Test Power Grade:	Default
Test Software of EUT:	PhyPlusKit.exe
Antenna Type:	PCB antenna
Antenna Gain:	-1.38dBi
Power Supply:	Battery: DC 3.7V
Sample Received Date:	Jul. 07, 2025
Sample tested Date:	Jul. 07, 2025 to Jul. 15, 2025
Remark:	Model No.: DBP-62F6L, BM62 Only the model DBP-62F6L was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being pack and model name.

2.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Hongwei Industrial Park, Zone 70, Bao'an District, Shenzhen, Guangdong, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.1.3 EUT RF Exposure Evaluation**For Stand alone:**

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
2402	0.5	-0.03	-1.38	-2.18	0.6053	2.7877	0.2171	Pass

Note:

- ①EIRP=conducted power+antenna gain;
- ②ERP=EIRP-2.15;
- ③EIRP(dBm) = Field strength of the fundamental signal(dBuV/m@3m) – 95.23;
- ④ERP(mW) = $10^{(ERP\ (dBm)/10)}$;
- ⑤The estimation distance is 0.5cm;
- ⑥The test data please refer to the report of EED32R81122601 and only the worst case data was recorded in the report.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full;

*** End of Report ***