



## FCC 47 CFR PART 15 SUBPART C

### TEST REPORT

For

INTERACTIVE SCREEN ALL IN ONE  
Model: G065EUH

Brand:  GRAND WON

Test Report Number:  
**C180817Z01-RP1**

Issued for

**SHENZHEN GUANGWEN INDUSTRIAL CO.,LTD**

Room No.402, D Building, Jinhao Pioneer Park, No.9 Dafu Industrial Area, Aobei  
Community, Guanlan Street, Longhua New District, Shenzhen City

Issued by:

**COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.**  
No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd.,  
Guan Lan Town, Baoan District, Shenzhen China

TEL: 86-755-28055000

FAX: 86-755-28055221

E-Mail: [service@ccssz.com](mailto:service@ccssz.com)

Issued Date: Aug 17, 2018



Certificate Number: 2861.01

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST, CNAS or any government agencies. The test result of this report relate only to the tested sample identified in this report.



## Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	Aug 17, 2018	Initial Issue	ALL	Anna Liu



## TABLE OF CONTENTS

<b>1. TEST RESULT CERTIFICATION .....</b>	<b>4</b>
<b>2. EUT DESCRIPTION .....</b>	<b>5</b>
<b>3. TEST METHODOLOGY .....</b>	<b>6</b>
3.1 DESCRIPTION OF TEST MODES.....	6
3.2 SETUP CONFIGURATION OF EUT.....	6
3.3 SUPPORT EQUIPMENT.....	6
<b>4. FACILITIES AND ACCREDITATIONS .....</b>	<b>7</b>
4.1 FACILITIES .....	7
4.2 ACCREDITATIONS.....	7
4.3 MEASUREMENT UNCERTAINTY.....	7
<b>5. FCC PART 15.247 REQUIREMENTS .....</b>	<b>8</b>
5.1 RADIATED EMISSIONS.....	8



## 1. TEST RESULT CERTIFICATION

<b>Product</b>	INTERACTIVE SCREEN ALL IN ONE
<b>Model</b>	G065EUH
<b>Brand</b>	 GRAND WON
<b>Tested</b>	Aug 17, 2018
<b>Applicant</b>	<b>SHENZHEN GUANGWEN INDUSTRIAL CO.,LTD</b>
<b>Manufacturer</b>	Room No.402, D Building,Jinhao Pioneer Park, No.9 Dafu Industrial Area,Aobei Community,Guanlan Street,Longhua New District,Shenzhen City


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

### We hereby certify that:

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10:2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.207, 15.209 and 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

**Approved by:**



Eve Wang  
Supervisor of EMC Dept.  
Compliance Certification Services (Shenzhen) Inc.

**Reviewed by:**



Nancy Fu  
Supervisor of Report Dept.  
Compliance Certification Services (Shenzhen) Inc.



## 2. EUT DESCRIPTION

<b>Product</b>	INTERACTIVE SCREEN ALL IN ONE
<b>Model Number</b>	G043EUH、G049EUH、G055EUH、G065EUH、G075EUH、G086EUH、G098EUH、GW-TPC0156EH、GW-TPC0195EH、GW-TPC0215EH、GW-TPC027EH、GW-TPC032EH、GW-TPC043EH、GW-TPC049EH、GW-TPC055EH、GW-TPC065EUH、GW-TPC075EUH、GW-TPC086EUH、GW-TPC098EUH
<b>Brand</b>	 GRAND WON
<b>Model Discrepancy</b>	The difference between the models of the touch-one machine (with display and TV function) of this application is: different model names are only used for market destination area differentiation or customer differentiation, and other dimensions including internal dimensions, internal structure, key components and electrical principles are the same. Does not affect the safety and electromagnetic compatibility of the product.
<b>Identify Number</b>	C180817Z01-RP1
<b>Received Date</b>	Aug 17, 2018
<b>Power Supply</b>	100-240V~ 50/60Hz 2A
<b>Frequency Range</b>	2412 ~ 2462 MHz
<b>Modulation Technique</b>	IEEE 802.11b mode: DSSS(CCK,QPSK, BPSK) IEEE 802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT20 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM)
<b>Number of Channels</b>	IEEE 802.11b mode: 11 Channels IEEE 802.11g mode: 11 Channels IEEE 802.11n HT20 MHz mode: 11 Channels
<b>Antenna Specification</b>	External PiFA antenna with 5.0 dBi gain (Max)
<b>Hardware Version</b>	V1.0
<b>Software Version</b>	V1.0

**Note:** This submittal(s) (test report) is intended for FCC ID: 2AQXD-G065EUH filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.





### 3. TEST METHODOLOGY

#### 3.1 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Use Certification Tool 1.26 to control the EUT for staying in continuous transmitting and receiving mode.

Test Item	Test mode	Worse mode
Radiated Emission	<b>Mode 1: TX</b>	<input checked="" type="checkbox"/>

**Note:**

1. Channel Low (2412MHz) Mid (2437MHz) and High (2462MHz) were chosen for pre-testing for DSSS and print in the report.
2. Radiated band edges were tested with both fixed and hopping mode; the fixed mode was the worse case and recorded in the report.

#### 3.2 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

#### 3.3 SUPPORT EQUIPMENT

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Notebook	TianYi310-14ISK	NA	DoC	Lenovo	NA	NA

**Notes:**

*Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*



## 4. FACILITIES AND ACCREDITATIONS

### 4.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

**No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd.,  
Guan Lan Town, Baoan District, Shenzhen, China**

The sites are constructed in conformance with the requirements of ANSI C63.10:2013, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 4.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

<b>USA</b>	A2LA
<b>China</b>	CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

<b>USA</b>	FCC
<b>Japan</b>	VCCI(C-4815, R-4320, T-2317, G-10624)
<b>Canada</b>	INDUSTRY CANADA

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccssz.com>

### 4.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.



## 5. FCC PART 15.247 REQUIREMENTS

### 5.1 RADIATED EMISSIONS

#### LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

**Note:** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54




## MEASUREMENT EQUIPMENT USED



Radiated Emission Test Site 966(2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	N9010A	MY52221469	02/18/2018	02/19/2019
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/18/2018	02/19/2019
Amplifier	EMEC	EM330	060661	02/17/2018	03/16/2019
High Noise Amplifier	Agilent	8449B	3008A01838	02/20/2018	02/19/2019
Loop Antenna	COM-POWER	AL-130	121044	09/25/2017	09/24/2018
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/20/2018	02/19/2019
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/20/2018	02/19/2019
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/20/2018	02/19/2019
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/20/2018	02/19/2019
Test S/W	FARAD		LZ-RF / CCS-SZ-3A2		

**Remark:** Each piece of equipment is scheduled for calibration once a year.

### Test Configuration

#### Below 30MHz



**Below 1 GHz****Above 1 GHz**



## **MEASURING SETTING**

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/T for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/T for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

## **TEST PROCEDURE**

### **1) Sequence of testing 9 kHz to 30**

#### **MHz Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### **Pre measurement:**

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions



### **Final measurement:**

- Identified emissions during the pre measurement the software maximizes by rotating the turntable position (0°to 360°) and by rotating the elevation axes (0°to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement and the limit will be stored.

## **2) Sequence of testing 30 MHz to 1**

### **GHz Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### **Pre measurement:**

- The turntable rotates from 0°to 315°using 45°steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.



#### **Final measurement:**

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

### **3) Sequence of testing 1 GHz to 18**

#### **GHz Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### **Pre measurement:**

- The turntable rotates from  $0^\circ$  to  $315^\circ$  using  $45^\circ$  steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.



### **Final measurement:**

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement with marked maximum final measurements and the limit will be stored.

### **4) Sequence of testing above 18**

#### **GHz Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

#### **Pre measurement:**

- The antenna is moved spherical over the EUT in different polarisations of the antenna.

#### **Final measurement:**

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.



## TEST RESULTS

### Above 1 GHz

Test Mode: TX / IEEE 802.11b (CH Low)	Tested by: Darry Wu
Ambient temperature: 24°C Relative humidity: 52% RH	Date: Aug 17, 2018

Frequency (MHz)	Reading (dB <sub>u</sub> V)	Correction Factor (dB/m)	Result (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1735	46.20	-3.42	42.78	74	-31.22	V	peak
1974	43.37	-3.11	40.26	74	-33.74	V	peak
4824	47.22	1.31	48.53	74	-25.47	V	peak
7236	41.94	4.15	46.09	74	-27.91	V	peak
1587	46.73	-3.41	43.32	74	-30.68	H	Peak
1953	41.33	-3.12	38.21	74	-35.79	H	Peak
4824	47.56	1.31	48.87	74	-25.13	H	Peak
7236	42.76	4.15	46.91	74	-27.09	H	peak

#### Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 3MHz, Sweep time = auto.
  - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.
5. Frequency (MHz). = Emission frequency in MHz  
Reading (dB<sub>u</sub>V/m) = Uncorrected Analyzer / Receiver Reading  
Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain  
Limit (dB<sub>u</sub>V/m) = Limit stated in standard  
Margin (dB) = Result (dB<sub>u</sub>V/m)- Limit (dB<sub>u</sub>V/m)  
Peak = Peak Reading  
AVG. = Average Reading  
Remark = Mark Peak Reading or Average Reading

**Test Mode: TX / IEEE 802.11b (CH Mid)****Tested by: Darry Wu****Ambient temperature: 24°C Relative humidity: 52% RH****Date: Aug 17, 2018**

Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1241	45.35	-5.91	39.44	74	-34.56	V	peak
2056	40.69	-2.29	38.40	74	-35.60	V	peak
4874	44.96	1.33	46.29	74	-27.71	V	peak
7311	40.12	4.17	44.29	74	-29.71	V	peak
1263	42.94	-5.84	37.10	74	-36.90	H	peak
2195	41.88	-2.07	39.81	74	-34.19	H	peak
4874	44.58	1.33	45.91	74	-28.09	H	peak
7311	41.73	4.17	45.90	74	-28.10	H	peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 3MHz, Sweep time = auto.
  - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.
5. Frequency (MHz).  
Reading (dB $\mu$ V/m) = Emission frequency in MHz  
Correction Factor (dB) = Uncorrected Analyzer / Receiver Reading  
Limit (dB $\mu$ V/m) = Antenna factor + Cable loss – Amplifier gain  
Margin (dB) = Limit stated in standard  
Peak = Result (dB $\mu$ V/m)- Limit (dB $\mu$ V/m)  
AVG. = Peak Reading  
Remark = Average Reading  
= Mark Peak Reading or Average Reading

**Test Mode: TX / IEEE 802.11b (CH High)****Tested by: Darry Wu****Ambient temperature: 24°C Relative humidity: 52% RH****Date: Aug 17, 2018**

Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1481	44.64	-4.85	39.79	74	-34.21	V	peak
2163	43.15	-2.14	41.01	74	-32.99	V	peak
4924	43.10	1.33	44.43	74	-29.57	V	peak
7386	42.83	4.17	47.00	74	-27.00	V	peak
1384	44.17	-5.62	38.55	74	-35.45	H	peak
1783	44.10	-3.49	40.61	74	-33.39	H	peak
4924	45.82	1.38	47.20	74	-26.80	H	peak
7386	43.06	4.25	47.31	74	-26.69	H	peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 3MHz, Sweep time = auto.
  - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.
5. Frequency (MHz). = Emission frequency in MHz  
Reading (dB $\mu$ V/m) = Uncorrected Analyzer / Receiver Reading  
Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain  
Limit (dB $\mu$ V/m) = Limit stated in standard  
Margin (dB) = Result (dB $\mu$ V/m)- Limit (dB $\mu$ V/m)  
Peak = Peak Reading  
AVG. = Average Reading  
Remark = Mark Peak Reading or Average Reading