


FCC Test Report

FCC ID : 2AQYEFMP176
Equipment : Mobile Phone
Model No. : F-51A
Brand Name : FUJITSU
Applicant : FUJITSU CONNECTED TECHNOLOGIES Ltd.
Address : Chuorinkan 7-10-1 Yamato, Kanagawa
242-0007, Japan.
Standard : 47 CFR FCC Part 15.247
Received Date : Mar. 06, 2020
Tested Date : Mar. 12 ~ Apr. 29, 2020

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	Test Equipment List and Calibration Data.....	8
1.5	Test Standards	9
1.6	Deviation from Test Standard and Measurement Procedure.....	9
1.7	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	20
3.4	Power Spectral Density	23
3.5	Emissions in Restricted Frequency Bands.....	29
3.6	Emissions in non-restricted Frequency Bands	39
4	TEST LABORATORY INFORMATION	44

Release Record

Report No.	Version	Description	Issued Date
FR011605AE	Rev. 01	Initial issue	May 18, 2020

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 0.502MHz 29.29 (Margin -16.71dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 70.85MHz 29.64 (Margin -10.36dB) - PK	Pass
15.247(b)(3)	Maximum Output Power	Power [dBm]: 3.36	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Product Details

Product Name	Mobile Phone
Brand Name	FUJITSU
Model Name	F-51A
IMEI Code	353704110013257 / 353704110013364
H/W Version	v2.1.0
S/W Version	R047.4

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Freq. (MHz)	Channel Number	Data Rate
2400-2483.5	V5.1 LE	2402-2480	0-39 [40]	125 kbps
				500 kbps
				1 Mbps
2400-2483.5	V5.1 LE	2402-2480	0-39 [40]	2 Mbps
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.				

1.1.3 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)	Remarks
1	Monopole	No	-6.0	---

1.1.4 Power Supply Type of Equipment under Test (EUT)

Supply Voltage	3.83Vdc from battery: 9Vdc,1.5A from adapter (No bundle, support unit only)
----------------	--

1.1.5 Accessories

Accessories		
No.	Equipment	Description
1	Battery	Brand: FUJITSU CONNECTED TECHNOLOGIES LIMITED Model: CA54310-0079-A1 Rated: 4000mAh, 15.4Wh Typ. 4070mAh, 15.6Wh
2	Type-C <-> Earphone	9.5cm non-shielded without core

1.1.6 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

1.1.7 Test Tool and Duty Cycle

Test Tool	QDART, V00071	
Modulation Mode	Duty Cycle Of Test Signal (%)	Duty Factor (dB)
GFSK-125kbps	84.09%	0.75
GFSK-500kbps	57.82%	2.38
GFSK-1Mbps	65.68%	1.83
GFSK-2Mbps	34.81%	4.58


1.1.8 Power Index of Test Tool

Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK/125kbps	Default	Default	Default
GFSK/500kbps	Default	Default	Default
GFSK/1Mbps	Default	Default	Default
GFSK/2Mbps	Default	Default	Default

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	S/N	Remarks
1	AC Adapter	NTT docomo	AC Adapter 06	---	Provided by applicant.
2	Notebook	DELL	Latitude E5470	7BMHVF2	---

1.3 Test Setup Chart

Test Setup Diagram	
	
No.	Signal cable / Length (m)
1	USB, 1.2m non-shielded with one core.

Note: The support notebook is disconnected from EUT and removed from test table after sending command to EUT to control EUT to transmit continuously.

1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101658	Dec. 12, 2019	Dec. 11, 2020
LISN	R&S	ENV216	101579	Mar. 12, 2020	Mar. 11, 2021
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 22, 2019	Oct. 21, 2020
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 17, 2019	Dec. 16, 2020
Receiver	R&S	ESR3	101657	Feb. 14, 2020	Feb. 13, 2021
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 12, 2019	Jul. 11, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 12, 2019	Dec. 11, 2020
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2019	Nov. 14, 2020
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2019	Nov. 12, 2020
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 07, 2019	Oct. 06, 2020
Preamplifier	EMC	EMC02325	980225	Jul. 09, 2019	Jul. 08, 2020
Preamplifier	Agilent	83017A	MY39501308	Oct. 08, 2019	Oct. 07, 2020
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020
RF Cable	EMC	EMC104-SM-SM-8000	181106	Oct. 07, 2019	Oct. 06, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 07, 2019	Oct. 06, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 07, 2019	Oct. 06, 2020
LF cable 1M	EMC	EMCCFD400-NM-NM-1000	160502	Oct. 07, 2019	Oct. 06, 2020
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 07, 2019	Oct. 06, 2020
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Oct. 07, 2019	Oct. 06, 2020
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101499	Jan. 09, 2020	Jan. 08, 2021
Power Meter	Anritsu	ML2495A	1241002	Oct. 23, 2019	Oct. 22, 2020
Power Sensor	Anritsu	MA2411B	1207366	Oct. 23, 2019	Oct. 22, 2020
AC POWER SOURCE	APC	AFC-500W	F312060012	Dec. 02, 2019	Dec. 01, 2020
Measurement Software	--	SENSE-15247_FS	V5.10.1	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.130 Hz
Conducted power	± 0.808 dB
Power density	± 0.583 dB
Conducted emission	± 2.715 dB
AC conducted emission	± 2.92 dB
Radiated emission ≤ 1 GHz	± 3.41 dB
Radiated emission > 1 GHz	± 4.59 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	23°C / 58%	Alex Tsai
Radiated Emissions	03CH01-WS	20-23°C / 65-69%	Roger Lu Akun Chung
RF Conducted	TH01-WS	24°C / 68%	Aska Huang

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions Radiated Emissions $\leq$ 1GHz	BT LE	2402	1Mbps	---
Maximum Output Power 6dB bandwidth Power spectral density	BT LE	2402, 2440, 2480	125kbps 500kbps 1Mbps 2Mbps	---
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	---
NOTE: 1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.				

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	BT LE-1Mbps	Test Freq. (MHz)	2402
Power Phase	Line		




Freq	Level	Limit	Over	Read	LISN	cable	Remark	
MHz	dBuV	Line	Limit	Level	factor	loss		
		dBuV	dB	dBuV	dB	dB		
1	0.510	24.20	46.00	-21.80	14.21	9.63	0.09	Average
2*	0.510	35.58	56.00	-20.42	25.59	9.63	0.09	QP
3	0.948	15.67	46.00	-30.33	5.60	9.63	0.12	Average
4	0.948	25.66	56.00	-30.34	15.59	9.63	0.12	QP
5	2.567	11.33	46.00	-34.67	1.12	9.64	0.22	Average
6	2.567	20.71	56.00	-35.29	10.50	9.64	0.22	QP
7	3.123	9.22	46.00	-36.78	-1.04	9.65	0.25	Average
8	3.123	21.59	56.00	-34.41	11.33	9.65	0.25	QP
9	4.315	12.04	46.00	-33.96	1.72	9.65	0.30	Average
10	4.315	23.37	56.00	-32.63	13.05	9.65	0.30	QP
11	5.898	11.61	50.00	-38.39	1.23	9.67	0.33	Average
12	5.898	23.11	60.00	-36.89	12.73	9.67	0.33	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).

2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	BT LE-1Mbps	Test Freq. (MHz)	2402
Power Phase	Neutral		



The graph displays the measured level (blue line) against frequency (MHz) on a logarithmic scale. Two red lines represent the CISPR/CNS/VCCI-B and CISPR/CNS/VCCI-B AV limits. The measured level is generally below the limits, with some peaks around 0.5 MHz and 3 MHz. The graph is labeled with 'Level (dBuV)' on the y-axis and 'Frequency (MHz)' on the x-axis. The y-axis ranges from 0 to 80 dBuV, and the x-axis ranges from 0.15 to 30 MHz. The CISPR/CNS/VCCI-B limit starts at approximately 65 dBuV at 0.15 MHz and decreases to about 55 dBuV at 5 MHz, then remains constant. The CISPR/CNS/VCCI-B AV limit starts at approximately 55 dBuV at 0.15 MHz and decreases to about 45 dBuV at 5 MHz, then remains constant. The measured level (blue line) shows several peaks, with the highest peak around 0.5 MHz reaching approximately 40 dBuV. Other peaks are visible around 1 MHz, 2 MHz, 3 MHz, and 6 MHz, all generally below the 40 dBuV mark.

Freq	Level	Limit	Over	Read	LISN	cable	Remark	
MHz	dBuV	Line	Limit	Level	factor	loss		
		dBuV	dB	dBuV	dB	dB		
1*	0.502	29.29	46.00	-16.71	19.37	9.65	0.09	Average
2	0.502	38.19	56.00	-17.81	28.27	9.65	0.09	QP
3	0.948	18.62	46.00	-27.38	8.65	9.65	0.12	Average
4	0.948	27.12	56.00	-28.88	17.15	9.65	0.12	QP
5	2.001	15.29	46.00	-30.71	5.19	9.66	0.18	Average
6	2.001	22.53	56.00	-33.47	12.43	9.66	0.18	QP
7	3.190	16.66	46.00	-29.34	6.48	9.67	0.25	Average
8	3.190	26.10	56.00	-29.90	15.92	9.67	0.25	QP
9	3.820	19.37	46.00	-26.63	9.16	9.67	0.28	Average
10	3.820	28.38	56.00	-27.62	18.17	9.67	0.28	QP
11	6.914	20.06	50.00	-29.94	9.70	9.71	0.35	Average
12	6.914	26.01	60.00	-33.99	15.65	9.71	0.35	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).

Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set resolution bandwidth (RBW) = 1% ~ 5 % of OBW, Video bandwidth = 3 x RBW
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup



3.2.4 Test Result of 6dB and Occupied Bandwidth

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE0.125_Nss1_1TX	655.797k	1.046M	1M05F1D	626.812k	1.045M
BT-LE0.5_Nss1_1TX	666.667k	1.016M	1M02F1D	648.551k	1.014M
BT-LE(1Mbps)	670.29k	1.021M	1M02F1D	663.043k	1.02M
BT-LE(2Mbps)	1.159M	1.991M	1M99F1D	1.138M	1.99M

Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;

Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE0.125_Nss1_1TX	-	-	-	-
2402MHz	Pass	500k	637.681k	1.045M
2440MHz	Pass	500k	626.812k	1.045M
2480MHz	Pass	500k	655.797k	1.046M
BT-LE0.5_Nss1_1TX	-	-	-	-
2402MHz	Pass	500k	648.551k	1.015M
2440MHz	Pass	500k	655.797k	1.014M
2480MHz	Pass	500k	666.667k	1.016M
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	670.29k	1.021M
2440MHz	Pass	500k	663.043k	1.02M
2480MHz	Pass	500k	663.043k	1.02M
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	500k	1.159M	1.991M
2440MHz	Pass	500k	1.138M	1.99M
2480MHz	Pass	500k	1.152M	1.99M

Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

BT-LE0.125_Nss1_1TX

EBW


2402MHz



BT-LE0.125_Nss1_1TX

EBW


2440MHz



BT-LE0.125_Nss1_1TX

EBW


2480MHz



BT-LE0.5_Nss1_1TX

EBW


2402MHz



BT-LE0.5_Nss1_1TX

EBW


2440MHz



BT-LE0.5_Nss1_1TX

EBW


2480MHz



BT-LE(1Mbps)

EBW


2402MHz



BT-LE(1Mbps)

EBW


2440MHz



BT-LE(1Mbps)

EBW


2480MHz



BT-LE(2Mbps)

EBW


2402MHz



BT-LE(2Mbps)

EBW


2440MHz



BT-LE(2Mbps)

EBW

2480MHz



3.3 RF Output Power

3.3.1 Limit of RF Output Power


Conducted power shall not exceed 1Watt.

Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.

3.3.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Summary of Peak Conducted Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE0.125_Nss1_1TX	3.34	0.00216
BT-LE0.5_Nss1_1TX	3.35	0.00216
BT-LE(1Mbps)	3.36	0.00217
BT-LE(2Mbps)	3.34	0.00216

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE0.125_Nss1_1TX	-	-	-	-
2402MHz	Pass	-6.00	3.34	30.00
2440MHz	Pass	-6.00	3.08	30.00
2480MHz	Pass	-6.00	3.09	30.00
BT-LE0.5_Nss1_1TX	-	-	-	-
2402MHz	Pass	-6.00	3.35	30.00
2440MHz	Pass	-6.00	3.08	30.00
2480MHz	Pass	-6.00	3.09	30.00
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	-6.00	3.36	30.00
2440MHz	Pass	-6.00	3.09	30.00
2480MHz	Pass	-6.00	3.11	30.00
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	-6.00	3.34	30.00
2440MHz	Pass	-6.00	3.07	30.00
2480MHz	Pass	-6.00	3.10	30.00

Summary of Conducted (Average) Output Power

Mode	Power	Power
	(dBm)	(W)
2.4-2.4835GHz	-	-
BT-LE0.125_Nss1_1TX	3.08	0.00203
BT-LE0.5_Nss1_1TX	3.10	0.00204
BT-LE(1Mbps)	3.12	0.00205
BT-LE(2Mbps)	3.11	0.00205

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE0.125_Nss1_1TX	-	-	-	-
2402MHz	Pass	-6.00	3.08	-
2440MHz	Pass	-6.00	2.81	-
2480MHz	Pass	-6.00	2.85	-
BT-LE0.5_Nss1_1TX	-	-	-	-
2402MHz	Pass	-6.00	3.10	-
2440MHz	Pass	-6.00	2.82	-
2480MHz	Pass	-6.00	2.86	-
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	-6.00	3.12	-
2440MHz	Pass	-6.00	2.85	-
2480MHz	Pass	-6.00	2.87	-
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	-6.00	3.11	-
2440MHz	Pass	-6.00	2.84	-
2480MHz	Pass	-6.00	2.86	-

Note: Average power is for reference only.

3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

1. Set the RBW = 3 kHz, VBW = 10 kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE0.125_Nss1_1TX	-2.73
BT-LE0.5_Nss1_1TX	-2.81
BT-LE(1Mbps)	-10.63
BT-LE(2Mbps)	-13.90


Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE0.125_Nss1_1TX	-	-	-	-
2402MHz	Pass	-6.00	-2.73	8.00
2440MHz	Pass	-6.00	-2.89	8.00
2480MHz	Pass	-6.00	-2.95	8.00
BT-LE0.5_Nss1_1TX	-	-	-	-
2402MHz	Pass	-6.00	-2.81	8.00
2440MHz	Pass	-6.00	-3.24	8.00
2480MHz	Pass	-6.00	-2.96	8.00
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	-6.00	-11.38	8.00
2440MHz	Pass	-6.00	-11.09	8.00
2480MHz	Pass	-6.00	-10.63	8.00
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	-6.00	-14.10	8.00
2440MHz	Pass	-6.00	-13.90	8.00
2480MHz	Pass	-6.00	-14.39	8.00

BT-LE0.125_Nss1_1TX

PSD


2402MHz



BT-LE0.125_Nss1_1TX

PSD


2440MHz



BT-LE0.125_Nss1_1TX

PSD


2480MHz



BT-LE0.5_Nss1_1TX

PSD


2402MHz



BT-LE0.5_Nss1_1TX

PSD


2440MHz



BT-LE0.5_Nss1_1TX

PSD


2480MHz



BT-LE(1Mbps)

PSD


2402MHz



BT-LE(1Mbps)

PSD


2440MHz



BT-LE(1Mbps)

PSD


2480MHz



BT-LE(2Mbps)

PSD


2402MHz



BT-LE(2Mbps)

PSD


2440MHz



BT-LE(2Mbps)

PSD

2480MHz



3.5 Emissions in Restricted Frequency Bands

3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	BT LE-1Mbps	Test Freq. (MHz)	2402
Polarization	Horizontal		
Level (dBuV/m) <			

Modulation	BT LE-1Mbps	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	33.88	23.21	40.00	-16.79	32.76	-9.55	Peak	---	---
2	47.52	25.32	40.00	-14.68	33.72	-8.40	Peak	---	---
3	70.85	29.64	40.00	-10.36	40.38	-10.74	Peak	---	---
4	92.58	23.54	43.50	-19.96	37.56	-14.02	Peak	---	---
5	120.85	25.11	43.50	-18.39	35.70	-10.59	Peak	---	---
6	155.69	21.87	43.50	-21.63	30.20	-8.33	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	BT LE-1Mbps	Test Freq. (MHz)	2402
Polarization	Horizontal		
Level (dBuV/m) </			

Modulation	BT LE-1Mbps	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.22	54.00	-15.78	41.02	-2.80	Average	161	101
2	2390.00	51.46	74.00	-22.54	54.26	-2.80	Peak	161	101
3	4804.00	31.99	54.00	-22.01	28.46	3.53	Average	100	80
4	4804.00	44.79	74.00	-29.21	41.26	3.53	Peak	100	80
5	12010.00	43.09	54.00	-10.91	29.37	13.72	Average	100	20
6	12010.00	56.30	74.00	-17.70	42.58	13.72	Peak	100	20

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	BT LE-1Mbps	Test Freq. (MHz)	2440
Polarization	Horizontal		
Level (dBuV/m) <			

Modulation	BT LE-1Mbps	Test Freq. (MHz)	2440
Polarization	Vertical		
Level (dBuV/m) <			

Modulation	BT LE-1Mbps	Test Freq. (MHz)	2480
Polarization	Horizontal		
Level (dBuV/m)			

Modulation	BT LE-1Mbps	Test Freq. (MHz)	2480
Polarization	Vertical		
Level (dBuV/m) <			

3.6 Emissions in non-restricted Frequency Bands

3.6.1 Emissions in non-restricted frequency bands limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level


Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.6.3 Test Setup




3.6.4 Test Result of Emissions in non-restricted Frequency Bands



BT-LE0.5_Nss1_1TX

CSE NdB


2402MHz



BT-LE0.5_Nss1_1TX

CSE NdB


2440MHz



BT-LE0.5_Nss1_1TX

CSE NdB


2480MHz



BT-LE(1Mbps)

2402MHz


CSE NdB



BT-LE(1Mbps)

2440MHz


CSE NdB



BT-LE(1Mbps)

2480MHz


CSE NdB



BT-LE(2Mbps)

CSE NdB


2402MHz



BT-LE(2Mbps)

CSE NdB


2440MHz



BT-LE(2Mbps)

CSE NdB

2480MHz



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==