

# FCC Test Report

**Applicant** : Gopod Group Limited.

---

**Address** : 6/F., 235 Wing Lok Trade Centre, Sheung Wan,  
Hong Kong

---

**Product Name** : Magnetic Car Wireless Charger

---

**Report Date** : Jul. 20, 2023

---

**Shenzhen Anbotek Compliance Laboratory Limited**



# Contents

1. General Information .....	5
1.1. Client Information .....	5
1.2. Description of Device (EUT) .....	5
1.3. Auxiliary Equipment Used During Test .....	6
1.4. Test Equipment List .....	6
1.5. Measurement Uncertainty .....	6
1.6. Description of Test Facility .....	6
2. Measurement and Result .....	7
2.1. Requirements .....	7
2.2. Test Setup .....	8
2.3. Test Procedure .....	9
2.4. Test Result .....	9
APPENDIX I -- TEST SETUP PHOTOGRAPH .....	12
APPENDIX II -- EXTERNAL PHOTOGRAPH .....	12
APPENDIX III -- INTERNAL PHOTOGRAPH .....	12



# TEST REPORT

Applicant : Gopod Group Limited.  
Manufacturer : Gopod Group Holding Limited  
Product Name : Magnetic Car Wireless Charger  
Model No. : D677A3, T605F, Z677  
Trade Mark : Gmobi  
Rating(s) : Input: 5V $\overline{=}$  2A, 9V $\overline{=}$  2.22A  
Wireless output: 5W/7.5W/15W  
**Test Standard(s) : FCC Part 1.1310, 1.1307(b)**  
**Test Method(s) : KDB680106 D01 RF Exposure Wireless Charging Apps v03r01**  
**TCB Workshop November 2019**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 1.1307 & KDB680106 D01 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Jun. 12, 2023

Date of Test

Jun. 12~20, 2023

Prepared By

*Ella Liang*

(Ella Liang)

Approved & Authorized Signer

*Kingkong Jin*

(Kingkong Jin)





## Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Jul. 20, 2023



## 1. General Information

### 1.1. Client Information

Applicant	:	Gopod Group Limited.
Address	:	6/F., 235 Wing Lok Trade Centre, Sheung Wan, Hong Kong
Manufacturer	:	Gopod Group Holding Limited
Address	:	301, 4/F, 5/F, 6/F, Building#8 & 6/F, 7/F, Tower#C, Lian Jian Industrial Park II, Shang Henglang Community, DaLang St, LongHua Dist, Shenzhen
Factory	:	Gopod Group Holding Limited
Address	:	301, 4/F, 5/F, 6/F, Building#8 & 6/F, 7/F, Tower#C, Lian Jian Industrial Park II, Shang Henglang Community, DaLang St, LongHua Dist, Shenzhen

### 1.2. Description of Device (EUT)

Product Name	:	Magnetic Car Wireless Charger
Model No.	:	D677A3, T605F, Z677 (Note: All samples are the same except for model number, so we prepare "D677A3" for testing only.)
Trade Mark	:	Gmobi
Test Power Supply	:	DC 12V
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A
<b>RF Specification</b>		
Operation Frequency	:	110.1~360kHz
Modulation Type	:	FSK
Antenna Type	:	Inductive loop coil Antenna
Antenna Gain(Peak)	:	0 dBi (Provided by customer)
<b>Remark:</b> 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		



### 1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
Car Charger	Input: DC 12-24V Output: USB-C: 5V= 3A, 9V= 2.22A, 12V= 1.67A USB-A: 5V= 3A, 9V= 2A, 12V= 1.5A Total: 38W(max)
Wireless charging load:	Manufacturer: Shenzhen Ouju Technology Co., Ltd. M/N: CD2531 Power: 5W/7.5W/10W/15W

### 1.4. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Electric and Magnetic field Analyzer	NARDA	EHP-200A	180ZX10202	Oct. 17, 2022	1 Year

### 1.5. Measurement Uncertainty

Magnetic Field Reading(A/m)	:	+/-0.04282(A/m)
Electric Field Reading(V/m)	:	+/-0.03679(V/m)

### 1.6. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

#### ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

#### Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China. 518128





## 2. Measurement and Result

### 2.1. Requirements

According to the item 5.b) of KDB 680106 D01v03:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.


- 1) Power transfer frequency is less than 1 MHz
- 2) Output power from each primary coil is less than or equal to 15 watts.
- 3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils
- 4) Client device is inserted in or placed directly in contact with the transmitter
- 5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion)
- 6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

#### Limits For Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30
F=frequency in MHz *=Plane-wave equivalent power density RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).				




## 2.2. Test Setup



**Note:**

H-field data are taken along all three axes the device, from 0 cm to 10 cm, in 2 cm minimum increment measured from the edge of the device, with one axis coincident with the axis of the main coil.



Note: Measurements should be made at 15 cm surrounding the EUT and 20cm above the top surface of the EUT. (probe radius is 4.75cm)





### 2.3. Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at required test distance (from 0 cm to 10 cm, in 2 cm minimum increment) which is between the edge/top surface of the charger and the edge of probe.  
and the measurement probe was placed at required test distance 15cm and 20cm which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points  
(A, B, C, D, E) were completed.(A is the right, B is the back, C is the left, D is the front, and E is the top.)
- 4) The EUT was measured according to the dictates of TCB Workshop November 2019 and KDB 680106 D01 v03r01.

**Remark;**

The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

### 2.4. Test Result

#### 2.4.1. Equipment Approval Considerations item 5.b of KDB 680106 D01 v03.

- 1) Power transfer frequency is less than 1 MHz
  - The device operate in the frequency range 110.1~360kHz.
- 2) Output power from each primary coil is less than 15 watts
  - The maximum output power of the primary coil is 15W.
- 3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils
  - The transfer system including a charging system with only single primary coils is to detect and allow only between individual pairs of coils.
- 4) Client device is inserted in or placed directly in contact with the transmitter
  - Client device is placed directly in contact with the transmitter.
- 5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion)
  - The EUT is a Mobile exposure conditions
- 6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
  - Conducted the measurement with the required distance and the test results please refer to the section 2.4.



2.4.2. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

Temperature:	22.5°C	Relative Humidity:	49 %
Pressure:	1012 hPa	Test Voltage:	DC 12V

**Between the edge/top surface of the charger and the edge of probe**

H-Field Strength:

Test distance	Battery power	Frequency Range (kHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
0cm	1%	110.1-360	0.058	0.061	0.102	0.048	0.091	0.815	1.63
	50%	110.1-360	0.635	0.423	0.439	0.402	0.451	0.815	1.63
	99%	110.1-360	0.642	0.447	0.484	0.429	0.472	0.815	1.63
	Stand-by	110.1-360	0.217	0.235	0.200	0.180	0.197	0.815	1.63
2cm	1%	110.1-360	0.043	0.047	0.088	0.033	0.076	0.815	1.63
	50%	110.1-360	0.642	0.430	0.446	0.409	0.457	0.815	1.63
	99%	110.1-360	0.633	0.438	0.477	0.420	0.465	0.815	1.63
	Stand-by	110.1-360	0.211	0.228	0.194	0.174	0.191	0.815	1.63
4cm	1%	110.1-360	0.053	0.059	0.101	0.044	0.087	0.815	1.63
	50%	110.1-360	0.633	0.420	0.437	0.399	0.446	0.815	1.63
	99%	110.1-360	0.637	0.441	0.480	0.424	0.468	0.815	1.63
	Stand-by	110.1-360	0.201	0.219	0.187	0.165	0.183	0.815	1.63
6cm	1%	110.1-360	0.048	0.054	0.097	0.039	0.078	0.815	1.63
	50%	110.1-360	0.632	0.419	0.436	0.397	0.444	0.815	1.63
	99%	110.1-360	0.635	0.440	0.477	0.421	0.465	0.815	1.63
	Stand-by	110.1-360	0.198	0.217	0.183	0.163	0.182	0.815	1.63
8cm	1%	110.1-360	0.038	0.044	0.088	0.030	0.069	0.815	1.63
	50%	110.1-360	0.634	0.421	0.440	0.399	0.448	0.815	1.63
	99%	110.1-360	0.628	0.432	0.469	0.411	0.457	0.815	1.63
	Stand-by	110.1-360	0.201	0.219	0.185	0.165	0.183	0.815	1.63
10cm	1%	110.1-360	0.039	0.043	0.089	0.029	0.071	0.815	1.63
	50%	110.1-360	0.624	0.411	0.429	0.389	0.436	0.815	1.63
	99%	110.1-360	0.636	0.439	0.476	0.417	0.464	0.815	1.63
	Stand-by	110.1-360	0.219	0.216	0.185	0.168	0.182	0.815	1.63





**Between the edge of the charger and the geometric center of probe**

H-Field Strength at 15 cm surrounding the EUT and 20cm above the top surface of the EUT

Battery power	Frequency Range (kHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
1%	110.1-360	0.031	0.034	0.077	0.021	0.063	0.031	1.63
50%	110.1-360	0.625	0.413	0.429	0.389	0.437	0.625	1.63
99%	110.1-360	0.624	0.427	0.464	0.410	0.451	0.624	1.63
Stand-by	110.1-360	0.221	0.218	0.189	0.171	0.186	0.221	1.63

Note: All modulation and situation(full load, half load and empty load) has been tested,only the worst situation (full load 15W) was recorded in the report.





## APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph\_MPE

## APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

## APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

