

# TEST REPORT

Report No.: SHATBL2503013W02

**Applicant** : Satellite Electronics (Zhong shan) Co Ltd.

**Product Name** : CEILING FAN REMOTE CONTROL

**Brand Name** : N/A

**Model Name** : TRD068S1Z

**FCC ID** : 2AQZU-18063

**Test Standard** : 47 CFR Part 2.1091


**Issue Date** : 2025.04.18

**Report Prepared by** :



(Emily)

**Report Approved by** :



(Guozheng Li)

**Authorized Signatory** :



(Terry Yang)



## TABLE OF CONTENTS

REVISION HISTORY .....	3
DECLARATION OF REPORT .....	4
1. GENERAL DESCRIPTION .....	5
1.1. Applicant .....	5
1.2. Manufacturer .....	5
1.3. Factory .....	5
1.4. General Information of EUT .....	6
1.5. Laboratory Information .....	6
2. FCC 47CFR §2.1091 Requirement .....	7
2.1. Test Standards .....	7
2.2. Limit .....	7
2.3. MPE Calculation Method .....	8
2.4. Antenna Information .....	8
2.5. Manufacturing Tolerance .....	8
2.6. Test Result .....	9

## REVISION HISTORY

Rev.	Issue Date	Revisions	Revised by
00	2025.04.18	Initial Release	Emily



## DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR Part 2.1091. And it is applicable only to the tested sample identified in the report.

2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.

3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.

4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.

5. In this report, '☐' indicates that EUT does not support content after '☐', and '☑' indicates that it supports content after '☑'

## 1. GENERAL DESCRIPTION

### 1.1. Applicant

Name : Satellite Electronics (Zhong shan) Co Ltd.

Address : No.8, Chuang Ye Road, Torch Development Zone, Zhongshan, Guangdong, China

### 1.2. Manufacturer

Name : Satellite Electronics (Zhong shan) Co Ltd.

Address : No.8, Chuang Ye Road, Torch Development Zone, Zhongshan, Guangdong, China

### 1.3. Factory

Name 1 : Satellite Electronics (Zhong shan) Co Ltd.

Address 1 : No.8, Chuang Ye Road, Torch Development Zone, Zhongshan, Guangdong, China

Name 2 : CHUNGGEAR INDUSTRIAL CO., LTD.

Address 2 : No.12, Jingke 8th Rd., Nantun Dist., Taichung City 40852, Taiwan (R.O.C.)

**1.4. General Information of EUT**

Product Name	CEILING FAN REMOTE CONTROL
Trade Name	N/A
Model Name	TRD068S1Z
Series Model	N/A
Frequency band	304.25MHz
Power supply	DC 3V
Modulation Type	ASK
Antenna type:	PCB Antenna
Antenna gain:	-6dBi
Hardware version number	TRD068S1Z 250317
Software version number	TRD068S1Z V1.0

**1.5. Laboratory Information**

Company Name:	Shanghai ATBL Technology Co., Ltd.
Address:	Building 8, No. 160, Basheng Road, Waigaoqiao Free Trade Zone, Pudong New Area, Shanghai
Telephone:	+86(0)21-51298625
FCC-Registration Number:	485917
Designation Number:	CN1306
A2LA-Lab Cert. No.:	6184.01
ISED Designation Number:	27371



## 2. FCC 47CFR §2.1091 Requirement

### 2.1. Test Standards

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

### 2.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 2.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 2.4. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Antenna	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range: (MHz)
304.25M	/	PCB Antenna	-6dBi	304.25

### 2.5. Manufacturing Tolerance

Frequency (MHz)	ANT0		
	304.25	--	--
Target (dBm)	-37.39	--	--
Tolerance ± (dB)	1.0	--	--

Note: dBm= dBuV-95.2=57.81dBuV-95.2=-37.39dBm



**2.6. Test Result**

Modulation Type	Output power (Target)		Antenna Gain (dBi)	MPE Exemption
	dBm	mW		
304.25MHz	-37.39	0.00018	-6.0	<1mW

Note:

- 1.The Maximum power is less than the limit, complies with the exemption requirements.
- 2.Output power including turn-up tolerance.

\*\*\*\*\*END OF THE REPORT\*\*\*\*\*