




## CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China  
Tel: +86-755-27521059 Fax: +86-755-27521011 Http://www.sz-ctc.org.cn

# TEST REPORT

**Report No.** ..... CTC20210600E02  
**FCC ID** ..... 2AR24-AIBOX30S  
**Applicant** ..... Shenzhen Absen Optoelectronic Co.,Ltd  
Address ..... 18-20F Building 3A, Cloud Park, Bantian, Longgang District, Shenzhen, China  
**Manufacturer** ..... Shenzhen Absen Optoelectronic Co.,Ltd  
Address ..... 18-20F Building 3A, Cloud Park, Bantian, Longgang District, Shenzhen, China  
**Product Name** ..... LED Multimedia Processor  
Trade Mark ..... /  
Model/Type reference ..... Ai Box3.0 S  
Listed Model(s) ..... /  
**Standard** ..... FCC CFR Title 47 Part 15 Subpart C Section 15.247  
Date of receipt of test sample.... Apr. 08, 2021  
Date of testing ..... Apr. 08, 2021 to Apr. 28, 2021  
Date of issue ..... Apr. 28, 2021  
**Result** ..... PASS

Compiled by:  
(Printed name+signature) Jim Jiang   
Supervised by:  
(Printed name+signature) Miller Ma   
Approved by:  
(Printed name+signature) Walter Chen 

**Testing Laboratory Name** ..... CTC Laboratories, Inc.  
Address ..... 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

**Table of Contents**

	Page
<b>1. TEST SUMMARY .....</b>	<b>3</b>
1.1. TEST STANDARDS.....	3
1.2. REPORT VERSION .....	3
1.3. TEST DESCRIPTION.....	3
1.4. TEST FACILITY .....	4
1.5. MEASUREMENT UNCERTAINTY.....	4
1.6. ENVIRONMENTAL CONDITIONS.....	5
<b>2. GENERAL INFORMATION .....</b>	<b>6</b>
2.1. CLIENT INFORMATION .....	6
2.2. GENERAL DESCRIPTION OF EUT.....	6
2.3. ACCESSORY EQUIPMENT INFORMATION .....	7
2.4. OPERATION STATE .....	8
2.5. MEASUREMENT INSTRUMENTS LIST .....	9
<b>3. TEST ITEM AND RESULTS .....</b>	<b>11</b>
3.1. CONDUCTED EMISSION.....	11
3.2. RADIATED EMISSION .....	14
3.3. BAND EDGE EMISSIONS (RADIATED) .....	37
3.4. BAND EDGE AND SPURIOUS EMISSIONS (CONDUCTED) .....	50
3.5. 20DB BANDWIDTH.....	65
3.6. CHANNEL SEPARATION.....	69
3.7. NUMBER OF HOPPING CHANNEL.....	73
3.8. DWELL TIME .....	75
3.9. PEAK OUTPUT POWER .....	80
3.10. DUTY CYCLE .....	81
3.11. ANTENNA REQUIREMENT.....	85



# 1. TEST SUMMARY

## 1.1. Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

RSS 247 Issue 2: Standard Specifications for Frequency Hopping Systems (FHSs) and Digital Transmission Systems (DTSs) Operating in the Bands 902-928MHz, 2400-2483.5MHz and 5725-5850MHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

## 1.2. Report Version

Revised No.	Date of issue	Description
01	Apr. 28, 2021	Original

## 1.3. Test Description

FCC Part 15 Subpart C (15.247)/ RSS 247 Issue 2				
Test Item	Standard Section		Result	Test Engineer
	FCC	IC		
Antenna Requirement	15.203	/	Pass	Rod Luo
Conducted Emission	15.207	RSS-Gen 8.8	Pass	Rod Luo
Restricted Bands	15.205	RSS-Gen 8.10	Pass	Rod Luo
Hopping Channel Separation	15.247(a)(1)	RSS 247 5.1 (b)	Pass	Rod Luo
Dwell Time	15.247(a)(iii)	RSS 247 5.1 (d)	Pass	Rod Luo
Peak Output Power	15.247(b)(1)	RSS 247 5.4 (b)	Pass	Rod Luo
Number of Hopping Frequency	15.247(a)(iii)	RSS 247 5.1 (d)	Pass	Rod Luo
Conducted Band Edge and Spurious Emissions	15.247(d)	RSS 247 5.5	Pass	Rod Luo
Radiated Band Edge and Spurious Emissions	15.205&15.209&15.247(d)	RSS 247 5.5	Pass	Rod Luo
Radiated Spurious Emission	15.247(d)&15.209	RSS 247 5.5&RSS-Gen 8.9	Pass	Rod Luo
20dB Bandwidth	15.247(a)	RSS 247 5.1 (b)	Pass	Rod Luo

Note:

(1)The measurement uncertainty is not included in the test result.

(2)The test data except AC conducted emission and Radiated emission below 1GHz refer to CTC20210599E02(FCC ID: 2AR24-AIBOX30XS; Equipment code: DSS). The EUT wireless module, antenna, PCB layout and electrical circuit are the same, the difference is EUT size.



## 1.4. Test Facility

### CTC Laboratories, Inc.

Add: 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

### Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS-Lab Code: L5365

CTC Laboratories, Inc. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation. Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

#### A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)

CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

#### FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 951311, Aug 26, 2017.

## 1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.42 dB	(1)
Transmitter power Radiated	2.14 dB	(1)
Conducted spurious emissions 9kHz~40GHz	1.60 dB	(1)
Radiated spurious emissions 9kHz~40GHz	2.20 dB	(1)
Conducted Emissions 9kHz~30MHz	3.08 dB	(1)
Radiated Emissions 30~1000MHz	4.51 dB	(1)
Radiated Emissions 1~18GHz	5.84 dB	(1)
Radiated Emissions 18~40GHz	6.12 dB	(1)
Occupied Bandwidth	-----	(1)

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

## 1.6. Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	21°C~27°C
Relative Humidity:	40%~60%
Air Pressure:	101kPa



## 2. GENERAL INFORMATION

### 2.1. Client Information

Applicant:	Shenzhen Absen Optoelectronic Co.,Ltd
Address:	18-20F Building 3A, Cloud Park, Bantian, Longgang District, Shenzhen, China
Manufacturer:	Shenzhen Absen Optoelectronic Co.,Ltd
Address:	18-20F Building 3A, Cloud Park, Bantian, Longgang District, Shenzhen, China

### 2.2. General Description of EUT

Product Name:	LED Multimedia Processor
Trade Mark:	/
Model/Type reference:	Ai Box3.0 S
Listed Model(s):	/
Model Difference:	/
Power supply:	100-240V~ 50/60Hz 23W
RF Module Model:	ZK-7668U
Hardware version:	V1.0
Software version:	V1.0
<b>Bluetooth 4.2/ EDR</b>	
Modulation:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB Antenna
Antenna gain:	5dBi



## 2.3. Accessory Equipment Information

<b>Equipment Information</b>			
Name	Model	S/N	Manufacturer
Notebook	X220	/	Lenovo
<b>Cable Information</b>			
Name	Shielded Type	Ferrite Core	Length
USB Cable	Unshielded	NO	150cm
AC Cable	Unshielded	NO	120cm
<b>Test Software Information</b>			
Name	Software version	/	/
WCN_Combo_Tool	#1	/	/

## 2.4. Operation State

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. BT EDR, 79 channels are provided to the EUT. Channels 00/39/78 were selected for testing.

Operation Frequency List:

Channel	Frequency (MHz)
<b>00</b>	<b>2402</b>
01	2403
:	:
38	2440
<b>39</b>	<b>2441</b>
40	2442
:	:
77	2479
<b>78</b>	<b>2480</b>

Note: The display in grey were the channel selected for testing.

Test mode

For RF test items:
The engineering test program was provided and enabled to make EUT continuous transmit
For AC power line conducted emissions:
The EUT was set to connect with the Bluetooth instrument under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.



## 2.5. Measurement Instruments List

Tonscend JS0806-2 Test system					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Rohde & Schwarz	FSU26	100105	Dec. 25, 2021
2	Spectrum Analyzer	Rohde & Schwarz	FUV40-N	101331	Mar. 15, 2022
3	MXG Vector Signal Generator	Agilent	N5182A	MY47420864	Dec. 25, 2021
4	Signal Generator	Agilent	E8257D	MY46521908	Dec. 25, 2021
5	Power Sensor	Agilent	U2021XA	MY5365004	Dec. 25, 2021
6	Power Sensor	Agilent	U2021XA	MY5365006	Dec. 25, 2021
7	Simultaneous Sampling DAQ	Agilent	U2531A	TW54493510	Dec. 25, 2021
8	Climate Chamber	TABAI	PR-4G	A8708055	Dec. 25, 2021
9	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	116410	Dec. 25, 2021
10	Climate Chamber	ESPEC	MT3065	/	Dec. 25, 2021
11	300328 v2.2.2 test system	TONSCEND	v2.6	/	/

Radiated Emission and Transmitter spurious emissions					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	EMI Test Receiver	Rohde & Schwarz	ESCI	100658	Dec. 25, 2021
2	High pass filter	micro-tranics	HPM50111	142	Dec. 25, 2021
3	Log-Bicon Antenna	Schwarzbeck	CBL6141A	4180	Dec. 25, 2021
4	Ultra-Broadband Antenna	ShwarzBeck	BBHA9170	25841	Dec. 25, 2021
5	Loop Antenna	LAPLAC	RF300	9138	Dec. 25, 2021
6	Spectrum Analyzer	Rohde & Schwarz	FSU26	100105	Dec. 25, 2021
7	Horn Antenna	Schwarzbeck	BBHA 9120D	647	Dec. 25, 2021
8	Pre-Amplifier	HP	8447D	1937A03050	Dec. 25, 2021
9	Pre-Amplifier	EMCI	EMC051835	980075	Dec. 25, 2021
10	Antenna Mast	UC	UC3000	N/A	N/A
11	Turn Table	UC	UC3000	N/A	N/A
12	Cable Below 1GHz	Schwarzbeck	AK9515E	33155	Dec. 25, 2021
13	Cable Above 1GHz	Hubersuhner	SUCOFLEX102	DA1580	Dec. 25, 2021
14	Splitter	Mini-Circuit	ZAPD-4	400059	Dec. 25, 2021
15	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	Dec. 25, 2021
16	RF Connection Cable	Chengdu E-Microwave	---	---	Dec. 25, 2021



17	High pass filter	Compliance Direction systems	BSU-6	34202	Dec. 25, 2021
18	Attenuator	Chengdu E-Microwave	EM-CAXX-10RNZ-3	---	Dec. 25, 2021
19	High and low temperature box	ESPEC	MT3065	12114019	Dec. 25, 2021

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	LISN	Rohde & Schwarz	ENV216	101112	Dec. 25, 2021
2	LISN	Rohde & Schwarz	ENV216	101113	Dec. 25, 2021
3	EMI Test Receiver	Rohde & Schwarz	ESCI	100658	Dec. 25, 2021

Note: 1. The Cal. Interval was one year.

2. The cable loss has calculated in test result which connection between each test instruments.

### 3. TEST ITEM AND RESULTS

### 3.1. Conducted Emission


## Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.207/ RSS – Gen 8.8

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

## Test Configuration




## Test Procedure

1. The EUT was setup according to ANSI C63.10:2013 requirements.
  2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
  3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
  4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
  5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
  6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
  7. During the above scans, the emissions were maximized by cable manipulation.

## Test Mode

Please refer to the clause 2.4.

## Test Results




### Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)	Comment
0.182410	46.0	1000.00	9.000	On	L1	10.1	18.4	64.4	
0.230850	41.6	1000.00	9.000	On	L1	10.1	20.8	62.4	
0.231770	42.0	1000.00	9.000	On	L1	10.1	20.4	62.4	

### Final Measurement Detector 2

Frequency (MHz)	Average (dB $\mu$ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)	Comment
0.183140	34.2	1000.00	9.000	On	L1	10.1	20.1	54.3	
5.649840	31.4	1000.00	9.000	On	L1	10.3	18.6	50.0	
5.950790	31.0	1000.00	9.000	On	L1	10.3	19.0	50.0	

Emission Level= Read Level+ Correct Factor



## 3.2. Radiated Emission

### Limit

#### FCC CFR Title 47 Part 15 Subpart C Section 15.209/ RSS – Gen 8.9


Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54


### **Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dB<sub>u</sub>V/m)=20log Emission Level (uV/m).


### Test Configuration



Below 30MHz Test Setup



Below 1000MHz Test Setup



### **Test Procedure**

1. The EUT was setup and tested according to ANSI C63.10:2013
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Below 1 GHz:  
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;  
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  - (3) From 1 GHz to 10<sup>th</sup> harmonic:  
RBW=1MHz, VBW=3MHz Peak detector for Peak value.  
RBW=1MHz, VBW $\geq$ 1/T Peak detector for Average value.

Note 1: For the 1/T& Duty Cycle please refer to clause 3.10 Duty Cycle.

### **Test Mode**


Please refer to the clause 2.4.


### **Test Result**

#### **9 KHz-30 MHz**

From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.







Above 1GHz

Ant. Pol.	Horizontal
Test Mode:	TX GFSK Mode 2402MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4804.110	-2.82	39.18	36.36	54.00	-17.64	AVG
2	4804.421	-2.82	53.60	50.78	74.00	-23.22	peak

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China  
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : [yz.cnca.cn](http://yz.cnca.cn)



Ant. Pol.	Vertical
Test Mode:	TX GFSK Mode 2402MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4804.221	-2.82	38.22	35.40	54.00	-18.60	AVG
2	4804.330	-2.82	52.42	49.60	74.00	-24.40	peak

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.	Horizontal						
Test Mode:	TX GFSK Mode 2441MHz						
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.						

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4881.703	-2.60	53.70	51.10	74.00	-22.90	peak
2	4882.223	-2.60	38.90	36.30	54.00	-17.70	AVG

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.	Vertical
Test Mode:	TX GFSK Mode 2441MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4882.080	-2.60	38.27	35.67	54.00	-18.33	AVG
2	4882.235	-2.60	52.70	50.10	74.00	-23.90	peak

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value



Ant. Pol.	Horizontal						
Test Mode:	TX GFSK Mode 2480MHz						
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.						

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4959.846	-2.38	38.74	36.36	54.00	-17.64	AVG
2	4960.189	-2.38	53.36	50.98	74.00	-23.02	peak

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.	Vertical
Test Mode:	TX GFSK Mode 2480MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4959.798	-2.38	52.29	49.91	74.00	-24.09	peak
2	4960.302	-2.38	38.16	35.78	54.00	-18.22	AVG

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.	Horizontal						
Test Mode:	TX $\pi/4$ -DQPSK Mode 2402MHz						
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.						

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4803.857	-2.82	54.05	51.23	74.00	-22.77	peak
2	4804.421	-2.82	38.98	36.16	54.00	-17.84	AVG

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China  
Tel.: (86)755-27521059 Fax: (86)755-27521011 [Http://www.sz-ctc.org.cn](http://www.sz-ctc.org.cn)For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : [yz.cnca.cn](http://yz.cnca.cn)



Ant. Pol.	Vertical
Test Mode:	TX $\pi/4$ -DQPSK Mode 2402MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4804.080	-2.82	52.75	49.93	74.00	-24.07	peak
2	4804.284	-2.82	38.15	35.33	54.00	-18.67	AVG

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China  
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cnFor anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : [yz.cnca.cn](http://yz.cnca.cn)



Ant. Pol.	Horizontal						
Test Mode:	TX $\pi/4$ -DQPSK Mode 2441MHz						
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.						

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4881.918	-2.60	53.35	50.75	74.00	-23.25	peak
2	4882.210	-2.60	39.17	36.57	54.00	-17.43	AVG

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China  
Tel.: (86)755-27521059 Fax: (86)755-27521011 [Http://www.sz-ctc.org.cn](http://www.sz-ctc.org.cn)For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : [yz.cnca.cn](http://yz.cnca.cn)



Ant. Pol.	Vertical
Test Mode:	TX $\pi/4$ -DQPSK Mode 2441MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4882.231	-2.60	38.37	35.77	54.00	-18.23	AVG
2	4882.300	-2.60	52.49	49.89	74.00	-24.11	peak

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value



Ant. Pol.	Horizontal						
Test Mode:	TX $\pi/4$ -DQPSK Mode 2480MHz						
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.						

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4959.665	-2.38	53.40	51.02	74.00	-22.98	peak
2	4960.444	-2.38	38.64	36.26	54.00	-17.74	AVG

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value



Ant. Pol.	Vertical
Test Mode:	TX $\pi/4$ -DQPSK Mode 2480MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4959.921	-2.38	38.28	35.90	54.00	-18.10	AVG
2	4960.201	-2.38	52.16	49.78	74.00	-24.22	peak

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value



Ant. Pol.	Horizontal						
Test Mode:	TX 8-DPSK Mode 2402MHz						
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.						

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4803.598	-2.82	39.82	37.00	54.00	-17.00	AVG
2	4803.777	-2.82	54.25	51.43	74.00	-22.57	peak

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.	Vertical
Test Mode:	TX 8-DPSK Mode 2402MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4801.829	-2.83	52.82	49.99	74.00	-24.01	peak
2	4802.200	-2.83	38.11	35.28	54.00	-18.72	AVG

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value



Ant. Pol.	Horizontal						
Test Mode:	TX 8-DPSK Mode 2441MHz						
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.						

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4881.567	-2.60	39.28	36.68	54.00	-17.32	AVG
2	4882.143	-2.60	53.35	50.75	74.00	-23.25	peak

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value



Ant. Pol.	Vertical
Test Mode:	TX 8-DPSK Mode 2441MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4882.221	-2.60	52.38	49.78	74.00	-24.22	peak
2	4882.350	-2.60	38.21	35.61	54.00	-18.39	AVG

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.	Horizontal						
Test Mode:	TX 8-DPSK Mode 2480MHz						
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.						

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4959.849	-2.38	39.41	37.03	54.00	-16.97	AVG
2	4960.032	-2.38	52.93	50.55	74.00	-23.45	peak

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.	Vertical
Test Mode:	TX 8-DPSK Mode 2480MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4959.697	-2.38	52.50	50.12	74.00	-23.88	peak
2	4960.221	-2.38	37.70	35.32	54.00	-18.68	AVG

## Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value


### 3.3. Band Edge Emissions (Radiated)

#### Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

Restricted Frequency Band (MHz)	(dBuV/m)(at 3m)	
	Peak	Average
2310 ~ 2390	74	54
2483.5 ~ 2500	74	54

#### Test Configuration



#### Test Procedure


1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:  
RBW=1MHz, VBW=3MHz Peak detector for Peak value.  
RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.


Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 3.9 Duty Cycle.


#### Test Mode


Please refer to the clause 2.4.


## Test Results























No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.500	31.24	19.11	50.35	74.00	-23.65	peak
2	2483.500	31.24	6.22	37.46	54.00	-16.54	AVG
3	2531.200	31.37	21.66	53.03	74.00	-20.97	peak
4	2531.200	31.37	10.86	42.23	54.00	-11.77	AVG


**Remarks:**

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor  
2. Margin value = Level -Limit value










### 3.4. Band edge and Spurious Emissions (Conducted)

#### Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### Test Configuration



#### Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
RBW = 100 kHz, VBW  $\geq$  RBW, scan up through 10<sup>th</sup> harmonic.  
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.


#### Test Mode


Please refer to the clause 2.4.


#### Test Results


##### (1) Band edge Conducted Test

Test Mode	Ch Name	Frequency (MHz)	Ref Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
GFSK	Low	2402	4.67	-51.39	<=-15.33	PASS
	High	2480	3.95	-57.24	<=-16.05	PASS
	Low	Hop_2402	4.79	-59.81	-15.21	PASS
	High	Hop_2480	3.46	-59.41	-16.54	PASS
$\pi/4$ -DQPSK	Low	2402	3.29	-54.82	<=-16.71	PASS
	High	2480	3.37	-58.00	<=-16.63	PASS
	Low	Hop_2402	2.01	-59.18	-17.99	PASS
	High	Hop_2480	4.40	-58.42	-15.60	PASS
8-DPSK	Low	2402	4.83	-53.92	<=-15.17	PASS
	High	2480	3.26	-57.01	<=-16.74	PASS
	Low	Hop_2402	1.09	-59.85	-18.91	PASS
	High	Hop_2480	3.85	-59.24	-16.15	PASS















## (2) Conducted Spurious Emissions Test


Test Mode	Frequency (MHz)	Freq Range [MHz]	Ref Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
GFSK	2402	Reference	4.98	4.98	---	PASS
		30~1000	30~1000	-71.00	<=-15.02	PASS
		1000~26500	1000~26500	-34.63	<=-15.02	PASS
	2441	Reference	4.77	4.77	---	PASS
		30~1000	30~1000	-70.94	<=-15.23	PASS
		1000~26500	1000~26500	-34.79	<=-15.23	PASS
	2480	Reference	4.03	4.03	---	PASS
		30~1000	30~1000	-71.23	<=-15.97	PASS
		1000~26500	1000~26500	-34.81	<=-15.97	PASS
$\pi/4$ -DQPSK	2402	Reference	5.49	5.49	---	PASS
		30~1000	30~1000	-71.17	<=-14.51	PASS
		1000~26500	1000~26500	-34.68	<=-14.51	PASS
	2441	Reference	5.21	5.21	---	PASS
		30~1000	30~1000	-71.16	<=-14.79	PASS
		1000~26500	1000~26500	-34.69	<=-14.79	PASS
	2480	Reference	4.50	4.50	---	PASS
		30~1000	30~1000	-71.21	<=-15.5	PASS
		1000~26500	1000~26500	-34.60	<=-15.5	PASS
8-DPSK	2402	Reference	5.53	5.53	---	PASS
		30~1000	30~1000	-71.29	<=-14.47	PASS
		1000~26500	1000~26500	-34.66	<=-14.47	PASS
	2441	Reference	5.23	5.23	---	PASS
		30~1000	30~1000	-70.46	<=-14.77	PASS
		1000~26500	1000~26500	-34.62	<=-14.77	PASS
	2480	Reference	4.50	4.50	---	PASS
		30~1000	30~1000	-69.57	<=-15.50	PASS
		1000~26500	1000~26500	-34.82	<=-15.50	PASS
























### 3.5. 20dB Bandwidth

#### Limit

N/A

#### Test Configuration



#### Test Procedure

5. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
6. OCB and 20dB Spectrum Setting:
  - (1) Set RBW = 1% ~ 5% occupied bandwidth.
  - (2) Set the video bandwidth (VBW)  $\geq$  3 RBW.
  - (3) Detector = Peak.
  - (4) Trace mode = Max hold.
  - (5) Sweep = Auto couple.


Note: The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.


#### Test Mode


Please refer to the clause 2.4.

#### Test Results

Test Mode	Frequency (MHz)	20dB EBW[MHz]	FL[MHz]	FH[MHz]	20dB Bandwidth *2/3 (kHz)	Verdict
GFSK	2402	0.957	2401.529	2402.486	638.00	PASS
	2441	0.957	2440.529	2441.486	638.00	PASS
	2480	0.954	2479.529	2480.483	636.00	PASS
$\pi/4$ -DQPSK	2402	1.293	2401.361	2402.654	862.00	PASS
	2441	1.293	2440.361	2441.654	862.00	PASS
	2480	1.296	2479.358	2480.654	864.00	PASS
8-DPSK	2402	1.293	2401.349	2402.642	862.00	PASS
	2441	1.290	2440.352	2441.642	860.00	PASS
	2480	1.293	2479.349	2480.642	862.00	PASS








### 3.6. Channel Separation

#### Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1)/ RSS-247 5.1 b :

Test Item	Limit	Frequency Range(MHz)
Channel Separation	>25KHz or >two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

#### Test Configuration



#### Test Procedure


7. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
8. Spectrum Setting:
  - (1) Set RBW = 100 kHz.
  - (2) Set the video bandwidth (VBW)  $\geq$  3 RBW.
  - (3) Detector = Peak.
  - (4) Trace mode = Max hold.
  - (5) Sweep = Auto couple.


#### Test Mode


Please refer to the clause 2.4.

#### Test Results

Test Mode	Frequency(MHz)	Result[MHz]	Limit[MHz]	Verdict
GFSK	Hop_2402	1.000	$\geq$ 0.638	PASS
	Hop_2441	1.000	$\geq$ 0.638	PASS
	Hop_2480	1.004	$\geq$ 0.638	PASS
$\pi/4$ -DQPSK	Hop_2402	1.004	$\geq$ 0.864	PASS
	Hop_2441	1.000	$\geq$ 0.864	PASS
	Hop_2480	1.000	$\geq$ 0.864	PASS
8-DPSK	Hop_2402	1.000	$\geq$ 0.862	PASS
	Hop_2441	1.004	$\geq$ 0.862	PASS
	Hop_2480	1.000	$\geq$ 0.862	PASS








### 3.7. Number of Hopping Channel

#### Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(iii)/ RSS-247 5.1 d:

Section	Test Item	Limit
15.247 (a)(iii)/ RSS-247 5.1 d:	Number of Hopping Channel	>15

#### Test Configuration



#### Test Procedure


1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
  - (1) Peak Detector: RBW=100 kHz, VBW $\geq$ RBW, Sweep time= Auto.

#### Test Mode

Please refer to the clause 2.4.

#### Test Result

Modulation type	Channel number	Limit	Result
GFSK	79	$\geq$ 15.00	Pass
$\pi/4$ -DQPSK	79		
8DPSK	79		




### 3.8. Dwell Time

#### Limit

Section	Test Item	Limit
15.247(a)(iii)/ RSS-247 5.1 d	Average Time of Occupancy	0.4 sec

#### Test Configuration



#### Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
  - (1) Spectrum Setting:  $RBW=1\text{MHz}$ ,  $VBW \geq RBW$ .
  - (2) Use video trigger with the trigger level set to enable triggering only on full pulses.
  - (3) Sweep Time is more than once pulse time.
  - (4) Set the center frequency on any frequency would be measure and set the frequency span to zero.
  - (5) Measure the maximum time duration of one single pulse.
  - (6) Set the EUT for packet transmitting.

#### Test Mode

Please refer to the clause 2.4.




**Test Result**




Modulation type	Channel	Frequency (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (ms)	Limit (Second)	Result
GFSK	DH1	2441	0.37	118.40	31.60	$\leq 0.40$	Pass
	DH3	2441	1.62	259.20	31.60		
	DH5	2441	2.87	306.13	31.60		
$\pi/4$ -DQPSK	2DH1	2441	0.37	118.40	31.60	$\leq 0.40$	Pass
	2DH3	2441	1.62	259.20	31.60		
	2DH5	2441	2.87	306.13	31.60		
8-DPSK	3DH1	2441	0.38	121.60	31.60	$\leq 0.40$	Pass
	3DH3	2441	1.62	259.20	31.60		
	3DH5	2441	2.87	306.13	31.60		




Note: 1DH1/2DH1/3DH1 Total of Dwell= Pulse Time\*(1600/2)\*31.6/79

1DH3/2DH3/3DH3 Total of Dwell= Pulse Time\*(1600/4)\*31.6/79

1DH5/2DH5/3DH5 Total of Dwell= Pulse Time\*(1600/6)\*31.6/79

Modulation Type:		GFSK
DH1		 <p>Date: 10.APR.2021 15:48:27</p>
DH3		 <p>Date: 10.APR.2021 15:49:03</p>
DH5		 <p>Date: 10.APR.2021 15:47:47</p>

Modulation Type:		$\pi/4$ -DQPSK
2DH1		 <p>Date: 10.APR.2021 16:10:26</p>
2DH3		 <p>Date: 10.APR.2021 16:10:58</p>
2DH5		 <p>Date: 10.APR.2021 16:09:46</p>

Modulation Type:		8-DPSK
3DH1		 <p>3DH1 Spectrum Analysis</p> <p>Ref Level: 30.00 dBm, Att: 40 dB, SWT: 10 ms, RBW: 1 MHz, VBW: 3 MHz, SGL, TRG: VID, 1Pk Clrw.</p> <p>Carrier Frequency (CF): 2.441 GHz, Sample Points (8000 pts), Time Scale (1.0 ms/).</p> <p>Peak M1[1] at 0.48 dBm, -1.23 μs, 4.29 dB, 375.05 μs.</p> <p>Peak D2[1] at 0.48 dBm, -1.23 μs, 4.29 dB, 375.05 μs.</p> <p>Date: 10.APR.2021 16:45:15</p>
3DH3		 <p>3DH3 Spectrum Analysis</p> <p>Ref Level: 30.00 dBm, Att: 40 dB, SWT: 20 ms, RBW: 1 MHz, VBW: 3 MHz, SGL, TRG: VID, 1Pk Clrw.</p> <p>Carrier Frequency (CF): 2.441 GHz, Sample Points (8000 pts), Time Scale (2.0 ms/).</p> <p>Peak M1[1] at 4.13 dBm, -2.48 μs, 1.95 dB, 1.62020 ms.</p> <p>Peak D2[1] at 4.13 dBm, -2.48 μs, 1.95 dB, 1.62020 ms.</p> <p>Date: 10.APR.2021 16:46:27</p>
3DH5		 <p>3DH5 Spectrum Analysis</p> <p>Ref Level: 30.00 dBm, Att: 40 dB, SWT: 30 ms, RBW: 1 MHz, VBW: 3 MHz, SGL, TRG: VID, 1Pk Clrw.</p> <p>Carrier Frequency (CF): 2.441 GHz, Sample Points (8000 pts), Time Scale (3.0 ms/).</p> <p>Peak M1[1] at 3.13 dBm, -1.23 μs, 1.73 dB, 2.86911 ms.</p> <p>Peak D2[1] at 3.13 dBm, -1.23 μs, 1.73 dB, 2.86911 ms.</p> <p>Date: 10.APR.2021 16:41:54</p>


### 3.9. Peak Output Power

#### Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1) / RSS-247 5.4 b:

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125mW(21dBm)	2400~2483.5

#### Test Configuration



#### Test Procedure

1. The EUT was directly connected to the Power Meter and antenna output port as show in the block diagram above.
2. Read the power value in the test software and record it.

#### Test Mode

Please refer to the clause 2.4.

#### Test Result


Test Mode	Frequency (MHz)	Result[dBm]	Limit[dBm]	Verdict
GFSK	2402	5.32	<=21	PASS
	2441	5.47	<=21	PASS
	2480	4.88	<=21	PASS
$\pi/4$ -DQPSK	2402	7.42	<=21	PASS
	2441	7.59	<=21	PASS
	2480	7.26	<=21	PASS
8-DPSK	2402	7.74	<=21	PASS
	2441	7.97	<=21	PASS
	2480	7.52	<=21	PASS

### 3.10. Duty Cycle

#### Limit

None, for report purposes only.

#### Test Configuration



#### Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
3. Spectrum Setting:

Set analyzer center frequency to test channel center frequency.

Set the span to 0Hz

Set the RBW to 10MHz

Set the VBW to 10MHz

Detector: Peak

Sweep time: Auto


Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.


#### Test Mode


Please refer to the clause 2.4.

#### Test Result

Test Mode	Frequency (MHz)	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
GFSK	2402	2.86	4.97	57.47	0.35	1
	2441	2.86	4.97	57.46	0.35	1
	2480	2.86	4.97	57.47	0.35	1
$\pi/4$ -DQPSK	2402	2.86	4.97	57.53	0.35	1
	2441	2.86	4.97	57.53	0.35	1
	2480	2.86	4.97	57.53	0.35	1
8-DPSK	2402	2.86	4.97	57.58	0.35	1
	2441	2.86	4.97	57.58	0.35	1
	2480	2.86	4.97	57.58	0.35	1









## 3.11. Antenna Requirement

### Requirement

#### FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### Test Result

Complies

Directional gain =  $G_{ANT}$  = 5dBi

Note: Bluetooth mode only supports SISO mode and does not support MIMO transmission.

\*\*\*\*\*THE END\*\*\*\*\*