



Maximum Permissible Exposure Evaluation

FCC ID: 2AR24-X4K-BOX

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

EUT Specification

Product Name:	LED Multimedia Processor
Trade Mark:	Abjen
Model/Type Reference:	Absen X4K-BOX
Listed Model(s):	/
Model Differences:	/
Frequency Band (Operating)	BT: 2402MHz ~ 2480MHz BLE: 2402MHz ~ 2480MHz WLAN: 2412MHz ~ 2462MHz U-NII-1: 5180MHz ~ 5240MHz U-NII-3: 5745MHz ~ 5825MHz
Device Category	☐ Portable (<5mm separation) ☐ Mobile (>20cm separation) ☒ Fixed (>20cm separation) ☐ Others _____
Exposure Classification	☐ Occupational/Controlled exposure (S=5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna Diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna Gain (Max)	AP6275S: BT: 2.98dBi WLAN: ANT1:2.98dBi, ANT2: 2.33dBi RLAN: ANT1:1.00dBi, ANT2: 0.23dBi FRX-M79AU-21: WLAN: ANT1:1.73dBi, ANT2: 0.22dBi RLAN: ANT1: 1.95dBi, ANT2:1.58dBi
Evaluation Applied	☒ MPE Evaluation ☐ SAR Evaluation

FRX-M79AU-21 WIFI ANT 1 & ANT2:

WLAN: 2412MHz ~ 2462MHz; U-NII-1: 5180MHz ~ 5240MHz; U-NII-3: 5745MHz ~ 5825MHz

AP6275S WIFI ANT1&BT ANT:

BT: 2402MHz ~ 2480MHz; BLE: 2402MHz ~ 2480MHz; WLAN: 2412MHz ~ 2462MHz

U-NII-1: 5180MHz ~ 5240MHz; U-NII-3: 5745MHz ~ 5825MHz

AP6275S WIFI ANT2:

WLAN: 2412MHz ~ 2462MHz; U-NII-1: 5180MHz ~ 5240MHz; U-NII-3: 5745MHz ~ 5825MHz

CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-066_A2

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

**Limits for Maximum Permissible Exposure (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
300-1500	--	--	F/300	<6
1500-100000	--	--	5	<6
(B) Limits for General Population/Uncontrolled Exposure				
300-1500	--	--	F/1500	<30
1500-100000	--	--	1	<30

Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where:

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d limit of MPE is 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result**RF Module: AP6275S**

Mode	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Tune Up Tolerance (dB)	Max. Tune Up Power (dBm)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Result
BT/EDR	2480	2.98	4.19	±1	5.19	0.00131	1	PASS
BLE 2M	2440	2.98	2.97	±1	3.97	0.00099	1	PASS
WLAN 802.11G Ant 2	2437	2.33	22.3	±1	23.3	0.07273	1	PASS
RLAN U-NII-1 802.11N (HT40)	5230	1	14.98	±1	15.98	0.00993	1	PASS
RLAN U-NII-3 802.11N (HT40)	5755	1	15.02	±1	16.02	0.01002	1	PASS

RF Module: FRX-M79AU-21

Mode	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Tune Up Tolerance (dB)	Max. Tune Up Power (dBm)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Result
WLAN 802.11b Ant 2	2412	0.22	18.64	±1	19.64	0.01926	1	PASS
RLAN U-NII-1 802.11a Ant 2	5200	1.58	16.8	±1	17.8	0.01725	1	PASS
RLAN U-NII-3 802.11a Ant 2	5745	1.58	16.61	±1	17.61	0.01651	1	PASS

CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-066_A2

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com



Note:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
3. For a more detailed features description, please refer to the RF Test Report.

*****THE END*****