FCC Part 15, Subpart C
Test Report

FCC ID:	2AR2STAH6206D
Applicant:	MMD Hong Kong Holding Limited
Address:	Unit 1006, 10th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Manufacturer:	MMD Hong Kong Holding Limited
Address:	Unit 1006, 10th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Product(s):	Wireless TV headphones
Brand(s):	PHILIPS or
Test Model(s):	TAH6206
Series Model(s):	TAH6206xx/yy (xx=AA-ZZ or blank denoted different color, yy=00-99 denoted different country destination)
Test Date:	Apr. 10, 2022~ Apr. 22, 2022
Issued Date:	May 17, 2022
Issued By:	Hwa-Hsing (Dongguan) Testing Co., Ltd.
Address:	No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China
Test Firm Registration No.:	915896
Standards:	47 CFR FCC Part 15, Subpart C (Section 15.247) ANSI C63.10:2013

The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : *Tank Tan*

Reviewed by : *Scott He*

Approved by : *Harry Li*

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into the account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the federal government. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record **4**

1 Summary of Test Results **5**

1.1 Measurement Uncertainty 5
1.2 Modification Record 5

2 General Information **6**

2.1 General Description of EUT 6
2.2 Description of Channel list 7
2.3 Test Mode Applicability and Tested Channel Detail 8
2.4 Description of Support Units 10
2.4.1 Configuration of System under Test 10

3 Test Types and Results **11**

3.1 Radiated Emission and Band-edge Measurement 11
3.1.1 Limits of Radiated Emission and Band-edge Measurement 11
3.1.2 Test Instruments 12
3.1.3 Test Procedures 13
3.1.4 Deviation from Test Standard 14
3.1.5 Test Setup 15
3.1.6 EUT Operating Conditions 16
3.1.7 Test Results 17
3.2 Conducted Emission Measurement 29
3.2.1 Limits of Conducted Emission Measurement 29
3.2.2 Test Instruments 29
3.2.3 Test Procedures 30
3.2.4 Test Setup 30
3.2.5 EUT Operating Condition 30
3.2.6 Deviation from Test Standard 30
3.2.7 Test Results 31
3.3 Number of Hopping Frequency Used 33
3.3.1 Limits of Hopping Frequency Used Measurement 33
3.3.2 Test Setup 33
3.3.3 Test Instruments 33
3.3.4 Test Procedure 33
3.3.5 Deviation fromTest Standard 33
3.3.6 Test Results 34
3.4 Dwell Time on Each Channel 35
3.4.1 Limits of Dwell Time on Each Channel Measurement 35
3.4.2 Test Setup 35
3.4.3 Test Instruments 35
3.4.4 Test Procedures 35
3.4.5 Deviation from Test Standard 35
3.4.6 Test Results 36
3.5 Channel Bandwidth 39
3.5.1 Limits of Channel Bandwidth Measurement 39
3.5.2 Test Setup 39
3.5.3 Test Instruments 39
3.5.4 Test Procedure 39
3.5.5 Deviation from Test Standard 39
3.5.6 EUT Operating Condition 39
3.5.7 Test Results 40
3.6 Occupied Bandwidth Measurement 42

3.6.1 Test Setup 42
3.6.2 Test Instruments 42
3.6.3 Test Procedure 42
3.6.4 Deviation from Test Standard 42
3.6.5 EUT Operating Conditions 42
3.6.6 Test Results 42
3.7 Hopping Channel Separation 44
3.7.1 Limits of Hopping Channel Separation Measurement 44
3.7.2 Test Setup 44
3.7.3 Test Instruments 44
3.7.4 Test Procedure 44
3.7.5 Deviation from Test Standard 44
3.7.6 Test Results 44
3.8 Maximum Output Power 46
3.8.1 Limits of Maximum Output Power Measurement 46
3.8.2 Test Setup 46
3.8.3 Test Instruments 46
3.8.4 Test Procedure 47
3.8.5 Deviation fromTest Standard 47
3.8.6 EUT Operating Condition 48
3.8.7 Test Results 48
3.9 Conducted Out of Band Emission Measurement 50
3.9.1 Limits of Conducted Out of Band Emission Measurement 50
3.9.2 Tets Setup 50
3.9.3 Test Instruments 50
3.9.4 Test Procedure 51
3.9.5 Deviation from Test Standard 51
3.9.6 EUT Operating Condition 51
3.9.7 Test Results 52

4 Pictures of Test Arrangements 58

5 Test Instruments 59

Appendix – Information on the Testing Laboratories 60

Release Control Record

Issue No.	Description	Date Issued
220412KH01-2-RF-US-01	Original Release	May 17, 2022

1 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247) KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2013;			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit.
15.247(a)(1) (iii)	Number of Hopping Frequency Used	Pass	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	Pass	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	Pass	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
---	Occupied Bandwidth Measurement	Pass	Reference only
15.205 & 209	Radiated Emissions	Pass	Meet the requirement of limit.
15.247(d)	Band Edge Measurement	Pass	Meet the requirement of limit.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note 1: If the Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

Note 2: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (sDoC). The test report has been issued separately.

1.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUTas specified in CISPR 16-4-2:

The listed uncertainties are the worst-case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.66 dB
Radiated Emissions up to 1 GHz	9KHz ~ 30MHz	2.16 dB
	30MHz ~ 1000MHz	3.47 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	4.84 dB
	18GHz ~ 40GHz	4.67 dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

1.2 Modification Record

There were no modifications required for compliance.

2 General Information

2.1 General Description of EUT

Product	Wireless TV headphones
Test Model(s)	TAH6206
Sample No.	HS220412-01-02; HS220412-01-03
Series Model(s)	TAH6206xx/yy (xx=AA-ZZ or blank denoted different color, yy=00-99 denoted different country destination)
Status of EUT	Engineering Prototype
Power Supply Rating	DC 5V from USB port input
Modulation Type	GFSK, π/4 DQPSK, 8DPSK
Transfer Rate	1Mbps, 2Mbps, 3Mbps
Operating Frequency	2402 ~ 2480MHz
Number of Channel	79
Output Power (Peak)	-0.180dBm
Antenna Type	Chip Antenna
Antenna Gain	0.5dBi Maximum peak Gain
Antenna Connector	N/A
Accessory Device	N/A
Cable Supplied	USB-A to Type-C Cable: 0.5m 3.5mm Audio Cable: 1.6m

Note:

1. Please refer to the EUT photo document (Reference No.: 220412KH01-2-01&-02) for detailed product photo.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
3. Model difference: These models are only different for model name for trade purpose.

2.2 Description of Channel list

79 channels are provided to this EUT:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

2.3 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable test items	X-Axis	Y-Axis	Z-Axis	Voltage Supply
Conducted	AC Power Conducted Emission	N/A	N/A	N/A	DC5V
Radiated	Radiated Emissions	√	√	√	
Antenna Port Conducted Measurement	Number of Hopping Frequency Used	N/A	N/A	N/A	
	Dwell Time on Each Channel	N/A	N/A	N/A	
	Band Edge Measurement	N/A	N/A	N/A	
	Antenna Port Emission	N/A	N/A	N/A	
	Conducted power	N/A	N/A	N/A	
	Hopping Channel Separation	N/A	N/A	N/A	
	Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	N/A	N/A	N/A	

1. *: The EUT had been pre-tested on the positioned of each 3 Axis. The worst case was found when positioned on **Z-plane**.
2. "N/A" means no effect.

Test Condition:

Applicable test items	Environmental Conditions	Test Data	Tested by
AC Power Conducted Emission	24.5deg. C, 60%RH	Apr. 23, 2022	Jim Xu
Radiated Emissions	23deg. C, 45%RH	Apr. 24, 2022	Jim Xu
Antenna Port Conducted Measurement	24.5deg. C, 60%RH	Apr. 22, 2022	Dragon Long

Evaluation of difference data rate:

Applicable test items	Modulation Type		The Worst-case Modulation
	π/4DQPSK	8DPSK	
Radiated Emissions	√	√	**8DPSK**
Maximum Peak Output Power	√	√	**8DPSK**
Occupied Bandwidth Measurement	√	√	**8DPSK**
Number of Hopping Frequency Used	√	√	**8DPSK**
Dwell Time on Each Channel	√	√	**8DPSK**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Radiated Emission Test (Above 1 GHz):

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Radiated Emission Test (Below 1 GHz):

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
-	0 to 78	78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Power Line Conducted Emission Test:

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
-	0 to 78	78	FHSS	GFSK	DH5

Antenna Port Conducted Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

2.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	Notebook	DELL	Latitude 5300	N/A	N/A

No.	Signal Cable Description of The Above Support Units
1.	USB serial cable Un-shieldin1.2m
2.	/
3.	/

2.4.1 Configuration of System under Test



3 Test Types and Results

3.1 Radiated Emission and Band-edge Measurement

3.1.1 Limits of Radiated Emission and Band-edge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3
* DTS emissions in non-restricted frequency bands Subclause 11.11 of ANSI C63.10 is applicable. * DTS emissions in restricted frequency bands Subclause 11.12 of ANSI C63.10 is applicable		

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

3.1.2 Test Instruments

Radiated emission below 30MHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	100962	2023-01-13
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	NSEMC003	2023-04-15*
Test software	FARAD	FARAD	EZ_EMCV1.1.4.2	N/A
Loop Antenna	EMCI	HLA 6121	56735	2023-04-15*
Preamplifier	EMCI	EMC001340	980201	2022-09-08
Antenna Tower	MF	MFA-440H	NA	NA
Turn Table	MF	MFT-201SS	NA	NA
Antenna Tower&Turn Table Controller	MF	MF-7802	NA	NA

Frequency Range below 1GHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	NSEMC003	2023-04-15*
EMI Test Receiver	Rohde&Schwarz	ESR7	100962	2023-01-13
Broadband antenna	Schwarzbeck	VULB 9168	00937	2023-09-12*
Signal Amplifier	Com-power	PAM-103	18020051	2022-09-08
Attenuator	Rohde&Schwarz	TS2GA-6dB	18101101	N/A
Test software	FARAD	FARAD	EZ_EMCV1.1.4.2	N/A

Frequency Range 1-18GHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	NSEMC003	2023-04-15*
Horn Antenna	Schwarzbeck	BBHA 9120D	01959	2022-09-12*
Broadband Coaxial Preamplifier	Com-power	PAM-118A	1804003	2022-09-07
Spectrum	Keysight	N9020A	MY51240612	2022-09-08
Antenna Tower	MF	MFA-440H	NA	NA
Turn Table	MF	MFT-201SS	NA	NA
Antenna Tower&Turn Table Controller	MF	MF-7802	NA	NA

Frequency Range 18-40GHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	NSEMC003	2023-04-15*
Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101783	2023-01-13
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170242	2023-04-10*
Pre-Amplifier	EMCI	EMC 184045	980102	2023-01-12
Antenna Tower	MF	MFA-440H	NA	NA
Turn Table	MF	MFT-201SS	NA	NA
Antenna Tower&Turn Table Controller	MF	MF-7802	NA	NA

Note: 1. The calibration interval of the above test instruments is 12/24months(*) and the calibrations are traceable to CEPREI/CHINA.
2. The test was performed in 966(designation number of test lab: CN1255).

3.1.3 Test Procedures

a. Peak emission levels are measured by setting the instrument as follow:

1) RBW& VBWsetting as a function of frequency:

Frequency	RBW	VBW
9kHz~150kHz	200Hz	600Hz
0.15MHz~30MHz	9kHz	30kHz
30MHz~1000MHz	120kHz	300kHz
>1000MHz	1MHz	3MHz

2) Detector = peak.
3) Sweep time = auto.
4) Trace mode = max hold.
5) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Note: If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement

b. Average emission levels are measured by setting the instrument as follow:

- **Trace averaging with continuous EUT transmission at full power**

If the EUT can be configured or modified to transmit continuously (D ≥ 98%). then the average emission levels shall be measured using the following method (with EUT transmitting continuously):

1) RBW=1 MHz (unless otherwise specified).
2) VBW≥ 3 *RBW.
3) Detector =RMS
4) Sweep time = auto.
5) Perform a trace average of at least 100 traces.

- **Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction**

If continuous transmission of the EUT (D≥98%) cannot be achieved and the duty cycle is constant (duty cycle variations are less than ±2%). then the following procedure shall be used

1) The EUT shall be configured to operate at the maximum achievable duty cycle.
2) Measure the duty cycle D of the transmitter output signal as described in 11.6.
3) RBW=1 MHz (unless otherwise specified).
4) VBW≥ 3 *RBW.
5) Detector =RMS
6) Sweep time = auto.
7) Perform a trace average of at least 100 traces.

A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

*If power averaging (rms) mode was used in step 5). then the applicable correction factor is [10 10g (1/ D)], where D is the duty cycle.

**If linear voltage averaging mode was used in step f). then the applicable correction factor is [20 10g (1/D)], where D is the duty cycle.

***If a specific emission is demonstrated to be continuous (D > 98%) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that

- **Reduced VBW Averaqing across ON and OFF times of the EUT transmissions with max hold**

If continuous transmission of the EUT (D > 98%) cannot be achieved and the duty cycle is not constant (duty cycle variations exceed ±2%), then the following procedure shall be used:

1) RBW = 1 MHz.
2) VBW≥1/T.
3) Detector =peak
4) Sweep time = auto.
5) Trace mode = max hold.
6) Allow max hold to run for at least [50 x (1/ D)] traces

c. The EUT was placed on the top of a rotating table 0.8 meters (below 1GHz) / 1.5 meters (1-18GHz) / 1.5 meters (18-40GHz) above the reference ground. The table was rotated 360 degrees to determine the position of the highest radiation.
d. The EUT was set 3 meters away from the interference-receiving antenna (Below 1GHz) & (Above 1-18GHz), which was mounted on the top of a variable-height antenna tower. The EUT was set 1meters away from the interference-receiving antenna (18-40GHz).
e. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
f. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
g. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. Test procedures for measuring FHSS device: The use of a duty cycle correction factor (DCCF) is permitted for calculating average radiated field strength emission levels for an FHSS device in 15.247. This DCCF can be applied when the unwanted emission limit is subject to an average field strength limit (e.g., within a Government Restricted band) and the conditions specified in Section 15.35(c) can be satisfied. The average radiated field strength is calculated by subtracting the DCCF from the maximum radiated field strength level as determined through measurement. The maximum radiated field strength level represents the worst-case (maximum amplitude) RMS measurement of the emission(s) during continuous transmission (i.e., not including any time intervals during which the transmitter is off or is transmitting at a reduced power level). It is also acceptable to apply the DCCF to a measurement performed with a peak detector instead of the specified RMS power averaging detector. Note that Section 15.35(c) specifies that the DCCF shall represent the worst-case (greatest duty cycle) over any 100 msec transmission period. Subclause 7.5 of ANSI C63.10 provides additional measurement guidance applicable to determination of the DCCF.
2. All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 Deviation from Test Standard

No deviation.

3.1.5 Test Setup

Radiated emission below 30MHz:



Frequency Range below 1GHz:



Frequency Range above 1GHz:



Frequency Range 18-40GHz:



*For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT Operating Conditions

Set the EUT under transmission condition continuously at specific channel frequency.

3.1.7 Test Results

9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30 MHz ~ 1GHz Worst-Case Data:

Frequency Range	30MHz ~ 1GHz	Detector Function	Peak (PK) Quasi-peak (QP)
Test Channel	Channel 78		

Antenna Polarity & Test Distance: Horizontal at 3 m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1	125.8059	55.80	-15.84	39.96	43.50	-3.54	peak	200	251
2	159.7586	50.50	-13.04	37.46	43.50	-6.04	peak	300	184
3	202.8745	54.43	-16.67	37.76	43.50	-5.74	peak	300	44
4	220.7241	55.83	-16.13	39.70	46.00	-6.30	peak	200	102
5	498.7303	38.80	-9.06	29.74	46.00	-16.26	peak	200	236
6	569.9688	40.96	-7.64	33.32	46.00	-12.68	peak	200	128

Remarks:

1.Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)

2.Margin value = Emission level – Limit value

Frequency Range	30MHz ~ 1GHz	Detector Function	Peak (PK) Quasi-peak (QP)
Test Channel	Channel 78		

Antenna Polarity & Test Distance: Vertical at 3 m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1	39.7371	40.56	-16.73	23.83	40.00	-16.17	peak	100	215
2	75.3208	43.26	-17.38	25.88	40.00	-14.12	peak	200	188
3	125.8059	44.91	-15.84	29.07	43.50	-14.43	peak	200	75
4	183.8660	44.51	-14.67	29.84	43.50	-13.66	peak	100	302
5	220.7241	50.67	-16.13	34.54	46.00	-11.46	peak	100	315
6	363.5231	40.74	-12.52	28.22	46.00	-17.78	peak	200	245

Remarks:

1.Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)

2. Margin value = Emission level – Limit value

Above 1GHz Data:

GFSK

Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AVG)
Test Channel	Channel 0		

Antenna Polarity & Test Distance: Horizontal at 3 m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1	2354.168	48.28	-1.32	46.96	74.00	-27.04	peak	100	190
2	2354.168	45.23	-1.32	43.91	54.00	-10.09	AVG	100	190
3#	2402.144	114.53	-1.30	113.23			peak	100	190
4#	2402.144	114.24	-1.30	112.94			AVG	100	190
5	4804.000	41.26	4.43	45.69	74.00	-28.31	peak	100	56
6	4804.000	32.77	4.43	37.20	54.00	-16.80	AVG	100	56
7	7206.000	40.03	9.09	49.12	74.00	-24.88	peak	100	215
8	7206.000	29.55	9.09	38.64	54.00	-15.36	AVG	100	215

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
   Margin value = Emission level – Limit value
2. #2402MHz: Fundamental frequency.
3. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AVG)
Test Channel	Channel 0		

Antenna Polarity & Test Distance: Vertical at 3 m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1	2353.978	46.53	-1.32	45.21	74.00	-28.79	peak	100	107
2	2353.978	42.97	-1.32	41.65	54.00	-12.35	AVG	100	107
3#	2402.144	110.24	-1.30	108.94			peak	100	107
4#	2402.144	109.89	-1.30	108.59			AVG	100	107
5	4804.000	40.21	4.43	44.64	74.00	-29.36	peak	100	65
6	4804.000	31.72	4.43	36.15	54.00	-17.85	AVG	100	65
7	7206.000	39.16	9.09	48.25	74.00	-25.75	peak	100	154
8	7206.000	30.05	9.09	39.14	54.00	-14.86	AVG	100	154

Remarks:

1.Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)

Margin value = Emission level – Limit value

2.#2402MHz: Fundamental frequency.

3.The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AVG)
Test Channel	Channel 39		

Antenna Polarity & Test Distance: Horizontal at 3 m									
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1 #	2441.000	108.11	-1.27	106.84			peak	100	206
2 #	2441.000	107.01	-1.27	105.74			AVG	100	206
3	4882.000	43.67	4.66	48.33	74.00	-25.67	peak	100	174
4	4882.000	34.48	4.66	39.14	54.00	-14.86	AVG	100	174
5	7323.000	38.61	9.24	47.85	74.00	-26.15	peak	100	211
6	7323.000	29.96	9.24	39.20	54.00	-14.80	AVG	100	211
Antenna Polarity & Test Distance: Vertical at 3 m									
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1 #	2441.000	106.74	-1.27	105.47			peak	100	234
2 #	2441.000	105.89	-1.27	104.62			AVG	100	234
3	4882.000	42.89	4.66	47.55	74.00	-26.45	peak	100	269
4	4882.000	34.49	4.66	39.15	54.00	-14.85	AVG	100	269
5	7323.000	39.12	9.24	48.36	74.00	-25.64	peak	100	147
6	7323.000	28.90	9.24	38.14	54.00	-15.86	AVG	100	147

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
   Margin value = Emission level – Limit value
2. #2402MHz: Fundamental frequency.
3. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AVG)
Test Channel	Channel 78		

Antenna Polarity & Test Distance: Horizontal at 3 m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1#	2479.852	101.13	-1.24	99.89			peak	100	186
2#	2479.852	100.83	-1.24	99.59			AVG	100	186
3	2483.500	58.14	-1.25	56.89	74.00	-17.11	peak	100	186
4	2483.500	46.02	-1.25	44.77	54.00	-9.23	AVG	100	186
5	4804.000	41.81	4.43	46.24	74.00	-27.76	peak	100	57
6	4804.000	34.21	4.43	38.64	54.00	-15.36	AVG	100	57
7	7206.000	39.22	9.09	48.31	74.00	-25.69	peak	100	115
8	7206.000	27.15	9.09	36.24	54.00	-17.76	AVG	100	115

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
   Margin value = Emission level – Limit value
2. #2480MHz: Fundamental frequency.
3. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AVG)
Test Channel	Channel 78		

Antenna Polarity & Test Distance: Vertical at 3 m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1#	2479.896	101.58	-1.24	100.34			peak	100	187
2#	2479.896	101.31	-1.24	100.07			AVG	100	187
3	2483.500	59.75	-1.25	58.50	74.00	-15.50	peak	100	187
4	2483.500	48.24	-1.25	46.99	54.00	-7.01	AVG	100	187
5	4804.000	41.19	4.43	45.62	74.00	-28.38	peak	100	46
6	4804.000	34.03	4.43	38.46	54.00	-15.54	AVG	100	46
7	7206.000	38.23	9.09	47.32	74.00	-26.68	peak	100	210
8	7206.000	28.12	9.09	37.21	54.00	-16.79	AVG	100	210

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
   Margin value = Emission level – Limit value
2. #2480MHz: Fundamental frequency.
3. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

8DPSK

Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AVG)
Test Channel	Channel 0		

Antenna Polarity & Test Distance: Horizontal at 3 m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1	2369.589	46.79	-1.31	45.48	74.00	-28.52	peak	100	191
2	2369.589	32.87	-1.31	31.56	54.00	-22.44	AVG	100	191
3#	2402.144	101.34	-1.30	100.04			peak	100	191
4#	2402.144	97.15	-1.30	95.85			AVG	100	191
5	4804.000	42.50	4.43	46.93	74.00	-27.07	peak	200	44
6	4804.000	34.27	4.43	38.70	54.00	-15.30	AVG	200	44
	7206.000	40.74	9.09	49.83	74.00	-24.17	peak	100	114
	7206.000	29.33	9.09	38.42	54.00	-15.58	AVG	100	114

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
   Margin value = Emission level – Limit value
2. #2402MHz: Fundamental frequency.
3. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AVG)
Test Channel	Channel 0		

Antenna Polarity & Test Distance: Vertical at 3 m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1	2335.701	43.09	-1.32	41.77	74.00	-32.23	peak	100	124
2	2335.701	31.39	-1.32	30.07	54.00	-23.93	AVG	100	124
3#	2402.144	96.46	-1.30	95.16			peak	100	124
4#	2402.144	93.15	-1.30	91.85			AVG	100	124
5	4804.000	43.34	4.43	47.77	74.00	-26.23	peak	100	75
6	4804.000	32.41	4.43	36.84	54.00	-17.16	AVG	100	75
7	7206.000	40.55	9.09	49.64	74.00	-24.36	peak	300	114
8	7206.000	29.37	9.09	38.46	54.00	-15.54	AVG	300	114

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
   Margin value = Emission level – Limit value
2. #2402MHz: Fundamental frequency.
3. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AVG)
Test Channel	Channel 39		

Antenna Polarity & Test Distance: Horizontal at 3 m									
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1#	2441.000	106.88	-1.27	105.61			peak	100	302
2#	2441.000	105.63	-1.27	104.36			AVG	100	302
3	4882.000	45.98	4.66	50.64	74.00	-23.36	peak	200	161
4	4882.000	35.56	4.66	40.22	54.00	-13.78	AVG	200	161
5	7323.000	45.07	9.24	54.31	74.00	-19.69	peak	100	223
6	7323.000	29.37	9.24	38.61	54.00	-15.39	AVG	100	223
Antenna Polarity & Test Distance: Vertical at 3 m									
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1#	2441.000	104.12	-1.27	102.85			peak	100	203
2#	2441.000	102.81	-1.27	101.54			AVG	100	203
3	4882.000	45.46	4.66	50.12	74.00	-23.88	peak	100	164
4	4882.000	36.16	4.66	40.82	54.00	-13.18	AVG	100	164
5	7323.000	44.23	9.24	53.47	74.00	-20.53	peak	200	145
6	7323.000	28.98	9.24	38.22	54.00	-15.78	AVG	200	145

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
   Margin value = Emission level – Limit value
2. #2441MHz: Fundamental frequency.
3. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AVG)
Test Channel	Channel 78		

Antenna Polarity & Test Distance: Horizontal at 3 m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1#	2479.896	100.98	-1.24	99.74			peak	100	187
2#	2479.896	96.66	-1.24	95.42			AVG	100	187
3	2483.500	61.00	-1.25	59.75	74.00	-14.25	peak	100	187
4	2483.500	49.69	-1.25	48.44	54.00	-5.56	AVG	100	187
5	4960.000	45.46	4.90	50.36	74.00	-23.64	peak	100	334
6	4960.000	36.31	4.90	41.21	54.00	-12.79	AVG	100	334
7	7440.000	43.66	9.40	53.06	74.00	-20.94	peak	100	264
8	7440.000	29.12	9.40	38.52	54.00	-15.48	AVG	100	264

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
   Margin value = Emission level – Limit value
2. #2480MHz: Fundamental frequency.
3. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AVG)
Test Channel	Channel 78		

Antenna Polarity & Test Distance: Vertical at 3 m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detecter	Antenna Height (cm)	Table Angle (Degree)
1#	2479.984	98.20	-1.24	96.96			peak	386	132
2#	2479.984	93.88	-1.24	92.64			AVG	386	132
3	2483.500	57.17	-1.25	55.92	74.00	-18.08	peak	386	132
4	2483.500	47.26	-1.25	46.01	54.00	-7.99	AVG	386	132
5	4960.000	44.86	4.90	49.76	74.00	-24.24	peak	100	89
6	4960.000	34.92	4.90	39.82	54.00	-14.18	AVG	100	89
7	7440.000	43.34	9.40	52.74	74.00	-21.26	peak	100	214
8	7440.000	28.81	9.40	38.21	54.00	-15.79	AVG	100	214

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
   Margin value = Emission level – Limit value
2. #2480MHz: Fundamental frequency.
3. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

3.2 Conducted Emission Measurement

3.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Due Date of Calibration
EMI Test Receiver Rohde&Schwarz	ESR 7	101961	2023-01-13
Artificial Mains Network Rohde&Schwarz	ENV216	3560.6550.15	2023-01-12
Test software FARAD	EZ_EMC V1.1.4.2	N/A	N/A

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA.
2. The test was performed in Shielded Room 1.

3.2.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit – 20dB) was not recorded.

Note: All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.5 EUT Operating Condition

Set the EUT under transmission condition continuously at specific channel frequency.

3.2.6 Deviation from Test Standard

No deviation.

3.2.7 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution andwidth	Quasi-Peak (QP) / Average (AV), 9kHz

Phase of Power: Line (L)



No.	Frequency	Reading	Correcttion Factor	Emission Level	Limit	Margin	Remark
	(MHz)	(dBuV)	dB	(dBuV)	(dBuV)	(dB)	Detecter
1	0.1500	29.53	10.19	39.72	66.00	-26.28	peak
2	0.1522	14.03	10.18	24.21	55.88	-31.67	AVG
3	0.5392	19.98	10.10	30.08	46.00	-15.92	AVG
4	0.5482	27.54	10.10	37.64	56.00	-18.36	peak
5	1.9770	17.00	10.09	27.09	46.00	-18.91	AVG
6	2.3820	27.01	10.09	37.10	56.00	-18.90	peak
7	5.9573	18.17	10.00	28.17	50.00	-21.83	AVG
8	6.2183	31.87	10.00	41.87	60.00	-18.13	peak
9	7.4063	33.49	10.03	43.52	60.00	-16.48	peak
10	8.6145	19.93	10.07	30.00	50.00	-20.00	AVG
11	12.8783	38.42	10.21	48.63	60.00	-11.37	peak
12	14.3858	25.76	10.24	36.00	50.00	-14.00	AVG

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution andwidth	Quasi-Peak (QP) / Average (AV), 9kHz

Phase of Power: Neutral (N)



No.	Frequency	Reading	Correct Factor	Emission Level	Limit	Margin	Remark
	(MHz)	(dBuV)	dB	(dBuV)	(dBuV)	(dB)	Detecter
1	0.1522	29.29	10.18	39.47	65.88	-26.41	peak
2	0.1522	13.09	10.18	23.27	55.88	-32.61	AVG
3	0.5415	19.14	10.11	29.25	46.00	-16.75	AVG
4	0.5482	29.21	10.11	39.32	56.00	-16.68	peak
5	0.9690	13.19	10.05	23.24	46.00	-22.76	AVG
6	1.1017	24.03	10.05	34.08	56.00	-21.92	peak
7	1.4438	14.52	10.07	24.59	46.00	-21.41	AVG
8	1.4865	24.97	10.07	35.04	56.00	-20.96	peak
9	4.8728	11.92	10.04	21.96	46.00	-24.04	AVG
10	5.7053	23.98	10.00	33.98	60.00	-26.02	peak
11	13.1055	28.69	10.24	38.93	60.00	-21.07	peak
12	13.9200	19.01	10.25	29.26	50.00	-20.74	AVG

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.

3.3 Number of Hopping Frequency Used

3.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

3.3.2 Test Setup



Spectrum analyzer test configuration

3.3.3 Test Instruments

Refer to section 5 to get information of above instrument.

3.3.4 Test Procedure

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
d. Set the SA on View mode and then plot the result on SA screen.
e. Repeat above procedures until all frequencies measured were complete.

3.3.5 Deviation fromTest Standard

No deviation.

3.3.6 Test Results

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK



8DPSK



3.4 Dwell Time on Each Channel

3.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.4.2 Test Setup



Spectrum analyzer test configuration

3.4.3 Test Instruments

Refer to section 5 to get information of above instrument.

3.4.4 Test Procedures

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
e. Repeat above procedures until all different time-slot modes have been completed.

3.4.5 Deviation from Test Standard

No deviation.

3.4.6 Test Results

GFSK

Mode	Number of Hopping Channel	Number of transmision in a period (channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	Verdict
		Period (sec)	Sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	3.16	23	230	0.351	80.73	400	Pass
DH3	79	31.6	3.16	14	140	1.574	220.36	400	Pass
DH5	79	31.6	3.16	10	100	1.895	189.50	400	Pass

Note: Test plots of the transmitting time slot are shown as below.

8DPSK

Mode	Number of Hopping Channel	Number of transmision in a period (channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	Verdict
		Period (sec)	Sweep time (sec)	times in a sweep	times in a period				
2DH1	79	31.6	3.16	19	190	0.366	69.54	400	Pass
2DH3	79	31.6	3.16	9	90	1.615	145.35	400	Pass
2DH5	79	31.6	3.16	7	70	2.861	200.27	400	Pass

Note: Test plots of the transmitting time slot are shown as below.

GFSK

DH1





DH3





DH5





8DPSK

3DH1





3DH3





3DH5





3.5 Channel Bandwidth

3.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5 MHz, if the 20 dB bandwidth of hopping channel is greater than 25 kHz, two-thirds 20 dB bandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

3.5.2 Test Setup



Spectrum analyzer test configuration

3.5.3 Test Instruments

Refer to section 5 to get information of above instrument.

3.5.4 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the instrument equal to the highest peak value.
c. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
d. Repeat above procedures until all frequencies measured were complete.

3.5.5 Deviation from Test Standard

No deviation.

3.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

3.5.7 Test Results

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	
		GFSK	8DPSK
0	2402	0.927	1.290
39	2441	0.891	1.275
78	2480	0.948	1.284

The test plots as below page:

GFSK	8DPSK
CH0	CH0
CH39	CH39
CH78	CH78

3.6 Occupied Bandwidth Measurement

3.6.1 Test Setup



Spectrum analyzer test configuration

3.6.2 Test Instruments

Refer to section 5 to get information of above instrument

3.6.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5%of the total mean power of a given emission.

3.6.4 Deviation from Test Standard

No deviation.

3.6.5 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.6.6 Test Results

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	
		GFSK	8DPSK
0	2402	0.85640	1.2098
39	2441	0.85613	1.1776
78	2480	0.87218	1.1803

GFSK	8DPSK
	
CH0	CH0
	
CH39	CH39
	
CH78	CH78

3.7 Hopping Channel Separation

3.7.1 Limits of Hopping Channel Separation Measurement

At least 25 kHz or two-third of 20 dB hopping channel bandwidth (whichever is greater).

3.7.2 Test Setup



3.7.3 Test Instruments

Refer to section 5 to get information of above instrument.

3.7.4 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
c. By using the MaxHold function record the separation of two adjacent channels.
d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
e. Repeat above procedures until all frequencies measured were complete.

3.7.5 Deviation from Test Standard

No deviation.

3.7.6 Test Results

Channel No.	Frequency (MHz)	Adjacent Channel Separation (MHz)		Minimum Limit (MHz)		Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK	
0	2402	0.999	0.999	0.618	0.860	Pass
39	2441	1.002	1.002	0.594	0.850	Pass
78	2480	0.996	0.999	0.632	0.856	Pass

Note: The minimum limit is two-third 20 dB bandwidth.

GFSK	8DPSK
	
CH0	CH0
	
CH39	CH39
	
CH78	CH78

3.8 Maximum Output Power

3.8.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

3.8.2 Test Setup



Spectrum analyzer test configuration

3.8.3 Test Instruments

Refer to section 5 to get information of above instrument.

3.8.4 Test Procedure

Measurement using a spectrum analyzer (SA)，Selection of test method：

The proper test method is selected based on the following criteria:

a) **Method AVGSA-1 or method AVGSA-1A (alternative)** shall be applied if either of the following conditions can be satisfied:
1) The EUT transmits continuously (or with a D> 98%).
2) Sweep triggering can be implemented in such a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the instrument configured as in method AVGSA-1) is equal to or shorter than the duration T of each transmission from the EUT, and if those transmissions exhibit full power throughout their durations.

b) **Method AVGSA-2 or method AVGSA-2A (alternative)** shall be applied if the conditions of the preceding item a) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than +2%.

c) **Method AVGSA-3 or method AVGSA-3A** (alternative) shall be applied if the conditions of the preceding item a) and item b) cannot be achieved.

Method AVGSA-3 or method AVGSA-3A:

a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b) Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c) SA Setting:
1* Set span to at least 1.5 times the OBW
2* Set sweep trigger to "free run."
3* Set RBW= 1% to 5% of the OBW. not to exceed 1MHz.
4* Set VBW ≥ 3 x RBW
5* Number of points in sweep≥2 x span /RBW.(This gives bin-to-bin spacing ≤ RBW / 2. so that narrowband signals are not lost between frequency bins).
6* Sweep time ≤ (number of points in sweep) x T. where T is defined in 11.6. If this gives a sweep time less than the auto sweep time of the instrument. then method AVGSA-3 shall not be used (use AVGSA-3A). The purpose of this step is so that the averaging time in each bin is less than or equal to the minimum time of a transmission.
7* Detector =RMS (power averaging).
8* Trace mode =max hold.
9* Allow max hold to run for at least 60 s or longer as needed to allow the trace to stabilize.
10* Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function. then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW

d. Measure the captured power within the band and recording the plot.

e. Repeat above procedures until all frequencies required were complete.

3.8.5 Deviation fromTest Standard

No deviation.

3.8.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

3.8.7 Test Results

Peak power

Channel No.	Freq. (MHz)	Output Power (mW)		Output Power (dBm)		Power Limit (mW)	Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	0.919	**0.959**	-0.365	**-0.180**	125	Pass
39	2441	0.727	0.755	-1.383	-1.218	125	Pass
78	2480	0.627	0.677	-2.030	-1.693	125	Pass

Peak Power Spectrum Plot

GFSK	8DPSK
CH0	CH0
CH39	CH39
	
CH78	CH78

3.9 Conducted Out of Band Emission Measurement

3.9.1 Limits of Conducted Out of Band Emission Measurement

a. **If the maximum peak conducted output power procedure was used to determine compliance as described in 11.9.1**, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

b. If maximum conducted (average) output power was used to determine compliance as described in 11.9.2. then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc)

3.9.2 Tets Setup

- DTS emissions in non-restricted frequency bands Subclause 11.11 of ANSI C63.10 is applicable.
- DTS emissions in restricted frequency bands Subclause 11.12 of ANSI C63.10 is applicable



Spectrum analyzer test configuration

3.9.3 Test Instruments

Refer to section 5 to get information of above instrument.

3.9.4 Test Procedure

a. Establish a reference level by using the following procedure:

1) Set instrument center frequency to DTS channel center frequency.
2) Set the span to 21.5 times the DTS bandwidth)
3) Set the RBW= 100 kHz)
4) Set the VBW ≥3 x RBW
5) Detector = peak
6) Sweep time = auto coupling
7) Trace mode =max hold
8) Allow trace to fully stabilize
9) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

b. Establish an emission level by using the following procedure:

1) Set the center frequency and span to encompass frequency range to be measured.
2) Set the RBW = 100 kHz
3) Set the VBW ≥ 300 kHz.
4) Detector = peak.
5) Sweep time = auto couple.
6) Trace mode = max hold.
7) Allow trace to fully stabilize.
8) Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

3.9.5 Deviation from Test Standard

No deviation.

3.9.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

3.9.7 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK

Hopping Disabled_Low Channel	Hopping Disabled_Mid Channel
	
	

Hopping Disabled_High Channel





8DPSK

Hopping Disabled_Low Channel	Hopping Disabled_Mid Channel
	
	
	

Hopping Disabled_High Channel





Bandedge:

GFSK

Hopping Disabled_Low Channel	Hopping Disabled_High Channel
	

8DPSK

Hopping Disabled_Low Channel	Hopping Disabled_High Channel
	

GFSK

Hopping Enabled_Low Channel	Hopping Enabled_High Channel
	

8DPSK

Hopping Enabled_Low Channel	Hopping Enabled_High Channel
	

4 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

5 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Due Date of Calibration
Spectrum Keysight	N9020A	MY51240612	2022-09-08
Spectrum Analyzer Rohde&Schwarz	FSV-40N	101783	2023-01-13
Power Meter 10Hz~18GHz Tonscend	JS0806-2	188060126	2022-09-08
Signal generator Keysight	E4421B	GB40051020	2022-09-12
Signal generator Keysight	N5182A	MY47420944	2022-09-08
Test Software Tonscend	JS0806-2	NA	NA
Hygrothermograph Yuhuaze	HTC-1	NA	2022-09-09

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA.
2. The test was performed in Chamber 1.

Appendix – Information on the Testing Laboratories

We, Hwa-Hsing (Dongguan) Co., Ltd., A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values "HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT", commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China
Contact Tel: 0769-83078199
Email: Customerservice.dg@hwa-hsing.com
Web Site: www.hwa-hsing.com

The address and road map of all our labs can be found in our web site also.

--- END ---