

5.8 CONDUCTED OUT OF BAND EMISSION

Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247(d) RSS-247 Issue 2, Section 5.5
Test Method:	ANSI C63.10-2013 Section 6.10.4 & Section 7.8.8
Limit:	In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.
Test Procedure:	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings:

Step 1: Measurement Procedure REF

- Set instrument center frequency to 2400 MHz or 2483.5 MHz.
- Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
- Set the RBW = 100 kHz.
- Set the VBW $\geq 3 \times$ RBW.
- Detector = peak.
- Sweep time = auto couple.
- Sweep points $\geq 2 \times$ Span/RBW
- Trace mode = max hold.
- Allow the trace to stabilize.
- Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.


Step 2: Measurement Procedure OOB

- Set RBW = 100 kHz.
- Set VBW ≥ 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup:	Refer to section 4.5.3 for details.
Instruments Used:	Refer to section 3 for details
Test Mode:	Hopping Frequencies Transmitter mode
Test Results:	Pass
Test Data:	

The test plots as follows:



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1







5.9 RADIATED SPURIOUS EMISSIONS

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209
RSS-Gen Issue 5, Section 6.13/8.9/8.10

Test Method: ANSI C63.10-2013 Section 6.3 & 6.5 & 6.6

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

Spurious Emissions

Frequency	Field strength (microvolt/meter)	Limit (dB μ V/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

- 1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

2. Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

- 2) Test the EUT in the lowest channel ,middle channel, the Highest channel
- 3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the Y axis positioning which it is worse case.
- 4) Repeat above procedures until all frequencies measured was complete.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

Radiated Emission Test Data (9 KHz ~ 30 MHz):


The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Left Earbuds

Radiated Emission Test Data (30 MHz ~ 1 GHz):


Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.513	26.48	-4.65	21.83	40.00	-18.17	QP
2	47.703	34.36	-13.04	21.32	40.00	-18.68	QP
3	50.461	35.40	-14.73	20.67	40.00	-19.33	QP
4	651.383	25.07	0.37	25.44	46.00	-20.56	QP
5	739.214	25.35	2.00	27.35	46.00	-18.65	QP
6	875.013	24.55	3.87	28.42	46.00	-17.58	QP

Vertical



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	32.411	26.60	-4.77	21.83	40.00	-18.17	QP
2	250.486	26.63	-8.82	17.81	46.00	-28.19	QP
3	401.105	25.41	-4.43	20.98	46.00	-25.02	QP
4	651.383	25.65	0.37	26.02	46.00	-19.98	QP
5	771.047	25.11	2.13	27.24	46.00	-18.76	QP
6	893.656	24.37	4.26	28.63	46.00	-17.37	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>


UTTR-RF-RSS247-V1.1

Right Earbuds

Radiated Emission Test Data (30 MHz ~ 1 GHz):

Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.212	26.19	-4.42	21.77	40.00	-18.23	QP
2	50.461	34.34	-14.73	19.61	40.00	-20.39	QP
3	250.486	28.25	-8.82	19.43	46.00	-26.57	QP
4	458.399	26.29	-3.70	22.59	46.00	-23.41	QP
5	749.676	25.15	1.89	27.04	46.00	-18.96	QP
6	893.656	24.45	4.26	28.71	46.00	-17.29	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Vertical



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.425	25.67	-4.46	21.21	40.00	-18.79	QP
2	43.845	28.64	-10.40	18.24	40.00	-21.76	QP
3	250.486	27.00	-8.82	18.18	46.00	-27.82	QP
4	491.770	25.98	-3.03	22.95	46.00	-23.05	QP
5	809.924	25.37	2.64	28.01	46.00	-17.99	QP
6	887.398	24.50	4.12	28.62	46.00	-17.38	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Left Earbuds

Radiated Emission Test Data (Above 1GHz):
Lowest Channel:

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	39.34	-2.34	37.00	74.00	-37.00	Peak	Horizontal
2	4804.00	28.08	-2.34	25.74	54.00	-28.26	Average	Horizontal
3	7206.00	38.82	1.43	40.25	74.00	-33.75	Peak	Horizontal
4	7206.00	26.69	1.43	28.12	54.00	-25.88	Average	Horizontal
5	4804.00	40.16	-2.34	37.82	74.00	-36.18	Peak	Vertical
6	4804.00	27.99	-2.34	25.65	54.00	-28.35	Average	Vertical
7	7206.00	39.21	1.43	40.64	74.00	-33.36	Peak	Vertical
8	7206.00	26.69	1.43	28.12	54.00	-25.88	Average	Vertical

Middle Channel:

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4882.00	39.70	-2.30	37.40	74.00	-36.60	Peak	Horizontal
2	4882.00	25.35	-2.30	23.05	54.00	-30.95	Average	Horizontal
3	9764.00	38.49	1.61	40.10	74.00	-33.90	Peak	Horizontal
4	9764.00	28.60	1.61	30.21	54.00	-23.79	Average	Horizontal
5	4882.00	38.79	-2.30	36.49	74.00	-37.51	Peak	Vertical
6	4882.00	28.43	-2.30	26.13	54.00	-27.87	Average	Vertical
7	9764.00	40.22	1.61	41.83	74.00	-32.17	Peak	Vertical
8	9764.00	28.74	1.61	30.35	54.00	-23.65	Average	Vertical

Highest Channel:

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4960.00	40.09	8.41	48.50	74.00	-25.50	Peak	Horizontal
2	4960.00	29.33	8.41	28.98	54.00	-25.02	Average	Horizontal
3	9920.00	40.55	-0.43	40.12	74.00	-33.88	Peak	Horizontal
4	9920.00	29.47	-0.43	27.74	54.00	-26.26	Average	Horizontal
5	4960.00	40.20	-1.16	39.04	74.00	-34.96	Peak	Vertical
6	4960.00	29.33	-1.16	26.45	54.00	-27.55	Average	Vertical
7	9920.00	40.24	-1.80	38.44	74.00	-35.56	Peak	Vertical
8	9920.00	28.61	-1.80	26.15	54.00	-27.85	Average	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Right Earbuds

Radiated Emission Test Data (Above 1GHz):
Lowest Channel:

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	40.01	-2.34	37.67	74.00	-36.33	Peak	Horizontal
2	4804.00	26.26	-2.34	23.92	54.00	-30.08	Average	Horizontal
3	7206.00	39.28	1.43	40.71	74.00	-33.29	Peak	Horizontal
4	7206.00	27.86	1.43	29.29	54.00	-24.71	Average	Horizontal
5	4804.00	38.64	-2.34	36.30	74.00	-37.70	Peak	Vertical
6	4804.00	28.08	-2.34	25.74	54.00	-28.26	Average	Vertical
7	7206.00	39.80	1.43	41.23	74.00	-32.77	Peak	Vertical
8	7206.00	27.86	1.43	29.29	54.00	-24.71	Average	Vertical

Middle Channel:

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4882.00	39.38	-2.30	37.08	74.00	-36.92	Peak	Horizontal
2	4882.00	27.35	-2.30	25.05	54.00	-28.95	Average	Horizontal
3	9764.00	38.33	1.61	39.94	74.00	-34.06	Peak	Horizontal
4	9764.00	28.74	1.61	30.35	54.00	-23.65	Average	Horizontal
5	4882.00	40.04	-2.30	37.74	74.00	-36.26	Peak	Vertical
6	4882.00	25.59	-2.30	23.29	54.00	-30.71	Average	Vertical
7	9764.00	38.74	1.61	40.35	74.00	-33.65	Peak	Vertical
8	9764.00	28.67	1.61	30.28	54.00	-23.72	Average	Vertical

Highest Channel:

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4960.00	39.63	-2.25	37.38	74.00	-36.62	Peak	Horizontal
2	4960.00	28.26	-2.25	26.01	54.00	-27.99	Average	Horizontal
3	9920.00	39.46	1.81	41.27	74.00	-32.73	Peak	Horizontal
4	9920.00	28.74	1.81	30.55	54.00	-23.45	Average	Horizontal
5	4960.00	40.27	-2.25	38.02	74.00	-35.98	Peak	Vertical
6	4960.00	28.41	-2.25	26.16	54.00	-27.84	Average	Vertical
7	9920.00	39.12	1.81	40.93	74.00	-33.07	Peak	Vertical
8	9920.00	28.67	1.81	30.48	54.00	-23.52	Average	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

5.10 BAND EDGE MEASUREMENTS (RADIATED)

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209
RSS-247 Issue 2, Section 5.5

Test Method: ANSI C63.10-2013 Section 6.10.5

Limits:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Frequency	Limit (dB μ V/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).



1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

Left Earbuds



Shenzhen UnionTrust Quality and Technology Co., Ltd.



Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888



Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Right Earbuds



Shenzhen UnionTrust Quality and Technology Co., Ltd.



Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
