

# Shenzhen Inlong Photoelectricity Co.,Ltd

Four floor, G building, No. 204 art, StrongIndustria I Zone, Golf Road, Guanlan Street, Shenzhen City, Guangdong Province, China  
(Tel):0755-28376607  
(Contact person):Xuefeng Lu  
E-mail: [947723450@qq.com](mailto:947723450@qq.com)  
(Fax): 0755-28376607

---

To whom it may concern,

## Statement

The product (FCCID:2AR7H-INL-08) meets all six conditions of KDB680106 D01v03 section 5.as follows:

1. Power transfer frequency is less than 1MHz.

Power transfer frequency is 110~205KHz.conform.

2. Output power from each primary coil is less than or equal to 15 watts.

Output power is 7.5W.conform.

3. The transfer system includes only single primary and secondary coil.This includes charging system that may have multiple primary coils and client that are able to detect and allow coupling only between individual pairs of coils.

The transfer system includes only single primary coils.conform.

4. Client device is placed directly in contact with the transmitter.

Client device is placed directly in contact with the transmitter,conform.

5. Mobil exposure conditions only(portable exposure conditions are not covered by this exclusion)

Conform.

6. The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simulations transmitting coils are demonstrated to be less than 50% of the MPE limit.

Conform.Please refer to RFExposure

Yours sincerely,

Name: Lihui Huang

Position:Manager

Company: Shenzhen Inlong Photoelectricity Co.,Ltd

