

FCC RF EXPOSURE REPORT

For

IEEE 802.11a/b/g/n 2T2R USB Wi-Fi Module

MODEL NUMBER: SKO.W618U.1_638BU

FCC ID: 2AR82-SKOW618U101 IC: 24728- SKOW618U101

REPORT NUMBER: 4789279523.1-3

ISSUE DATE: December 25, 2019

Prepared for

Guangzhou Shikun Electronics Co., Ltd NO.6 Liankun Road, Huangpu District, Guangzhou, China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone, Dongguan, People's Republic of China

> Tel: +86 769-22038881 Fax: +86 769 33244054 Website: www.ul.com






TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	.3
2.	TEST METHODOLOGY	.3
3.	FACILITIES AND ACCREDITATION	.4
4	REQUIREMENT	F



PASS

Page 3 of 6

1. ATTESTATION OF TEST RESULTS

A	рp	licant	Inform	ation
---	----	--------	--------	-------

Company Name: Guangzhou Shikun Electronics Co., Ltd

Address: NO.6 Liankun Road, Huangpu District, Guangzhou, China

Manufacturer Information

Company Name: Guangzhou Shikun Electronics Co., Ltd

Address: NO.6 Liankun Road, Huangpu District, Guangzhou, China

EUT Description

EUT Name: IEEE 802.11a/b/g/n 2T2R USB Wi-Fi Module

Model: SKO.W618U.1_638BU

Sample Status: Normal

Sample Received Date: December 6, 2019

Date of Tested: December 6~December 25, 2019

APPLICABLE STANDARDS

STANDARD TEST RESULTS

FCC 47CFR§2.1091

KDB-447498 D01 V06

Prepared By: Checked By:

Kebo Zhang

kelo. Thurs

Project Engineer

Shawn Wen Laboratory Leader

Shemy les

Approved By:

Stephen Guo

Laboratory Manager

Sephenbuo



Page 4 of 6

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

3. FACILITIES AND ACCREDITATION

5. FACILITIES AND ACCREDITATION					
	A2LA (Certificate No.: 4102.01)				
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.				
	has been assessed and proved to be in compliance with A2LA.				
	FCC (FCC Designation No.: CN1187)				
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.				
	Has been recognized to perform compliance testing on equipment subject				
	to the Commission's Delcaration of Conformity (DoC) and Certification				
	rules				
Accreditation	ISED(Company No.: 21320)				
Certificate	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.				
Continuato	has been registered and fully described in a report filed with				
	Industry Canada. The Company Number is 21320.				
	VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)				
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.				
	has been assessed and proved to be in compliance with VCCI, the				
	Membership No. is 3793.				
	Facility Name:				
	Chamber D, the VCCI registration No. is G-20019 and R-20004				
	Shielding Room B, the VCCI registration No. is C-20012 and T-20011				

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.

Page 5 of 6

4. REQUIREMENT

LIMIT

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ² , H ² or S (minutes)			
0.3-1.34	614	1.63	(100)*	30			
1.34-30	824/f	2.19/f	(180/f2)*	30			
30-300	27.5	0.073	0.2	30			
300-1500			f/150	30			
1500-100,000			1.0	30			

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm² is available for this EUT.

MPE CALCULATION METHOD

 $S = PG/(4\pi R^2)$

where: S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



Page 6 of 6

CALCULATED RESULTS

Radio Frequency Radiation Exposure Evaluation

reading residency reading in Experience I remaind								
WIFI 2.4G (Worst case)								
Operating	Max. Tune up Power	Max. Antenna Gain	Power density	Limit				
Mode	ode (dBm)	(dBi)	(mW/ cm ²)					
802.11b SISO	18	1.81	0.019043	1				

WIFI5G (Worst case)								
Operating	Max. Tune up Power	Max. Antenna Gain	Power density	Limit				
Mode	(dBm)	(dBi)	(mW/ cm ²)					
802.11a SISO	16	2.03	0.01264	1				

WIFI 2.4G (Worst case)							
Operating Mode	Antenna port	Max. Tune up Power	Max. Antenna Gain	Single Power density	Total Power density	Limit	
		(dBm)	(dBi)	(mW/ cm ²)	(mW/ cm ²)		
802.11n HT20	0	14	1.68	0.007357	0.014938	1	
MIMO	1	14	1.81	0.007581	0.014936	1	

WIFI 5G (Worst case)							
Operating A Mode	ΔntΔnna I	Max. Tune up Power	Max. Antenna Gain	Single Power density	Total Power density	Limit	
		(dBm)	(dBi)	(mW/ cm ²)	(mW/ cm ²)		
802.11ac HT40	0	15	2.01	0.009994	0.020034	1	
MIMO	1	15	2.03	0.010040	0.020034	1	

Note:

- 1. The calculated distance is 20cm.
- 2. WLAN 2.4G & WLAN 5G can't transmit simultaneously.

END OF REPORT