

**CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 Issue 3**

TEST REPORT

For

IEEE 802.11b/g/n/a/ac/ax 2T2R PCIE WiFi Module Integrated BT 2.1+EDR/4.2/5.3

MODEL NUMBER: SKO.WB276P.1

REPORT NUMBER: 4791083360-RF-1

ISSUE DATE: December 25, 2023

FCC ID:2AR82-SKOWB276P1

IC:24728-SKOWB276P1

Prepared for

**Guangzhou Shikun Electronics Co., Ltd
NO.6 Liankun Road, Huangpu District, Guangzhou 510530 China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	December 25, 2023	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	/	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3) RSS-247 Clause 5.4 (d)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2) RSS-247 Clause 5.2 (a) RSS-Gen Clause 6.7	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d) RSS-247 Clause 5.5	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.12 & Clause 11.13	FCC Part 15.247 (d) FCC Part 15.205/15.209 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C and ISED RSS-247 Issue 3> when <Simple Acceptance> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY.....	8
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>8</i>
4.2. <i>MEASUREMENT UNCERTAINTY</i>	<i>8</i>
5. EQUIPMENT UNDER TEST.....	9
5.1. <i>DESCRIPTION OF EUT.....</i>	<i>9</i>
5.2. <i>CHANNEL LIST.....</i>	<i>9</i>
5.3. <i>MAXIMUM POWER.....</i>	<i>9</i>
5.4. <i>TEST CHANNEL CONFIGURATION</i>	<i>9</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	<i>10</i>
5.6. <i>WORST-CASE CONFIGURATIONS.....</i>	<i>10</i>
5.7. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>11</i>
5.8. <i>SUPPORT UNITS FOR SYSTEM TEST.....</i>	<i>13</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED	13
7. ANTENNA PORT TEST RESULTS	16
7.1. <i>CONDUCTED OUTPUT POWER</i>	<i>16</i>
7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH</i>	<i>17</i>
7.3. <i>POWER SPECTRAL DENSITY</i>	<i>19</i>
7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION.....</i>	<i>20</i>
7.5. <i>DUTY CYCLE.....</i>	<i>21</i>
8. RADIATED TEST RESULTS	22
8.1. <i>RESTRICTED BANDEdge</i>	<i>31</i>
8.1. <i>SPURIOUS EMISSIONS (1 GHZ ~ 3 GHZ)</i>	<i>47</i>
8.2. <i>SPURIOUS EMISSIONS (3 GHZ ~ 18 GHZ)</i>	<i>53</i>
8.3. <i>SPURIOUS EMISSIONS (9 KHZ ~ 30 MHZ)</i>	<i>77</i>
8.4. <i>SPURIOUS EMISSIONS (18 GHZ ~ 26 GHZ)</i>	<i>80</i>
8.5. <i>SPURIOUS EMISSIONS (30 MHZ ~ 1 GHZ)</i>	<i>82</i>
9. ANTENNA REQUIREMENT.....	84
10. AC POWER LINE CONDUCTED EMISSION	85
11. TEST DATA	88
11.1. <i>APPENDIX A: DTS BANDWIDTH</i>	<i>88</i>

11.1.1.	Test Result.....	88
11.1.2.	Test Graphs	89
11.2.	<i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH</i>	96
11.2.1.	Test Result.....	96
11.2.2.	Test Graphs	97
11.3.	<i>APPENDIX C: MAXIMUM AVERAGE CONDUCTED OUTPUT POWER</i>	104
11.3.1.	Test Result.....	104
11.4.	<i>APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY</i>	105
11.4.1.	Test Result.....	105
11.4.2.	Test Graphs	106
11.5.	<i>APPENDIX E: BAND EDGE MEASUREMENTS</i>	113
11.5.1.	Test Result.....	113
11.5.2.	Test Graphs	114
11.6.	<i>APPENDIX F: CONDUCTED SPURIOUS EMISSION</i>	119
11.6.1.	Test Result.....	119
11.6.2.	Test Graphs	121
11.7.	<i>APPENDIX G: DUTY CYCLE</i>	142
11.7.1.	Test Result.....	142
11.7.2.	Test Graphs	143

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Guangzhou Shikun Electronics Co., Ltd
Address: NO.6 Liankun Road, Huangpu District, Guangzhou 510530 China

Manufacturer Information

Company Name: Guangzhou Shikun Electronics Co., Ltd
Address: NO.6 Liankun Road, Huangpu District, Guangzhou 510530 China

EUT Information

EUT Name: IEEE 802.11b/g/n/a/ac/ax 2T2R PCIE WiFi Module Integrated BT 2.1+EDR/4.2/5.3
Model: SKO.WB276P.1
Brand: /
Sample Received Date: November 27, 2023
Sample Status: Normal
Date of Tested: November 27, 2023 to December 22, 2023

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C ISED RSS-247 Issue 3	Pass

Prepared By:



Denny Huang

Senior Project Engineer

Checked By:



Kebo Zhang

Senior Project Engineer

Approved By:



Stephen Guo

Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C ISED RSS-247 Issue 3, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01, CFR 47 FCC Part 2, ANSI C63.10-2013 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20192, R-20202, C-20153 and T-20155) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.</p> <p>Facility Name: Chamber D, the VCCI registration No. is G-20192 and C-20153 Shielding Room B , the VCCI registration No. is C-20153 and T-20155</p>
---------------------------	--

Note 1:

All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	IEEE 802.11b/g/n/a/ac/ax 2T2R PCIE WiFi Module Integrated BT 2.1+EDR/4.2/5.3
Model	SKO.WB276P.1
Radio Technology	WLAN (IEEE 802.11b/g/n HT20/ax HE20)
Operation frequency	IEEE 802.11b: 2412MHz ~ 2462MHz IEEE 802.11g: 2412MHz ~ 2462MHz IEEE 802.11n HT20: 2412MHz ~ 2462MHz IEEE 802.11ax HE20: 2412MHz ~ 2462MHz
Modulation	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax 20: OFDMA (256QAM, 64-QAM, 16-QAM, QPSK, BPSK)
Ratings	DC 3.3 V

5.2. CHANNEL LIST

Channel List For Bandwidth=20 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

5.3. MAXIMUM POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted Average Output Power (dBm)
b	2412 ~ 2462	1-11[11]	18.10
g	2412 ~ 2462	1-11[11]	15.69
n HT20	2412 ~ 2462	1-11[11]	16.74
ax HE20	2412 ~ 2462	1-11[11]	19.01

5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
ax HE20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band						
Test Software		MobaXterm22.1				
Modulation Mode	Transmit Antenna Number	Test Channel				
		NCB: 20MHz			NCB: 40MHz	
		CH 1	CH 6	CH 11	CH 3	CH 6
802.11b	1	19	19	19	/	
	2	19	19	19		
802.11g	1	15	15	15		
	2	15	15	15		
802.11n HT20	1	13	13	13		
	2	13	13	13		
802.11ax HE20	1	14	14	14		
	2	14	14	14		

5.6. WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps

802.11g mode: 6 Mbps

802.11n HT20 CDD mode: MCS0

802.11ax HE20 CDD mode: MCS0

The EUT has 2 separate antennas which correspond to 2 separate antenna ports. Core 1, Core 2 correspond to antenna 1, antenna 2 respectively.

The 3 kinds of antenna above used for tested were provided by customer, the antenna type is the same but the antenna gain is different, pre-scan had been done for all the antennas, but only the worst data was recorded (antenna type 2) in the report, for more information about the antennas, please refer to clause 5.7.

802.11b and 802.11g mode does not support MIMO mode.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

When installed in the host product, the radio can support “hotspot” features and operate as a master device only working at WiFi 2.4 GHz (2412 MHz ~ 2462 MHz) and WiFi GHz (5180 MHz ~ 5240 MHz and 5745 MHz ~ 5825 MHz), but the RF parameter is the same when act as a client.

5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna Type 1			
Antenna	Frequency (MHz)	Antenna Type	Maximum Antenna Gain (dBi)
1	2412-2462	Dipole Antenna	3.28
2	2412-2462	Dipole Antenna	3.28

The EUT support Cyclic Shift Diversity (CDD) mode.

MIMO output power port and MIMO PSD port summing were performed in accordance with KDB 662911 D01. For the CDD results the Directional Gain was calculated in accordance with the following mothed.

For output power measurements:

Directional gain= $G_{ANT} + \text{Array Gain} = 3.28 \text{ dBi}$

G_{ANT} : equal to the gain of the antenna having the highest gain

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$

For power spectral density (PSD) measurements:

Directional gain= $G_{ANT} + \text{Array Gain} = 6.29 \text{ dBi}$

Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

N_{ANT} : number of transmit antennas

N_{SS} : number of spatial streams, The worst case directional gain will occur when $N_{SS} = 1$

Antenna Type 2			
Antenna	Frequency (MHz)	Antenna Type	Maximum Antenna Gain (dBi)
1	2412-2462	Dipole Antenna	3.83
2	2412-2462	Dipole Antenna	3.83

The EUT support Cyclic Shift Diversity (CDD) mode.

MIMO output power port and MIMO PSD port summing were performed in accordance with KDB 662911 D01. For the CDD results the Directional Gain was calculated in accordance with the following mothed.

For output power measurements:

Directional gain= $G_{ANT} + \text{Array Gain} = 3.83 \text{ dBi}$

G_{ANT} : equal to the gain of the antenna having the highest gain

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$

For power spectral density (PSD) measurements:

Directional gain= $G_{ANT} + \text{Array Gain} = 6.84 \text{ dBi}$

Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

N_{ANT} : number of transmit antennas

N_{SS} : number of spatial streams, The worst case directional gain will occur when $N_{SS} = 1$

Antenna Type 3			
Antenna	Frequency (MHz)	Antenna Type	Maximum Antenna Gain (dBi)
1	2412-2462	Dipole Antenna	3.57
2	2412-2462	Dipole Antenna	3.57

The EUT support Cyclic Shift Diversity (CDD) mode.

MIMO output power port and MIMO PSD port summing were performed in accordance with KDB 662911 D01. For the CDD results the Directional Gain was calculated in accordance with the following mothod.

For output power measurements:

Directional gain= $G_{ANT} + \text{Array Gain} = 3.57 \text{ dBi}$

G_{ANT} : equal to the gain of the antenna having the highest gain

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$

For power spectral density (PSD) measurements:

Directional gain= $G_{ANT} + \text{Array Gain} = 6.58 \text{ dBi}$

Array Gain = $10 \log(N_{ANT}/N_{ss}) \text{ dB}$.

N_{ANT} : number of transmit antennas

N_{ss} : number of spatial streams, The worst case directional gain will occur when $N_{ss} = 1$

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1, ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11g	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1, ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1, ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11ax HE20	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1, ANT 2 can be used as transmitting/receiving antenna.

Note: The value of the antenna gain was declared by customer.

5.8. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	ThinkPad	X230i	/
2	Main Board	/	/	/
3	USB to Serial Cable	/	/	/
4	Antenna 1	KTC	4791083360	/
5	Antenna 2	CVTE	004.032.0052703	/
6	Antenna 3	SLEing	SLEingA100080168-C07	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
/	/	/	/	/	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	SWITCHING ADAPTER	SOY	SOY-1200400US	Input: AC 100-240 V, 50 / 60 Hz, 1.2 A Output: DC 12.0 V, 4 A

TEST SETUP

The EUT can work in engineering mode with a software through a laptop.

SETUP DIAGRAM FOR TESTS



6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Mar.31,2023	Mar.30,2024
Vector Signal Generator	R&S	SMBV100A	261637	Oct.12, 2023	Oct.11, 2024
Signal Generator	R&S	SMB100A	178553	Oct.12, 2023	Oct.11, 2024
Signal Analyzer	R&S	FSV40	101118	Oct.12, 2023	Oct.11, 2024
Software					
Description	Manufacturer	Name		Version	
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32		10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.12, 2023	Oct.11, 2024
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.25, 2023	Sep.24, 2024
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.12, 2023	Oct.11, 2024
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.12, 2023	Oct.11, 2024
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.12, 2023	Oct.11, 2024
DC power supply	Keysight	E3642A	MY55159130	Oct.12, 2023	Oct.11, 2024
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Oct.12, 2023	Oct.11, 2024
Attenuator	Aglient	8495B	2814a12853	Oct.12, 2023	Oct.11, 2024
RF Control Unit	Tonsend	JS0806-2	23B80620666	April 18, 2023	April 17, 2024
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Oct.13, 2023	Oct.12, 2024
Two-Line V-Network	R&S	ENV216	101983	Oct.13, 2023	Oct.12, 2024
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Oct.13, 2023	Oct.12, 2024
Software					
Description		Manufacturer		Name	Version
Test Software for Conducted Emissions		Farad		EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.12, 2023	Oct.11, 2024
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.12, 2023	Oct.11, 2024
EMI Measurement Receiver	R&S	ESR26	101377	Oct.12, 2023	Oct.11, 2024
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.12, 2023	Oct.11, 2024
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.12, 2023	Oct.11, 2024
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.12, 2023	Oct.11, 2024
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.12, 2023	Oct.11, 2024
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Oct.12, 2023	Oct.11, 2024
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Oct.12, 2023	Oct.11, 2024
Software					
Description		Manufacturer		Name	Version
Test Software for Radiated Emissions		Farad		EZ-EMC	Ver. UL-3A1

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	AVG Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.2 °C	Relative Humidity	51.8%
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

- Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
- Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.2 °C	Relative Humidity	51.8%
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

TEST RESULTS

Please refer to section "Test Data" - Appendix A & B

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.5.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms)
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{OBW}$ bandwidth
Trace	Employ trace averaging(rms)mode over a minimum of 100 traces
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.2 °C	Relative Humidity	51.8%
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
measurement points	\geq span/RBW
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.2 °C	Relative Humidity	51.8%
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

TEST RESULTS

Please refer to section "Test Data" - Appendix E & F

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.2 °C	Relative Humidity	51.8%
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

TEST RESULTS

Please refer to section "Test Data" - Appendix G

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz					
Frequency Range (MHz)		Field Strength Limit (uV/m) at 3 m		Field Strength Limit (dBuV/m) at 3 m	
				Quasi-Peak	
30 - 88		100		40	
88 - 216		150		43.5	
216 - 960		200		46	
Above 960		500		54	
Above 1000		500		Peak	Average
				74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μ A/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands ^{Note 1}		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.028	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.877 - 5.883	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 38.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2380	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2665 - 2900	
13.36 - 13.41	3280 - 3287	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3287	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dB μ V/m, which is equivalent to $Y-51.5 = Z$ dB μ A/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: EUT uses an adjustable antenna, pre-scan had been done for the typical positions and the other positions that customer can use, only the worst data was recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $dBuA/m = dBuV/m - 20\log_{10}[120\pi] = dBuV/m - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.


For Radiate Spurious Emission (3 GHz ~ 18 GHz):**Note:**

1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.


For Radiate Spurious emission (18 GHz ~ 26 GHz):**Note:**

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz




TEST ENVIRONMENT

Temperature	25.3 °C	Relative Humidity	61%
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

TEST RESULTS


8.1. RESTRICTED BANDEDGE

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.040	22.03	32.15	54.18	74.00	-19.82	peak
2	2390.000	23.67	32.16	55.83	74.00	-18.17	peak

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.040	14.10	32.15	46.25	54.00	-7.75	AVG
2	2390.000	11.92	32.16	44.08	54.00	-9.92	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	23.79	32.44	56.23	74.00	-17.77	peak
2	2484.105	24.63	32.44	57.07	74.00	-16.93	peak

Test Mode:	802.11b AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	13.24	32.44	45.68	54.00	-8.32	AVG
2	2484.105	12.72	32.44	45.16	54.00	-8.84	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	30.09	32.16	62.25	74.00	-11.75	peak

Test Mode:	802.11g AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dB _u V)	Correct (dB/m)	Result (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Remark
1	2390.000	14.54	32.16	46.70	54.00	-7.30	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	32.07	32.44	64.51	74.00	-9.49	peak
2	2487.405	34.08	32.45	66.53	74.00	-7.47	peak

Test Mode:	802.11g AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dB _u V)	Correct (dB/m)	Result (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Remark
1	2483.500	15.61	32.44	48.05	54.00	-5.95	AVG
2	2487.405	14.03	32.45	46.48	54.00	-7.52	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.800	35.91	32.16	68.07	74.00	-5.93	peak
2	2390.000	36.38	32.16	68.54	74.00	-5.46	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.800	18.81	32.16	50.97	54.00	-3.03	AVG
2	2390.000	19.01	32.16	51.17	54.00	-2.83	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.56	32.44	72.00	74.00	-2.00	peak
2	2483.610	39.85	32.44	72.29	74.00	-1.71	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.55	32.44	49.99	54.00	-4.01	AVG
2	2483.610	17.77	32.44	50.21	54.00	-3.79	AVG

Test Mode:	802.11ax HE20 PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.320	39.58	32.16	71.74	74.00	-2.26	peak
2	2390.000	39.52	32.16	71.68	74.00	-2.32	peak

Test Mode:	802.11ax HE20 AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.230	19.50	32.16	51.66	54.00	-2.34	AVG
2	2390.000	20.60	32.16	52.76	54.00	-1.24	AVG

Test Mode:	802.11ax HE20 PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	37.99	32.44	70.43	74.00	-3.57	peak
2	2483.885	40.50	32.44	72.94	74.00	-1.06	peak


Test Mode:	802.11ax HE20 AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	19.32	32.44	51.76	54.00	-2.24	AVG
2	2483.885	19.08	32.44	51.52	54.00	-2.48	AVG


8.1. SPURIOUS EMISSIONS (1 GHZ ~ 3 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1386.000	51.98	-13.24	38.74	74.00	-35.26	peak
2	1722.000	46.05	-11.98	34.07	74.00	-39.93	peak
3	2178.000	45.61	-10.15	35.46	74.00	-38.54	peak
4	2338.000	46.64	-9.32	37.32	74.00	-36.68	peak
5	2414.000	49.66	-8.93	40.73	74.00	-33.27	peak
6	2574.000	50.57	-8.27	42.30	74.00	-31.70	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1742.000	45.95	-11.91	34.04	74.00	-39.96	peak
2	2112.000	46.62	-10.48	36.14	74.00	-37.86	peak
3	2338.000	47.85	-9.32	38.53	74.00	-35.47	peak
4	2414.000	52.59	-8.93	43.66	74.00	-30.34	peak
5	2572.000	49.49	-8.27	41.22	74.00	-32.78	peak
6	2906.000	44.69	-7.27	37.42	74.00	-36.58	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1060.000	49.87	-14.76	35.11	74.00	-38.89	peak
2	1386.000	51.00	-13.24	37.76	74.00	-36.24	peak
3	1782.000	53.02	-11.78	41.24	74.00	-32.76	peak
4	2440.000	52.58	-8.80	43.78	74.00	-30.22	peak
5	2586.000	47.18	-8.24	38.94	74.00	-35.06	peak
6	2970.000	44.32	-7.07	37.25	74.00	-36.75	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1600.000	46.51	-12.38	34.13	74.00	-39.87	peak
2	2114.000	51.61	-10.47	41.14	74.00	-32.86	peak
3	2352.000	47.74	-9.24	38.50	74.00	-35.50	peak
4	2440.000	56.29	-8.80	47.49	74.00	-26.51	peak
5	2598.000	51.05	-8.19	42.86	74.00	-31.14	peak
6	2838.000	44.69	-7.46	37.23	74.00	-36.77	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1386.000	50.99	-13.24	37.75	74.00	-36.25	peak
2	1730.000	47.05	-11.95	35.10	74.00	-38.90	peak
3	1974.000	46.26	-11.14	35.12	74.00	-38.88	peak
4	2464.000	49.71	-8.68	41.03	74.00	-32.97	peak
5	2626.000	48.07	-8.10	39.97	74.00	-34.03	peak
6	2970.000	46.18	-7.07	39.11	74.00	-34.89	peak


Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1386.000	47.94	-13.24	34.70	74.00	-39.30	peak
2	1782.000	50.74	-11.78	38.96	74.00	-35.04	peak
3	2116.000	54.05	-10.47	43.58	74.00	-30.42	peak
4	2464.000	50.23	-8.68	41.55	74.00	-32.45	peak
5	2586.000	51.86	-8.24	43.62	74.00	-30.38	peak
6	2624.000	52.17	-8.12	44.05	74.00	-29.95	peak


8.2. SPURIOUS EMISSIONS (3 GHZ ~ 18 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4350.000	47.05	-2.16	44.89	74.00	-29.11	peak
2	7890.000	38.99	6.31	45.30	74.00	-28.70	peak
3	8940.000	38.06	10.04	48.10	74.00	-25.90	peak
4	11580.000	33.64	16.82	50.46	74.00	-23.54	peak
5	13605.000	28.86	21.12	49.98	74.00	-24.02	peak
6	18000.000	24.51	25.69	50.20	74.00	-23.80	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	47.25	-0.26	46.99	74.00	-27.01	peak
2	7035.000	37.33	6.67	44.00	74.00	-30.00	peak
3	8985.000	37.44	10.37	47.81	74.00	-26.19	peak
4	11460.000	33.48	16.46	49.94	74.00	-24.06	peak
5	13170.000	31.17	19.46	50.63	74.00	-23.37	peak
6	18000.000	24.01	25.69	49.70	74.00	-24.30	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4350.000	44.50	-2.16	42.34	74.00	-31.66	peak
2	7770.000	38.83	6.31	45.14	74.00	-28.86	peak
3	9345.000	37.68	10.63	48.31	74.00	-25.69	peak
4	11055.000	35.02	14.96	49.98	74.00	-24.02	peak
5	14025.000	28.32	21.86	50.18	74.00	-23.82	peak
6	17775.000	25.34	24.36	49.70	74.00	-24.30	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4995.000	40.29	0.43	40.72	74.00	-33.28	peak
2	7680.000	38.59	6.32	44.91	74.00	-29.09	peak
3	8940.000	38.40	10.04	48.44	74.00	-25.56	peak
4	11730.000	33.05	17.22	50.27	74.00	-23.73	peak
5	12735.000	32.77	18.12	50.89	74.00	-23.11	peak
6	17940.000	25.40	25.34	50.74	74.00	-23.26	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4350.000	47.59	-2.16	45.43	74.00	-28.57	peak
2	9150.000	37.52	10.54	48.06	74.00	-25.94	peak
3	10920.000	35.38	14.49	49.87	74.00	-24.13	peak
4	12660.000	32.40	17.95	50.35	74.00	-23.65	peak
5	13635.000	28.59	21.19	49.78	74.00	-24.22	peak
6	17940.000	24.64	25.34	49.98	74.00	-24.02	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	47.06	0.14	47.20	74.00	-26.80	peak
2	9300.000	37.27	10.61	47.88	74.00	-26.12	peak
3	11880.000	32.15	17.63	49.78	74.00	-24.22	peak
4	12285.000	32.25	17.75	50.00	74.00	-24.00	peak
5	13140.000	30.75	19.33	50.08	74.00	-23.92	peak
6	17985.000	23.93	25.60	49.53	74.00	-24.47	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4350.000	49.57	-2.16	47.41	74.00	-26.59	peak
2	9330.000	37.57	10.62	48.19	74.00	-25.81	peak
3	11805.000	32.25	17.43	49.68	74.00	-24.32	peak
4	12585.000	32.37	17.78	50.15	74.00	-23.85	peak
5	13605.000	29.27	21.12	50.39	74.00	-23.61	peak
6	18000.000	23.80	25.69	49.49	74.00	-24.51	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4665.000	42.28	-0.83	41.45	74.00	-32.55	peak
2	7965.000	38.74	6.31	45.05	74.00	-28.95	peak
3	9300.000	38.11	10.61	48.72	74.00	-25.28	peak
4	11895.000	32.51	17.68	50.19	74.00	-23.81	peak
5	13890.000	28.20	21.72	49.92	74.00	-24.08	peak
6	17985.000	24.59	25.60	50.19	74.00	-23.81	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7290.000	37.98	6.48	44.46	74.00	-29.54	peak
2	8940.000	37.37	10.04	47.41	74.00	-26.59	peak
3	10230.000	36.23	12.46	48.69	74.00	-25.31	peak
4	11730.000	32.07	17.22	49.29	74.00	-24.71	peak
5	13320.000	29.71	20.11	49.82	74.00	-24.18	peak
6	17985.000	23.46	25.60	49.06	74.00	-24.94	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5865.000	39.97	1.88	41.85	74.00	-32.15	peak
2	7305.000	37.59	6.47	44.06	74.00	-29.94	peak
3	9360.000	36.79	10.64	47.43	74.00	-26.57	peak
4	11925.000	32.95	17.75	50.70	74.00	-23.30	peak
5	13410.000	30.20	20.50	50.70	74.00	-23.30	peak
6	17985.000	25.21	25.60	50.81	74.00	-23.19	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4350.000	48.62	-2.16	46.46	74.00	-27.54	peak
2	7890.000	38.93	6.31	45.24	74.00	-28.76	peak
3	9240.000	38.26	10.58	48.84	74.00	-25.16	peak
4	11055.000	35.66	14.96	50.62	74.00	-23.38	peak
5	12705.000	32.87	18.06	50.93	74.00	-23.07	peak
6	17955.000	25.46	25.42	50.88	74.00	-23.12	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	43.52	0.14	43.66	74.00	-30.34	peak
2	7695.000	38.15	6.32	44.47	74.00	-29.53	peak
3	9240.000	37.38	10.58	47.96	74.00	-26.04	peak
4	10290.000	36.56	12.59	49.15	74.00	-24.85	peak
5	13605.000	28.94	21.12	50.06	74.00	-23.94	peak
6	17940.000	25.03	25.34	50.37	74.00	-23.63	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4740.000	44.14	-0.54	43.60	74.00	-30.40	peak
2	9270.000	37.67	10.59	48.26	74.00	-25.74	peak
3	10620.000	36.41	13.42	49.83	74.00	-24.17	peak
4	11400.000	34.11	16.23	50.34	74.00	-23.66	peak
5	13635.000	29.68	21.19	50.87	74.00	-23.13	peak
6	17985.000	25.40	25.60	51.00	74.00	-23.00	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	42.26	-0.26	42.00	74.00	-32.00	peak
2	7650.000	37.98	6.33	44.31	74.00	-29.69	peak
3	9240.000	38.13	10.58	48.71	74.00	-25.29	peak
4	11070.000	34.84	15.03	49.87	74.00	-24.13	peak
5	12735.000	32.65	18.12	50.77	74.00	-23.23	peak
6	17940.000	24.43	25.34	49.77	74.00	-24.23	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4740.000	42.32	-0.54	41.78	74.00	-32.22	peak
2	7815.000	39.00	6.32	45.32	74.00	-28.68	peak
3	8910.000	38.45	9.82	48.27	74.00	-25.73	peak
4	11760.000	32.81	17.31	50.12	74.00	-23.88	peak
5	13905.000	28.69	21.76	50.45	74.00	-23.55	peak
6	17700.000	25.80	23.91	49.71	74.00	-24.29	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4350.000	43.12	-2.16	40.96	74.00	-33.04	peak
2	9255.000	37.66	10.59	48.25	74.00	-25.75	peak
3	11655.000	32.69	17.01	49.70	74.00	-24.30	peak
4	12750.000	31.60	18.16	49.76	74.00	-24.24	peak
5	13620.000	28.40	21.15	49.55	74.00	-24.45	peak
6	17925.000	24.80	25.25	50.05	74.00	-23.95	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7770.000	39.21	6.31	45.52	74.00	-28.48	peak
2	9255.000	37.22	10.59	47.81	74.00	-26.19	peak
3	10965.000	34.02	14.64	48.66	74.00	-25.34	peak
4	12150.000	32.17	17.86	50.03	74.00	-23.97	peak
5	13410.000	29.55	20.50	50.05	74.00	-23.95	peak
6	17985.000	24.44	25.60	50.04	74.00	-23.96	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	43.17	-0.26	42.91	74.00	-31.09	peak
2	7635.000	38.47	6.33	44.80	74.00	-29.20	peak
3	9195.000	37.72	10.56	48.28	74.00	-25.72	peak
4	11070.000	35.37	15.03	50.40	74.00	-23.60	peak
5	13140.000	31.31	19.33	50.64	74.00	-23.36	peak
6	17925.000	24.70	25.25	49.95	74.00	-24.05	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5160.000	41.07	0.58	41.65	74.00	-32.35	peak
2	8025.000	38.85	6.34	45.19	74.00	-28.81	peak
3	9225.000	38.29	10.58	48.87	74.00	-25.13	peak
4	12675.000	33.12	17.99	51.11	74.00	-22.89	peak
5	13890.000	28.92	21.72	50.64	74.00	-23.36	peak
6	17850.000	25.05	24.81	49.86	74.00	-24.14	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	44.30	-0.26	44.04	74.00	-29.96	peak
2	7725.000	38.98	6.32	45.30	74.00	-28.70	peak
3	8985.000	37.39	10.37	47.76	74.00	-26.24	peak
4	11550.000	33.01	16.74	49.75	74.00	-24.25	peak
5	13080.000	31.13	19.07	50.20	74.00	-23.80	peak
6	17910.000	24.32	25.16	49.48	74.00	-24.52	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4350.000	43.24	-2.16	41.08	74.00	-32.92	peak
2	7875.000	37.95	6.31	44.26	74.00	-29.74	peak
3	8925.000	38.76	9.94	48.70	74.00	-25.30	peak
4	11985.000	32.50	17.92	50.42	74.00	-23.58	peak
5	13170.000	30.93	19.46	50.39	74.00	-23.61	peak
6	17715.000	26.70	24.00	50.70	74.00	-23.30	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4590.000	41.93	-1.12	40.81	74.00	-33.19	peak
2	7275.000	37.58	6.49	44.07	74.00	-29.93	peak
3	9015.000	36.93	10.49	47.42	74.00	-26.58	peak
4	11820.000	32.62	17.47	50.09	74.00	-23.91	peak
5	13890.000	28.90	21.72	50.62	74.00	-23.38	peak
6	17985.000	24.53	25.60	50.13	74.00	-23.87	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4695.000	42.45	-0.71	41.74	74.00	-32.26	peak
2	7710.000	38.55	6.33	44.88	74.00	-29.12	peak
3	8985.000	38.49	10.37	48.86	74.00	-25.14	peak
4	11055.000	34.48	14.96	49.44	74.00	-24.56	peak
5	13545.000	29.83	20.99	50.82	74.00	-23.18	peak
6	17775.000	25.81	24.36	50.17	74.00	-23.83	peak


Test Mode:	802.11ax HE20	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6015.000	38.80	2.31	41.11	74.00	-32.89	peak
2	7890.000	38.68	6.31	44.99	74.00	-29.01	peak
3	9060.000	37.13	10.51	47.64	74.00	-26.36	peak
4	11520.000	32.83	16.65	49.48	74.00	-24.52	peak
5	13455.000	29.22	20.71	49.93	74.00	-24.07	peak
6	17760.000	25.22	24.27	49.49	74.00	-24.51	peak


8.3. SPURIOUS EMISSIONS (9 KHZ ~ 30 MHZ)

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Loop Antenna Face On To The EUT	Test Voltage:	DC 3.3 V




No.	Frequency	Reading	Correct	Result	Result	Limit	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuA/m)	(dBuV/m)	(dBuA/m)	(dB)	
1	0.01	77.72	-101.4	-23.68	-75.18	47.6	-3.9	-71.28	peak
2	0.0131	74.47	-101.38	-26.91	-78.41	45.25	-6.25	-72.16	peak
3	0.0212	72.54	-101.35	-28.81	-80.31	41.07	-10.43	-69.88	peak
4	0.0279	70.17	-101.38	-31.21	-82.71	38.69	-12.81	-69.90	peak
5	0.0354	67.97	-101.41	-33.44	-84.94	36.62	-14.88	-70.06	peak
6	0.0636	63.31	-101.54	-38.23	-89.73	31.53	-19.97	-69.76	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Loop Antenna Face On To The EUT	Test Voltage:	DC 3.3 V



No.	Frequency	Reading	Correct	Result	Result	Limit	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuA/m)	(dBuV/m)	(dBuA/m)	(dB)	
1	0.1595	77.36	-101.65	-24.29	-75.79	23.55	-27.95	-47.84	peak
2	0.1794	75.27	-101.68	-26.41	-77.91	22.53	-28.97	-48.94	peak
3	0.2064	70.58	-101.73	-31.15	-82.65	21.31	-30.19	-52.46	peak
4	0.2247	67.88	-101.75	-33.87	-85.37	20.57	-30.93	-54.44	peak
5	0.2605	66.64	-101.81	-35.17	-86.67	19.28	-32.22	-54.45	peak
6	0.3251	62.71	-101.88	-39.17	-90.67	17.36	-34.14	-56.53	peak


Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Loop Antenna Face On To The EUT	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Result (dBuA/m)	Limit (dBuV/m)	Limit (dBuA/m)	Margin (dB)	Remark
1	0.508	64.85	-62.07	2.78	-48.72	33.49	-18.01	-30.71	peak
2	0.7641	63.92	-62.12	1.8	-49.70	29.94	-21.56	-28.14	peak
3	1.5443	59.35	-62.03	-2.68	-54.18	23.83	-27.67	-26.51	peak
4	3.71	55.7	-61.41	-5.71	-57.21	29.54	-21.96	-35.25	peak
5	6.5998	54.62	-61.27	-6.65	-58.15	29.54	-21.96	-36.19	peak
6	16.6021	53.52	-60.96	-7.44	-58.94	29.54	-21.96	-36.98	peak


8.4. SPURIOUS EMISSIONS (18 GHZ ~ 26 GHZ)

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18144.000	49.77	-5.48	44.29	74.00	-29.71	peak
2	19392.000	50.62	-5.57	45.05	74.00	-28.95	peak
3	20264.000	49.97	-5.60	44.37	74.00	-29.63	peak
4	21600.000	48.52	-4.54	43.98	74.00	-30.02	peak
5	23744.000	47.15	-3.20	43.95	74.00	-30.05	peak
6	25000.000	46.36	-2.10	44.26	74.00	-29.74	peak


Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18824.000	48.64	-5.37	43.27	74.00	-30.73	peak
2	19984.000	48.71	-5.44	43.27	74.00	-30.73	peak
3	21264.000	47.35	-4.76	42.59	74.00	-31.41	peak
4	22792.000	46.61	-3.65	42.96	74.00	-31.04	peak
5	24568.000	45.60	-2.33	43.27	74.00	-30.73	peak
6	25728.000	45.11	-0.72	44.39	74.00	-29.61	peak


8.5. SPURIOUS EMISSIONS (30 MHZ ~ 1 GHZ)

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	257.9500	43.91	-17.82	26.09	46.00	-19.91	QP
2	332.6400	43.71	-13.30	30.41	46.00	-15.59	QP
3	756.5300	37.85	-6.58	31.27	46.00	-14.73	QP
4	806.9699	40.27	-6.21	34.06	46.00	-11.94	QP
5	832.1900	43.32	-6.08	37.24	46.00	-8.76	QP
6	996.1200	42.28	-3.72	38.56	54.00	-15.44	QP

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.9700	45.45	-17.85	27.60	40.00	-12.40	QP
2	165.8000	44.56	-16.61	27.95	43.50	-15.55	QP
3	378.2300	42.56	-12.51	30.05	46.00	-15.95	QP
4	499.4800	42.51	-10.34	32.17	46.00	-13.83	QP
5	832.1900	41.78	-6.08	35.70	46.00	-10.30	QP
6	995.1500	44.24	-3.74	40.50	54.00	-13.50	QP

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP




TEST ENVIRONMENT

Temperature	22.5 °C	Relative Humidity	56%
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Line	L1	Test Voltage	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.4674	24.00	9.60	33.60	56.56	-22.96	QP
2	0.4674	5.07	9.60	14.67	46.56	-31.89	AVG
3	0.9436	8.77	9.61	18.38	56.00	-37.62	QP
4	0.9436	-2.98	9.61	6.63	46.00	-39.37	AVG
5	1.2665	9.50	9.61	19.11	56.00	-36.89	QP
6	1.2665	-3.48	9.61	6.13	46.00	-39.87	AVG
7	2.2966	8.61	9.64	18.25	56.00	-37.75	QP
8	2.2966	-2.94	9.64	6.70	46.00	-39.30	AVG
9	4.8269	7.86	9.71	17.57	56.00	-38.43	QP
10	4.8269	-2.95	9.71	6.76	46.00	-39.24	AVG
11	13.2609	16.32	9.76	26.08	60.00	-33.92	QP
12	13.2609	-1.47	9.76	8.29	50.00	-41.71	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Test Mode:	802.11ax HE20	Frequency(MHz):	2437
Line	N	Test Voltage	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1600	14.74	9.59	24.33	65.46	-41.13	QP
2	0.1600	2.42	9.59	12.01	55.46	-43.45	AVG
3	0.4675	32.96	9.60	42.56	56.56	-14.00	QP
4	0.4675	15.92	9.60	25.52	46.56	-21.04	AVG
5	0.7265	19.03	9.60	28.63	56.00	-27.37	QP
6	0.7265	3.56	9.60	13.16	46.00	-32.84	AVG
7	1.1043	17.20	9.61	26.81	56.00	-29.19	QP
8	1.1043	2.67	9.61	12.28	46.00	-33.72	AVG
9	1.8432	16.44	9.62	26.06	56.00	-29.94	QP
10	1.8432	2.45	9.62	12.07	46.00	-33.93	AVG
11	2.3030	16.55	9.64	26.19	56.00	-29.81	QP
12	2.3030	5.32	9.64	14.96	46.00	-31.04	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.


11. TEST DATA


11.1. APPENDIX A: DTS BANDWIDTH


11.1.1. Test Result


Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	7.12	2408.44	2415.56	≥ 0.5	PASS
	Ant2	2412	7.04	2408.48	2415.52	≥ 0.5	PASS
	Ant1	2437	7.12	2433.44	2440.56	≥ 0.5	PASS
	Ant2	2437	7.08	2433.44	2440.52	≥ 0.5	PASS
	Ant1	2462	7.04	2458.48	2465.52	≥ 0.5	PASS
	Ant2	2462	7.08	2458.44	2465.52	≥ 0.5	PASS
11G	Ant1	2412	16.36	2403.80	2420.16	≥ 0.5	PASS
	Ant2	2412	16.36	2403.80	2420.16	≥ 0.5	PASS
	Ant1	2437	16.32	2428.84	2445.16	≥ 0.5	PASS
	Ant2	2437	16.32	2428.84	2445.16	≥ 0.5	PASS
	Ant1	2462	16.32	2453.84	2470.16	≥ 0.5	PASS
	Ant2	2462	16.36	2453.80	2470.16	≥ 0.5	PASS
11N20MIMO	Ant1	2412	17.60	2403.20	2420.80	≥ 0.5	PASS
	Ant2	2412	15.40	2404.16	2419.56	≥ 0.5	PASS
	Ant1	2437	17.60	2428.20	2445.80	≥ 0.5	PASS
	Ant2	2437	17.60	2428.20	2445.80	≥ 0.5	PASS
	Ant1	2462	17.60	2453.20	2470.80	≥ 0.5	PASS
	Ant2	2462	17.60	2453.20	2470.80	≥ 0.5	PASS
11AX20MIMO	Ant1	2412	18.24	2402.84	2421.08	≥ 0.5	PASS
	Ant2	2412	18.36	2402.56	2420.92	≥ 0.5	PASS
	Ant1	2437	17.80	2428.24	2446.04	≥ 0.5	PASS
	Ant2	2437	18.36	2428.04	2446.40	≥ 0.5	PASS
	Ant1	2462	18.52	2452.76	2471.28	≥ 0.5	PASS
	Ant2	2462	17.88	2452.72	2470.60	≥ 0.5	PASS


11.1.2. Test Graphs



















11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH


11.2.1. Test Result


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
11B	Ant1	2412	11.429	2406.3257	2417.7542	PASS
	Ant2	2412	10.989	2406.4855	2417.4745	PASS
	Ant1	2437	11.389	2431.4056	2442.7942	PASS
	Ant2	2437	10.989	2431.5654	2442.5544	PASS
	Ant1	2462	11.508	2456.3257	2467.8342	PASS
	Ant2	2462	11.029	2456.4855	2467.5145	PASS
11G	Ant1	2412	17.742	2403.1688	2420.9111	PASS
	Ant2	2412	17.822	2403.0889	2420.9111	PASS
	Ant1	2437	17.662	2428.2488	2445.9111	PASS
	Ant2	2437	17.702	2428.2088	2445.9111	PASS
	Ant1	2462	17.702	2453.2088	2470.9111	PASS
	Ant2	2462	17.662	2453.1688	2470.8312	PASS
11N20MIMO	Ant1	2412	18.621	2402.6893	2421.3107	PASS
	Ant2	2412	18.062	2402.9690	2421.0310	PASS
	Ant1	2437	18.621	2427.7692	2446.3906	PASS
	Ant2	2437	18.102	2427.9690	2446.0709	PASS
	Ant1	2462	18.581	2452.7692	2471.3506	PASS
	Ant2	2462	18.062	2452.9690	2471.0310	PASS
11AX20MIMO	Ant1	2412	19.141	2402.4496	2421.5904	PASS
	Ant2	2412	19.101	2402.4496	2421.5504	PASS
	Ant1	2437	19.101	2427.4895	2446.5904	PASS
	Ant2	2437	19.101	2427.4895	2446.5904	PASS
	Ant1	2462	19.061	2452.5295	2471.5904	PASS
	Ant2	2462	19.061	2452.4895	2471.5504	PASS


11.2.2. Test Graphs

















11.3. APPENDIX C: MAXIMUM AVERAGE CONDUCTED OUTPUT POWER

11.3.1. Test Result

Test Mode	Antenna	Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	18.10	≤30.00	PASS
	Ant2	2412	18.03	≤30.00	PASS
	Ant1	2437	17.90	≤30.00	PASS
	Ant2	2437	17.43	≤30.00	PASS
	Ant1	2462	17.43	≤30.00	PASS
	Ant2	2462	17.65	≤30.00	PASS
11G	Ant1	2412	15.85	≤30.00	PASS
	Ant2	2412	15.19	≤30.00	PASS
	Ant1	2437	15.63	≤30.00	PASS
	Ant2	2437	15.08	≤30.00	PASS
	Ant1	2462	15.69	≤30.00	PASS
	Ant2	2462	15.20	≤30.00	PASS
11N20MIMO	Ant1	2412	13.72	≤30.00	PASS
	Ant2	2412	13.57	≤30.00	PASS
	total	2412	16.66	≤30.00	PASS
	Ant1	2437	13.48	≤30.00	PASS
	Ant2	2437	13.41	≤30.00	PASS
	total	2437	16.46	≤30.00	PASS
	Ant1	2462	13.67	≤30.00	PASS
	Ant2	2462	13.79	≤30.00	PASS
	total	2462	16.74	≤30.00	PASS
	Ant1	2412	15.87	≤30.00	PASS
11AX20MIMO	Ant2	2412	15.85	≤30.00	PASS
	total	2412	18.87	≤30.00	PASS
	Ant1	2437	15.61	≤30.00	PASS
	Ant2	2437	15.88	≤30.00	PASS
	total	2437	18.76	≤30.00	PASS
	Ant1	2462	15.92	≤30.00	PASS
	Ant2	2462	16.07	≤30.00	PASS
	total	2462	19.01	≤30.00	PASS

Note: 1. Conducted Power=Meas. Level+ Correction Factor

2. The Duty Cycle Factor (refer to section 7.5) had already compensated to the test data.

11.4. APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY

11.4.1. Test Result

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-14.24	≤8.00	PASS
	Ant2	2412	-13.42	≤8.00	PASS
	Ant1	2437	-14.12	≤8.00	PASS
	Ant2	2437	-14.09	≤8.00	PASS
	Ant1	2462	-14.06	≤8.00	PASS
	Ant2	2462	-14.26	≤8.00	PASS
11G	Ant1	2412	-15.27	≤8.00	PASS
	Ant2	2412	-16.24	≤8.00	PASS
	Ant1	2437	-15.81	≤8.00	PASS
	Ant2	2437	-16.09	≤8.00	PASS
	Ant1	2462	-15.87	≤8.00	PASS
	Ant2	2462	-15.80	≤8.00	PASS
11N20MIMO	Ant1	2412	-20.56	≤8.00	PASS
	Ant2	2412	-20.88	≤8.00	PASS
	total	2412	-17.71	≤8.00	PASS
	Ant1	2437	-20.67	≤8.00	PASS
	Ant2	2437	-20.73	≤8.00	PASS
	total	2437	-17.69	≤8.00	PASS
	Ant1	2462	-20.27	≤8.00	PASS
	Ant2	2462	-20.54	≤8.00	PASS
	total	2462	-17.39	≤8.00	PASS
11AX20MIMO	Ant1	2412	-17.48	≤8.00	PASS
	Ant2	2412	-17.67	≤8.00	PASS
	total	2412	-14.56	≤8.00	PASS
	Ant1	2437	-17.32	≤8.00	PASS
	Ant2	2437	-16.70	≤8.00	PASS
	total	2437	-13.99	≤8.00	PASS
	Ant1	2462	-17.05	≤8.00	PASS
	Ant2	2462	-16.83	≤8.00	PASS
	total	2462	-13.93	≤8.00	PASS

Note: The Duty Cycle Factor (refer to section 7.5) had already compensated to the test data.