



## RF Exposure evaluation

**Test report  
On Behalf of  
SHENZHEN UTEPO Tech Co.Ltd  
For  
5.8G Outdoor CPE  
Model No.: CP5-1200, CP5-300, CP5-450, CP5-900**

**FCC ID: 2AR8QCP5-1200**

**Prepared for :** SHENZHEN UTEPO Tech Co.Ltd  
Room No. 4C08, 4th Floor, Sub-Building of Mindray Mansion, Keji 12th Road  
South, High-tech Industrial Park, Nanshan, Shenzhen 518057, China.

**Prepared By :** Shenzhen HUAKE Testing Technology Co., Ltd.  
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,  
Bao'an District, Shenzhen City, China

**Date of Test:** Dec. 19, 2018 ~ Dec. 28, 2018

**Date of Report:** Dec. 28, 2018

**Report Number:** HK1812202011-1E



### 1.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

### 1.2 Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

### 1.3 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6



300 – 1500	/	/	f/300	6
1500 –	/	/	5	6
100,000				

## Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 –	/	/	1.0	30
100,000				

F=frequency in MHz

\*=Plane-wave equivalent power density

## Manufacturing tolerance

## 5G WiFi (5725-5850) ANT.1

IEEE 802.11a (Average)			
Channel	Channel 5745	Channel 5785	Channel 5825
Target (dBm)	10	10	10
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 5745	Channel 5785	Channel 5825
Target (dBm)	9	9	9
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 5755	Channel 5795	
Target (dBm)	9	9	
Tolerance ±(dB)	1.0	1.0	
IEEE 802.11ac HT20 (Average)			
Channel	Channel 5745	Channel 5785	Channel 5825
Target (dBm)	9	9	9
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11ac HT40 (Average)			
Channel	Channel 5755	Channel 5795	



Target (dBm)	8	8
Tolerance ±(dB)	1.0	1.0
<b>IEEE 802.11ac HT80 (Average)</b>		
Channel	Channel 5775	
Target (dBm)	8	
Tolerance ±(dB)	1.0	

**5G WiFi (5725-5850) ANT.2**

<b>IEEE 802.11a (Average)</b>					
Channel	Channel 5745	Channel 5785	Channel 5825		
Target (dBm)	10	10	10		
Tolerance ±(dB)	1.0	1.0	1.0		
<b>IEEE 802.11n HT20 (Average)</b>					
Channel	Channel 5745	Channel 5785	Channel 5825		
Target (dBm)	9	9	10		
Tolerance ±(dB)	1.0	1.0	1.0		
<b>IEEE 802.11n HT40 (Average)</b>					
Channel	Channel 5755	Channel 5795			
Target (dBm)	9	9			
Tolerance ±(dB)	1.0	1.0			
<b>IEEE 802.11ac HT20 (Average)</b>					
Channel	Channel 5745	Channel 5785	Channel 5825		
Target (dBm)	9	9	9		
Tolerance ±(dB)	1.0	1.0	1.0		
<b>IEEE 802.11ac HT40 (Average)</b>					
Channel	Channel 5755	Channel 5795			
Target (dBm)	8	8			
Tolerance ±(dB)	1.0	1.0			
<b>IEEE 802.11ac HT80 (Average)</b>					
Channel	Channel 5775				
Target (dBm)	8				
Tolerance ±(dB)	1.0				

**5G WiFi (5725-5850) MIMO**

<b>IEEE 802.11n HT20 (Average)</b>			
Channel	Channel 5745	Channel 5785	Channel 5825
Target (dBm)	12	12	12
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>IEEE 802.11n HT40 (Average)</b>			
Channel	Channel 5755	Channel 5795	
Target (dBm)	12	12	12
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>IEEE 802.11ac HT20 (Average)</b>			
Channel	Channel 5745	Channel 5785	Channel 5825
Target (dBm)	12	12	12
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>IEEE 802.11ac HT40 (Average)</b>			
Channel	Channel 5755	Channel 5795	
Target (dBm)	11	11	11
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>IEEE 802.11ac HT80 (Average)</b>			
Channel	Channel 5775		
Target (dBm)	11		
Tolerance $\pm$ (dB)	1.0		



## 1.5 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum source-based Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna is 1.00 dBi for 5.8GHz WLAN, the power drift from Turn-up Procedure provided by manufacturer as following states, the RF power density can be obtained.



## 1.6 Evaluation Result

### 1.6.1 Standalone MPE

Mode	Minimum Separation Distance (cm)	Output Power (Turn-up Procedure)		Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm <sup>2</sup> )	Power Density Limit (mW/cm <sup>2</sup> )	Test Results
		dBm	mW				
5.8G WIFI	20.00	13	19.95	2.581	0.010249	1.0000	PASS

## 1.7 Conclusion

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

.....End of Report.....