

Passive Test For WIFIT2.4												
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBi)	UHS (%)	DMIS (%)	Max (dB)	Min (dB)	irectivity (dBi)	Beamwidth (3dB)	AttH (dB)	AttV (dB)
2400	33.08	-4.8	1.23	-0.92	12.005	21.078	1.23	-25.47	6.03	0	49.04	48.91
2410	32.78	-4.84	1.13	-1.02	12.135	20.637	1.13	-31.44	5.97	15	49.03	48.83
2420	33.57	-4.74	1.12	-1.03	12.788	20.785	1.12	-31.13	5.86	15	49.02	48.97
2430	33.95	-4.69	1.04	-1.11	13.204	20.743	1.04	-24.76	5.73	15	49.13	49.11
2440	35.12	-4.54	1.12	-1.03	13.836	21.285	1.12	-22.22	5.67	15	49.13	49.11
2450	36.11	-4.42	1.28	-0.87	14.268	21.841	1.28	-22.66	5.7	15	49.39	49.35
2460	35.42	-4.51	1.24	-0.91	13.925	21.491	1.24	-22.4	5.75	15	49.39	49.35
2470	33.8	-4.71	1.12	-1.03	13.17	20.63	1.12	-22.15	5.83	15	49.39	49.3
2480	32.59	-4.87	1.06	-1.09	12.536	20.057	1.06	-21.82	5.93	15	49.44	49.35
2490	28.98	-5.38	0.76	-1.39	10.991	17.985	0.76	-21.88	6.14	15	49.19	49.13
2500	27.53	-5.6	0.8	-1.35	10.283	17.248	0.8	-21.15	6.4	15	49.32	49.32

Application Information	
D4Version	4.95.303
TotalTime	13m 10s 609ms
AdditionalInfor	NULL

