




Fanguang Inspection & Testing Co., Ltd.
 Phone: +86-510-68790033
 Web: www.fgtest.cn



MEASUREMENT REPORT

FCC PART 15.247 WLAN 802.11b/g/n

Report No.: S202205270617E07
 Report Version: V01
 Issue Date: 08-12-2022

Applicant: ROIDMI Information Technology Co., Ltd.
Address: Layer4, Building C8, NO.1699, Huishan Road Huishan Economic Development District Wuxi, China
FCC ID: 2AR98-JCZ06
Application Type: Certification
Product: Base Station
Model No.: JCZ06RM,JCZ06RM*(*Could be 0-9 or A-Z,indicate for different color and accessories)
Trade Mark: 
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15 Subpart C (15.247)
Test Procedure(s): ANSI C63.10-2013, KDB 558074 D01v05r02
Test Date: July 26 ~ July 29, 2022

Compiled By Amos Xia
 (Amos Xia)
 Senior Test Engineer
 Approved By Zeming Zhang
 (Zeming Zhang)
 Engineer Manager

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of Fanguang Inspection & Testing Co., Ltd. Wuxi Branch

The test report must not be used by the client to claim product certifications, approval, or endorsement by NVLAP, NIST or any agency of U.S. Government.



Revision History

Report No.	Version	Description	Issue Date
S202205270617E07	Rev. 01	/	08-12-2022

CONTENTS

Description	Page
§2.1033 General Information	5
1. INTRODUCTION	6
1.1. Scope	6
1.2. Fangguang Test Location	6
2. PRODUCT INFORMATION	7
2.1. Equipment Description	7
2.2. Product Specification Subjective to this Report	7
2.3. Operation Frequency / Channel List	7
2.4. Device Capabilities	8
2.5. Description of Test Software	8
2.6. Test Mode	8
2.7. Test Configuration	8
2.8. EMI Suppression Device(s)/Modifications	8
2.9. Labeling Requirements	9
3. DESCRIPTION OF TEST	10
3.1. Evaluation Procedure	10
3.2. AC Line Conducted Emissions	10
3.3. Radiated Emissions	11
4. ANTENNA REQUIREMENTS	12
5. TEST EQUIPMENT CALIBRATION DATE	13
6. MEASUREMENT UNCERTAINTY	14
7. TEST RESULT	15
7.1. Summary	15
7.2. 6dB Bandwidth Measurement	16
7.2.1. Test Limit	16
7.2.2. Test Procedure used	16
7.2.3. Test Setting	16
7.2.4. Test Setup	16
7.2.5. Test Result	17
7.3. Output Power Measurement	22
7.3.1. Test Limit	22
7.3.2. Test Procedure Used	22

7.3.3. Test Setting	22
7.3.4. Test Setup	23
7.3.5. Test Result of Output Power	24
7.4. Power Spectral Density Measurement	30
7.4.1. Test Limit	30
7.4.2. Test Procedure Used	30
7.4.3. Test Setting	30
7.4.4. Test Setup	30
7.4.5. Test Result	31
7.5. Conducted Band Edge and Out-of-Band Emissions	36
7.5.1. Test Limit	36
7.5.2. Test Procedure Used	36
7.5.3. Test Setting	36
7.5.4. Test Setup	36
7.5.5. Test Result	37
7.6. Radiated Spurious Emission Measurement	55
7.6.1. Test Limit	55
7.6.2. Test Procedure Used	55
7.6.3. Test Setting	55
7.6.4. Test Setup	57
7.6.5. Test Result	59
7.7. Radiated Restricted Band Edge Measurement	74
7.7.1. Test Limit	74
7.7.2. Test Procedure Used	75
7.7.3. Test Setting	75
7.7.4. Test Setup	76
7.7.5. Test Result	77
7.8. AC Conducted Emissions Measurement	101
7.8.1. Test Limit	101
7.8.2. Test Setup	101
7.8.3. Test Result	102

§2.1033 General Information

Applicant:	ROIDMI Information Technology Co., Ltd.
Applicant Address:	Layer4, Building C8, NO.1699, Huishan Road Huishan Economic Development District Wuxi, China
Manufacturer:	ROIDMI Information Technology Co., Ltd.
Manufacturer Address:	Layer4, Building C8, NO.1699, Huishan Road Huishan Economic Development District Wuxi, China
Factory:	Guangdong Joy Intelligent Technology Co., LTD.
Factory Address:	Room 1201, No. 58, Second Street, Mawu New Village, Changping Town, Dongguan, Guangdong, China
Test Site:	Fanguang Inspection & Testing Co., Ltd.
Test Site Address:	200 Linghu Avenue, Xinwu District, Wuxi City, China
CAB ID:	CN0054
Test Device Serial No.:	<input checked="" type="checkbox"/> Production SN:RVWWBA0I07383 <input type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering
FCC Classification:	Digital Transmission System (DTS)

1. INTRODUCTION

1.1. Scope


Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2. Fangguang Test Location

These measurement tests were performed at the Fangguang Inspection and testing Co.,LTD located at 200 Linghu Avenue, Xinwu District, Wuxi City. The detailed description of the measurement facility was found to be in compliance with the requirements of ANSI C63.4-2014.

2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name:	Base Station
Model Name:	JCZ06RM
Additional Model:	JCZ06RM*(*Could be 0-9 or A-Z,indicate for different color and accessories)
Model Description:	All models are electrically identical, only color and accessories are different.
Trade Mark:	
Rated value :	Rated Input:100-130V~, 50-60Hz Rated Output:24Vdc 1.2A Dust Collection Power:850W Charging Power:30W Cleaning Power:40W
Wi-Fi Specification:	802.11b/g/n-HT20

2.2. Product Specification Subjective to this Report

Frequency Range:	802.11b/g/n-HT20: 2412 ~ 2462MHz
Channel Number:	802.11b/g/n-HT20: 11
Type of Modulation:	802.11b: DSSS 802.11g/n: OFDM
Data Rate:	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: MCS0~MCS7
Antenna Type:	PCB Antenna
Antenna Gain:	3.92dBi

2.3. Operation Frequency / Channel List

802.11b/g/n-HT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

2.4. Device Capabilities

This device contains the following capabilities:

2.4GHz WLAN (DTS)

Note: 2.4GHz WLAN (DTS) operation is possible in 20MHz channel bandwidths. The maximum achievable duty cycle was determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are 100%.

2.5. Description of Test Software

The test utility software used during testing was “wl tool”, and the power setting value is 12.

2.6. Test Mode

Test Mode	Mode 1: Transmit by 802.11b Ant 1
	Mode 2: Transmit by 802.11g Ant 1
	Mode 3: Transmit by 802.11n-HT20 Ant 1

2.7. Test Configuration

The EUT was tested per the guidance of KDB 558074 D01 v05r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.8. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.9. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. The turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-25GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- Use a permanently attached antenna.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	FWXGJC-2016-181	1 year	2023/04/27
Two-Line V-Network	R&S	ENV 216	FWXGJC-2016-182	1 year	2023/06/01
AMN	AFJ	LT32C/10	FWXGJC-2016-179	1 year	2022/10/19
Thermohygrometer	Yuhuaze	HTC-1	FWXDA-2016-385	1 year	2022/12/27

Radiated Emission

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Bi-Log Antenna	R&S	HL562E	FWXGJC-2016-267-06	1 year	2023/03/30
Broadband Horn Antenna	R&S	HF907	FWXGJC-2016-267-07	1 year	2023/03/12
EMI Receiver	R&S	ESR26	FWXGJC-2016-267-01	1 year	2022/11/26
Pre-Amplifier	R&S	SCU-18D	FWXGJC-2016-267-05	1 year	2022/12/12
Thermohygrometer	Yuhuaze	HTC-1	FWXDA-2016-386	1 year	2022/12/27
Anechoic Chamber	Aimuke	EMCCT-3	FWXGJC-2016-270	3 year	2023/04/07

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	Keysight	N9010B	FWXGJC-2018-010	1 year	2023/04/13
RF Control Unit	Toncend	JS0806-2	FWXGJC-2018-013	1 year	2022/07/27
Thermohygrometer	Yuhuaze	HTC-1	FWXDA-2016-385	1 year	2022/12/27

Test Software	Manufacturer	Version	Asset No.	Function
EMI Test Software	tonscend	/	/	/

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 2.05dB
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 3.06dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 30MHz-1GHz: 1.00 dB 1GHz-26.5GHz: 1.30 dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.60dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.80dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.20MHz

7. TEST RESULT

7.1. Summary

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.203	Antenna Requirement	/	/	Pass	Section 4
15.247(a)(2)	6dB Bandwidth	$\geq 500\text{kHz}$	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	$\leq 30\text{dBm}$		Pass	Section 7.3
15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$		Pass	Section 7.4
15.247(d)	Band Edge	$\geq 20\text{dBc}$		Pass	Section 7.5
15.247(d)	Out-of-Band Emissions	$\geq 20\text{dBc}$		Pass	Section 7.6
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	Section 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	AC Line Conducted	Pass	Section 7.8

Notes:

- 1) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) N/A is the DC power supply does not need to test the item.

7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.2.2. Test Procedure used


ANSI C63.10-2013 Section 11.8.2 Option 1

KDB 558074 D01 v05r02 – Section 8.2

7.2.3. Test Setting


1. Set RBW = 100 kHz
2. VBW $\geq 3 \times$ RBW
3. Detector = peak
4. Trace mode = max hold
5. Sweep = auto couple
6. Allow the trace was allowed to stabilize
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.2.4. Test Setup




7.2.5. Test Result

TestMode	Antenna	Channel	FL[MHz]	FH[MHz]	DTS BW [MHz]	Limit[MHz]	99% BW(MHz)	Verdict
11B	Ant1	2412	2407.440	2416.520	9.080	≥0.5	11.244	PASS
		2437	2432.480	2441.520	9.040	≥0.5	11.109	PASS
		2462	2457.400	2466.480	9.080	≥0.5	11.227	PASS
11G	Ant1	2412	2405.240	2418.560	13.320	≥0.5	15.595	PASS
		2437	2429.440	2444.480	15.040	≥0.5	15.529	PASS
		2462	2455.280	2469.520	14.240	≥0.5	15.542	PASS
11N20SISO	Ant1	2412	2405.320	2419.520	14.200	≥0.5	15.941	PASS
		2437	2430.320	2444.480	14.160	≥0.5	15.988	PASS
		2462	2455.440	2469.440	14.000	≥0.5	15.966	PASS



11B_Ant1_2437



11B_Ant1_2462



11G_Ant1_2412




11G_Ant1_2437



11G_Ant1_2462




11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



7.3. Output Power Measurement

7.3.1. Test Limit

The maximum peak conducted output power is 1 Watt (FCC).

7.3.2. Test Procedure Used


ANSI C63.10-2013 – Section 11.9.2.2

KDB 558074 D01 v05r02 – Section 8.3.2.2

7.3.3. Test Setting

1. Set the RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
2. Set the VBW $\geq [3 \times \text{RBW}]$.
3. Set span to at least 1.5 times the OBW.
4. Number of points in sweep $[2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
5. Sweep time = auto
6. Detector = RMS.
7. If transmit duty cycle < 98%, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at the maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no OFF intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”.
8. Trace average at least 100 traces in power averaging (rms) mode..
9. Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.3.4. Test Setup



7.3.5. Test Result of Output Power

Power output test was verified over all data rates of each mode shown as below, and then choose the maximum power output (yellow marker) for final test of each channel.


N _{TX}	Data Rate (Mbps)	
	802.11b	802.11g
1	1	6
1	2	9
1	5.5	12
1	11	18
1	--	24
1	--	36
1	--	48
1	--	54

N _{TX}	MCS Index for 802.11n	Data Rate (Mbps)			
		20MHz Bandwidth		40MHz Bandwidth	
		800ns GI	400ns GI	800ns GI	400ns GI
1	0	6.5	7.2	13.5	15.0
1	1	13.0	14.4	27.0	30.0
1	2	19.5	21.7	40.5	45.0
1	3	26.0	28.9	54.0	60.0
1	4	39.0	43.3	81.0	90.0
1	5	52.0	57.8	108.0	120.0
1	6	58.5	65.0	121.5	135.0
1	7	65.0	72.2	135.0	150.0


Note: Power output test was verified over all data rates of each mode shown as above, and then choose the maximum power output (yellow marker) for final test of each channel.

Test Result of Maximum conducted output power/E.I.R.P


Test Mode	Antenna	Channel	Power[dBm]	Limit[dBm]	E.I.R.P[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	15.95	≤30	19.87	≤36	PASS
		2437	17.48	≤30	21.40	≤36	PASS
		2462	16.96	≤30	20.88	≤36	PASS
11G	Ant1	2412	12.42	≤30	16.34	≤36	PASS
		2437	15.52	≤30	19.44	≤36	PASS
		2462	10.13	≤30	14.05	≤36	PASS
11N20SISO	Ant1	2412	11.76	≤30	15.68	≤36	PASS
		2437	14.29	≤30	18.21	≤36	PASS
		2462	8.60	≤30	12.52	≤36	PASS




11B_Ant1_2437




11B_Ant1_2462




11G_Ant1_2412



11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



7.4. Power Spectral Density Measurement

7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

7.4.2. Test Procedure Used


KDB 558074 D01 v05r02 - Section 8.4

ANSI C63.10 – Section 11.10.3

7.4.3. Test Setting


1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq [3 \times \text{RBW}]$.
5. Detector = power averaging (rms) or sample detector (when rms not available).
6. Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
7. Sweep time = auto couple.
8. Employ trace averaging (rms) mode over a minimum of 100 traces.
9. Use the peak marker function to determine the maximum amplitude level.

7.4.4. Test Setup




7.4.5. Test Result

Test Mode	Antenna	Channel	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-10.72	≤8.00	PASS
		2437	-8.83	≤8.00	PASS
		2462	-9.75	≤8.00	PASS
11G	Ant1	2412	-15.93	≤8.00	PASS
		2437	-12.26	≤8.00	PASS
		2462	-17.97	≤8.00	PASS
11N20SISO	Ant1	2412	-16.45	≤8.00	PASS
		2437	-13.76	≤8.00	PASS
		2462	-19.39	≤8.00	PASS




11G_Ant1_2412



11G_Ant1_2437



11G_Ant1_2462



11N20SISO_Ant1_2412

