

RF Exposure Requirements

Product Description:Feel

Model No.: Feel-1

FCC ID:2AR9G-FEEL-1

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation¹⁷

- The result is rounded to one decimal place for comparison

Calculation Result:

Tx frequency range:2402MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power:-4.99dBm(0.317mW)

Tune-Up output power: 1dBm(1.26mW)

RF channel transmit frequency:2402MHz

Result: 0.813

Limit: 3.0

Tx frequency range:2442MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power:-2.55dBm(0.5559 mW)

Tune-Up output power: 1dBm(1.26mW)

RF channel transmit frequency:2442MHz

Result: 0.8063

Limit: 3.0

Tx frequency range:2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power:-2.17dBm(0.6067 mW)

Tune-Up output power: 1dBm(1.26mW)

RF channel transmit frequency:2480MHz

Result: 0.8

Limit: 3.0

The exclusion thresholds is $0.813 < 3$, so the transmitter complies with the RF exposure requirements and the SAR is not required.