

MPE REPORT

FCC ID:2ARBY-CORE-200S

Date of issue: July 27, 2020

Report number: MTi20070716-1E4

Sample description: Smart True HEPA Air Purifier

Model(s): Core 200S

Applicant: Arovast corporation

Address: 1202 N Miller St, Suite A, Anaheim, CA 92806, USA

Date of test: July 16, 2020 to July 27, 2020

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel: (86-755) 88850135

Fax: (86-755) 88850136

Web: <http://www.mtitest.com>

E-mail: mti@51mti.com

Address: 101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.



TEST RESULT CERTIFICATION	
Applicant's name:	Arovast corporation
Address:	1202 N Miller St, Suite A, Anaheim, CA 92806, USA
Manufacture's name:	Xiamen Easepal Healthy Technology Co., Ltd.
Address:	No. 30 Ma An Road, Tong An District, Xiamen, Fujian, 361100
Product name:	Smart True HEPA Air Purifier
Trademark:	LEVOIT
Model and/or type reference:	Core 200S
Serial model:	N/A
RF exposure procedures:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Danny Xu

July 27, 2020

Reviewed by:

Leo Su

July 27, 2020

Approved by:

Tom Xue

July 27, 2020



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm(20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Measurement Result

Antenna Type: Antenna: PCB Antenna;
antenna gain: 3.7dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(3.7/10)}=2.34$

BLE:

Channel Freq. (MHz)	modulation n	conducte d power	Tune- up powe r (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Nume ric		
2402	GFSK	3.486	4±1	5	3.162	3.70	2.34	0.0015	1
2440		4.949	4±1	5	3.162	3.70	2.34	0.0015	1
2480		4.583	4±1	5	3.162	3.70	2.34	0.0015	1

BT:

Channel Freq. (MHz)	modulation n	conducte d power	Tune- up powe r (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Nume ric		
2402	GFSK	3.507	4±1	5	3.162	3.70	2.34	0.0015	1
2441		4.957	4±1	5	3.162	3.70	2.34	0.0015	1
2480		4.602	4±1	5	3.162	3.70	2.34	0.0015	1
2402	π/4- DQPSK	3.977	4±1	5	3.162	3.70	2.34	0.0015	1
2441		4.309	4±1	5	3.162	3.70	2.34	0.0015	1
2480		4.903	4±1	5	3.162	3.70	2.34	0.0015	1
2402	8DPSK	3.097	4±1	5	3.162	3.70	2.34	0.0015	1
2441		4.416	4±1	5	3.162	3.70	2.34	0.0015	1
2480		4.98	4±1	5	3.162	3.70	2.34	0.0015	1



2.4GWiFi:

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm ²)	(mW/cm ²)
				(dBm)	(mW)	Numeric		
		Ant A	Ant A	Ant A	Ant A	Ant A	Ant A	
2412	802.11b	13.58	14±1	15	31.62	2.34	0.01472	1
2437		14.31	14±1	15	31.62	2.34	0.01472	1
2462		14.06	14±1	15	31.62	2.34	0.01472	1
2412	802.11g	12.32	12±1	13	19.95	2.34	0.00929	1
2437		12.3	12±1	13	19.95	2.34	0.00929	1
2462		12.21	12±1	13	19.95	2.34	0.00929	1
2412	802.11n H20	12.46	12±1	13	19.95	2.34	0.00929	1
2437		12.26	12±1	13	19.95	2.34	0.00929	1
2462		12.16	12±1	13	19.95	2.34	0.00929	1

Conclusion:

For the max result(BT+WiFi): $0.0015+0.01472=0.01622 \leq 1.0$ for 1g SAR, No SAR is required.

----END OF REPORT----