

FCC 47 CFR MPE REPORT

Arovast Corporation

Air Purifier

Model Number: Core 400S, LAP-C401S-WUSR

Addition Model Number: LAP-C401S-KUSR, LAP-C401S-XXXX
(where "X" may be blank, number from 0 to 9 or letter from A to Z)

FCC ID: 2ARBY-CORE400S

Applicant:	Arovast Corporation
Address:	1775 FLIGHT WAY, SUITE 150 TUSTIN.CA 92782, USA
Prepared By:	EST Technology Co., Ltd.
Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China	
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2504106
Date of Test:	Mar. 04, 2025 ~ Apr. 07, 2025
Date of Report:	Apr. 14, 2025

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
				(dBi)	(Linear)			
2.4G Band								
GFSK	6.233	6±1	7	2.04	1.60	0.0016	1	Complies
π/4-DQPSK	8.694	8±1	9	2.04	1.60	0.0025	1	Complies
8-DPSK	9.014	9±1	10	2.04	1.60	0.0032	1	Complies
BLE	3.916	4±1	5	2.04	1.60	0.0010	1	Complies
IEEE 802.11b	15.67	15±1	16	2.04	1.60	0.01267	1	Complies
IEEE 802.11g	17.50	17±1	18	2.04	1.60	0.02008	1	Complies
IEEE 802.11n HT20	16.76	17±1	18	2.04	1.60	0.02008	1	Complies
IEEE 802.11n HT40	16.47	17±1	18	2.04	1.60	0.02008	1	Complies

End of Test Report