



# FCC TEST REPORT

## FCC ID:2ARCP-SK16

Report Number..... : ZKT-241127L16795E

Date of Test..... : Nov. 27, 2024 ~ Feb. 14, 2025

Date of issue..... : Feb. 14, 2025

Total number of pages..... 33

Test Result ..... : PASS

Testing Laboratory..... : **Shenzhen ZKT Technology Co., Ltd.**

Address ..... : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name ..... : Sinco Intelligent Technology Co., Ltd.

Address ..... : Room 805-807, No. 17, Wenheng Street, Sanzao Town, Jinwan District, Zhuhai City, China

Manufacturer's name ..... : Sinco Intelligent Technology Co., Ltd.

Address ..... : Room 805-807, No. 17, Wenheng Street, Sanzao Town, Jinwan District, Zhuhai City, China

Test specification:

Standard..... : FCC CFR Title 47 Part 15 Subpart C Section 15.249  
ANSI C63.10:2013

Test procedure..... : /

Non-standard test method ..... : N/A

**Test Report Form No.....** : TRF-EL-111\_V0

**Test Report Form(s) Originator.....** : ZKT Testing

**Master TRF** ..... : Dec. 04, 2024

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : Midi Controller

Trademark ..... : M-VAVE, LEKATO, AMW, AZOR, Ziron, EROK, UTIMO, CASON, DONNER, Btuty, Yuimer

Model/Type reference..... : SMC-PAD POCKET, Mini Pad, STARRYPAD MINI, SMARTPAD MINI, SK16

Ratings..... : DC 5.0V from adapter or DC 3.7V from Li-battery



Testing procedure and testing location:

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community  
Industrial Avenue, Fuhai Street, Bao'an District,  
Shenzhen, China

Tested by (name + signature).....: Jim Liu

Reviewer (name + signature).....: Jackson Fang

Approved (name + signature).....: Lake Xie



## Table of Contents

Page

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| <b>1.VERSION .....</b>                                            | <b>5</b>  |
| <b>2. SUMMARY OF TEST RESULTS .....</b>                           | <b>6</b>  |
| 2.1 TEST FACILITY .....                                           | 7         |
| 2.2 MEASUREMENT UNCERTAINTY .....                                 | 7         |
| <b>3. GENERAL INFORMATION .....</b>                               | <b>8</b>  |
| 3.1 GENERAL DESCRIPTION OF EUT .....                              | 8         |
| 3.2 DESCRIPTION OF TEST MODES .....                               | 9         |
| 3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED ..... | 9         |
| 3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) .....            | 10        |
| 3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS .....                      | 11        |
| <b>4. EMC EMISSION TEST .....</b>                                 | <b>12</b> |
| 4.1 CONDUCTED EMISSION MEASUREMENT .....                          | 12        |
| 4.1.1 POWER LINE CONDUCTED EMISSION Limits .....                  | 12        |
| 4.1.2 TEST PROCEDURE .....                                        | 12        |
| 4.1.3 DEVIATION FROM TEST STANDARD .....                          | 12        |
| 4.1.4 TEST SETUP .....                                            | 13        |
| 4.1.5 EUT OPERATING CONDITIONS .....                              | 13        |
| 4.2 RADIATED EMISSION MEASUREMENT .....                           | 16        |
| 4.2.1 RADIATED EMISSION LIMITS .....                              | 16        |
| 4.2.2 TEST PROCEDURE .....                                        | 17        |
| 4.2.3 DEVIATION FROM TEST STANDARD .....                          | 17        |
| 4.2.4 TEST SETUP .....                                            | 17        |
| 4.2.5 EUT OPERATING CONDITIONS .....                              | 18        |
| <b>5. BANDWIDTH OF FREQUENCY BAND EDGE .....</b>                  | <b>23</b> |
| <b>6. BANDWIDTH OF FREQUENCY BAND EDGE .....</b>                  | <b>25</b> |
| 6.1 TEST REQUIREMENT: .....                                       | 25        |
| 6.2 TEST PROCEDURE .....                                          | 25        |
| 6.3 DEVIATION FROM TEST STANDARD .....                            | 25        |
| 6.4 TEST SETUP .....                                              | 25        |
| 6.5 EUT OPERATING CONDITIONS .....                                | 26        |
| 6.6 TEST RESULT .....                                             | 27        |
| <b>7. CHANNEL BANDWIDTH .....</b>                                 | <b>29</b> |
| 7.1 APPLIED PROCEDURES / LIMIT .....                              | 29        |
| 7.2 TEST PROCEDURE .....                                          | 29        |
| 7.3 DEVIATION FROM STANDARD .....                                 | 29        |



| Table of Contents                    | Page |
|--------------------------------------|------|
| 7.4 TEST SETUP .....                 | 29   |
| 7.5 EUT OPERATION CONDITIONS .....   | 29   |
| 7.6 TEST RESULT .....                | 30   |
| 8.ANTENNA REQUIREMENT .....          | 32   |
| 9. TEST SETUP PHOTO .....            | 33   |
| 10. EUT CONSTRUCTIONAL DETAILS ..... | 33   |



## 1.VERSION

| Report No.        | Version | Description             | Approved      |
|-------------------|---------|-------------------------|---------------|
| ZKT-241127L16795E | Rev.01  | Initial issue of report | Feb. 14, 2025 |
|                   |         |                         |               |
|                   |         |                         |               |



## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.249) , Subpart C |                                                     |          |        |
|---------------------------------|-----------------------------------------------------|----------|--------|
| Standard Section                | Test Item                                           | Judgment | Remark |
| FCC part 15.203                 | Antenna requirement                                 | PASS     |        |
| FCC part 15.207                 | AC Power Line Conducted Emission                    | PASS     |        |
| FCC part15.249(a)               | Field Strength of Fundamental                       | PASS     |        |
| FCC part 15.249                 | Fundamental &Radiated Spurious Emission Measurement | PASS     |        |
| FCC part 15.215 (c)             | 20dB Channel Bandwidth                              | PASS     |        |
| FCC part 15.205                 | Band Edge                                           | PASS     |        |

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



## 2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

## 2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$  , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  , providing a level of confidence of approximately 95 % .

| No. | Item                         | Uncertainty               |
|-----|------------------------------|---------------------------|
| 1   | Conducted Emission Test      | $\pm 1.38\text{dB}$       |
| 2   | RF power conducted           | $\pm 0.16\text{dB}$       |
| 3   | Spurious emissions conducted | $\pm 0.21\text{dB}$       |
| 4   | All emissions radiated(<1G)  | $\pm 4.68\text{dB}$       |
| 5   | All emissions radiated(>1G)  | $\pm 4.89\text{dB}$       |
| 6   | Temperature                  | $\pm 0.5^{\circ}\text{C}$ |
| 7   | Humidity                     | $\pm 2\%$                 |



### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                      |                                                                                                                                                       |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:        | Midi Controller                                                                                                                                       |
| Model No.:           | SMC-PAD POCKET, Mini Pad, STARRYPAD MINI, SMARTPAD MINI, SK16                                                                                         |
| Model Different.:    | All model' s the function, software and electric circuit are the same, only Product color and model named different.Test sample model: SMC-PAD POCKET |
| Serial No.:          | N/A                                                                                                                                                   |
| Hardware Version:    | H1.0                                                                                                                                                  |
| Software Version:    | S1.0                                                                                                                                                  |
| Sample(s) Status:    | Engineer sample                                                                                                                                       |
| Operation Frequency: | 2402MHz-2480MHz                                                                                                                                       |
| Channel Numbers:     | 40CH                                                                                                                                                  |
| Modulation Type:     | GFSK                                                                                                                                                  |
| Antenna Type:        | PCB Antenna                                                                                                                                           |
| Antenna gain:        | 0.67 dBi                                                                                                                                              |
| Power supply:        | DC 5.0V from adapter or DC 3.7V from Li-battery                                                                                                       |

| Channel List |                 |         |                 |         |                 |         |                 |
|--------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel      | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 00           | 2402            | 10      | 2422            | 20      | 2442            | 30      | 2462            |
| 01           | 2404            | 11      | 2424            | 21      | 2444            | 31      | 2464            |
| 02           | 2406            | 12      | 2426            | 22      | 2446            | 32      | 2466            |
| 03           | 2408            | 13      | 2428            | 23      | 2448            | 33      | 2468            |
| 04           | 2410            | 14      | 2430            | 24      | 2450            | 34      | 2470            |
| 05           | 2412            | 15      | 2432            | 25      | 2452            | 35      | 2472            |
| 06           | 2414            | 16      | 2434            | 26      | 2454            | 36      | 2474            |
| 07           | 2416            | 17      | 2436            | 27      | 2456            | 37      | 2476            |
| 08           | 2418            | 18      | 2438            | 28      | 2458            | 38      | 2478            |
| 09           | 2420            | 19      | 2440            | 29      | 2460            | 39      | 2480            |

| Channel             | Frequency |
|---------------------|-----------|
| The lowest channel  | 2402MHz   |
| The middle channel  | 2440MHz   |
| The Highest channel | 2480MHz   |






### 3.2 DESCRIPTION OF TEST MODES

|                                                                                                                                                                                                                                       |                                                |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| Transmitting mode                                                                                                                                                                                                                     | Keep the EUT in continuously transmitting mode |
| Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data. |                                                |


|                   |                        |
|-------------------|------------------------|
| Test Software     | FCC_assist_1.0.2.2.exe |
| Power level setup | default                |

### 3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

#### Radiated Emission



#### Conducted Spurious





### 3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment      | Mfr/Brand | Model/Type No. | Series No. | Note |
|------|----------------|-----------|----------------|------------|------|
| E-1  | SMC-PAD POCKET | /         | SMC-PAD POCKET | /          | EUT  |
| A-1  | Adapter        | /         | MDY-11-EX      | /          | /    |
|      |                |           |                |            |      |
|      |                |           |                |            |      |
|      |                |           |                |            |      |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|--------|------|
| C-1  | /             | /            | /      | /    |
|      |               |              |        |      |
|      |               |              |        |      |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



### 3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

#### Equipment List:

| Item | Equipment                            | Manufacturer   | Type No.           | Serial No.           | Last calibration | Calibrated until |
|------|--------------------------------------|----------------|--------------------|----------------------|------------------|------------------|
| 1    | Spectrum Analyzer<br>(9kHz-26.5GHz)  | KEYSIGHT       | 9020A              | MY55370835           | Sep. 29, 2024    | Sep. 28, 2025    |
| 2    | Spectrum Analyzer<br>(10kHz-39.9GHz) | R&S            | FSQ                | 100363               | Sep. 30, 2024    | Sep. 29, 2025    |
| 3    | EMI Test Receiver<br>(9kHz-7GHz)     | R&S            | ESCI7              | 101169               | Sep. 29, 2024    | Sep. 28, 2025    |
| 4    | Bilog Antenna<br>(30MHz-1500MHz)     | Schwarzbeck    | VULB9168           | N/A                  | Sep. 30, 2024    | Sep. 29, 2025    |
| 5    | Horn Antenna<br>(1GHz-18GHz)         | Agilent        | AH-118             | 071145               | Sep. 30, 2024    | Sep. 29, 2025    |
| 6    | Horn Antenna<br>(15GHz-40GHz)        | A.H.System     | SAS-574            | 588                  | Sep. 30, 2024    | Sep. 29, 2025    |
| 7    | Loop Antenna                         | TESEQ          | HLA6121            | 58357                | Oct. 11, 2024    | Oct. 10, 2025    |
| 8    | Amplifier<br>(30-1000MHz)            | EM Electronics | EM330<br>Amplifier | 060747               | Sep. 29, 2024    | Sep. 28, 2025    |
| 9    | Amplifier<br>(1GHz-26.5GHz)          | Agilent        | 8449B              | 3008A00315           | Sep. 29, 2024    | Sep. 28, 2025    |
| 10   | Amplifier<br>(500MHz-40GHz)          | Quanjuda       | DLE-161            | 097                  | Sep. 30, 2024    | Sep. 29, 2025    |
| 11   | Test Cable                           | N/A            | R-01               | N/A                  | Sep. 30, 2024    | Sep. 29, 2025    |
| 12   | Test Cable                           | N/A            | R-02               | N/A                  | Sep. 30, 2024    | Sep. 29, 2025    |
| 13   | Test Cable                           | N/A            | R-03               | N/A                  | Sep. 30, 2024    | Sep. 29, 2025    |
| 14   | Test Cable                           | N/A            | RF-01              | N/A                  | Sep. 30, 2024    | Sep. 29, 2025    |
| 15   | Test Cable                           | N/A            | RF-02              | N/A                  | Sep. 30, 2024    | Sep. 29, 2025    |
| 16   | Test Cable                           | N/A            | RF-03              | N/A                  | Sep. 30, 2024    | Sep. 29, 2025    |
| 17   | ESG Signal<br>Generator              | Agilent        | E4421B             | N/A                  | Sep. 29, 2024    | Sep. 28, 2025    |
| 18   | Signal Generator                     | Agilent        | N5182A             | N/A                  | Sep. 29, 2024    | Sep. 28, 2025    |
| 19   | Magnetic Field<br>Probe Tester       | Narda          | ELT-400            | 0-0344               | Nov. 15, 2024    | Nov. 14, 2025    |
| 20   | Wideband Radio<br>Communication Test | R&S            | CMW500             | 106504               | Sep. 30, 2024    | Sep. 29, 2025    |
| 21   | MWRF Power Meter<br>Test system      | MW             | MW100-RPCB         | N/A                  | Sep. 29, 2024    | Sep. 28, 2025    |
| 22   | D.C. Power Supply                    | LongWei        | TPR-6405D          | N/A                  | \                | \                |
| 23   | EMC Software                         | Frad           | EZ-EMC             | Ver.EMC-CON<br>3A1.1 | \                | \                |
| 24   | RF Software                          | MW             | MTS8310            | V2.0.0.0             | \                | \                |
| 25   | Turntable                            | MF             | MF-7802BS          | N/A                  | \                | \                |
| 26   | Antenna tower                        | MF             | MF-7802BS          | N/A                  | \                | \                |



#### 4. EMC EMISSION TEST

##### 4.1 CONDUCTED EMISSION MEASUREMENT

|                       |                                      |
|-----------------------|--------------------------------------|
| Test Requirement:     | FCC Part15 C Section 15.207          |
| Test Method:          | ANSI C63.10:2013                     |
| Test Frequency Range: | 150KHz to 30MHz                      |
| Receiver setup:       | RBW=9KHz, VBW=30KHz, Sweep time=auto |

##### 4.1.1 POWER LINE CONDUCTED EMISSION Limits

| FREQUENCY (MHz) | Limit (dBuV) |           | Standard |
|-----------------|--------------|-----------|----------|
|                 | Quas-peak    | Average   |          |
| 0.15 -0.5       | 66 - 56 *    | 56 - 46 * | FCC      |
| 0.50 -5.0       | 56.00        | 46.00     | FCC      |
| 5.0 -30.0       | 60.00        | 50.00     | FCC      |

Note:

(1) \*Decreases with the logarithm of the frequency.

##### 4.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

##### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation



#### 4.1.4 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
  - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes


#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

#### 4.1.6 Test Result



|               |                                   |                    |      |
|---------------|-----------------------------------|--------------------|------|
| Temperature:  | 26°C                              | Relative Humidity: | 60%  |
| Test Voltage: | AC 120V, 60Hz                     | Phase:             | Line |
| Test Mode:    | Transmitting mode of GFSK 2480MHz |                    |      |




| No. | Frequency<br>(MHz) | QuasiPeak<br>reading<br>(dBuV) | Average<br>reading<br>(dBuV) | Correction<br>factor<br>(dB) | QuasiPeak<br>result<br>(dBuV) | Average<br>result<br>(dBuV) | QuasiPeak<br>limit<br>(dBuV) | Average<br>limit<br>(dBuV) | QuasiPeak<br>margin<br>(dB) | Average<br>margin<br>(dB) | Remark |
|-----|--------------------|--------------------------------|------------------------------|------------------------------|-------------------------------|-----------------------------|------------------------------|----------------------------|-----------------------------|---------------------------|--------|
| 1P  | 0.2660             | 29.27                          | 18.17                        | 10.08                        | 39.35                         | 28.25                       | 61.24                        | 51.24                      | -21.89                      | -22.99                    | Pass   |
| 2P  | 0.4220             | 32.13                          | 21.30                        | 10.07                        | 42.20                         | 31.37                       | 57.41                        | 47.41                      | -15.21                      | -16.04                    | Pass   |
| 3P  | 0.5020             | 33.68                          | 18.22                        | 10.08                        | 43.76                         | 28.30                       | 56.00                        | 46.00                      | -12.24                      | -17.70                    | Pass   |
| 4*  | 0.5580             | 37.30                          | 25.37                        | 10.07                        | 47.37                         | 35.44                       | 56.00                        | 46.00                      | -8.63                       | -10.56                    | Pass   |
| 5P  | 0.6140             | 28.39                          | 17.06                        | 10.06                        | 38.45                         | 27.12                       | 56.00                        | 46.00                      | -17.55                      | -18.88                    | Pass   |
| 6P  | 1.6420             | 27.42                          | 17.97                        | 10.17                        | 37.59                         | 28.14                       | 56.00                        | 46.00                      | -18.41                      | -17.86                    | Pass   |

Remark: Factor = Insertion Loss + Cable Loss, Result = Reading + Factor, Margin = Result – Limit.





|               |                                   |                    |         |
|---------------|-----------------------------------|--------------------|---------|
| Temperature:  | 26°C                              | Relative Humidity: | 60%     |
| Test Voltage: | AC 120V, 60Hz                     | Phase:             | Neutral |
| Test Mode:    | Transmitting mode of GFSK 2480MHz |                    |         |



| No. | Frequency<br>(MHz) | QuasiPeak<br>reading<br>(dBuV) | Average<br>reading<br>(dBuV) | Correction<br>factor<br>(dB) | QuasiPeak<br>result<br>(dBuV) | Average<br>result<br>(dBuV) | QuasiPeak<br>limit<br>(dBuV) | Average<br>limit<br>(dBuV) | QuasiPeak<br>margin<br>(dB) | Average<br>margin<br>(dB) | Remark |
|-----|--------------------|--------------------------------|------------------------------|------------------------------|-------------------------------|-----------------------------|------------------------------|----------------------------|-----------------------------|---------------------------|--------|
| 1P  | 0.2660             | 30.69                          | 18.18                        | 10.08                        | 40.77                         | 28.26                       | 61.24                        | 51.24                      | -20.47                      | -22.98                    | Pass   |
| 2P  | 0.4180             | 31.98                          | 20.34                        | 10.07                        | 42.05                         | 30.41                       | 57.49                        | 47.49                      | -15.44                      | -17.08                    | Pass   |
| 3P  | 0.5100             | 33.77                          | 18.27                        | 10.08                        | 43.85                         | 28.35                       | 56.00                        | 46.00                      | -12.15                      | -17.65                    | Pass   |
| 4*  | 0.5580             | 36.91                          | 24.56                        | 10.07                        | 46.98                         | 34.63                       | 56.00                        | 46.00                      | -9.02                       | -11.37                    | Pass   |
| 5P  | 0.6180             | 29.65                          | 16.95                        | 10.06                        | 39.71                         | 27.01                       | 56.00                        | 46.00                      | -16.29                      | -18.99                    | Pass   |
| 6P  | 1.6420             | 28.11                          | 18.75                        | 10.17                        | 38.28                         | 28.92                       | 56.00                        | 46.00                      | -17.72                      | -17.08                    | Pass   |

Remark: Factor = Insertion Loss + Cable Loss, Result = Reading + Factor, Margin = Result – Limit.



#### 4.2 RADIATED EMISSION MEASUREMENT

|                       |                             |            |        |        |            |
|-----------------------|-----------------------------|------------|--------|--------|------------|
| Test Requirement:     | FCC Part15 C Section 15.209 |            |        |        |            |
| Test Method:          | ANSI C63.10:2013            |            |        |        |            |
| Test Frequency Range: | 9kHz to 25GHz               |            |        |        |            |
| Test site:            | Measurement Distance: 3m    |            |        |        |            |
| Receiver setup:       | Frequency                   | Detector   | RBW    | VBW    | Value      |
|                       | 9KHz-150KHz                 | Quasi-peak | 200Hz  | 600Hz  | Quasi-peak |
|                       | 150KHz-30MHz                | Quasi-peak | 9KHz   | 30KHz  | Quasi-peak |
|                       | 30MHz-1GHz                  | Quasi-peak | 100KHz | 300KHz | Quasi-peak |
|                       | Above 1GHz                  | Peak       | 1MHz   | 3MHz   | Peak       |
|                       |                             | Peak       | 1MHz   | 10Hz   | Average    |

##### 4.2.1 RADIATED EMISSION LIMITS

| Frequencies<br>(MHz) | Field Strength<br>(micorvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                          | 300                              |
| 0.490~1.705          | 24000/F(KHz)                         | 30                               |
| 1.705~30.0           | 30                                   | 30                               |
| 30~88                | 100                                  | 3                                |
| 88~216               | 150                                  | 3                                |
| 216~960              | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

##### LIMITS OF RADIATED EMISSION MEASUREMENT

| FREQUENCY (MHz) | Limit (dBuV/m) (at 3M) |         |
|-----------------|------------------------|---------|
|                 | PEAK                   | AVERAGE |
| Above 1000      | 74                     | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).





#### 4.2.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.
- For the radiated emission test above 1GHz:  
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.  
The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.  
Note:  
Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

#### 4.2.3 DEVIATION FROM TEST STANDARD

No deviation


#### 4.2.4 TEST SETUP

##### (A) Radiated Emission Test-Up Frequency Below 30MHz






(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


#### 4.2.6 TEST RESULTS (Between 9KHz – 30 MHz)

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.



Between 30MHz – 1GHz

|               |                                   |                    |            |
|---------------|-----------------------------------|--------------------|------------|
| Temperature:  | 25℃                               | Relative Humidity: | 60%        |
| Test Voltage: | AC 120V, 60Hz                     | Phase:             | Horizontal |
| Test Mode:    | Transmitting mode of GFSK 2402MHz |                    |            |




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (deg.) | Height (cm) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|---------------|-------------|--------|
| 1   | 191.7450        | 41.07          | -20.65                  | 20.42           | 43.50          | -23.08      |               |             | QP     |
| 2   | 287.9904        | 45.26          | -17.79                  | 27.47           | 46.00          | -18.53      |               |             | QP     |
| 3   | 336.0352        | 40.41          | -17.26                  | 23.15           | 46.00          | -22.85      |               |             | QP     |
| 4   | 399.0302        | 37.54          | -14.79                  | 22.75           | 46.00          | -23.25      |               |             | QP     |
| 5   | 798.9797        | 36.65          | -8.74                   | 27.91           | 46.00          | -18.09      |               |             | QP     |
| 6*  | 869.1302        | 43.05          | -7.72                   | 35.33           | 46.00          | -10.67      |               |             | QP     |

Remark: Result = Reading Level + Factor, Margin = Result - Limit  
 Factor = Ant. Factor + Cable Loss - Pre-amplifier



|               |                                   |                    |          |
|---------------|-----------------------------------|--------------------|----------|
| Temperature:  | 25℃                               | Relative Humidity: | 60%      |
| Test Voltage: | AC 120V, 60Hz                     | Phase:             | Vertical |
| Test Mode:    | Transmitting mode of GFSK 2480MHz |                    |          |



| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (deg.) | Height (cm) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|---------------|-------------|--------|
| 1   | 46.5030         | 49.19          | -27.88                  | 21.31           | 40.00          | -18.69      |               |             | QP     |
| 2   | 59.0251         | 46.57          | -26.07                  | 20.50           | 40.00          | -19.50      |               |             | QP     |
| 3   | 87.4177         | 47.06          | -24.85                  | 22.21           | 40.00          | -17.79      |               |             | QP     |
| 4   | 96.0986         | 48.87          | -24.26                  | 24.61           | 43.50          | -18.89      |               |             | QP     |
| 5*  | 191.7450        | 52.25          | -20.65                  | 31.60           | 43.50          | -11.90      |               |             | QP     |
| 6   | 607.7867        | 45.67          | -11.94                  | 33.73           | 46.00          | -12.27      |               |             | QP     |

Remark: Result = Reading Level + Factor, Margin = Result - Limit  
Factor = Ant. Factor + Cable Loss - Pre-amplifier



GFSK 1GHz~25GHz

| Polar<br>(H/V)      | Frequency | Meter<br>Reading | Pre-ampli<br>fier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|---------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                     | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| Low Channel:2402MHz |           |                  |                   |               |                   |                   |          |        |                  |
| V                   | 4804.00   | 54.32            | 30.55             | 5.77          | 24.66             | 54.2              | 74       | -19.8  | Pk               |
| V                   | 4804.00   | 43.35            | 30.55             | 5.77          | 24.66             | 43.23             | 54       | -10.77 | AV               |
| V                   | 7206.00   | 54.11            | 30.33             | 6.32          | 24.55             | 54.65             | 74       | -19.35 | Pk               |
| V                   | 7206.00   | 43.71            | 30.33             | 6.32          | 24.55             | 44.25             | 54       | -9.75  | AV               |
| V                   | 9608.00   | 52.52            | 30.85             | 7.45          | 24.69             | 53.81             | 74       | -20.19 | Pk               |
| V                   | 9608.00   | 43.42            | 30.85             | 7.45          | 24.69             | 44.71             | 54       | -9.29  | AV               |
| V                   | 12010.00  | 52.65            | 31.02             | 8.99          | 25.57             | 56.19             | 74       | -17.81 | Pk               |
| V                   | 12010.00  | 43.28            | 31.02             | 8.99          | 25.57             | 46.82             | 54       | -7.18  | AV               |
| H                   | 4804.00   | 51.54            | 30.55             | 5.77          | 24.66             | 51.42             | 74       | -22.58 | Pk               |
| H                   | 4804.00   | 43.53            | 30.55             | 5.77          | 24.66             | 43.41             | 54       | -10.59 | AV               |
| H                   | 7206.00   | 54.51            | 30.33             | 6.32          | 24.55             | 55.05             | 74       | -18.95 | Pk               |
| H                   | 7206.00   | 43.15            | 30.33             | 6.32          | 24.55             | 43.69             | 54       | -10.31 | AV               |
| H                   | 9608.00   | 52.57            | 30.85             | 7.45          | 24.69             | 53.86             | 74       | -20.14 | Pk               |
| H                   | 9608.00   | 43.98            | 30.85             | 7.45          | 24.69             | 45.27             | 54       | -8.73  | AV               |
| H                   | 12010.00  | 54.94            | 31.02             | 8.99          | 25.57             | 58.48             | 74       | -15.52 | Pk               |
| H                   | 12010.00  | 43.59            | 31.02             | 8.99          | 25.57             | 47.13             | 54       | -6.87  | AV               |

| Polar<br>(H/V)         | Frequency | Meter<br>Reading | Pre-ampli<br>fier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                        | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| Middle Channel:2440MHz |           |                  |                   |               |                   |                   |          |        |                  |
| V                      | 4880.00   | 50.65            | 30.55             | 5.77          | 24.66             | 50.53             | 74       | -23.47 | Pk               |
| V                      | 4880.00   | 43.35            | 30.55             | 5.77          | 24.66             | 43.23             | 54       | -10.77 | AV               |
| V                      | 7320.00   | 50.75            | 30.33             | 6.32          | 24.55             | 51.29             | 74       | -22.71 | Pk               |
| V                      | 7320.00   | 43.52            | 30.33             | 6.32          | 24.55             | 44.06             | 54       | -9.94  | AV               |
| V                      | 9760.00   | 54.23            | 30.85             | 7.45          | 24.69             | 55.52             | 74       | -18.48 | Pk               |
| V                      | 9760.00   | 43.87            | 30.85             | 7.45          | 24.69             | 45.16             | 54       | -8.84  | AV               |
| V                      | 12200.00  | 56.42            | 31.02             | 8.99          | 25.57             | 59.96             | 74       | -14.04 | Pk               |
| V                      | 12200.00  | 43.12            | 31.02             | 8.99          | 25.57             | 46.66             | 54       | -7.34  | AV               |
| H                      | 4880.00   | 51.54            | 30.55             | 5.77          | 24.66             | 51.42             | 74       | -22.58 | Pk               |
| H                      | 4880.00   | 43.91            | 30.55             | 5.77          | 24.66             | 43.79             | 54       | -10.21 | AV               |
| H                      | 7320.00   | 50.35            | 30.33             | 6.32          | 24.55             | 50.89             | 74       | -23.11 | Pk               |
| H                      | 7320.00   | 43.91            | 30.33             | 6.32          | 24.55             | 44.45             | 54       | -9.55  | AV               |
| H                      | 9760.00   | 53.05            | 30.85             | 7.45          | 24.69             | 54.34             | 74       | -19.66 | Pk               |
| H                      | 9760.00   | 43.16            | 30.85             | 7.45          | 24.69             | 44.45             | 54       | -9.55  | AV               |
| H                      | 12200.00  | 53.38            | 31.02             | 8.99          | 25.57             | 56.92             | 74       | -17.08 | Pk               |
| H                      | 12200.00  | 43.72            | 31.02             | 8.99          | 25.57             | 47.26             | 54       | -6.74  | AV               |





Page 22 of 65

| Polar<br>(H/V)       | Frequency | Meter<br>Reading | Pre-ampli<br>fier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|----------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                      | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| High Channel:2480MHz |           |                  |                   |               |                   |                   |          |        |                  |
| V                    | 4960.00   | 50.52            | 30.55             | 5.77          | 24.66             | 50.4              | 74       | -23.6  | Pk               |
| V                    | 4960.00   | 43.45            | 30.55             | 5.77          | 24.66             | 43.33             | 54       | -10.67 | AV               |
| V                    | 7440.00   | 54.82            | 30.33             | 6.32          | 24.55             | 55.36             | 74       | -18.64 | Pk               |
| V                    | 7440.00   | 43.55            | 30.33             | 6.32          | 24.55             | 44.09             | 54       | -9.91  | AV               |
| V                    | 9920.00   | 51.46            | 30.85             | 7.45          | 24.69             | 52.75             | 74       | -21.25 | Pk               |
| V                    | 9920.00   | 43.25            | 30.85             | 7.45          | 24.69             | 44.54             | 54       | -9.46  | AV               |
| V                    | 12400.00  | 53.62            | 31.02             | 8.99          | 25.57             | 57.16             | 74       | -16.84 | Pk               |
| V                    | 12400.00  | 43.63            | 31.02             | 8.99          | 25.57             | 47.17             | 54       | -6.83  | AV               |
| H                    | 4960.00   | 54.14            | 30.55             | 5.77          | 24.66             | 54.02             | 74       | -19.98 | Pk               |
| H                    | 4960.00   | 43.37            | 30.55             | 5.77          | 24.66             | 43.25             | 54       | -10.75 | AV               |
| H                    | 7440.00   | 51.33            | 30.33             | 6.32          | 24.55             | 51.87             | 74       | -22.13 | Pk               |
| H                    | 7440.00   | 43.53            | 30.33             | 6.32          | 24.55             | 44.07             | 54       | -9.93  | AV               |
| H                    | 9920.00   | 50.54            | 30.85             | 7.45          | 24.69             | 51.83             | 74       | -22.17 | Pk               |
| H                    | 9920.00   | 43.81            | 30.85             | 7.45          | 24.69             | 45.1              | 54       | -8.9   | AV               |
| H                    | 12400.00  | 52.98            | 31.02             | 8.99          | 25.57             | 56.52             | 74       | -17.48 | Pk               |
| H                    | 12400.00  | 43.74            | 31.02             | 8.99          | 25.57             | 47.28             | 54       | -6.72  | AV               |

## Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



## 5. BANDWIDTH OF FREQUENCY BAND EDGE


### 5.1 Limit

| Fundamental frequency | Field strength of fundamental@3m (millivolts/meter) | Average Limit@3m dBμV/m | Peak Limit@3m dBμV/m |
|-----------------------|-----------------------------------------------------|-------------------------|----------------------|
| 902-928MHz            | 50                                                  | 94                      | 114                  |
| 2407-2477MHz          | 50                                                  | 94                      | 114                  |
| 5725-5875MHz          | 50                                                  | 94                      | 114                  |
| 24.0-24.25            | 250                                                 | 108                     | 128                  |

Note :

1. Average Limit (dBμV/m)= $20 \times \log[1000 \times \text{Field Strength (mV/m)}]$ .
2. Peak Limit (dBμV/m)= Average Limit (dBμV/m)+20dB

### 5.2 Test Setup



### 5.2 Spectrum Analyzer Setting

| Spectrum Parameters | Setting    |
|---------------------|------------|
| RBW                 | $\geq$ OBW |
| VBW                 | 3×RBW      |
| Start frequency     | 2407MHz    |
| Stop frequency      | 2477MHz    |
| Sweep Time          | Auto       |
| Detector            | PEAK/AVG   |
| Trace Mode          | Max Hold   |





#### 5.4 Test Procedure

- a. EUT was placed on a turn table, which is 1.5 meter high above the ground.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Spectrum analyzer setting parameters in accordance with section 3.3.
- d. Set the EUT transmit continuously with maximum output power.
- e. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- f. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test, record the average and peak value.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.

#### 5.5 Test Result

| Test frequency<br>(MHz) | Fundamental<br>Frequency (MHz) | Field strength of<br>fundamental level<br>(dBμV/m) |       | Limit (dBuV) |      | Result | Antenna<br>Pole (H/V) |
|-------------------------|--------------------------------|----------------------------------------------------|-------|--------------|------|--------|-----------------------|
|                         |                                | AVG                                                | Peak  | AVG          | Peak |        |                       |
| 2402                    | 2402.952                       | 89.52                                              | 92.32 | 94           | 114  | Pass   | H                     |
|                         | 2402.916                       | 89.92                                              | 93.32 | 94           | 114  | Pass   | V                     |
| 2440                    | 2440.732                       | 91.25                                              | 92.25 | 94           | 114  | Pass   | H                     |
|                         | 2440.525                       | 92.21                                              | 92.71 | 94           | 114  | Pass   | V                     |
| 2480                    | 2480.731                       | 91.85                                              | 93.25 | 94           | 114  | Pass   | H                     |
|                         | 2480.154                       | 92.19                                              | 93.69 | 94           | 114  | Pass   | V                     |



## 6. BANDWIDTH OF FREQUENCY BAND EDGE

### 6.1 TEST REQUIREMENT:

|                       |                                                                                                    |          |      |      |         |
|-----------------------|----------------------------------------------------------------------------------------------------|----------|------|------|---------|
| Test Requirement:     | FCC Part15 C Section 15.209 and 15.205                                                             |          |      |      |         |
| Test Method:          | ANSI C63.10: 2013                                                                                  |          |      |      |         |
| Test Frequency Range: | All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed. |          |      |      |         |
| Test site:            | Measurement Distance: 3m                                                                           |          |      |      |         |
| Receiver setup:       | Frequency                                                                                          | Detector | RBW  | VBW  | Value   |
|                       | Above                                                                                              | Peak     | 1MHz | 3MHz | Peak    |
|                       | 1GHz                                                                                               | Average  | 1MHz | 3MHz | Average |

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation

### 6.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


### 6.3 DEVIATION FROM TEST STANDARD

No deviation

### 6.4 TEST SETUP



## Radiated Emission Test-Up Frequency Above 1GHz



### 6.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



## 6.6 TEST RESULT

Operation Mode: TX CH00 (2402MHz)

Horizontal:

| Frequency | Reading Result | Factor | Emission Level | Limits   | Margin | Detector |
|-----------|----------------|--------|----------------|----------|--------|----------|
| (MHz)     | (dBμV)         | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   | Type     |
| 2310      | 56.24          | -5.81  | 50.43          | 74       | -23.57 | PK       |
| 2310      | /              | -5.81  | /              | 54       | /      | AV       |
| 2390      | 57.52          | -5.84  | 51.68          | 74       | -22.32 | PK       |
| 2390      | /              | -5.84  | /              | 54       | /      | AV       |
| 2400      | 57.74          | -5.84  | 51.9           | 74       | -22.1  | PK       |
| 2400      | /              | -5.84  | /              | 54       | /      | AV       |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

| Frequency | Reading Result | Factor | Emission Level | Limits   | Margin | Detector |
|-----------|----------------|--------|----------------|----------|--------|----------|
| (MHz)     | (dBμV)         | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   | Type     |
| 2310      | 56.62          | -5.81  | 50.81          | 74       | -23.19 | PK       |
| 2310      | /              | -5.81  | /              | 54       | /      | AV       |
| 2390      | 56.92          | -5.84  | 51.08          | 74       | -22.92 | PK       |
| 2390      | /              | -5.84  | /              | 54       | /      | AV       |
| 2400      | 57.57          | -5.84  | 51.73          | 74       | -22.27 | PK       |
| 2400      | /              | -5.84  | /              | 54       | /      | AV       |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Operation Mode: TX CH39 (2480MHz)

Horizontal:

| Frequency<br>(MHz) | Reading Result<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Detector<br>Type |
|--------------------|--------------------------|----------------|----------------------------|--------------------|----------------|------------------|
| 2483.5             | 55.82                    | -5.65          | 50.17                      | 74                 | -23.83         | PK               |
| 2483.5             | /                        | -5.65          | /                          | 54                 | /              | AV               |
| 2500               | 56.73                    | -5.72          | 51.01                      | 74                 | -22.99         | PK               |
| 2500               | /                        | -5.72          | /                          | 54                 | /              | AV               |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

| Frequency<br>(MHz) | Reading Result<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Detector<br>Type |
|--------------------|--------------------------|----------------|----------------------------|--------------------|----------------|------------------|
| 2483.5             | 57.62                    | -5.65          | 51.97                      | 74                 | -22.03         | PK               |
| 2483.5             | /                        | -5.65          | /                          | 54                 | /              | AV               |
| 2500               | 56.67                    | -5.72          | 50.95                      | 74                 | -23.05         | PK               |
| 2500               | /                        | -5.72          | /                          | 54                 | /              | AV               |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Note:

Since the peak value is less than the average limit, the average value does not reflected in the report.



## 7. CHANNEL BANDWIDTH

|                   |                                    |
|-------------------|------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.249/15.215 |
| Test Method:      | ANSI C63.10: 2013                  |

### 7.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.249) , Subpart C |           |                          |        |
|---------------------------------|-----------|--------------------------|--------|
| Section                         | Test Item | Frequency Range<br>(MHz) | Result |
| 15.249(c)                       | Bandwidth | 2400-2483.5              | PASS   |

### 7.2 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 1-5% or DTS BW, not to exceed 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 7.3 DEVIATION FROM STANDARD

No deviation.

### 7.4 TEST SETUP



### 7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.






## 7.6 TEST RESULT

GFSK 1M Modulation:

| Channel | Frequency<br>(MHz) | 20dB Bandwidth<br>(MHz) | Result |
|---------|--------------------|-------------------------|--------|
| CH00    | 2402               | 1.085                   | PASS   |
| CH19    | 2440               | 1.087                   | PASS   |
| CH39    | 2480               | 1.081                   | PASS   |

CH00: 2402MHz





CH19: 2440MHz



CH39: 2480MHz





## 8.ANTENNA REQUIREMENT

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| Standard requirement:                                                                                                                                                                                                                                                                                                                                                                                                                                                     | FCC Part15 C Section 15.203 |
| 15.203 requirement:<br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |                             |
| EUT Antenna:                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                             |
| The antennas are PCB antenna, the best case gain of the antennas are 0.67dBi, reference to the appendix II for details.                                                                                                                                                                                                                                                                                                                                                   |                             |



#### 9. TEST SETUP PHOTO

Reference to the appendix I for details.

#### 10. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

\*\*\*\*\* END OF REPORT \*\*\*\*\*