

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

*FCC PART 15.247, SUBPART C
TEST REPORT**for**the*

Hearing Aid

Model: KLARO LP

Prepared for

iSuniye LLC
15270 Sobey Road
Saratoga, California, 95070

Prepared by:

Andreas Davidsson

Approved by:

Kevin Bothmann

Electro Magnetic Test, Inc.
1547 Plymouth Street
Mountain View, California 94043
(650) 965-4000

Date: November 19, 2018

	REPORT BODY	APPENDICES				TOTAL
		<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	
PAGES	26	27	3	2	3	61

This report shall not be reproduced except in full, without the written approval of Electro Magnetic Test, Inc.



Electro Magnetic Test, Inc. (EMT) is accredited by NVLAP, Lab Code 200147-0 to perform the tests listed in this report, except where noted otherwise. This report and the information contained herein represent the test results related only to the sample tested. This report should not be relied upon as an endorsement or certification by EMT or NVLAP for the sample tested, nor does it represent any statement whatsoever as to its marketing status or fitness of the equipment for a particular purpose.

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

REVISION HISTORY

REVISION	DATE	COMMENTS	MODIFIED BY
1.0	November 19, 2018	Original Document	-
1.1	December 5, 2018	Updated due to comments from reviewer.	Andreas Davidsson
1.2	December 9, 2018	Updated EIRP calculations.	Andreas Davidsson
1.3	December 18, 2018	Updated Peak Spectral calculations.	Andreas Davidsson


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

TABLE OF CONTENTS

SECTION	TITLE	PAGE
REVISION HISTORY		2
GENERAL REPORT SUMMARY		5
SUMMARY OF TEST RESULTS		6
TECHNICAL DESCRIPTION OF THE EUT		7
1. PURPOSE		8
2. ADMINISTRATIVE DATA		9
2.1 Location of Testing		9
2.2 Traceability Statement		9
2.3 Cognizant Personnel		9
2.4 Date Test Sample was Received		9
2.5 Disposition of the Test Sample		9
2.6 Abbreviations and Acronyms		9
3. APPLICABLE DOCUMENTS		10
4. DESCRIPTION OF TEST CONFIGURATION		11
4.1 Description of Test Configuration - EMI		11
4.1.1 Cable Construction and Termination		12
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT		13
5.1 EUT and Accessory List		13
5.2 EMI Test Equipment		14
6. TEST SITE DESCRIPTION		16
6.1 Test Facility Description		16
6.2 EUT Mounting, Bonding and Grounding		16
6.3 Facility Environmental Characteristics		16
7. TEST PROCEDURES		17
7.1 Emissions in Restricted and Non-Restricted Bands		17
7.1.3 Test Procedure (Radiated)		19
7.1.4 Test Procedure (Conducted)		20
7.2 Conducted Emissions Test – Mains Ports		21
7.2.1 Limit (FCC PART 15 Section 15.207(a), IC RSS-GEN Issue 4 [8.8])		21
7.2.2 Test Procedure		21
7.3 Occupied Bandwidth		22
7.3.1 Limit (FCC PART 15 Section 15.247(a)(2), IC-RSS 247 Issue 1, [5.2.1])		22
7.3.2 Test Procedure		22
7.3.3 Test Result		22
7.4 Maximum Peak Output Power		23
7.4.1 Limit (FCC PART 15 Section 15.247(b)(3), IC-RSS 247 Issue 1, [5.4.4])		23
7.4.2 Test Procedure		23
7.4.3 Test Result		23
7.5 Maximum Peak Power Spectral Density		24
7.5.1 Limit (FCC PART 15 Section 15.247(e), IC-RSS 247 Issue 1, [5.2.2])		24
7.5.2 Test Procedure		24
7.5.3 Test Result		24
7.6 Antenna Requirement		25
7.6.1 Requirement (FCC PART 15 SECTION 15.203,15.247(b)(4))		25
7.6.2 Test Result		25
8. CONCLUSIONS / COMPLIANCE STATEMENT		26
APPENDIX A		1
APPENDIX B		1
APPENDIX C		1
APPENDIX D		1

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

LIST OF APPENDICES

APPENDIX	TITLE
A	Radiated and Conducted Data Sheets • Radiated Emissions Test Data (General Requirements, and Restricted Bands) • Emissions in Non-Restricted Frequency Bands Test Data • Occupied Bandwidth Test Data • Maximum Peak Output Power Test Data • Maximum Peak Power Spectral Density Test Data
B	Test Setup Diagrams
C	Modifications To The EUT
D	Additional Models Covered Under This Report

LIST OF FIGURES

FIGURE	TITLE
1	Conducted Emissions Test Setup
2	Plot Map And Layout of Test Site
3	Layout of 5 Meter Semi-Anechoic Chamber


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Electro Magnetic Test, Inc., which is an independent testing and consulting firm. The test report is based on testing performed Electro Magnetic Test, Inc. personnel according to the measurement procedure described in the test specification given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Federal Government.

The measurement data and conclusions contained in this test report are deemed satisfactory evidence of compliance with Industry Canada Interference-Causing Equipment Standard ICES-003, Issue 6, January 2016.

Electro Magnetic Test, Inc. is recognized by the following agencies for performing EMI/EMC testing:

COUNTRY	AGENCY	IDENTIFYING #
USA	Federal Communications Commission (FCC) (EMT's test site is recognized by the FCC)	Registration Number: 90576
USA, Canada, Taiwan, Australia/New Zealand, European Community	National Voluntary Lab Accreditation Program (NVLAP) (EMT is accredited by NVLAP. A copy of the NVLAP Scope Of Accreditation is available upon request.)	Lab Code: 200147-0
Canada	Industry Canada	File No.: IC 2804
Japan	Voluntary Control Council For Interference (VCCI)	A-0118
	Open Field Test Site "A"	-
	Mains Conducted Emissions Test Site "D"	-
	Telecom Conducted Emissions Test Site "D"	-
	3 Meter Semi-Anechoic Chamber Site "E"	-
	3 Meter Semi-Anechoic Chamber Site "E" (1GHz – 6GHz)	-
	Mains Conducted Emissions Test Site "E"	-
	Telecom Conducted Emissions Test Site "E"	-
Korea	Ministry of Information and Communication's Radio Research Laboratory (RRL) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (A copy of the Scope Of Accreditation is available upon request)	US0036
Taiwan	Bureau Of Standards, Metrology and Inspection (BSMI)	Reference Number: SL2-IN-E-1024
Australia / New Zealand	Australian Communications Authority (AUSTEL)	*

*These agencies do not issue an identifying number to test labs.

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

GENERAL REPORT SUMMARY (CONTINUED)

Device Tested: Hearing Aid
Model: KLARO LP
S/N: N/A

Product Description: The EUT is a BLE enabled, battery operated hearing aid.

Modifications: The EUT was not modified during the testing.

Manufacturer: iSunie LLC
15270 Sobey Road
Saratoga, California, 95070

Test Date(s): October 4, 8, 24, 2018

Test Specifications: EMI requirements
Limits: CISPR 22: 1997 plus A1:2000 & A2:2002 Class B
FCC Title 47, Part 15 Subpart B, Class B
Test Procedure: ANSI C63.4: 2014

Test Deviations: The test procedure was not deviated from during the testing.

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	FCC STANDARD	RESULTS
7.1	Emissions in Restricted and Non-Restricted Bands	15.209, 15.247, 15.247(d)	PASS
7.2	Conducted Emissions	15.207(a)	N/A This device is battery operated
7.3	Occupied Bandwidth	15.247(a)(2)	PASS
7.4	Maximum Peak Output Power	15.247 (b)	PASS
7.5	Maximum Peak Power Spectral Density	15.247(e)	PASS
7.6	Antenna Requirement	15.203,15.247(b)(4))	PASS


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

TECHNICAL DESCRIPTION OF THE EUT

Manufacturer:		iSuniye LLC					
Manufacturer Address:		15270 Sobey Road					
EUT Name:		Hearing Aid					
Model No:		Model: KLARO LP					
Operation frequency:		2402 MHz to 2480 MHz					
Channel Number:		40					
Modulation Technology:		DSSS					
Antenna Type:		PCB Antenna					
Antenna Gain:		4 dBi					
Maximum Output Power:		-18.67 dBm					
Description of Channel:							
Bluetooth LE							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

1. PURPOSE

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the Hearing Aid Model: KLARO LP. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4: 2014. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the specification limits defined in FCC Title 47, Part 15, Subpart C.


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

2. ADMINISTRATIVE DATA

2.1 Location of Testing

The EMI tests described herein were performed at the test facility of Electro Magnetic Test, Inc., 1547 Plymouth Street, Mountain View, California, 94043.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The measurement results in this report and the calibration of the test equipment are traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

iSuniye LLC

Nilesh Shah CEO

Electro Magnetic Test, Inc.

Alok Patel	Test Technician
Andreas Davidsson	Test Technician
David Vivanco	Test Technician
Simeet Gandhi	Test Technician
Manan Modi	Test Technician
Sagar Bombaywala	Test Technician
Kevin Bothmann	Lab Manager

2.4 Date Test Sample was Received

The test sample was received on October 4, 2018.

2.5 Disposition of the Test Sample

The test sample was returned to iSuniye LLC. on October 24, 2018

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
CML	Corrected Meter Limit
LISN	Line Impedance Stabilization Network
CISPR	International Special Committee On Radio Interference
FCC	Federal Communications Commission

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this EMI Test Report.

SPEC	TITLE
FCC Title 47, Part 15, Subpart C	FCC Rules - Radio frequency devices (including digital devices).
FCC Publication KDB558074	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the fcc rules, August 24, 2018
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description of Test Configuration - EMI

The EUT was set to continuously output on the Bluetooth LE spectrum. The EUT was tested in three configurations, flat, vertical with antenna facing upwards, and vertical with antenna facing downwards. The flat orientation was found to have the highest emissions.

It was determined that the emissions were at their highest level when the EUT was operating in the above configuration. The final conducted as well as radiated data was taken in this mode of operation. All initial investigations were performed with the EMI receiver in manual mode scanning the frequency range continuously.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

4.1.1

Cable Construction and Termination

The EUT does not contain any attached cables.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT**5.1 EUT and Accessory List**

EQUIPMENT TYPE	MANUFACTURER	MODEL	SERIAL NUMBER	FCC ID
Hearing Aid (EUT)	iSuniye LLC	KLARO LP	N/A	N/A
THE FOLLOWING WERE LOCATED OUTSIDE THE TEST SITE:				
Tablet	Samsung	Galaxy Tab A	C08084B066A6B89	DoC
Charging Dock	iSuniye LLC	N/A	N/A	N/A


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

5.2 EMI Test Equipment

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
Spectrum Analyzer	Hewlett Packard	8566B	3024A20115	September 30, 2018	1 Year
RF Preselector	Hewlett Packard	85685A	3010A01157	September 30, 2018	1 Year
Quasi-Peak Adapter	Hewlett Packard	85650A	2430A00451	September 30, 2018	1 Year
Radiated EMI Software	Sector Design	N/A	Ver.1.4.6	N/A	N/A
EMI Receiver (Conducted EMI)	Rohde & Schwarz	ESU40	100295	July 18, 2018	1 Year
Conducted EMI Software	ETS-Lindgren	Tile!	Rev. 7.0.12.697	N/A	N/A
Preamplifier	Hewlett Packard	8447D	1937A02579	March 5, 2018	1 Year
RF Attenuator	Com-Power	LIT-153A	531175	December 15, 2017	1 Year
LISN	Solar Electronics	Type 21107-50-TS-50-N	21107150701	June 2, 2018	1 Year
LISN	Solar Electronics	Type 21107-50-TS-50-N	21107150702	June 2, 2018	1 Year
LISN	Solar Electronics	Type 21107-50-TS-50-N	21107150703	June 2, 2018	1 Year
LISN	Solar Electronics	Type 21107-50-TS-50-N	21107150704	June 2, 2018	1 Year
Biconical Antenna	Com Power	AB-100	01557	July 20, 2018	1 Year
Log Periodic Antenna	Com Power	AL-100	16001	July 7, 2018	1 Year
Antenna Mast	Com Power	AM-400	N/A	N/A	N/A
Turntable	Com Power	TT-100	N/A	N/A	N/A
Computer	Dell, Inc.	DHS	DNSV641	N/A	N/A
Printer	Hewlett Packard	C8124A	CN39A220ZD	N/A	N/A


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

5.2 EMI Test Equipment (Continued)

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
EMI Receiver	Rohde & Schwarz	ESU40	100127	February 2, 2018	1 Year
EMI Test Software	Rohde & Schwarz	EMC32	V8.54.0	N/A	N/A
BiConiLog Antenna	ETS-Lindgren	3143B	00206757	August 28, 2018	1 Year
Horn Antenna	ETS-Lindgren	3117	00109294	February 5, 2018	1 Year
Preamplifier	Rohde & Schwarz	TS-PR18	100056	December 12, 2017	1 Year
Antenna Mast	ETS-Lindgren	2171B	00150364	N/A	N/A
Turntable	ETS-Lindgren	2187-3.0	00118231	N/A	N/A
Computer	Dell, Inc.	Optiplex 745	4T50WC1	N/A	N/A
Multi-Function Controller	ETS-Lindgren	2090	00102270	N/A	N/A

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to the table below and section 7.1 of this report for the details of which sites were used for testing. All sites are located at 1547 Plymouth Street, Mountain View, California 94043.

Site Used For Test	Site Description
	Open Field Test Site "A"
	Mains Conducted Emissions Test Site "D"
	Telecom Conducted Emissions Test Site "D"
X	3 Meter Semi-Anechoic Chamber Site "E"
X	Mains Conducted Emissions Test Site "E"
	Telecom Conducted Emissions Test Site "E"

6.2 EUT Mounting, Bonding and Grounding

The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane for all tests not including radiated measurements above 1GHz.

For radiated measurements above 1GHz the EUT was mounted on a 0.7 meter non-conductive hollow cube that was placed on a 1.0 by 1.5 meter table 0.8 meters above the ground plane with a total height of 1.5 meters.

The EUT was not grounded.

6.3 Facility Environmental Characteristics

All tests were performed in a climate controlled building. The temperature was 24° C, humidity 45%, and barometric pressure 101.6 kPa.


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests.

7.1 Emissions in Restricted and Non-Restricted Bands

7.1.1 General Requirements Limit (FCC PART 15 Section 15.209(a)(1), IC-RSS-GEN Issue 4, [8.9])

Frequency of Emission (MHz)	Field Strength		Measurement Distance (Meters)
	$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$	
0.009-0.49	2400/F(kHz)		300
0.49-1.705	24000/F(kHz)		30
1.705-30	30		30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

7.1.2 Emissions in Restricted and Non-Restricted Bands Limit (FCC PART 15 Section 15.247(d), IC RSS-GEN Issue 4, [8.10], IC-RSS 247 Issue 1, [5.5])

Emissions in Restricted and Non-Restricted Bands FCC PART 15 Section 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.1.2 Emissions in Restricted and Non-Restricted Bands Limit (FCC PART 15 Section 15.247(d), IC-RSS-GEN Issue 4, [8.10], IC-RSS 247 Issue 1, [5.5]) (Continued)

Emissions in Restricted Bands IC-RSS-GEN Issue 4, [8.10]:

Restricted bands, identified in Table 6, are designated primarily for safety-of-life services (distress calling and certain aeronautical bands), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following restrictions apply:

- (a) Fundamental components of modulation of licence-exempt radio apparatus shall not fall within the restricted bands of Table 6 except for apparatus complying under RSS-287
- (b) Unwanted emissions that fall into restricted bands of Table 6 shall comply with the limits specified in RSS-Gen; and
- (c) Unwanted emissions that do not fall within the restricted frequency bands of Table 6 shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.

Limit (For Restricted Bands)
See General Limits Requirement In Above Chart (Section 7.1.1)

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.1.3 Test Procedure (Radiated)

The Rohde & Schwarz ESU40 EMI receiver was used as a measuring meter while under software control by the Rohde & Schwarz EMC32 software. To increase the sensitivity of the instrument, the built in preamplifier was used from 9 KHz to 1 GHz and an external preamplifier was used from 1 GHz to 26.5 GHz. The EMI receiver was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the EMI receiver records the highest measured reading over all the sweeps. The built in quasi-peak or average detector was used only for those readings which are marked accordingly on the data sheets. The effective measurement bandwidth used for the radiated emissions test was 100 kHz from 9 kHz to 26.5 GHz.

The Loop Antenna, Broadband BiConiLog and horn antennas were used as transducers during the measurement. The Loop antenna was used from 9 KHz to 30 MHz, the BiConiLog antenna was used from 30 MHz to 1000 MHz and horn antennas were used from 1GHz – 26.5 GHz. The frequency spans were wide (9 kHz to 150 kHz, 150 kHz to 30 MHz, 30 MHz to 88 MHz, 88 MHz to 216 MHz, 216 to 300 MHz, 300 MHz to 1 GHz, 1 GHz to 18 GHz and 18 GHz to 26.5 GHz) during preliminary investigations. The final data was taken with a frequency span of 1 MHz. Furthermore, the frequency span was reduced during the preliminary investigations as deemed necessary.

The 5 meter semi-anechoic chamber of Electro Magnetic Test, Inc. was used for radiated emission testing. This test site is set up according to ANSI C63.4: 2014. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. The EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength).

The presence of non EUT signals was verified by turning the EUT off. In case a non EUT signal was detected, the measurement bandwidth was reduced temporarily and verification was made that an additional adjacent peak did not exist. This ensures that the other signal does not hide any emissions from the EUT. The EUT was tested at a 3 meter test distance from 9 kHz to 26.5 GHz. to obtain final test data.

The test was run through fully three times with the EUT having its output set to low, middle, and high channels on each test respectively. The data was then combined to provide the worst case of all three tests.

Calculation Of Radiated Emission Test Data:

Amplitude - Gain + Antenna Factor + Cable Loss = Corrected Amplitude

Corrected Amplitude - Limit = Margin

Associated with the radiated emission test data in this report is a ± 5.1 dB measurement uncertainty.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.1.4 Test Procedure (Conducted)

This testing was not required; please see the results table for reasoning.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.2 Conducted Emissions Test – Mains Ports**7.2.1 Limit (FCC PART 15 Section 15.207(a), IC RSS-GEN Issue 4 [8.8])**

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

*Note: Decreases with the logarithm of the frequency

7.2.2 Test Procedure

This testing was not required; please see the results table for reasoning.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.3 Occupied Bandwidth

7.3.1 Limit (FCC PART 15 Section 15.247(a)(2), IC-RSS 247 Issue 1, [5.2.1])

FCC PART 15 Section 15.247(a)(2)

Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz

Limit
6 dB Bandwidth $\geq$ 500 kHz

7.3.2 Test Procedure

Follow the radiated test procedure but set the Spectrum Analyzer as below:

RBW: 100 kHz

VBW: $\geq 3 \times$ RBW

Detector: Peak

Trace Mode: Max Hold

- (1) Set analyzer center frequency to center of signal
- (2) Turn on occupied bandwidth measurement mode
- (3) Set measurement to 6db bandwidth

Associated with the Occupied Bandwidth test data in this report is a $\pm 2.5\%$ measurement uncertainty.

7.3.3 Test Result

The EUT meets the requirements. Please see the datasheets in Appendix A for the measurement results.


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.4 Maximum Peak Output Power

7.4.1 Limit (FCC PART 15 Section 15.247(b)(3), IC-RSS 247 Issue 1, [5.4.4])

FCC PART 15 Section 15.247(b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Limit
Maximum Peak Output Power (Digital Modulation) $\leq$ 1Watt or 30 dBm

7.4.2 Test Procedure

Follow the radiated test procedure but set the Spectrum Analyzer as below:

RBW > DTS Bandwidth

VBW $\geq$ 3 x RBW

Span $\geq$ 3 * RBW

Detector: Peak

Trace Mode: Max Hold

1. When the trace is completed, mark the peak value
2. Calculate the Field strength at 3Meters.
 - a. $E3 = \text{Results} - GP + AF + CL + 107$
Where:
 - b. Results = Specific uncorrected results from test (dBm)
 - c. GP = Pre-Amp Gain (dB)
 - d. AF = Antenna Factor (dB/m)
 - e. CL = Cable Loss (dB)
3. Calculate the EIRP by using the following equation:
 - a. $EIRP = E3 - 95.2$
Where:
 - b. $E3 = \text{See Step 2 (dBuV/m @ 3m)}$
4. Calculate the Peak Output Power by using the following equation:
 - a. Peak Power = EIRP - G_A
Where:
 - b. EIRP = See step 3 (dBm)
 - c. G_A = Antenna Gain (dBi)

Associated with the Maximum Peak Output Power test data in this report is a ± 5.1 dB measurement uncertainty.

7.4.3 Test Result

The EUT meets the requirements. Please see the datasheets in Appendix A for the measurement results.


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.5 Maximum Peak Power Spectral Density

7.5.1 Limit (FCC PART 15 Section 15.247(e), IC-RSS 247 Issue 1, [5.2.2])

FCC PART 15 Section 15.247(e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density

Limit
8 dBm/3 KHz

7.5.2 Test Procedure

Follow the radiated test procedure but set the Spectrum Analyzer as below:

$$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$$

$$\text{VBW} \geq 3 \times \text{RBW}$$

$$\text{Span} \geq 1.5 \times \text{DTS Bandwidth}$$

Detector: Peak

Sweep Time auto

- 1) Use Peak Marker Function
- 2) If value Exceeds limit, reduce RBW (no less than 3 kHz)
- 3) Calculate the Field strength at 3Meters.
 - a) $E_3 = \text{Results} - G_p + \text{AF} + \text{CL} + 107$
Where:
 - b) Results = Specific uncorrected results from test (dBm)
 - c) G_p = Pre-Amp Gain (dB)
 - d) AF = Antenna Factor (dB/m)
 - e) CL = Cable Loss (dB)
- 4) Calculate the EIRP by using the following equation:
 - a) $\text{EIRP} = E_3 - 95.2$
Where:
 - b) E_3 = See Step 3 (dBuV/m @ 3m)
- 5) Calculate the Peak Output Power by using the following equation:
 - a) Peak Power = EIRP - G_A
Where:
 - b) EIRP = See step 4 (dBm)
 - c) G_A = Antenna Gain (dBi)

Associated with the Maximum Peak Output Power test data in this report is a ± 5.1 dB measurement uncertainty.

7.5.3 Test Result

The EUT meets the requirements. Please see the datasheets in Appendix A for the measurement results.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.6 Antenna Requirement

7.6.1 Requirement (FCC PART 15 SECTION 15.203,15.247(b)(4))

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.6.2 Test Result

The antenna is integrated on the main PCB with no consideration for replacement on the Hearing Aid.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

8. CONCLUSIONS / COMPLIANCE STATEMENT

Based upon the results contained in this report, Electro Magnetic Test, Inc. has determined that the Hearing Aid, Model: KLARO LP meets all of the specification limits defined in FCC Title 47, Part 15, Subpart C.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX A

RADIATED AND CONDUCTED EMISSIONS DATA SHEETS

Radiated Emission Test Report

Tested At:

Electro Magnetic Test, Inc.
1547 Plymouth Street
Mountain View, CA 94043
Tel. 650-965-4000
Fax. 650-965-3000


Common Information

Test Description:	FCC Class B Radiated Emissions
Operating Conditions:	Normal
Test Engineer:	Andreas Davidsson

EUT Information

Company Name:	iSuniye LCC
EUT Name	Hearing Aid
Model Number:	Klaro LP
Serial Number:	N/A
Comment:	None

FCC Class B Radiated Scan 3m PK QP2



— FCC Class B 3m
◆ Final Result 1-PK+
— Preview Result 1V-PK+
◆ Final Result 2-QPK
— Preview Result 1H-PK+

Final Result 1

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
39.540000	18.7	229.0	H	0.0	15.5	21.30	40.00	
157.770000	19.3	239.0	V	332.0	15.4	24.20	43.50	
950.550000	38.3	199.0	V	91.0	32.0	7.70	46.00	

Final Result 2

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
39.540000	12.8	229.0	H	0.0	15.5	27.20	40.00	
157.770000	13.3	239.0	V	332.0	15.4	30.20	43.50	
950.550000	31.7	199.0	V	91.0	32.0	14.30	46.00	

Radiated Emission Test Report

Tested At:**Electro Magnetic Test, Inc.****1547 Plymouth Street****Mountain View, CA 94043****Tel. 650-965-4000****Fax. 650-965-3000****Common Information**

Test Description:	FCC Class B Radiated Emissions
Operating Conditions:	Normal
Test Engineer:	Andreas Davidsson

EUT Information

Company Name:	iSuniye LCC
EUT Name	Hearing Aid
Model Number:	Klaro LP
Serial Number:	N/A
Comment:	None

Radiated Emission Test Report

Tested At:

Electro Magnetic Test, Inc.
1547 Plymouth Street
Mountain View, CA 94043
Tel. 650-965-4000
Fax. 650-965-3000


Common Information

Test Description:	FCC Class B Radiated Emissions
Operating Conditions:	Normal
Test Engineer:	Andreas Davidsson

EUT Information

Company Name:	iSuniye LCC
EUT Name	Hearing Aid
Model Number:	Klaro LP
Serial Number:	N/A
Comment:	None

FCC Class B Radiated Scan 18GHz-26.5GHz 3m PK AVG




Final Result 1

Frequency (MHz)	MaxPeak (dB μ V/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
26036.325000	48.5	105.0	V	295.0	11.1	5.50	54.00	

Final Result 2

Frequency (MHz)	Average (dB μ V/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
26036.325000	34.9	105.0	V	295.0	11.1	19.20	54.00	

FCC Class B Radiated Sweep 1GHz-18GHz 3m PK AVG



Final Result 1

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1145.633333	33.9	354.0	V	147.0	-4.0	40.10	74.00	
2401.933333	88.0	126.0	H	342.0	1.8	-14.00	74.00	
2426.866667	85.0	100.0	H	333.0	1.9	-11.00	74.00	
2479.000000	80.2	118.0	H	340.0	2.1	-6.20	74.00	
4802.900000	51.3	100.0	H	249.0	5.7	22.70	74.00	
9038.733333	47.1	259.0	H	227.0	12.7	26.90	74.00	
16700.066667	55.9	100.0	H	132.0	23.6	18.10	74.00	


Final Result 2

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1145.633333	20.8	354.0	V	147.0	-4.0	33.20	54.00	
2401.933333	46.8	126.0	H	342.0	1.8	7.20	54.00	
2426.866667	33.0	100.0	H	333.0	1.9	21.00	54.00	
2479.000000	31.9	118.0	H	340.0	2.1	22.10	54.00	
4802.900000	29.8	100.0	H	249.0	5.7	24.20	54.00	
9038.733333	34.0	259.0	H	227.0	12.7	20.00	54.00	
16700.066667	42.6	100.0	H	132.0	23.6	11.40	54.00	



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000



FRONT VIEW

iSuniye LLC

Hearing Aid

Model: KLARO LP


CISPR 22/FCC Class B – Radiated Emissions

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000



REAR VIEW

iSuniye LLC

Hearing Aid

Model: KLARO LP

CISPR 22/FCC Class B – Radiated Emissions

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000



FRONT ZOOMED IN VIEW

iSuniye LLC

Hearing Aid

Model: KLARO LP


CISPR 22/FCC Class B – Radiated Emissions

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000



FRONT VIEW

iSuniye LLC

Hearing Aid

Model: KLARO LP


CISPR 22/FCC Class B – Radiated Emissions (>1GHz)

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000



REAR VIEW

iSunie LLC

Hearing Aid

Model: KLARO LP

CISPR 22/FCC Class B – Radiated Emissions (>1GHz)

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**




Company:	iSuniye LLC		Test Date:		10/04/18	
EUT Name:	Hearing Aid		Test Engineer:		Andreas Davidsson	
Model:	KLARO LP		Test Result:		PASS	
Operating Mode:	TX Mode					
Mode	Test CH	Frequency (MHz)	6 dB Bandwidth (KHz)	99% Occupied Bandwidth (MHz)	6 dB Bandwidth Limit (KHz)	Conclusion
Bluetooth LE	0	2402	624	1.070	≥ 500	PASS
	19	2440	720.5	1.128	≥ 500	PASS
	39	2480	736.4	1.080	≥ 500	PASS
Test Equipment: Please refer to section 5.2						



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000


Channel 0




ELECTRO MAGNETIC TEST, INC.


1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Channel 19



**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Channel 39


ELECTRO MAGNETIC TEST, INC.


1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Peak Output Power Test Data

Company:	iSuniye LLC			Test Date	10/04/18	
EUT Name	Hearing Aid			Test Engineer	Andreas Davidsson	
Model:	KLARO LP			Test Result	PASS	
Operating Mode	TX Mode					
Mode		Test CH	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Conclusion
Bluetooth LE		0	2402	-18.67	≤ 30	Pass
		19	2440	-23.19	≤ 30	Pass
		39	2480	-28.32	≤ 30	Pass
Test Equipment: Please refer to section 5.2						
Peak Output Power Calculation (See Section 7.4.2 for calculation explanation)						
Channel 0: $((-13.474 -54.9+37.7+4.2+107)-95.2) - 4 = -18.67$						
Channel 19: $((-17.987 -54.9+37.7+4.2+107)-95.2) - 4 = -23.19$						
Channel 39: $((-23.117 -54.9+37.7+4.2+107)-95.2) - 4 = -28.32$						


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Channel 0


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Channel 19

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Channel 39


ELECTRO MAGNETIC TEST, INC.


1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data

Company:	iSuniye LLC		Test Date	10/04/18	
EUT Name	Hearing Aid		Test Engineer	Andreas Davidsson	
Model:	KLARO LP		Test Result	PASS	
Operating Mode	TX Mode				
Mode	Test CH	Frequency (MHz)	Peak (dBm)	Limit (dBm)	Conclusion
Bluetooth LE	0	2402	-31.483	≤ 8	Pass
	19	2440	-32.028	≤ 8	Pass
	39	2480	-32.785	≤ 8	Pass
Test Equipment: Please refer to 5.2					
Peak Calculation (See Section 7.5.2 for calculation explanation)					
Channel 0: $((-1.283 - 79.9 + 37.7 + 4.2 + 107) - 95.2) - 4 = -31.483$					
Channel 19: $((-1.828 - 79.9 + 37.7 + 4.2 + 107) - 95.2) - 4 = -32.028$					
Channel 39: $((-2.585 - 79.9 + 37.7 + 4.2 + 107) - 95.2) - 4 = -32.785$					


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Channel 0


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Channel 19

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Channel 39



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX B

TEST SETUP DIAGRAMS





ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000




FIGURE 2 - PLOT MAP AND LAYOUT OF TEST SITE "A"




FIGURE 3 - LAYOUT OF 5 METER SEMI-ANECHOIC CHAMBER



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX C

MODIFICATIONS TO THE EUT



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

MODIFICATIONS TO THE EUT

No modifications were made to the EUT by Electro Magnetic Test, Inc. personnel during the testing.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX D

ADDITIONAL MODELS COVERED UNDER THIS REPORT



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

Hearing Aid
Model: KLARO LP
S/N: N/A

ALSO APPROVED UNDER THIS REPORT:

Model: KLARO MP
Model: KLARO HP

Reasoning:

These units have exact same hardware except for having a different speaker module. The speaker module produces audio only.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

End of Report

This page is intentionally left blank
and marks the last page of this report