

**RF EXPOSURE EVALUATION****1.1 Limit**

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength	Magnetic field Strength	Power density	Averaging time
1.34 - 30.....	824/f	2.19/f	*(180/ f <sup>2</sup> )	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	.....	.....	f/1500	30
1500 - 100.000.....	.....	.....	<b>1.0</b>	30

F = frequency in MHz

\* = Plane-wave equivalent power density

**1.2 MAXIMUM PERMISSIBLE EXPOSURE Prediction**

Prediction of MPE limit at a given distance

**Power density at the specific separation:**

$S = PG/(4R^2 \pi)$	Where,  $S$ = Maximum power density (mW/cm <sup>2</sup> ) $P$ = Power input to the antenna (mW) $G$ = Numeric power gain of the antenna $R$ = Distance to the center of the radiation of the antenna (20 cm = limit for MPE)
$S = (28.88 * 2.04) / (4 * 5^2 * \pi)$	
$S = 502.42$ mW/cm <sup>2</sup>	

**1.3 MAXIMUM PERMISSIBLE EXPOSURE Prediction**

- Calculated under the worst-case conditions of each mode.

(Measured power 29 dBm  $\pm$  0.5dB)

**3-1. 2.4 GHz WLAN Mode**

Max Peak output Power at antenna input terminal	28.88	dBm
Max Peak output Power at antenna input terminal	772.68	mW
Prediction distance	5	cm
Prediction frequency	915.25	MHz
Antenna Gain(typical)	3.1	dBi
Antenna Gain(numeric)	2.04	-
Power density at prediction frequency( S)	1.77	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	0.611	mW/cm <sup>2</sup>

This module is used more than 20 cm away.

SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance  $\leq$  200 mm = **Used**

$[(\text{max.power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}]$

$= [772.68 / 20] * [\sqrt{0.91525}] = 82.39$ , for 10g SAR