

RF Exposure Evaluation Report

Client: LYNQ Technologies, Inc.

Address: 4760 Walnut St Ste 108
Boulder, CO 80301

EUT: LNQ2900

FCC ID: 2ARHMLNQ2900
IC ID: 24896-LNQ2900

Test Report No.: R230330-70-M1

Approved By:



Blake Winter,
EMC Test Engineer
iNARTE EMC-50662-E

Date: July 5, 2024

Total Pages: 6

The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above-named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

Revision Page

Rev. No.	Date	Description
0	5 July 2024	Issued by BWinter Reviewed by FLane Prepared by BWinter

1 Regulatory Requirements:

FCC Part 1.1310, 2.1091, 2.1093
KDB 447498 D01

Summary:

The purpose of this report is to evaluate the EUT's transmitter for exemption from routine SAR testing.

EUT:

Model:

LNQ2900

FCC ID:

2ARHMLNQ2900

IC ID:

24896-LNQ2900

MPE Lab

Nebraska Center for Excellence in Electronics

MPE Labs FCC Cab Designation:

US1060

MPE Labs ISED Cab Designation:

US0177

2 FCC Limits, Part 1.1310

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Calculations:

EUT

Occupational/Controlled	☐
General Population/uncontrolled	☒

FCC Power Density Calculations

Freq.	Conducted Power	Antenna Gain	Peak Power EIRP	Peak Power EIRP +10% for Tolerance	Power Density	Limit at specified distance	% of limit	Result
MHz	mW	numerical	mW	mW	mW/cm ²	mW/cm ²	%	
902.00	891.300	1.23	1096.54	1206.19	0.240	0.60	39.905	PASS
915.00	901.600	1.23	1109.21	1220.13	0.243	0.61	39.793	PASS
930.00	935.400	1.23	1150.79	1265.87	0.252	0.62	40.619	PASS

Distance (d)	20	cm
--------------	----	----

$S = (P \times G) / (4 \times \pi \times d^2)$ – used to calculate exposure at "d" cm

$EIRP = P \times G$, measured as field strength

$d = \sqrt{(S / (P \times G) \times 4 \times \pi)}$ – used to calculate minimum distance to meet limits

S = power density (mW/cm²)

P = transmitter conducted power (in mW)

G = antenna numeric gain (Numerical)

d = distance to radiation center (cm)

Gain values were provided by customer provided antenna data sheet.

EIRP (mW) = Conducted power (mW) x antenna gain (numeric).

Result:

The EUT was found to be exempt from routine SAR testing and **COMPLIANT** with RF exposure requirements.

Result:

Complies

Note:

The user's manual will stipulate that a 20cm distance from the user is to be maintained.

EIRP values in mW were multiplied by 1.1 to account for a 10% tolerance.

REPORT END