

Maximum Permissible Exposure Evaluation

FCC ID: 2ARJA-R11S

1. Client Information

Applicant	:	Vsoon Smart Manufacture Co., Ltd.
Address	:	The 3rd Floor, B5 Building, Huachuang Industry Park , No.9 , Huateng Road, Shiqi Town, Panyu District , Guangzhou,Guangdong, China
Manufacturer	:	Vsoon Smart Manufacture Co., Ltd.
Address	:	The 3rd Floor, B5 Building, Huachuang Industry Park , No.9 , Huateng Road, Shiqi Town, Panyu District , Guangzhou,Guangdong, China

TB-RF-075-1.0

2. General Description of EUT

EUT Name	:	Projector
Models No.	:	R11S
Model Difference	:	All these models are identical in the same PCB layout and electrical circuit, the only difference is model name, appearance and color for commercial.
Product Description	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz Bluetooth/BLE: 2402MHz~2480MHz
	Max Output Power:	WIFI: 16.72dBm Bluetooth: 3.664dBm BLE: -0.492dBm
	Antenna Gain:	2.5dBi Copper tube Antenna
Power Supply	:	DC Voltage supplied by AC/DC Adapter DC Voltage supplied by Li-ion battery
Power Rating	:	AC/DC Adapter (DSX-120150-US): Input: AC 100~240V, 50/60Hz, 0.6A. Output: DC 12V, 1.5A. DC 3.8V by 4000mAh Li-ion battery.
Connecting I/O Port(S)	:	Please refer to the User's Manual

MPE Calculations for WIFI

1. Antenna Gain:

Copper tube Antenna: 2.5dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
802.11b	16.72	16±1	17	2.5	20	0.01773
802.11g	14.55	15±1	16	2.5	20	0.01408
802.11n (HT20)	13.68	13±1	14	2.5	20	0.00889
802.11n (HT40)	13.30	13±1	14	2.5	20	0.00889
BLE	-0.492	-1±1	0	2.5	20	0.00035

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
GFSK	3.664	3±1	4	2.5	20	0.00089
$\pi/4$ -DQPSK	3.141	3±1	4	2.5	20	0.00089
8-DPSK	3.214	3±1	4	2.5	20	0.00089

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 802.11b/g/n:2412~2462 MHz

For Bluetooth/BLE: 2402MHz~2480MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as **0.01773mW / cm² < limit 1mW / cm²**. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----