

SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological

Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555 Fax: +86 (0) 20 82075059 Email: ee.guangzhou@sgs.com Report No.: GZEM1812000229CR

Page: 1 of 2

RF Exposure Compliance Requirement

The product belongs to **standalone portable device** base the FCC rule part 2.1091&2.1093. The transmission frequencies of the device are between 100 MHz and 6 GHz. The worst case test separation distance is **5mm**.

The Max Conducted Output Power and SAR Test Exclusion Threshold (mW) are listed below:

Transmit frequency (GHz)	Power[dBm]	Max Conducted Output Power (mW)
2.402	-5.715	0.268
2.442	-5.694	0.270
2.480	-5.247	0.299

The Max Conducted Peak Output Power is -5.247dBm on the highest channel 2.480GHz -5.247dBm logarithmic terms convert to numeric result is nearly 0.299mW(the maximum power in three transmit frequencies)

According to the formula, calculate the test exclusion thresholds:

[(max. power of channel, including tune-up tolerance, mW)/

(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}]$

General RF Exposure = (0.299 mW / 5 mm) x $\sqrt{2.48 \text{GHz}} = 0.09 \text{ }\bigcirc$;

SAR requirement: S = 3.0 ②;

(1) < (2).

So the SAR report is not required.

Remark:

The SAR Test Exclusion Threshold for 100 MHz to 6 GHz is calculated from:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Tarms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Tarms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and its document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgety or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 5307 1443.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 5307 1443.

|Wo.18/KathuRoad, Sciented Park, Guergatiou Economic 8 Technology Development District, Guergatiou, Crime 510663 t (86–20) 82155555 f (86–20) 82075058 www.sgs.group.com.cn 中国 - 广州 - 经济技术开发区科学编科珠路198号 邮编: 510663 t (86–20) 82155555 f (86–20) 82075058 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological

Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555 Fax: +86 (0) 20 82075059 Email: ee.guangzhou@sgs.com Report No.: GZEM1812000229CR

Page: 2 of 2

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

According to SAR Exclusion Threshold in KDB 447498 (D01) General RF Exposure Guidance v06, the SAR report is not required.



Intess otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printeworked, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.appx and, for electronic format documents ubject to Terms and Conditions for Electronic Documents at https://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx stention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is divised that information contained hereon reflects the Company's foliangs at the inor of its Intervention only and within the limits of lies instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to cransaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized attention, forgery or falsification of the content of ppearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the exults show in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.