



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V04

Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No. : CQASZ20191201351E-02
Applicant: Shenzhenshishenhuashukeji Co. Ltd
Address of Applicant: Mofanggongyu 908 Shenzhen Guangdong, Shenzhen, China 518000
Equipment Under Test (EUT):
EUT Name: Karaoke Microphone
Model No.: WS-858 (Rose Gold), WS-858 (Black), WS-858 (Gold), WS-858 (Pink),
WS-858 (Blue), WS-858 (White)
Test Model No.: WS-858 (Rose Gold)
Brand Name: Tronic Master
FCC ID: 2ARLV-WS-858
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2019-12-30
Date of Test: 2019-12-30 to 2020-01-08
Date of Issue: 2020-01-08
Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Tom Chen

(Tom Chen)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20191201351E-02	Rev.01	Initial report	2020-01-08

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	Shenzhenshishenhuashukeji Co. Ltd
Address of Applicant:	Mofanggongyu 908 Shenzhen Guangdong, Shenzhen, China 518000
Manufacturer:	Shenzhenshishenhuashukeji Co. Ltd
Address of Manufacturer:	Mofanggongyu 908 Shenzhen Guangdong, Shenzhen, China 518000

3.2 General Description of EUT

Product Name:	Karaoke Microphone
Model No.:	WS-858 (Rose Gold), WS-858 (Black), WS-858 (Gold), WS-858 (Pink), WS-858 (Blue), WS-858 (White)
Test Model No.:	WS-858 (Rose Gold)
Trade Mark:	Tronic Master
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK
Transfer Rate:	1Mbps/2Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Test Software of EUT:	FCCAssist 2.4 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	2dBi
Power Supply:	lithium battery:DC3.7V, Charge by DC5.0V

Model No.: WS-858 (Rose Gold), WS-858 (Black), WS-858 (Gold), WS-858 (Pink), WS-858 (Blue),
WS-858 (White)

Only the model WS-858 (Rose Gold) was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being model name and color of appearance.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.720	0±1	1.0	1.259
Middle(2441MHz)	0.440	-0.5±1	0.5	1.122
Highest(2480MHz)	0.010	-0.5±1	0.5	1.122
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	2.630	2.0±1	3.0	1.995
Middle(2441MHz)	2.730	2.0±1	3.0	1.995
Highest(2480MHz)	2.250	1.5±1	2.5	1.778

Worst case: π/4DQPSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	2.630	2.0±1	3.0	1.995	0.618	3.0
Middle (2441MHz)	2.730	2.0±1	3.0	1.995	0.623	
Highest (2480MHz)	2.250	1.5±1	2.5	1.778	0.560	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20191201351E-01