

# TEST REPORT

Applicant Name: Shenzhen Jiayz photo industrial ., Ltd  
Address: A16 Building, Intelligent Terminal Industrial Park of Silicon Valley Power, Guanlan, Longhua District, Shenzhen, China  
Report Number: 2401V86256E-RF-00  
FCC ID: 2ARN3-112211TXA

## Test Standard (s)

FCC PART 15.247

## Sample Description

Product Type: Wireless Microphone  
Model No.: BY-V4-TX  
Multiple Model(s) No.: N/A  
Trade Mark: BOYA  
Date Received: 2024/08/06  
Issue Date: 2024/10/14

Test Result:

Pass▲

▲ In the configuration tested, the EUT complied with the standards above.

## Prepared and Checked By:

Ekko Wu

Ekko Wu  
RF Engineer

## Approved By:

Michelle Zeng

Michelle Zeng  
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

## Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

## **TABLE OF CONTENTS**

|                                                                                       |           |
|---------------------------------------------------------------------------------------|-----------|
| <b>DOCUMENT REVISION HISTORY .....</b>                                                | <b>4</b>  |
| <b>GENERAL INFORMATION.....</b>                                                       | <b>5</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                              | 5         |
| OBJECTIVE .....                                                                       | 5         |
| TEST METHODOLOGY .....                                                                | 5         |
| MEASUREMENT UNCERTAINTY .....                                                         | 6         |
| TEST FACILITY .....                                                                   | 6         |
| <b>SYSTEM TEST CONFIGURATION .....</b>                                                | <b>7</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                               | 7         |
| EUT EXERCISE SOFTWARE .....                                                           | 7         |
| SPECIAL ACCESSORIES .....                                                             | 7         |
| EQUIPMENT MODIFICATIONS .....                                                         | 7         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                              | 8         |
| EXTERNAL I/O CABLE.....                                                               | 8         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                     | 8         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                                  | <b>9</b>  |
| <b>TEST EQUIPMENT LIST .....</b>                                                      | <b>10</b> |
| <b>FCC§15.247 (I)&amp;§1.1307 (B) &amp;§2.1093 - RF EXPOSURE.....</b>                 | <b>11</b> |
| APPLICABLE STANDARD .....                                                             | 11        |
| <b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>                                         | <b>12</b> |
| APPLICABLE STANDARD .....                                                             | 12        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                                  | 12        |
| <b>FCC §15.205, §15.209&amp;§15.247(D) – RADIATED EMISSIONS .....</b>                 | <b>13</b> |
| APPLICABLE STANDARD .....                                                             | 13        |
| EUT SETUP .....                                                                       | 13        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                                     | 14        |
| TEST PROCEDURE .....                                                                  | 15        |
| FACTOR & OVER LIMIT/MARGIN CALCULATION .....                                          | 15        |
| TEST DATA .....                                                                       | 15        |
| <b>FCC §15.247(A) (1) - CHANNEL SEPARATION TEST .....</b>                             | <b>30</b> |
| APPLICABLE STANDARD .....                                                             | 30        |
| TEST PROCEDURE .....                                                                  | 30        |
| TEST DATA .....                                                                       | 31        |
| <b>FCC §15.247(A) (1) - 20DBEMISSION BANDWIDTH &amp; 99% OCCUPIED BANDWIDTH .....</b> | <b>33</b> |
| APPLICABLE STANDARD .....                                                             | 33        |
| TEST PROCEDURE .....                                                                  | 33        |
| TEST DATA .....                                                                       | 34        |
| <b>FCC §15.247(A) (1) (III) - QUANTITY OF HOPPING CHANNEL TEST.....</b>               | <b>37</b> |
| APPLICABLE STANDARD .....                                                             | 37        |
| TEST PROCEDURE .....                                                                  | 37        |
| TEST DATA .....                                                                       | 38        |

|                                                                       |           |
|-----------------------------------------------------------------------|-----------|
| <b>FCC §15.247(A) (1) (III) - TIME OF OCCUPANCY (DWELL TIME).....</b> | <b>40</b> |
| APPLICABLE STANDARD .....                                             | 40        |
| TEST PROCEDURE .....                                                  | 40        |
| TEST DATA .....                                                       | 40        |
| <b>FCC §15.247(B) (1) - PEAK OUTPUT POWER MEASUREMENT .....</b>       | <b>42</b> |
| APPLICABLE STANDARD .....                                             | 42        |
| TEST PROCEDURE .....                                                  | 42        |
| TEST DATA .....                                                       | 43        |
| <b>FCC §15.247(D) - BAND EDGES TESTING.....</b>                       | <b>45</b> |
| APPLICABLE STANDARD .....                                             | 45        |
| TEST PROCEDURE .....                                                  | 45        |
| TEST DATA .....                                                       | 45        |
| <b>EUT PHOTOGRAPHS.....</b>                                           | <b>48</b> |
| <b>TEST SETUP PHOTOGRAPHS .....</b>                                   | <b>49</b> |

DOCUMENT REVISION HISTORY

| Revision Number | Report Number     | Description of Revision | Date of Revision |
|-----------------|-------------------|-------------------------|------------------|
| 0               | 2401V86256E-RF-00 | Original Report         | 2024/10/14       |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                                     |                                                                                               |
|-------------------------------------|-----------------------------------------------------------------------------------------------|
| Product                             | Wireless Microphone                                                                           |
| Tested Model                        | BY-V4-TX                                                                                      |
| Multiple Model(s)                   | N/A                                                                                           |
| Frequency Range                     | 2402-2478MHz                                                                                  |
| Maximum conducted peak output power | 1.86 dBm                                                                                      |
| Modulation Technique                | GFSK                                                                                          |
| Antenna Specification <sup>#</sup>  | 0.5dBi (provided by the applicant)                                                            |
| Voltage Range                       | DC 3.7V from battery or DC 5V from charging box                                               |
| Sample serial number                | 2PDR-2 for RF Conducted Test<br>2PDR-1 for Radiated Emissions<br>(Assigned by BACL, Shenzhen) |
| Sample/EUT Status                   | Good condition                                                                                |
| Adapter Information                 | N/A                                                                                           |

### Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209 and 15.247 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

## Measurement Uncertainty

| Parameter                             |                             | Uncertainty                             |
|---------------------------------------|-----------------------------|-----------------------------------------|
| Occupied Channel Bandwidth            |                             | ±5%                                     |
| RF Frequency                          |                             | 213.55 Hz(k=2, 95% level of confidence) |
| RF output power, conducted            |                             | 0.72 dB(k=2, 95% level of confidence)   |
| Unwanted Emission, conducted          |                             | 1.75 dB(k=2, 95% level of confidence)   |
| AC Power Lines<br>Conducted Emissions | 9 kHz~150 KHz               | 3.94dB(k=2, 95% level of confidence)    |
|                                       | 150 kHz ~30MHz              | 3.84dB(k=2, 95% level of confidence)    |
| Radiated Emissions                    | 9kHz - 30MHz                | 3.30dB(k=2, 95% level of confidence)    |
|                                       | 30MHz~200MHz (Horizontal)   | 4.48dB(k=2, 95% level of confidence)    |
|                                       | 30MHz~200MHz (Vertical)     | 4.55dB(k=2, 95% level of confidence)    |
|                                       | 200MHz~1000MHz (Horizontal) | 4.85dB(k=2, 95% level of confidence)    |
|                                       | 200MHz~1000MHz (Vertical)   | 5.05dB(k=2, 95% level of confidence)    |
|                                       | 1GHz - 6GHz                 | 5.35dB(k=2, 95% level of confidence)    |
|                                       | 6GHz - 18GHz                | 5.44dB(k=2, 95% level of confidence)    |
|                                       | 18GHz - 40GHz               | 5.16dB(k=2, 95% level of confidence)    |
| Temperature                           |                             | ±1°C                                    |
| Humidity                              |                             | ±1%                                     |
| Supply voltages                       |                             | ±0.4%                                   |

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel list

| Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) |
|-------------|-----------------|-------------|-----------------|-------------|-----------------|-------------|-----------------|
| 1           | 2402            | 21          | 2422            | 41          | 2442            | 61          | 2462            |
| 2           | 2403            | 22          | 2423            | 42          | 2443            | 62          | 2463            |
| 3           | 2404            | 23          | 2424            | 43          | 2444            | 63          | 2464            |
| 4           | 2405            | 24          | 2425            | 44          | 2445            | 64          | 2465            |
| 5           | 2406            | 25          | 2426            | 45          | 2446            | 65          | 2466            |
| 6           | 2407            | 26          | 2427            | 46          | 2447            | 66          | 2467            |
| 7           | 2408            | 27          | 2428            | 47          | 2448            | 67          | 2468            |
| 8           | 2409            | 28          | 2429            | 48          | 2449            | 68          | 2469            |
| 9           | 2410            | 29          | 2430            | 49          | 2450            | 69          | 2470            |
| 10          | 2411            | 30          | 2431            | 50          | 2451            | 70          | 2471            |
| 11          | 2412            | 31          | 2432            | 51          | 2452            | 71          | 2472            |
| 12          | 2413            | 32          | 2433            | 52          | 2453            | 72          | 2473            |
| 13          | 2414            | 33          | 2434            | 53          | 2454            | 73          | 2474            |
| 14          | 2415            | 34          | 2435            | 54          | 2455            | 74          | 2475            |
| 15          | 2416            | 35          | 2436            | 55          | 2456            | 75          | 2476            |
| 16          | 2417            | 36          | 2437            | 56          | 2457            | 76          | 2477            |
| 17          | 2418            | 37          | 2438            | 57          | 2458            | 77          | 2478            |
| 18          | 2419            | 38          | 2439            | 58          | 2459            |             |                 |
| 19          | 2420            | 39          | 2440            | 59          | 2460            |             |                 |
| 20          | 2421            | 40          | 2441            | 60          | 2461            |             |                 |

Channel 1, 39, 77 was tested.

### EUT Exercise Software

“FCC.exe”<sup>#</sup> exercise software was used and the power level is 21<sup>#</sup>. The software and power level was provided by the applicant.

### Special Accessories

No special accessory.

### Equipment Modifications

No modification was made to the EUT tested.

**Support Equipment List and Details**


| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| /            | /           | /     | /             |

**External I/O Cable**

| Cable Description | Length (m) | From/Port | To |
|-------------------|------------|-----------|----|
| /                 | /          | /         | /  |

**Block Diagram of Test Setup**

For Radiated Emissions:



**SUMMARY OF TEST RESULTS**

| FCC Rules                                 | Description of Test                              | Result         |
|-------------------------------------------|--------------------------------------------------|----------------|
| FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 | RF Exposure                                      | Compliant      |
| §15.203                                   | Antenna Requirement                              | Compliant      |
| §15.207(a)                                | AC Line Conducted Emissions                      | Not Applicable |
| §15.205, §15.209 & §15.247(d)             | Radiated Emissions                               | Compliant      |
| §15.247(a)(1)                             | 20dB Emission Bandwidth & 99% Occupied Bandwidth | Compliant      |
| §15.247(a)(1)                             | Channel Separation Test                          | Compliant      |
| §15.247(a)(1)(iii)                        | Time of Occupancy (Dwell Time)                   | Compliant      |
| §15.247(a)(1)(iii)                        | Quantity of hopping channel Test                 | Compliant      |
| §15.247(b)(1)                             | Peak Output Power Measurement                    | Compliant      |
| §15.247(d)                                | Band edges                                       | Compliant      |

Not Applicable: The EUT is powered by battery and can not transmit when charging.

**TEST EQUIPMENT LIST**

| Manufacturer                  | Description                       | Model             | Serial Number | Calibration Date | Calibration Due Date |
|-------------------------------|-----------------------------------|-------------------|---------------|------------------|----------------------|
| <b>Radiated Emission Test</b> |                                   |                   |               |                  |                      |
| Rohde & Schwarz               | EMI Test Receiver                 | ESR3              | 102455        | 2024/01/16       | 2025/01/15           |
| Sonoma instrument             | Pre-amplifier                     | 310 N             | 186238        | 2024/05/21       | 2025/05/20           |
| Sunol Sciences                | Broadband Antenna                 | JB1               | A040904-1     | 2023/07/20       | 2026/07/19           |
| Unknown                       | Cable                             | Chamber A Cable 1 | N/A           | 2024/06/18       | 2025/06/17           |
| Unknown                       | Cable                             | XH500C            | J-10M-A       | 2024/06/18       | 2025/06/17           |
| BACL                          | Active Loop Antenna               | 1313-1A           | 4031911       | 2024/05/14       | 2027/05/13           |
| Unknown                       | Cable                             | 2Y194             | 0735          | 2024/05/21       | 2025/05/20           |
| Unknown                       | Cable                             | PNG214            | 1354          | 2024/05/21       | 2025/05/20           |
| Audix                         | EMI Test software                 | E3                | 19821b(V9)    | NCR              | NCR                  |
| Rohde & Schwarz               | Spectrum Analyzer                 | FSV40             | 101605        | 2024/03/27       | 2025/03/26           |
| COM-POWER                     | Pre-amplifier                     | PA-122            | 181919        | 2024/06/18       | 2025/06/17           |
| Schwarzbeck                   | Horn Antenna                      | BBHA9120D (1201)  | 1143          | 2023/07/26       | 2026/07/25           |
| Unknown                       | RF Cable                          | KMSE              | 735           | 2024/06/18       | 2025/06/17           |
| Unknown                       | RF Cable                          | UFA147            | 219661        | 2024/06/18       | 2025/06/17           |
| Unknown                       | RF Cable                          | XH750A-N          | J-10M         | 2024/06/18       | 2025/06/17           |
| JD                            | Multiplex Switch Test Control Set | DT7220FSU         | DQ77926       | 2024/06/18       | 2025/06/17           |
| A.H.System                    | Pre-amplifier                     | PAM-1840VH        | 190           | 2024/06/18       | 2025/06/17           |
| Electro-Mechanics Co          | Horn Antenna                      | 3116              | 2026          | 2023/09/18       | 2026/09/17           |
| UTIFLEX                       | RF Cable                          | NO. 13            | 232308-001    | 2024/06/18       | 2025/06/17           |
| Audix                         | EMI Test software                 | E3                | 191218(V9)    | NCR              | NCR                  |
| <b>RF Conducted Test</b>      |                                   |                   |               |                  |                      |
| Rohde & Schwarz               | Spectrum Analyzer                 | FSV40             | 101473        | 2024/01/16       | 2025/01/15           |
| R&S                           | Spectrum Analyzer                 | FSU26             | 200120        | 2024/01/08       | 2025/01/07           |
| Unknown                       | 10dB Attenuator                   | Unknown           | F-03-EM190    | 2024/06/27       | 2025/06/26           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## **FCC§15.247 (i)&§1.1307 (b) &§2.1093 - RF EXPOSURE**

### **Applicable Standard**

According to FCC §2.1093 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

### **Measurement Result**

| Mode      | Frequency (MHz) | Max tune-up conducted power <sup>#</sup> (dBm) | Max tune-up conducted power <sup>#</sup> (mW) | Distance (mm) | Calculated value | Threshold (1-g SAR) | SAR Test Exclusion |
|-----------|-----------------|------------------------------------------------|-----------------------------------------------|---------------|------------------|---------------------|--------------------|
| 2.4G FHSS | 2402-2478       | 2.00                                           | 1.58                                          | 5             | 0.5              | 3                   | Yes                |

**Result: Compliant**

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.



### **Antenna Connector Construction**


The EUT has a chip antenna arrangement which was permanently attached and the antenna gain<sup>#</sup> is 0.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result: Compliant**

**FCC §15.205, §15.209&§15.247(d) – RADIATED EMISSIONS****Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

**EUT Setup****9 kHz-30MHz:****30MHz-1GHz:**

**Above 1GHz:**

The radiated emission tests were performed in the 3meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

**EMI Test Receiver & Spectrum Analyzer Setup**

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW                                                           | Video B/W | IF B/W  | Measurement |
|-------------------|---------------------------------------------------------------|-----------|---------|-------------|
| 9 kHz – 150 kHz   | /                                                             | /         | 200 Hz  | QP          |
|                   | 300 Hz                                                        | 1 kHz     | /       | PK          |
| 150 kHz – 30 MHz  | /                                                             | /         | 9 kHz   | QP          |
|                   | 10 kHz                                                        | 30 kHz    | /       | PK          |
| 30 MHz – 1000 MHz | /                                                             | /         | 120 kHz | QP          |
|                   | 100 kHz                                                       | 300 kHz   | /       | PK          |
| Above 1 GHz       | Harmonics & Band Edge                                         |           |         |             |
|                   | 1MHz                                                          | 3 MHz     | /       | PK          |
|                   | Average Emission Level=Peak Emission Level+20*log(Duty cycle) |           |         |             |
|                   | Other Emissions                                               |           |         |             |
|                   | 1MHz                                                          | 3 MHz     | /       | PK          |
|                   | 1MHz                                                          | 10 Hz     | /       | Average     |

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle=On time/100milliseconds, On time= $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$ ,

Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulse, etc.

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

## Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit or Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit/margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned}\text{Margin/Over Limit} &= \text{Corrected Amplitude/Level-Limit} \\ \text{Corrected Amplitude/Level} &= \text{Reading} + \text{Factor}\end{aligned}$$

## Test Data

### Environmental Conditions

|                    |            |
|--------------------|------------|
| Temperature:       | 23~25.5 °C |
| Relative Humidity: | 50~55 %    |
| ATM Pressure:      | 101.0 kPa  |

*The testing was performed by Anson Su on 2024-08-23 for below 1GHz and Sadow Tan on 2024-08-29 for above 1GHz.*

*EUT operation mode: Transmitting*


*Note: Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.*

**9 kHz-30MHz (Maximum output power mode, Low channel):**

*The amplitude of spurious emissions attenuated more than 20 dB below the limit was not recorded.*

30MHz-1GHz (Maximum output power mode, Low channel):


Horizontal



Site : Chamber A  
Condition : 3m Horizontal  
Project Number: 2401V86256E-RF  
Test Mode : Transmitting  
Tester : Anson Su

|   | Freq Factor |        | Read  |        | Limit  | Over   | Remark |
|---|-------------|--------|-------|--------|--------|--------|--------|
|   | MHz         | dB/m   | Level | Level  | Line   | Limit  |        |
|   |             |        | dBuV  | dBuV/m | dBuV/m | dB     |        |
| 1 | 40.49       | -12.71 | 23.54 | 10.83  | 40.00  | -29.17 | QP     |
| 2 | 72.05       | -17.85 | 39.40 | 21.55  | 40.00  | -18.45 | QP     |
| 3 | 196.94      | -13.44 | 34.30 | 20.86  | 43.50  | -22.64 | QP     |
| 4 | 384.10      | -9.04  | 37.54 | 28.50  | 46.00  | -17.50 | QP     |
| 5 | 459.11      | -7.14  | 32.00 | 24.86  | 46.00  | -21.14 | QP     |
| 6 | 822.79      | -1.97  | 26.62 | 24.65  | 46.00  | -21.35 | QP     |

## Vertical



Site : Chamber A  
Condition : 3m Vertical  
Project Number: 2401V86256E-RF  
Test Mode : Transmitting  
Tester : Anson Su

|   | Freq Factor |        | Read Level |        | Limit | Over   | Remark |
|---|-------------|--------|------------|--------|-------|--------|--------|
|   | MHz         | dB/m   | dBuV       | dBuV/m | Line  | Limit  |        |
| 1 | 41.44       | -13.42 | 24.62      | 11.20  | 40.00 | -28.80 | QP     |
| 2 | 72.31       | -17.85 | 35.96      | 18.11  | 40.00 | -21.89 | QP     |
| 3 | 127.94      | -11.12 | 26.03      | 14.91  | 43.50 | -28.59 | QP     |
| 4 | 384.10      | -9.04  | 34.00      | 24.96  | 46.00 | -21.04 | QP     |
| 5 | 535.71      | -5.70  | 31.76      | 26.06  | 46.00 | -19.94 | QP     |
| 6 | 849.54      | -1.73  | 26.25      | 24.52  | 46.00 | -21.48 | QP     |

**Above 1GHz:**

| Frequency<br>(MHz)      | Receiver          |       | Polar<br>(H/V) | Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|-------------------------|-------------------|-------|----------------|------------------|------------------------------------|-------------------|----------------|
|                         | Reading<br>(dBμV) | PK/AV |                |                  |                                    |                   |                |
| Low Channel(2402MHz)    |                   |       |                |                  |                                    |                   |                |
| 2386.7                  | 54.42             | PK    | H              | -2.93            | 51.49                              | 74                | -22.51         |
| 2389.25                 | 54.38             | PK    | V              | -2.93            | 51.45                              | 74                | -22.55         |
| 4804.00                 | 45.75             | PK    | H              | 1.69             | 47.44                              | 74                | -26.56         |
| 4804.00                 | 46.67             | PK    | V              | 1.69             | 48.36                              | 74                | -25.64         |
| Middle Channel(2440MHz) |                   |       |                |                  |                                    |                   |                |
| 4880.00                 | 46.38             | PK    | H              | 1.69             | 48.07                              | 74                | -25.93         |
| 4880.00                 | 45.97             | PK    | V              | 1.69             | 47.66                              | 74                | -26.34         |
| High Channel(2478MHz)   |                   |       |                |                  |                                    |                   |                |
| 2483.89                 | 54.34             | PK    | H              | -3.17            | 51.17                              | 74                | -22.83         |
| 2486.496                | 54.33             | PK    | V              | -3.17            | 51.16                              | 74                | -22.84         |
| 4956.00                 | 45.84             | PK    | H              | 2.77             | 48.61                              | 74                | -25.39         |
| 4956.00                 | 46.17             | PK    | V              | 2.77             | 48.94                              | 74                | -25.06         |

**Note:**

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude/Level = Corrected Factor + Reading

Margin = Corrected Amplitude/Level - Limit

Other emissions which were more than 20dB below limit or on noise floor level was not recorded.

| Field Strength of Average |                               |             |                                  |                        |                |             |          |
|---------------------------|-------------------------------|-------------|----------------------------------|------------------------|----------------|-------------|----------|
| Frequency (MHz)           | Peak Measurement @3m (dBμV/m) | Polar (H/V) | Duty Cycle Corrected Factor (dB) | Average Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Comment  |
| Low Channel 2402MHz       |                               |             |                                  |                        |                |             |          |
| 2386.70                   | 51.49                         | H           | -42.62                           | 8.87                   | 54             | -45.13      | Bandedge |
| 2389.25                   | 51.45                         | V           | -42.62                           | 8.83                   | 54             | -45.17      | Bandedge |
| 4804.00                   | 47.44                         | H           | -42.62                           | 4.82                   | 54             | -49.18      | Harmonic |
| 4804.00                   | 48.36                         | V           | -42.62                           | 5.74                   | 54             | -48.26      | Harmonic |
| Middle Channel 2440MHz    |                               |             |                                  |                        |                |             |          |
| 4880.00                   | 48.07                         | H           | -42.62                           | 5.45                   | 54             | -48.55      | Harmonic |
| 4880.00                   | 47.66                         | V           | -42.62                           | 5.04                   | 54             | -48.96      | Harmonic |
| High Channel 2478MHz      |                               |             |                                  |                        |                |             |          |
| 2483.89                   | 51.17                         | H           | -42.62                           | 8.55                   | 54             | -45.45      | Bandedge |
| 2486.50                   | 51.16                         | V           | -42.62                           | 8.54                   | 54             | -45.46      | Bandedge |
| 4956.00                   | 48.61                         | H           | -42.62                           | 5.99                   | 54             | -48.01      | Harmonic |
| 4956.00                   | 48.94                         | V           | -42.62                           | 6.32                   | 54             | -47.68      | Harmonic |


Note: Average level= Peak level+ Duty Cycle Corrected Factor

Margin = Average level- Limit


Worst case duty cycle:


Duty cycle = Ton/100ms = 0.37\*2/100=0.0074

Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.0074 = -42.62





Test plots for Band Edge Measurements (Radiated):








Test plots for Harmonic and Emissions Measurements (Worst case, High channel):














## FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

### Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


### Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW)  $\geq$  RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined.



Note: The limit is  $\frac{2}{3} \times 20$  dB bandwidth

Test Data

Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 26.8 °C   |
| Relative Humidity: | 55 %      |
| ATM Pressure:      | 101.0 kPa |


The testing was performed by Kungfumaster Liang on 2024-08-18.

EUT operation mode: Transmitting

Test Result: Compliant

| Test Channel | Test Frequency (MHz) | Channel Separation (MHz) | Limits (MHz) |
|--------------|----------------------|--------------------------|--------------|
| Low          | 2402                 | 1.001                    | 0.691        |
| Middle       | 2440                 | 0.998                    | 0.689        |
| High         | 2478                 | 0.998                    | 0.689        |

Please refer to the below plots:



## **FCC §15.247(a) (1) - 20dBEMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH**

### **Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


### **Test Procedure**

Test Method: ANSI C63.10-2013 Clause 7.8.7 & Clause 6.9.2

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “–xx dB down” requirement; that is, if the requirement calls for measuring the –20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an un-modulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “–xx dB down amplitude” using  $[(\text{reference value}) - \text{xx}]$ . Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an un-modulated carrier, then turn the EUT modulation on, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “- xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “- xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



## Test Data

### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 26.8 °C   |
| Relative Humidity: | 55 %      |
| ATM Pressure:      | 101.0 kPa |


*The testing was performed by Kungfumaster Liang on 2024-08-18.*


*EUT operation mode: Transmitting*

### Test Result: Compliant

| Mode | Channel | Frequency (MHz) | 99% Emission Bandwidth (MHz) | 20 dB Emission Bandwidth (MHz) |
|------|---------|-----------------|------------------------------|--------------------------------|
| GFSK | Low     | 2402            | 0.998                        | 1.037                          |
|      | Middle  | 2440            | 0.998                        | 1.034                          |
|      | High    | 2478            | 0.998                        | 1.034                          |

Please refer to the below plots:





## **FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST**

### **Applicable Standard**


Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### **Test Procedure**

Test Method: ANSI C63.10-2013 Clause 7.8.3

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW  $\geq$  RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.

It might prove necessary to break the span up into sub ranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels.



Test Data

Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 26.8 °C   |
| Relative Humidity: | 55 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Cheeb Huang on 2024-09-07.*

*EUT operation mode: Transmitting*

***Test Result: Compliant***

| Mode | Frequency Range<br>(MHz) | Number of Hopping<br>Channel<br>(CH) | Limit<br>(CH) |
|------|--------------------------|--------------------------------------|---------------|
| GFSK | 2400-2483.5              | 77                                   | ≥15           |




**FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)****Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

**Test Procedure**

Test Method: ANSI C63.10-2013 Clause 7.8.4

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 26.8 °C   |
| Relative Humidity: | 55 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Kungfumaster Liang on 2024-09-02.*


*EUT operation mode: Transmitting*

**Test Result: Compliant**

| Test Mode | Test Frequency (MHz) | Pulse width (ms) | Observation time (s) | Hopping Numbers in Observation time | Dwell Time (s) | Limit (s) |
|-----------|----------------------|------------------|----------------------|-------------------------------------|----------------|-----------|
| GFSK      | 2440                 | 0.360            | 31                   | 320                                 | 0.115          | 0.400     |

Note 1: Observation time= Hopping Channel Number $\times$  0.4

Note 2: Dwell Time = Pulse width \*Hopping Numbers in Observation time



## **FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**

### **Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### **Test Procedure**

Test Method: ANSI C63.10-2013 Clause 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:


a) Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 2) RBW > 20 dB bandwidth of the emission being measured.
- 3) VBW  $\geq$  RBW.
- 4) Sweep: Auto.
- 5) Detector function: Peak.
- 6) Trace: Max hold.

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power, after any corrections for external attenuators and cables.



Test Data

Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 26.8 °C   |
| Relative Humidity: | 55 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Kungfumaster Liang on 2024-09-02.*

*EUT operation mode: Transmitting*

**Test Result: Compliant**

| Mode | Channel | Frequency (MHz) | Peak Output Power (dBm) | Limit (dBm) |
|------|---------|-----------------|-------------------------|-------------|
| GFSK | Low     | 2402            | 1.86                    | 21          |
|      | Middle  | 2440            | 1.58                    | 21          |
|      | High    | 2478            | 0.91                    | 21          |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Low Channel</p>    | <div><div>Spectrum</div><div><div>Ref Level 23.50 dBm</div><div>Offset 3.50 dB</div><div>RBW 3 MHz</div><div>Att 30 dB</div><div>SWT 1 ms</div><div>VBW 10 MHz</div><div>Mode Sweep</div></div><div><div>1Pk Max</div><div><div>20 dBm</div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div></div><div><div>M1[1]</div><div>1.86 dBm</div><div>2.40215000 GHz</div></div><div><div>CF 2.402 GHz</div><div>1001 pts</div><div>Span 10.0 MHz</div></div><div><div>ProjectNo.:2401V86256E-RF</div><div>Tester:Kungfumaster Liang</div><div>Date: 2.SEP.2024 22:34:26</div></div></div> |
| <p>Middle Channel</p> | <div><div>Spectrum</div><div><div>Ref Level 23.50 dBm</div><div>Offset 3.50 dB</div><div>RBW 3 MHz</div><div>Att 30 dB</div><div>SWT 1 ms</div><div>VBW 10 MHz</div><div>Mode Sweep</div></div><div><div>1Pk Max</div><div><div>20 dBm</div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div></div><div><div>M1[1]</div><div>1.58 dBm</div><div>2.44014000 GHz</div></div><div><div>CF 2.44 GHz</div><div>1001 pts</div><div>Span 10.0 MHz</div></div><div><div>ProjectNo.:2401V86256E-RF</div><div>Tester:Kungfumaster Liang</div><div>Date: 2.SEP.2024 22:33:53</div></div></div>  |
| <p>High Channel</p>   | <div><div>Spectrum</div><div><div>Ref Level 23.50 dBm</div><div>Offset 3.50 dB</div><div>RBW 3 MHz</div><div>Att 30 dB</div><div>SWT 1 ms</div><div>VBW 10 MHz</div><div>Mode Sweep</div></div><div><div>1Pk Max</div><div><div>20 dBm</div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div></div><div><div>M1[1]</div><div>0.91 dBm</div><div>2.47816000 GHz</div></div><div><div>CF 2.478 GHz</div><div>1001 pts</div><div>Span 10.0 MHz</div></div><div><div>ProjectNo.:2401V86256E-RF</div><div>Tester:Kungfumaster Liang</div><div>Date: 2.SEP.2024 22:33:09</div></div></div> |

## FCC §15.247(d) - BAND EDGES TESTING


### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.6 & Clause 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



### Test Data


#### Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 26.8 °C   |
| Relative Humidity: | 55 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Kungfumaster Liang on 2024-08-18.*

*EUT operation mode: Transmitting*

**Test Result: Compliant**





## **EUT PHOTOGRAPHS**

Please refer to the attachment 2401V86256E-RF External photo and 2401V86256E-RF Internal photo.

## **TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment 2401V86256E-RFA Test Setup photo.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***