

TEST REPORT

Applicant Name: Meizhou Guo Wei Electronics Co., Ltd.
Address: AD1 Section, Economic Development Area, Dongsheng Industrial District, Meizhou, Guangdong, China.
Report Number: 2401A113404E-RF
FCC ID: 2ARRB-K44K89BS
IC: 20353-K44K89BS

Test Standard (s)

FCC PART 15D; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2; RSS-213, ISSUE 3, MARCH 2015

Sample Description

Product Type: Digital Cordless Telephone
Model No.: Motorola DOT21-B
Multiple Model(s) No.: N/A
Trade Mark: Motorola
Date Received: 2025/01/13
Issue Date: 2025/08/28

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Allen. Bai

Allen Bai
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC 1.1307 (B) & §2.1091- MPE-BASED EXEMPTION	13
APPLICABLE STANDARD	13
RESULT	13
RSS-102 § 6.6 - FIELD REFERENCE LEVEL EXPOSURE EXEMPTION LIMITS.....	14
APPLICABLE STANDARD	14
TEST RESULT	14
FCC § 15.317, § 15.203 & RSS-GEN §6.8 ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC § 15.315, § 15.207 & RSS-213 §5.4 CONDUCTED EMISSIONS.....	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	17
FACTOR & OVER LIMIT CALCULATION.....	17
TEST DATA	17
FCC § 15.323 (A) & RSS-213 §5.5 EMISSION BANDWIDTH	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATA	23
FCC § 15.319 (C) & RSS-213 §5.6 PEAK TRANSMIT POWER	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	28
FCC § 15.319 (D) & RSS-213 §5.7 POWER SPECTRAL DENSITY	32
APPLICABLE STANDARD	32

TEST PROCEDURE	32
TEST DATA	33
FCC § 15.323 (D) & RSS-213 §5.8 EMISSION INSIDE AND OUTSIDE THE SUB-BAND	37
APPLICABLE STANDARD	37
TEST PROCEDURE	38
FACTOR & OVER LIMIT/MARGIN CALCULATION	39
EUT SETUP	40
TEST DATA	41
FCC § 15.323 (F) & RSS-213 §5.3 FREQUENCY STABILITY	76
APPLICABLE STANDARD	76
TEST PROCEDURE	76
TEST DATA	77
FCC § 15.323 (C)(E)§ 15.319 (F) & RSS-213 §5.1&§5.2 SPECIFIC REQUIREMENTS FOR UPCS DEVICE	78
APPLICABLE STANDARD	78
TEST PROCEDURE	78
TEST DATA	78
1) AUTOMATIC DISCONTINUATION OF TRANSMISSION	79
2) MONITORING TIME	79
3) LOWER MONITORING THRESHOLD	79
4) MAXIMUM TRANSMIT PERIOD	80
5) SYSTEM ACKNOWLEDGEMENT	80
6) LEAST INTERFERED CHANNEL (LIC)	81
7) RANDOM WAITING	83
8) MONITORING BANDWIDTH AND REACTION TIME	84
9) MONITORING ANTENNA	85
10) MONITORING THRESHOLD RELAXATION	85
11) DUPLEX CONNECTIONS	85
12) ALTERNATIVE MONITORING INTERVAL	87
13) FAIR ACCESS	88
14) FRAME REPETITION STABILITY FRAME PERIOD AND JITTER	88
EUT PHOTOGRAPHS	89
TEST SETUP PHOTOGRAPHS	90

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

HVIN	Motorola DOT21-B
FVIN	VB2583
Product	Digital Cordless Telephone
Tested Model	Motorola DOT21-B
Multiple Model(s)	N/A
Frequency Range	1921.536-1928.448 MHz
Maximum conducted peak output power	19.14dBm
Modulation Technique	GFSK
Antenna Specification [#]	ANT0: 3.06dBi, ANT1: 1.51dBi (It is provided by the applicant)
Voltage Range	DC 6V from adapter
Sample serial number	2WVC-1 for Conducted and Radiated Emissions Test 2WVC-5 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	Adapter1 Model: AT-332A-060040A Input: AC100-240V, 50/60Hz, 0.2A Max Output: DC 6.0V, 0.4A, 2.4W Adapter2 Model: EP04-060040WXLZ Input: AC100-240V, 50/60Hz, 0.2A Max Output: DC 6.0V, 0.4A, 2.4W

Objective

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart D, section 15.207, 15.315, 15.317, 15.319 and 15.323 rules. The EMI measurements were performed according to the measurement procedure described in ANSI C63.17 – 2013 and RSS-213 Issue 3, 2GHz License-Exempt Personal Communications Service Devices (PCS) OF THE Canadian Department of Industry rules and RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2 of the Innovation, Science and Economic Development Canada rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.17 - 2013, American National Standard Methods of Measurement of the Electromagnetic and Operational Compatibility of Unlicensed Personal Communications Services (UPCS) Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	109.2kHz(k=2, 95% level of confidence)	
RF Frequency	56.6Hz(k=2, 95% level of confidence)	
RF output power, conducted	0.86dB(k=2, 95% level of confidence)	
Unwanted Emission, conducted	1.60dB(k=2, 95% level of confidence)	
AC Power Lines Conducted Emissions	9kHz-150kHz 150kHz-30MHz	3.63dB(k=2, 95% level of confidence) 3.66dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
Temperature	±1°C	
Humidity	±1%	
Supply voltages	±0.4%	

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0023.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured to testing mode which is provided by the manufacturer.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“DECT-ExRFTool”# exercise software was used and the power level is default#. The software and power level was provided by the applicant.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Guo Wei	Handset	DOT2-HS	2412000016
YIKE	PBX	TC-208	Unknown
Kinhao	Telephone	KT86AS	Unknown
Rohde & Schwarz	Digital Radio Communication Tester	CMD60	830553/018
OUPU	Receptacle	PDU-OP1606K	6971041358020

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielded Un-detachable AC cable	1.5	Receptacle	LISN/AC Mains
Un-shielded Detachable AC cable	1.2	AC Mains	CMD60
Un-Shielding Un-Detachable DC Cable	1.6	Adapter	EUT
Un-Shielding Detachable RJ11 Cable	3.0	EUT	PBX
Un-Shielding Detachable RJ11 Cable	1.5	PBX	Telephone

Block Diagram of Test Setup


Conducted Emission:



Radiated Emission below 1GHz:



Radiated Emission Above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	RSS Rules	Description of Test	Result
§ 2.1091	/	MPE-Based Exemption	Compliant
	RSS-102 § 6.6	Field reference level exposure exemption limits	Compliant
§ 15.317, § 15.203	RSS-Gen §6.8	Antenna Requirement	Compliant
§ 15.315, § 15.207	RSS-213 §5.4	Conducted Emission	Compliant
§ 15.323 (a)	RSS-213 §5.5	Emission Bandwidth	Compliant
§ 15.319 (c)	RSS-213 §5.6	Peak Transmit Power	Compliant
§ 15.319 (d)	RSS-213 §5.7	Power Spectral Density	Compliant
§ 15.323 (d)	RSS-213 §5.8	Emission Inside and Outside the sub-band	Compliant
§15.205, §15.209, § 15.319 (g)	RSS-213 §5.8	Radiated Emission	Compliant
§ 15.323 (f)	RSS-213 §5.3	Frequency Stability	Compliant
§ 15.323 (c)(e) § 15.319 (f)	RSS-213 §5.1&§5.2	Specific Requirements for UPSCS	Compliant

Note: The product has two antennas, scan all antenna output power, the ANT1 which with the highest output power was selected to perform full test.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/12/04	2025/12/03
Rohde & Schwarz	LISN	ENV216	101613	2024/12/04	2025/12/03
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2024/05/21	2025/05/20
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2024/05/21	2025/05/20
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310 N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	Chamber A Cable 1	N/A	2024/06/18	2025/06/17
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	2Y194	0735	2024/12/04	2025/12/03
Unknown	Cable	PNG214	1354	2024/12/04	2025/12/03
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D (1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	735	2024/12/04	2025/12/03
Unknown	RF Cable	UFA147	219661	2024/12/04	2025/12/03
Unknown	RF Cable	XH750A-N	J-10M	2024/12/04	2025/12/03
JD	Filter Switch Unit	DT7220FSU	DS79906	2024/09/09	2025/09/08
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2024/09/09	2025/09/08
A.H.System	Pre-amplifier	PAM-1840VH	190	2024/06/18	2025/06/17
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/06/18	2025/06/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
BACL	Temperature & Humidity Chamber	BTH-150-40	30145	2024/12/06	2025/12/05
Rohde & Schwarz	Digital Radio Communication Tester	CMD60	830553/018	2024/05/21	2025/05/20
Rohde & Schwarz	Digital Radio Communication Tester	CMD60	830553/018	2025/04/29	2026/04/28
Rohde & Schwarz	Spectrum Analyzer	FSU26	200982	2024/09/20	2025/09/19
Rohde & Schwarz	Spectrum Analyzer	FSV40	101942	2024/09/20	2025/09/19
Keysight	MXG Vector Signal Generator	N5182B	MY53051503	2024/12/04	2025/12/03
HELLVIAO	Contact voltage regulator	TDGC2-5KVA	Unknown	NCR	NCR
Fluke	Digital Multimeter	287	19000011	2024/05/21	2025/05/20
Fluke	Digital Multimeter	287	19000011	2025/04/29	2026/04/28
WEINSCHEL	3dB Attenuator	Unknown	F-03-EM119	2024/06/27	2025/06/26
WEINSCHEL	3dB Attenuator	Unknown	F-03-EM119	2025/06/26	2026/06/25
Unknown	Power Splitter	PD2	2000-600	2024/06/27	2025/06/26
Unknown	Power Splitter	PD2	2000-600	2025/06/26	2026/06/25
Micro-Tronics	RF Cable	8082135	W1113	2024/06/27	2025/06/26
Micro-Tronics	RF Cable	8082135	W1113	2025/06/26	2026/06/25

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC 1.1307 (B) & §2.1091- MPE-BASED EXEMPTION

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

Frequency (MHz)	Tune up conducted power# (dBm)	Antenna Gain#		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBi)	(dBd)	(dBm)	(mW)		
1920-1930	19.5	3.06	0.91	20.41	109.90	0.2	768

Note: The tune up conducted power and antenna gain was declared by the applicant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

RSS-102 § 6.6 - FIELD REFERENCE LEVEL EXPOSURE EXEMPTION LIMITS

Applicable Standard

According to RSS-102 Issue 6§6.6:

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 1 W (adjusted for tune-up tolerance)
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance)
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than $1.31 \times 10^{-2}f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz
- at or above 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 5 W (adjusted for tune-up tolerance) In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the EIRP was derived.

Test Result

For worst case:

Mode	Frequency (MHz)	Maximum tune-up conducted power [#] (dBm)	Antenna Gain [#]	Maximum tune-up EIRP		Evaluation Distance (m)	Limit (mW)
				(dBi)	(dBm)		
DECT	1920-1930	19.5	3.06		22.56	180.30	0.2
							2297

Note: The tune up conducted power[#] and antenna gain[#] was declared by the applicant.

Result: Compliant

Note: To maintain compliance with the RF exposure guidelines, place the equipment at least 20cm from nearby persons.

FCC § 15.317, § 15.203 & RSS-Gen §6.8 ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has two integral antenna arrangements which were permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.


Antenna	Type	Antenna Gain [#]	Impedance
Antenna 0	Monopole	3.06dBi	50Ω
Antenna 1	Monopole	1.51dBi	50Ω

FCC § 15.315, § 15.207 & RSS-213 §5.4 CONDUCTED EMISSIONS

Applicable Standard

FCC§15.315, §15.207(a), RSS-213 §5.4, RSS-GEN § 8.8.

EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC 15.315, FCC 15.207 and RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$

$$\text{Level} = \text{Read Level} + \text{Factor}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Test Data

Environmental Conditions


Temperature:	21~26 °C
Relative Humidity:	45~66 %
ATM Pressure:	100~103 kPa

The testing was performed by Macy Shi on 2025-03-01.

EUT operation mode: Transmitting (Maximum output power mode, ANTI Low channel)

For Adapter I

AC 120V/60 Hz, Line




Condition: Line

Project : 2401A113404E-RF

tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz VBW:Auto SWT:Auto

Freq	Read		LISN	Cable	Limit	Over	Remark
	Level	Level					
1	0.153	25.10	45.65	10.42	10.13	65.82	-20.17 QP
2	0.402	27.40	48.05	10.55	10.10	57.81	-9.76 QP
3	2.707	17.32	38.50	11.01	10.17	56.00	-17.50 QP
4	7.810	23.64	44.35	10.51	10.20	60.00	-15.65 QP
5	8.592	28.87	49.50	10.43	10.20	60.00	-10.50 QP
6	8.964	25.18	45.77	10.39	10.20	60.00	-14.23 QP
Read		LISN	Cable	Limit	Over	Remark	
Freq	Level						
1	0.406	17.71	38.36	10.55	10.10	47.73	-9.37 Average
2	1.210	5.41	26.29	10.74	10.14	46.00	-19.71 Average
3	7.977	10.53	31.22	10.49	10.20	50.00	-18.78 Average
4	8.323	11.22	31.87	10.45	10.20	50.00	-18.13 Average
5	9.059	12.91	33.49	10.38	10.20	50.00	-16.51 Average
6	13.127	8.42	28.94	10.30	10.22	50.00	-21.06 Average


AC 120V/60 Hz, Neutral

Condition: Neutral
 Project : 2401A113404E-RF
 tester : Macy.shi Note:Transmitting
 Setting : RBW:9kHz VBW:Auto SWT:Auto


Freq	Read		LISN	Cable	Limit	Over	Remark
	MHz	dBuV	Level	Factor	Loss	Line	
1	0.152	24.70	45.24	10.41	10.13	65.91	-20.67 QP
2	0.200	22.50	43.39	10.80	10.09	63.62	-20.23 QP
3	0.322	15.71	36.46	10.64	10.11	59.66	-23.20 QP
4	0.410	26.81	47.47	10.56	10.10	57.64	-10.17 QP
5	8.501	19.64	40.39	10.55	10.20	60.00	-19.61 QP
6	8.869	18.72	39.45	10.53	10.20	60.00	-20.55 QP
Read	LISN	Cable	Limit	Line	Limit	Over	Remark
Freq	Level	Level	Factor	Loss	Line	Limit	
1	0.406	22.04	42.71	10.57	10.10	47.73	-5.02 Average
2	0.627	10.31	31.01	10.57	10.13	46.00	-14.99 Average
3	0.918	7.19	28.04	10.75	10.10	46.00	-17.96 Average
4	1.698	7.18	28.07	10.72	10.17	46.00	-17.93 Average
5	3.310	5.97	27.08	10.92	10.19	46.00	-18.92 Average
6	8.592	7.91	28.65	10.54	10.20	50.00	-21.35 Average

For Adapter 2

AC 120V/60 Hz, Line



Freq	Read		LISN	Cable	Limit	Over	Remark
	Level	Level					
1	0.322	24.10	44.81	10.60	10.11	59.66	-14.85 QP
2	3.241	19.90	41.05	10.96	10.19	56.00	-14.95 QP
3	3.381	18.90	40.04	10.95	10.19	56.00	-15.96 QP
4	3.603	20.34	41.47	10.93	10.20	56.00	-14.53 QP
5	3.720	21.50	42.62	10.92	10.20	56.00	-13.38 QP
6	8.592	20.74	41.37	10.43	10.20	60.00	-18.63 QP
Read		LISN	Cable	Limit	Over	Remark	
Freq	Level						
1	0.325	15.50	36.21	10.59	10.12	49.57	-13.36 Average
2	1.716	8.10	29.26	10.99	10.17	46.00	-16.74 Average
3	3.009	9.27	30.43	10.98	10.18	46.00	-15.57 Average
4	3.310	9.75	30.89	10.95	10.19	46.00	-15.11 Average
5	3.603	11.42	32.55	10.93	10.20	46.00	-13.45 Average
6	9.156	9.55	30.12	10.37	10.20	50.00	-19.88 Average

AC 120V/60 Hz, Neutral

Freq	Read		LISN	Cable	Limit	Over	Remark
	MHz	dBuV	Level	Factor	Loss	Line	
1	0.343	22.10	42.84	10.62	10.12	59.13	-16.29 QP
2	2.650	19.40	40.39	10.82	10.17	56.00	-15.61 QP
3	3.310	19.90	41.01	10.92	10.19	56.00	-14.99 QP
4	3.603	20.90	42.05	10.95	10.20	56.00	-13.95 QP
5	3.720	20.10	41.27	10.97	10.20	56.00	-14.73 QP
6	8.869	23.99	44.72	10.53	10.20	60.00	-15.28 QP
Read		LISN	Cable	Limit	Line	Over	Remark
Freq	Level	Level	Factor	Loss	Line	Limit	
1	0.325	11.38	32.14	10.64	10.12	49.57	-17.43 Average
2	0.471	6.02	26.67	10.52	10.13	46.49	-19.82 Average
3	1.734	5.02	25.91	10.72	10.17	46.00	-20.09 Average
4	3.310	7.28	28.39	10.92	10.19	46.00	-17.61 Average
5	3.642	9.23	30.39	10.96	10.20	46.00	-15.61 Average
6	9.059	8.88	29.61	10.53	10.20	50.00	-20.39 Average

FCC § 15.323 (A) & RSS-213 §5.5 EMISSION BANDWIDTH

Applicable Standard

According to FCC §15.323(a):


Operation shall be contained within the 1920–1930 MHz band. The emission bandwidth shall be less than 2.5 MHz and greater than 50 kHz.

According to RSS-213§ 5.5:

The emission bandwidth shall not be less than 50 kHz nor more than 2.5MHz.

The emission bandwidth is measured in accordance with ANSI C63.17 sub-clause 6.1.3 using the setup below:

Test Setup 1:



The width, in Hz, of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that is 26 dB down relative to the maximum level of the modulated carrier. It is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1% of the emission band-width of the device under measurement. [Extraction from 47 CFR 15, subpart D, 15.303 (C)].

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

Resolution bandwidth	1.0% of the emission bandwidth (as close as possible)
Video bandwidth	>3 times the resolution bandwidth
Number of sweeps	sufficient to stability the trace
Detection mode	peak detection with maximum hold

EBW:

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth.

OBW:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

Test Data

Environmental Conditions

Temperature:	25.7 °C
Relative Humidity:	46 %
ATM Pressure:	101.1 kPa

The testing was performed by Rainbow Zhu on 2025-02-06.


Test mode: Transmitting

Test Result: Compliant

Channel	Center Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)	Limit
Low	1921.536	1.240	1.488	50 kHz ~ 2.5 MHz
Middle	1924.992	1.245	1.475	50 kHz ~ 2.5 MHz
High	1928.448	1.245	1.474	50 kHz ~ 2.5 MHz


99% Emission Bandwidth

Low Channel




ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 03:16:30

Middle Channel




ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 03:14:13


High Channel



ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 03:10:53


26 dB Emission Bandwidth**Low Channel**

ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 03:06:27

Middle Channel

ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 02:57:35

High Channel



ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 02:52:13

FCC § 15.319 (c) & RSS-213 §5.6 PEAK TRANSMIT POWER

Applicable Standard

The peak power output as measured over an interval of time equal to the frame rate or transmission burst of the device under all conditions of modulation. Usually this parameter is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used[47 CFR 15, subpart D, 15.303].

The peak transmit power is according to ANSI C63.17-2013 §6.1.2

Per FCC Part15.319 (c) Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in hertz. Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

Per FCC Part15.319 (e), the peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

Calculation of Peak Transmit Power Limit:

$$\text{Peak Transmit Power Limit} = 100\mu\text{W} \times (\text{EBW})^{1/2}$$


EBW is the transmit emission bandwidth in Hz determined in the other test item:

Per RSS-213 §5.6, Peak transmit power shall not exceed 100 μW multiplied by the square root of the occupied bandwidth in hertz. The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	\geq Emission bandwidth
Video bandwidth	\geq RBW
Span	Zero
Center frequency	Nominal center frequency of channels
Amplitude scale	Log (linear may be used if analyzer has sufficient linear dynamic range and accuracy)
Detection	Peak detection
Trigger	Video
Sweep rate	Sufficiently rapid to permit the transmit pulse to be resolved accurately



Test Data**Environmental Conditions**

Temperature:	25.7 °C
Relative Humidity:	46 %
ATM Pressure:	101.1 kPa

The testing was performed by Rainbow Zhu on 2025-02-06.

Test mode: Transmitting:


Test Result: Compliant

Please refer to the following table and plots.


Channel	Frequency (MHz)	Peak Transmit Power (dBm)	FCC Limit (dBm)	ISEDC Limit (dBm)
ANT0				
Low	1921.536	17.29	20.80	20.41
Middle	1924.992	17.47	20.78	20.42
High	1928.448	17.61	20.78	20.42
ANT1				
Low	1921.536	19.14	20.86	20.47
Middle	1924.992	19.12	20.84	20.48
High	1928.448	19.07	20.84	20.48

For FCC: Peak Transmit Power Limit = $100(\text{EBW})^{1/2} \mu\text{W}$
For ISEDC: Peak Transmit Power Limit = $100(\text{OBW})^{1/2} \mu\text{W}$
When the antenna gain exceeds 3 dBi, the limit of peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi

ANT0


Low Channel

ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 01:37:28

Middle Channel

ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 01:32:16


High Channel



ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 01:30:30


ANT1

Low Channel




ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 02:11:48

Middle Channel



ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 02:07:48

High Channel



ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 6.FEB.2025 01:53:38

FCC § 15.319 (d) & RSS-213 §5.7 POWER SPECTRAL DENSITY

Applicable Standard

According to FCC § 15.319 (d):

The average pulse energy in a 3 kHz bandwidth is divided by the pulse duration.

The power spectral density shall not exceed 3mW in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.

The power spectral density is measured in accordance with ANSI C63.17-2013 Clause 6.1.5.


According to RSS-213 §5.7:

The peak-hold power spectral density of transmitters shall not exceed 12 mW per any 3 kHz bandwidth. As an alternative to the peak-hold power spectral density, the time-averaged power spectral density may be measured and it shall not exceed 3 mW per any 3 kHz bandwidth.

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	3 kHz
Video bandwidth	$\geq 3 \times \text{RBW}$
Span	Zero span at frequency with the maximum level (frequency determined in 6.1.3 if the same type of signal (continuous versus burst) was used in 6.1.3)
Center frequency	Spectral peak as determined in 6.1.3
Sweep time	For burst signals, sufficient to include essentially all of the maximum length burst at the output of a 3 kHz filter (e.g., maximum input burst duration plus 600 μs). For continuous signals, 20 ms.
Amplitude scale	Log power
Detection	Sample detection and averaged for a minimum of 100 sweeps
Trigger	External or internal



Test Data**Environmental Conditions**

Temperature:	27.1 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa


The testing was performed by Rainbow Zhu on 2025-08-28.

Test mode: Transmitting


Test Result: Compliant. Please refer to following table and plots

Channel	Frequency (MHz)	Power Spectral Density		Limit (mW/3kHz)
		(dBm/3kHz)	(mW/3kHz)	
Low	1921.536	-1.98	0.634	3
Middle	1924.992	-2.40	0.575	3
High	1928.448	-2.71	0.536	3

Low Channel




ProjectNo.:2401A113404E-RF-FF Tester:Rainbow Zhu
 Date: 28.AUG.2025 14:54:36




ProjectNo.:2401A113404E-RF-FF Tester:Rainbow Zhu
 Date: 28.AUG.2025 15:03:12

Middle Channel





ProjectNo.:2401A113404E-RF-FF Tester:Rainbow Zhu
 Date: 28.AUG.2025 14:39:11



ProjectNo.:2401A113404E-RF-FF Tester:Rainbow Zhu
 Date: 28.AUG.2025 14:46:38

High Channel



FCC § 15.323 (d) & RSS-213 §5.8 EMISSION INSIDE AND OUTSIDE THE SUB-BAND

Applicable Standard

According to FCC § 15.323 (d):

Emissions inside the sub-band must comply with the following emission mask:

1. In the bands between 1B and 2B measured from the center of the emission bandwidth the total power emitted by the device shall be at least 30 dB below the transmit power permitted for that device;
2. in the bands between 2B and 3B measured from the center of the emission bandwidth the total power emitted by an intentional radiator shall be at least 50 dB below the transmit power permitted for that radiator;
3. in the bands between 3B and the sub-band edge the total power emitted by an intentional radiator in the measurement bandwidth shall be at least 60 dB below the transmit power permitted for that radiator.

Where B = emission bandwidth

Emission Outside the sub-band shall be attenuated below a reference power of 112 mw (20.5 dBm) as follows:

1. 30 dB between the sub-band and 1.25 MHz above or below the sub-band;
2. 50 dB between 1.25 and 2.5 MHz above or below the sub-band;
3. 60 dB at 2.5 MHz or greater above or below the sub-band.

According to RSS-213 §5.8:

Emissions outside the 1920-1930 MHz Band

Emissions outside the 1920-1930 MHz band shall be attenuated below a reference power of 112 milliwatts (-9.5 dBW) by at least:

- 30 dB between the band edges and 1.25 MHz above and below the band edges;
- 50 dB between 1.25 MHz and 2.5 MHz above or below the band edges; and
- 60 dB at 2.5 MHz or greater above or below the band edges.

Emissions inside the 1920-1930 MHz Band

Emissions inside the 1920-1930 MHz band shall be attenuated below the transmit power permitted for that device, as follows:

- 30 dB between the frequencies 1B and 2B measured from the centre of the occupied bandwidth;
- 50 dB between the frequencies 2B and 3B measured from the centre of the occupied bandwidth; and
- 60 dB between the frequencies 3B and band edge, where B is the occupied bandwidth in hertz.

Test Procedure

According to ANSI C63.17.2013 Clause 6.1.6.

In-band emission:

Spectrum analyzer settings for measuring in-band emission

RBW	Approximately 1% of the emission bandwidth (B)
Video bandwidth	$3 \times$ RBW
Sweep time	The sweep time shall be sufficiently slow that the swept frequency rate shall not exceed one RBW per three transmit bursts.
Number of sweeps	Sufficient to stabilize the trace
Amplitude scale	Log
Detection	Peak detection and max hold enabled
Span	Approximately equal to $3.5 B$

Out-band emission:

Out-of-band tests shall be performed with the RF carrier set to the lowest and highest carriers defined by the EUT. The spectrum analyzer settings for in-band unwanted emissions in 6.1.6.1 also apply to out-of-band emissions. The EUT shall pass the tests of item a), item b), and item d), as follows:

- a) In the region between the band edges and 1.25 MHz below and above the lower and the upper band edges, respectively, the measured emission level shall not exceed -9.5dBm.
- b) In the region between 1.25 and 2.5 MHz below and above the lower and the upper band edges, respectively, the measured emission level shall not exceed -29.5dBm.
- d) In the region at 2.5 MHz or greater below and above the lower and upper band edges, respectively, the measured emission level shall not exceed the limits of 47CFR15.209. Measurement shall be made as a radiated test.

For Radiated Emission:

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK
Above 1 GHz	Fundamental & Harmonics			
	1MHz	3 MHz	/	PK
	Average level= Peak level+ 20lg (Duty cycle)			
	Emissions other than harmonics			
	1MHz	3 MHz	/	PK
	1MHz	≥10 Hz	/	Average

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:


$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:


$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$


EUT Setup

9 kHz-30MHz:




30MHz-1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters test site.

RF Conducted Emission:**Test Data****Environmental Conditions**

Temperature:	21.8~25.7 °C
Relative Humidity:	45~54 %
ATM Pressure:	101.1~102 kPa


The testing was performed by Anson Su on 2025-02-12 for below 1GHz, Visen Wu on 2025-02-13 for above 1GHz and Rainbow Zhu on 2025-08-27 for RF conducted.

Test mode: Transmitting


Test Result: Compliant

Please refer to following plots



FCC:


Low Channel (Unwanted Emission inside the Sub-band)

ProjectNo.:2401A113404E-RF-FF Tester:Rainbow Zhu
Date: 27.AUG.2025 11:38:12


Middle Channel (Unwanted Emission inside the Sub-band)

ProjectNo.:2401A113404E-RF-FF Tester:Rainbow Zhu
Date: 27.AUG.2025 11:35:58



High Channel (Unwanted Emission inside the Sub-band)**ISEDC:****Low Channel (Unwanted Emission inside the Sub-band)**


Middle Channel (Unwanted Emission inside the Sub-band)

ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 27.AUG.2025 11:45:32

High Channel (Unwanted Emission inside the Sub-band)

ProjectNo.:2401A113404E-RF-FP Tester:Rainbow Zhu
Date: 27.AUG.2025 11:43:37

Low Channel (Unwanted Emission outside the Sub-band)**Middle Channel (Unwanted Emission outside the Sub-band)**

High Channel (Unwanted Emission outside the Sub-band)


ProjectNo.:2401A113404E-RF-FF Tester:Rainbow Zhu
Date: 27.AUG.2025 11:55:06

9 kHz-30MHz: (Worst case is parallel)

Note: The spurious emission from 9 kHz-30MHz of IC RSS-Gen standard, the unit of final result on the test plots are $\text{dB}\mu\text{V}/\text{m}$, so the limit should be added by 51.5 dB from $\text{dB}\mu\text{A}/\text{m}$ to $\text{dB}\mu\text{V}/\text{m}$.


When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.

For Adapter 1_ANT0: (Maximum output power mode, High channel)



Site : Chamber A
 Condition : 3m
 Project Number : 2401A113404E-RF
 Test Mode : Transmitting
 Detector: Peak RBW/VBW: 0.3/1kHz
 Tester : Anson Su


	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.01	32.30	23.05	55.35	127.60	-72.25	Peak
2	0.02	30.50	22.31	52.81	121.82	-69.01	Peak
3	0.03	28.26	20.55	48.81	117.42	-68.61	Peak
4	0.06	25.60	23.54	49.14	112.34	-63.20	Peak
5	0.09	22.37	19.72	42.09	108.07	-65.98	Peak
6	0.14	19.81	19.80	39.61	104.87	-65.26	Peak



Site : Chamber A
Condition : 3m
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 10/30kHz
Tester : Anson Su


	Freq	Factor	Read Level	Limit Level	Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.45	7.27	35.63	42.90	94.46	-51.56	Peak
2	0.59	5.26	34.61	39.87	72.12	-32.25	Peak
3	0.74	3.38	34.53	37.91	70.08	-32.17	Peak
4	0.86	2.27	34.22	36.49	68.84	-32.35	Peak
5	1.21	0.62	32.33	32.95	65.81	-32.86	Peak
6	1.59	-0.44	32.60	32.16	63.38	-31.22	Peak

For Adapter 1_ANT1: (Maximum output power mode, Low channel)



Site : Chamber A
Condition : 3m
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su


Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	
1	0.01	32.17	23.70	55.87	127.01	-71.14	Peak
2	0.02	29.76	20.29	50.05	120.23	-70.18	Peak
3	0.03	28.31	22.15	50.46	117.56	-67.10	Peak
4	0.06	25.60	24.38	49.98	112.34	-62.36	Peak
5	0.09	22.87	19.58	42.45	108.75	-66.30	Peak
6	0.12	20.76	19.05	39.81	105.94	-66.13	Peak



Site : Chamber A
Condition : 3m
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 10/30kHz
Tester : Anson Su


Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	dBuV/m	
1	0.49	6.56	34.33	40.89	73.77	-32.88	Peak
2	0.62	4.89	33.15	38.04	71.68	-33.64	Peak
3	0.86	2.28	35.38	37.66	68.85	-31.19	Peak
4	1.19	0.68	32.19	32.87	65.97	-33.10	Peak
5	1.39	0.09	32.51	32.60	64.52	-31.92	Peak
6	1.54	-0.32	32.57	32.25	63.63	-31.38	Peak

For Adapter 2_ANT0: (Maximum output power mode, High channel)



Site : Chamber A
Condition : 3m
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su


Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	
1	0.01	32.12	24.21	56.33	126.83	-70.50	Peak
2	0.02	29.95	21.22	51.17	120.61	-69.44	Peak
3	0.04	27.80	21.01	48.81	116.32	-67.51	Peak
4	0.06	25.60	24.70	50.30	112.34	-62.04	Peak
5	0.09	22.45	19.28	41.73	108.18	-66.45	Peak
6	0.13	20.35	20.93	41.28	105.46	-64.18	Peak



Site : Chamber A
Condition : 3m
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 10/30kHz
Tester : Anson Su


Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	dBuV/m	
1	0.68	4.20	36.63	40.83	70.92	-30.09	Peak
2	0.81	2.62	34.91	37.53	69.34	-31.81	Peak
3	0.96	1.48	32.83	34.31	67.80	-33.49	Peak
4	1.09	0.95	32.45	33.40	66.71	-33.31	Peak
5	1.24	0.53	31.76	32.29	65.58	-33.29	Peak
6	1.64	-0.60	31.62	31.02	63.08	-32.06	Peak

For Adapter 2_ANT1: (Maximum output power mode, Low channel)



Site : Chamber A
Condition : 3m
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	
1	0.01	32.40	22.98	55.38	128.06	-72.68	Peak
2	0.02	29.92	21.23	51.15	120.55	-69.40	Peak
3	0.04	27.45	20.64	48.09	115.57	-67.48	Peak
4	0.06	25.60	24.07	49.67	112.34	-62.67	Peak
5	0.10	22.33	20.15	42.48	108.02	-65.54	Peak
6	0.13	20.33	18.43	38.76	105.44	-66.68	Peak




Site : Chamber A
Condition : 3m
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 10/30kHz
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	dBuV/m	
1	0.52	6.10	34.25	40.35	73.20	-32.85	Peak
2	0.66	4.45	33.16	37.61	71.18	-33.57	Peak
3	0.77	3.02	33.80	36.82	69.74	-32.92	Peak
4	0.88	2.09	33.64	35.73	68.59	-32.86	Peak
5	1.03	1.12	31.90	33.02	67.22	-34.20	Peak
6	1.34	0.23	31.77	32.00	64.84	-32.84	Peak

30MHz-1GHz:

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.


For Adapter 1_ANT0: (Maximum output power mode, High channel)

Horizontal

Site : Chamber A
 Condition : 3m Horizontal
 Project Number : 2401A113404E-RF
 Test Mode : Transmitting
 Detector: Peak RBW/VBW: 100/300kHz
 Tester : Anson Su

Freq	Factor	Read		Limit	Over	Remark	
		MHz	dB/m	Level	dBuV	dBuV/m	dBuV/m
1	129.92	-11.21	33.22	22.01	43.50	-21.49	Peak
2	141.83	-11.96	33.63	21.67	43.50	-21.83	Peak
3	160.70	-12.72	36.08	23.36	43.50	-20.14	Peak
4	196.68	-13.45	30.50	17.05	43.50	-26.45	Peak
5	234.99	-13.54	31.47	17.93	46.00	-28.07	Peak
6	508.04	-5.77	30.13	24.36	46.00	-21.64	Peak

Vertical




Site : Chamber A
Condition : 3m Vertical
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB _{uV}	dB _{uV/m}		
1	36.16	-9.61	43.14	33.53	40.00	-6.47	Peak
2	41.29	-13.31	40.56	27.25	40.00	-12.75	Peak
3	45.75	-16.31	42.99	26.68	40.00	-13.32	Peak
4	56.67	-18.31	40.60	22.29	40.00	-17.71	Peak
5	122.40	-11.20	30.47	19.27	43.50	-24.23	Peak
6	151.00	-12.46	39.47	27.01	43.50	-16.49	Peak

For Adapter 1_ANT1: (Maximum output power mode, Low channel)


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark			
		Level	Level	Line				
		MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	119.91	-11.46	30.67	19.21	43.50	-24.29	Peak	
2	129.75	-11.21	30.76	19.55	43.50	-23.95	Peak	
3	144.46	-12.18	33.79	21.61	43.50	-21.89	Peak	
4	151.93	-12.54	32.40	19.86	43.50	-23.64	Peak	
5	196.51	-13.46	30.94	17.48	43.50	-26.02	Peak	
6	221.30	-14.16	31.91	17.75	46.00	-28.25	Peak	

Vertical




Site : Chamber A
Condition : 3m Vertical
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB _{uV}	dB _{uV/m}		
1	35.20	-9.01	42.30	33.29	40.00	-6.71	Peak
2	36.57	-9.94	42.93	32.99	40.00	-7.01	Peak
3	40.99	-13.07	39.25	26.18	40.00	-13.82	Peak
4	45.59	-16.23	43.77	27.54	40.00	-12.46	Peak
5	56.03	-18.32	39.38	21.06	40.00	-18.94	Peak
6	128.96	-11.21	29.96	18.75	43.50	-24.75	Peak

For Adapter 2_ANT0: (Maximum output power mode, High channel)


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq	Factor	Read Level	Limit Level	Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	32.32	-7.23	29.39	22.16	40.00	-17.84	Peak
2	117.00	-11.79	29.31	17.52	43.50	-25.98	Peak
3	142.45	-12.02	29.41	17.39	43.50	-26.11	Peak
4	158.46	-12.68	34.38	21.70	43.50	-21.80	Peak
5	279.29	-11.24	29.59	18.35	46.00	-27.65	Peak
6	579.18	-5.26	29.55	24.29	46.00	-21.71	Peak

Vertical




Site : Chamber A
Condition : 3m Vertical
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

Freq Factor	MHz	Read		Limit		Over	Remark
		dB/m	dB _{uV}	dB _{uV/m}	dB _{uV/m}		
1	30.91	-6.42	29.76	23.34	40.00	-16.66	Peak
2	36.57	-9.94	35.23	25.29	40.00	-14.71	Peak
3	40.26	-12.55	35.16	22.61	40.00	-17.39	Peak
4	120.43	-11.41	28.91	17.50	43.50	-26.00	Peak
5	162.25	-12.75	28.93	16.18	43.50	-27.32	Peak
6	283.11	-11.23	33.88	22.65	46.00	-23.35	Peak

For Adapter 2_ANT1: (Maximum output power mode, Low channel)


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq	Factor	Read Level	Limit Level	Line	Over Limit	Remark	
			MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	31.00	-6.47	29.21	22.74	40.00	-17.26	Peak	
2	129.70	-11.21	28.22	17.01	43.50	-26.49	Peak	
3	156.05	-12.64	34.12	21.48	43.50	-22.02	Peak	
4	297.35	-11.21	29.11	17.90	46.00	-28.10	Peak	
5	400.96	-8.38	29.72	21.34	46.00	-24.66	Peak	
6	664.35	-3.88	29.79	25.91	46.00	-20.09	Peak	

Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2401A113404E-RF
Test Mode : Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB _{uV}	dB _{uV/m}		
1	31.26	-6.63	29.01	22.38	40.00	-17.62	Peak
2	36.53	-9.90	35.61	25.71	40.00	-14.29	Peak
3	40.83	-12.95	35.04	22.09	40.00	-17.91	Peak
4	126.38	-11.12	28.86	17.74	43.50	-25.76	Peak
5	162.47	-12.76	31.50	18.74	43.50	-24.76	Peak
6	556.77	-5.29	29.88	24.59	46.00	-21.41	Peak

Above 1GHz:**ANT0**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	PK/AV					
Low Channel							
1921.54	117.02	PK	H	-13.26	103.76	/	/
1921.54	115.56	PK	V	-13.26	102.30	/	/
3843.07	60.20	PK	H	-9.96	50.24	74	-23.76
3843.07	57.80	PK	V	-9.96	47.84	74	-26.16
Middle Channel							
1924.99	117.56	PK	H	-13.24	104.32	/	/
1924.99	114.70	PK	V	-13.24	101.46	/	/
3849.98	58.94	PK	H	-9.97	48.97	74	-25.03
3849.98	57.91	PK	V	-9.97	47.94	74	-26.06
High Channel							
1928.45	117.60	PK	H	-13.21	104.39	/	/
1928.45	116.24	PK	V	-13.21	103.03	/	/
3856.90	58.69	PK	H	-9.97	48.72	74	-25.28
3856.90	56.87	PK	V	-9.97	46.90	74	-27.10

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dB μ V/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Comment
1921.536MHz							
1921.54	103.76	H	-27.86	75.90	/	/	Fundamental
1921.54	102.30	V	-27.86	74.44	/	/	Fundamental
3843.07	50.24	H	-27.86	22.38	54	-31.62	Harmonic
3843.07	47.84	V	-27.86	19.98	54	-34.02	Harmonic
1924.992MHz							
1924.99	104.32	H	-27.86	76.46	/	/	Fundamental
1924.99	101.46	V	-27.86	73.60	/	/	Fundamental
3849.98	48.97	H	-27.86	21.11	54	-32.89	Harmonic
3849.98	47.94	V	-27.86	20.08	54	-33.92	Harmonic
1928.448MHz							
1928.45	104.39	H	-27.86	76.53	/	/	Fundamental
1928.45	103.03	V	-27.86	75.17	/	/	Fundamental
3856.90	48.72	H	-27.86	20.86	54	-33.14	Harmonic
3856.90	46.90	V	-27.86	19.04	54	-34.96	Harmonic

Note: Average level= Peak level+ Duty Cycle Factor

Duty cycle:

Ton = 0.4058ms

Tp = 10.029 ms

Duty Cycle = Ton/Tp = 0.4058/10.029=0.04046

Duty Cycle Corrected Factor = 20lg (Duty Cycle) = 20lg0.04046 = -27.86

ANT1

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	PK/AV					
Low Channel							
1921.54	121.64	PK	H	-13.26	108.38	/	/
1921.54	120.35	PK	V	-13.26	107.09	/	/
3843.07	58.20	PK	H	-9.96	48.24	74	-25.76
3843.07	56.36	PK	V	-9.96	46.40	74	-27.60
Middle Channel							
1924.99	121.71	PK	H	-13.24	108.47	/	/
1924.99	120.63	PK	V	-13.24	107.39	/	/
3849.98	57.85	PK	H	-9.97	47.88	74	-26.12
3849.98	56.13	PK	V	-9.97	46.16	74	-27.84
High Channel							
1928.45	121.75	PK	H	-13.21	108.54	/	/
1928.45	121.19	PK	V	-13.21	107.98	/	/
3856.90	56.67	PK	H	-9.97	46.70	74	-27.30
3856.90	55.72	PK	V	-9.97	45.75	74	-28.25

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dB μ V/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Comment
1921.536MHz							
1921.54	108.38	H	-27.86	80.52	\	\	Fundamental
1921.54	107.09	V	-27.86	79.23	\	\	Fundamental
3843.07	48.24	H	-27.86	20.38	54	-33.62	Harmonic
3843.07	46.40	V	-27.86	18.54	54	-35.46	Harmonic
1924.992MHz							
1924.99	108.47	H	-27.86	80.61	\	\	Fundamental
1924.99	107.39	V	-27.86	79.53	\	\	Fundamental
3849.98	47.88	H	-27.86	20.02	54	-33.98	Harmonic
3849.98	46.16	V	-27.86	18.3	54	-35.7	Harmonic
1928.448MHz							
1928.45	108.54	H	-27.86	80.68	\	\	Fundamental
1928.45	107.98	V	-27.86	80.12	\	\	Fundamental
3856.90	46.70	H	-27.86	18.84	54	-35.16	Harmonic
3856.90	45.75	V	-27.86	17.89	54	-36.11	Harmonic

Note: Average level= Peak level+ Duty Cycle Factor

Duty Cycle:


$T_{on} = 0.4058\text{ms}$

$T_p = 10.029\text{ ms}$

$\text{Duty Cycle} = T_{on}/T_p = 0.4058/10.029 = 0.04046$


$\text{Duty Cycle Corrected Factor} = 20\lg(\text{Duty Cycle}) = 20\lg 0.04046 = -27.86$

Duty cycle




ProjectNo.:2401A113404E-RFTester:Visen Wu


Date: 13.FEB.2025 20:04:58





ProjectNo.:2401A113404E-RFTester:Visen Wu


Date: 13.FEB.2025 20:03:44


Listed with the worst harmonic margin test plot: (ANT0)

















FCC § 15.323 (f) & RSS-213 §5.3 FREQUENCY STABILITY

Applicable Standard

Per §15.323(f) & ANSI C63.17-2013 Clause 6.2.1, the frequency stability of the carrier frequency of the intentional radiator shall be maintained within ± 10 ppm over 1 hour or the interval between channel access monitoring, whichever is shorter. The frequency stability shall be maintained over a temperature variation of -20°C to $+50^{\circ}\text{C}$ or as declared by the manufacturer at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of 20°C . For equipment that is capable only of operating from a battery, the frequency stability tests shall be performed using a new battery without any further requirement to vary supply voltage.

According to RSS-213 Issue 3 (2015-03) § (5.3):

The carrier frequency stability shall be maintained within ± 10 ppm ($\pm 0.001\%$).

According to RSS-Gen Issue 5 (2021-02) § (8.11):

Transmitter frequency stability for licence-exempt radio apparatus shall be measured in accordance with Section 6.11. For licence-exempt radio apparatus, the frequency stability shall be measured at temperatures of -20°C (-4°F), $+20^{\circ}\text{C}$ ($+68^{\circ}\text{F}$) and $+50^{\circ}\text{C}$ ($+122^{\circ}\text{F}$) instead of at the temperatures specified in Section 6.11.


Test Procedure

This procedure should be carried out for each of the following test cases:

Temperature	Supply Voltage
20°C	85-115% or new batteries
-20°C	Normal
$+50^{\circ}\text{C}$	Normal

During test, the equipment shall be placed in the boxes and set the temperature to the specified requirement until the thermal balance has been reached.

Using the mean carrier frequency at 20°C and at nominal supply voltage as the reference, the mean carrier frequency shall be maintained within ± 10 ppm at the two extreme temperatures (or as declared by the manufacturer) and at normal temperature (typically 20°C) at the two extreme supply voltages. This test does not apply to a EUT that is capable only of operating from a battery.



Test Data**Environmental Conditions**

Temperature:	25.7 °C
Relative Humidity:	46 %
ATM Pressure:	101.1 kPa

The testing was performed by Rainbow Zhu on 2025-02-06.

Test Result: Compliant

Test mode: Transmitting

Temperature (°C)	Voltage (V _{AC} ☒, V _{DC} ☐)	Channel Frequency (MHz)	Measured Frequency Offset (kHz)	Measured Frequency Offset (ppm)	Limit (ppm)
-20	120	1924.992	-7	-3.636	±10
20	102	1924.992	-3	-1.558	±10
	138	1924.992	2	1.039	±10
50	120	1924.992	-9	-4.675	±10

Note: the extreme test condition was declared by applicant.

FCC § 15.323 (c)(e) & § 15.319 (f) & RSS-213 §5.1&§5.2 SPECIFIC REQUIREMENTS FOR UPCS DEVICE

Applicable Standard

FCC§15.323(c)(e) & §15.319(f) Specific Requirements for UPCS device.

ANSI C63.17 2013 §6.2 Frequency and time stability and §7.Monitoring tests and §8.Time and spectrum window access procedure.


According to RSS-213 §5.1&§5.2 type of modulation and access protocol
Equipment certified under this standard shall use digital modulation.

In order to provide equitable access to the radio frequency spectrum, the licence-exempt PCS device must possess an access protocol.

Test Procedure

Measurement method according to ANSI C63.17- 2013

Test configuration as below



Test Data

Environmental Conditions

Temperature:	25.7 °C
Relative Humidity:	46 %
ATM Pressure:	101.1 kPa

The testing was performed by Rainbow Zhu on 2025-02-06.

Test Result: Compliant

Please see the below data

1) Automatic Discontinuation of Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. The provisions in this section are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Test result:

The following tests were performed after a connection had been established with Handset.

Test condition	Reaction of EUT	Pass/Fail
Adapter removed from EUT	Connection break down	Pass
Battery remove from Handset	Connection break down	Pass

2) Monitoring Time

Immediately prior to initiating transmission, devices must monitor the combined time and spectrum window in which they intend to transmit. For a period of at least 10 milliseconds for systems designed to use a 10 milliseconds or shorter frame period or at least 20 milliseconds for systems designed to use a 20 milliseconds frame period

Test procedure:

Measurement method is in according to ANSI C63.17 -2013 clause 7.3.3.
RF signal generators apply uniform CW interference on all system carriers except two carriers (designated f_1 and f_2), each at level $T_L + U_M$. EUT can only transmit on these two carriers.

Test result:

This requirement is covered by the results of Least Interfered Channel (LIC).

Interference (Refer to ANSI C63.17 clause 7.3.3)	Reaction of EUT	Results
a) Apply the interference on f_1 at level $T_L + U_M + 20$ dB and no interference on f_2 . Initiate transmission and verify the transmission only on f_2 . Then terminate it.	EUT transmits on f_2	Pass
b) Apply the interference on f_2 at level $T_L + U_M + 20$ dB and immediately remove all interference from f_1 . The EUT should immediately attempt transmission on f_1 (but at least 20 ms after the interference on f_2 is applied), verify the transmission only on f_1 .	EUT transmission f_1	Pass

3) Lower Monitoring Threshold

The monitoring threshold must not be more than 30 dB above the thermal noise power for a bandwidth equivalent to the emission bandwidth used by the device.

Test procedure:

Measurement method according to ANSI C63.17 -2013 clause 7.3.1

Test result:

Not applicable because the EUT has more 40 defined duplex system access channels and meet the provision of the Least Interfered Channel (LIC).

4) Maximum Transmit Period

If no signal above the threshold level is detected, transmission may commence and continue with the same emission bandwidth in the monitored time and spectrum windows without further monitoring. However, occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

Test procedure:

The test procedure is as follows:

- a) Activate the EUT and initiate a communication channel with the companion device, and start a timer or frame counter.
- b) The centre frequency of spectrum analyzer was set to the carrier frequency and SPAN was set to ZERO. The spectrum analyzer was used to monitor the time and spectrum window of the communication channel.
- c) Stop the timer at the end of the EUT transmission on the current time and frequency window (measure the time until the EUT changes to a different slot).

Test result:

Repetition of Access Criteria	Measured Maximum Transmission Time (Second)	Limit (Second)	Results
First	17628	28,800	Pass
Second	17322	28,800	Pass

5) System Acknowledgement

Once access to specific combined time and spectrum windows is obtained an acknowledgment from a system participant must be received by the initiating transmitter within one second or transmission must cease.

Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgment, at which time the access criteria must be repeated.

Test procedure:

Measurement method according to ANSI C63.17 2013 clause 8.1, 8.2, 8.2.1

During testing initial transmission without acknowledgement, the signal from the EUT to the companion device is blocked by the circulator.

The test of the transmission time after loss of acknowledgements is performed by cutting off the signal from the companion device by a RF switch and measuring the time until the EUT stops transmitting.

Test result:

Test	Time taken (second)	Limit (second)	Result
Initial Connection acknowledgement	0.29	1	Pass
Change of access criteria for control information	N/A	30	N/A
Transmission cease time	8.14	30	Pass

Note: N/A=Not Applicable

6) Least Interfered Channel (LIC)

If access to spectrum is not available as determined by the above, and a minimum of 20 duplex system access channels are defined for the system, the time and spectrum windows with the lowest power level may be accessed.

A device utilizing the provisions of this paragraph (5) must have monitored all access channels defined for its system within the last 10 seconds and must verify, within the 20 milliseconds (40 milliseconds for devices designed to use a 20 millisecond frame period) immediately preceding actual channel access, that the detected power of the selected time and spectrum windows is no higher than the previously detected value.

The power measurement resolution bandwidth for this comparison must be accurate to within 6 dB. No device or group of cooperating devices located within 1 metre of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively, more than one third of the time and spectrum windows defined by the system.

Calculation of monitoring threshold limits for isochroous devices:

Calculation of monitoring threshold limits for isochroous devices:

Lower threshold: $TL = -174 + 10\log_{10}B + ML + P_{MAX} - PEUT$ (dBm)

Where: B=Emission bandwidth (Hz)

ML = dB the threshold may exceed thermal noise (30 for TL)

P MAX = $5\log_{10}B - 10$ (dBm)

PEUT = Transmitted power (dBm)

Calculated thresholds:

Monitor Threshold	B(MHz)	M _L (dB)	P _{MAX} (dBm)	P _{EUT} (dBm)	Threshold (dBm)
Lower threshold	1.488	30	20.86	19.14	-80.55

Note: 1. The upper threshold is applicable as the EUT utilizes more than 20 duplex system channels

Test procedure:

Measurement method according to ANSI C63.17 clause 7.3.2, 7.3.3

C63.17 clause 7.3.2, LIC procedure test:

- Allow EUT transmission on only two carrier frequencies, which will be designated f_1 and f_2 .
- Apply interference to the EUT on f_1 at a level of $TL + UM + 7$ dB and on f_2 at a level of $TL + UM$. Initiate transmission. The EUT should transmit on f_2 . Terminate the connection. Repeat five times. If the EUT transmits once on f_1 , the test failed.
- Apply interference to the EUT on f_1 at a level of $TL + UM$ and on f_2 at a level of $TL + UM + 7$ dB. Initiate transmission. The EUT should transmit on f_1 . Terminate the connection. Repeat five times. If the EUT transmits once on f_2 , the test failed.
- Apply interference to the EUT on f_1 at a level of $TL + UM + 1$ dB and on f_2 at a level of $TL + UM - 6$ dB. Initiate transmission. If the EUT transmits on f_2 , terminate the connection. Repeat five times. If the EUT transmits once on f_1 , the test failed.
- Apply interference to the EUT on f_1 at a level of $TL + UM - 6$ dB and on f_2 at a level of $TL + UM + 1$ dB. Initiate transmission. If the EUT transmits on f_1 , terminate the connection. Repeat five times. If the EUT transmits once on f_2 , the test failed.

C63.17 clause 7.3.3, Selected channel confirmation:

- Allow EUT transmission on only two carrier frequencies, which will be designated f_1 and f_2 . This limitation to carriers f_1 and f_2 is performed preferably by administration commands for the EUT, or alternatively by applying by a multicarrier interference generator uniform interference on all system carriers except f_1 and f_2 , at a level of $TL + UM + 20$ dB in-band per carrier. Set the interference level to the EUT on f_1 to a level of $TL + UM + 20$ dB, and let there be no interference applied on f_2 .
- Initiate transmission and verify that the EUT transmits on f_2 . If a connection was made, terminate it.
- Apply interference on f_2 at a level of $TL + UM + 20$ dB in-band, and immediately remove all interference from f_1 and immediately (but not sooner than 20 ms after the interference on f_2 is applied) cause the EUT to attempt transmission. The EUT should now transmit on f_1 , if it transmits.
- If the EUT transmits on f_2 , it fails.

Test result:**1) LIC procedure test:**

Interference (Refer to ANSI C63.17 clause 7.3.3)	Reaction of EUT	Results
a) Apply the interference on f_1 at level T_L+U_M+7 dB and the interference on f_2 at level T_L+U_M . Initiate transmission and verify the transmission only on f_2 . Repeat 5 times.	EUT transmits on f_2	Pass
b) Apply the interference on f_1 at level T_L+U_M and the interference on f_2 at level T_L+U_M+7 dB. Initiate transmission and verify the transmission only on f_1 . Repeat 5 times.	EUT transmits on f_1	Pass
c) Apply the interference on f_1 at level T_L+U_M+1 dB the interference on f_2 at level T_L+U_M-6 dB. Initiate transmission and verify the transmission only on f_2 . Repeat 5 times.	EUT transmits on f_2	Pass
d) Apply the interference on f_1 at level T_L+U_M-6 dB and the interference on f_2 at level T_L+U_M+1 dB. Initiate transmission and verify the transmission only on f_1 . Repeat 5 times.	EUT transmits on f_1	Pass

2) Selected channel confirmation:

Interference (Refer to ANSI C63.17 clause 7.3.4)	Reaction of EUT	Results
a) Apply the interference on f_1 at level T_U+U_M and no interference on f_2 . Initiate transmission and verify the transmission only on f_2 . Then terminate it.	EUT transmits on f_2	Pass
b) Apply the interference on f_2 at level T_L+U_M and immediately remove all interference from f_1 . The EUT should immediately attempt transmission on f_1 (but at least 20 ms after the interference on f_2 is applied), verify the transmission only on f_1 .	EUT transmission f_1	Pass

7) Random waiting

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same window after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

Test procedure:

This test is for EUTs that transmit control and signaling channels and that use the provisions of FCC §15.323(c)(6) & IC RSS-213 5.2(6), thus to verify that the EUT (if in deferral) waits for a channel to go clear, then implements a 10 ms to 150 ms hold off prior to using the channel. FCC §15.323(c)(6) is not restrictive for EUTs that use the LIC and offer 20 or more duplex communications channels, as a combined time and spectrum window cannot become unavailable as there is no threshold limit. Test method according to ANSI C63.17 2013 clause 8.1.2 or 8.1.3

- Restrict operation of the EUT to a single carrier designated f_1 . For TDMA system, further restrict EUT transmission to a single timeslot of the usable timeslots available in the TDMA frame structure and synchronize the interference so as to occur centered within the timeslot.

- b) Activate the EUT with no interference present. The EUT must transmit on f_1 . Then apply CW interference on f_1 . The interference level shall be at $TL + UM$ as appropriate for EUTs that do or do not meet the requirements for using the upper threshold. The EUT must stop transmitting within 30 s.
- c) Cancel the interference. Measure the time interval between the end of the interference transmission and the beginning of transmission by the EUT.
- d) Repeat step b) and step c) 100 times. If the measured time intervals vary uniformly between 10 ms and 150 ms, the EUT passes the test.

Note: This is Not Applicable

8) Monitoring Bandwidth and Reaction Time

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission and have a maximum reaction time less than $50\sqrt{1.25/B}$ (1.25/occupied bandwidth in MHz) microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds.

Note: Testing of the monitoring system bandwidth is not required if the designed bandwidth from the manufacturer is available and given in the test report.

The maximum reaction time of the monitor shall be less than $50\sqrt{1.25/B}$ (1.25/occupied bandwidth in MHz) μ s for signals at the applicable threshold level but shall not be required to be less than 50 μ s. If a signal of 6 dB or more above the threshold level is detected, the maximum reaction time shall be $35\sqrt{1.25/B}$ (1.25/occupied bandwidth in MHz) μ s but shall not be required to be less than 35 μ s.

Test procedure:

Measurement method according to ANSI C63.17 2013 clause 7.4 & 7.5

- a) Restrict the EUT to a single transmit carrier frequency f_1 , and verify that the EUT can establish a connection with no interference applied on f_1 .
- b) Apply time-synchronized, pulsed interference on f_1 at the pulsed level $TL + UM$, verify that the EUT does not establish a connection when the width of the interference pulse exceeds the largest of 50 μ s and $50\sqrt{1.25/B}$ μ s, where B is the emission bandwidth of the EUT in megahertz.
- c) With the channel interference level 6 dB above $TL + UM$, verify that the EUT does not establish a connection when the width of the interference pulse exceeds the largest of 35 μ s and $35\sqrt{1.25/B}$ μ s, where B is the emission bandwidth of the EUT in megahertz.

Test Pulse width Equation (μ s)	B(bandwidth) (MHz)	Pulse width (μ s)	Limit (largest) (μ s)
$50(1.25/B)^{1/2}$	1.488	45.83	50
$35(1.25/B)^{1/2}$	1.488	32.08	35

Test result:**1) Monitoring Bandwidth:**

The antenna of the EUT used for monitoring is the same interior antenna that used for transmission, so the monitoring system bandwidth is equal to the emission bandwidth of the intended transmission.

2) Reaction Time Test:

No.	Interference Pulse width (μs)	Reaction of EUT	Observing time (μs)	Result
1	50μs with level T_L+U_M	No transmission	25.36	Pass
2	35μs with level T_L+U_M+6dB	No transmission	24.21	Pass

9) Monitoring Antenna

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location.

Test procedure:

Measurement method according to ANSI C63.17 -2013 paragraph 4

Test result:

The antenna of the EUT used for transmission is the same interior antenna that used for monitoring.

10) Monitoring threshold relaxation

Devices that have a power output lower than the maximum permitted under the rules can increase their monitoring detection threshold by one decibel for each one decibel that the transmitter power is below the maximum permitted.

Test procedure:

Measurement method according to ANSI C63.17 -2013 clause 7.4 & paragraph 4

Test result:

This requirement is covered by the results of Least Interfered Channel (LIC).

11) Duplex Connections

An initiating device may attempt to establish a duplex connection by monitors both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

Test procedure:

This test validates proper operation of an EUT that operates according to the provisions of FCC §15.323(c)(10) using a check of both transmit and receive channels on one end of the link to qualify both ends of the link for transmissions. Test method according to ANSI C63.17 clause 8.3.2 Validation of dual access criteria check for EUTs that implement the upper threshold

- a) Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 40 dB above $TL + UM$.
- b) Restrict the EUT and its companion device to operation at a single carrier $f1$ for TDMA systems and on $f1$ and $f2$ and corresponding duplex carriers for FDMA systems. Verify that the EUT and its companion device can establish a connection on a time/spectrum window on the enabled carrier(s). Terminate the connection.
- c) Apply interference to the EUT on the EUT's *transmit* time/spectrum windows at $TL + UM$ per carrier on all time/spectrum windows except for one, which has interference at least 10 dB below TL . Adjust the interference to the EUT on its *receive* time/spectrum windows such that a single time/spectrum window has interference at least 10 dB below TL , and the interference on the other time/spectrum windows is at $TL + UM + 7$ dB. The interference to the companion device should be at least 10 dB below TL on all active time/spectrum windows. The interference-free *receive* time/spectrum window must not be the duplex mate of the interference-free *transmit* time/spectrum window.
- d) Cause the EUT to attempt to establish a connection. The connection should be made on the interference-free *receive* time/spectrum window and its duplex mate. Otherwise, the EUT fails the test.
- e) If a connection exists, terminate it. Reduce the interference on the EUT's *receive* time/spectrum windows to a level of $TL + UM$ per carrier on all time/spectrum windows except for one, which has interference at least 10 dB below TL . Raise the interference on the EUT's *transmit* time/spectrum windows to a level of $TL + UM + 7$ dB, maintaining one time/spectrum window with interference at least 10 dB below TL . The interference to the companion device should be at least 10 dB below TL on all active time/spectrum windows. Again, the interference-free *transmit* and *receive* time/spectrum windows should not constitute a duplex pair if the system designates a specific duplex pairing for time/spectrum windows.
- f) Cause the EUT to attempt to establish a connection. The connection should be made on the interference-free *transmit* time/spectrum window and its duplex mate. Otherwise, the system fails the test.
- g) Terminate the connection and raise the interference to the EUT on all of the EUT's *transmit* and *receive* time/spectrum windows to $TU + UM$ per carrier on all time/spectrum windows except for a single *transmit* time/spectrum window and a single *receive* time/spectrum window, which shall have interference at least 10 dB below TL . The low-interference *transmits* and *receives* time/spectrum windows shall not constitute a duplex pair. Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 30 dB above TU . Cause the EUT to attempt to establish a connection. If a connection is established, the test fails.

Test result:

Interference (Refer to ANSI C63.17 § 8.3& § 8.3.2)	Reaction of EUT	Results
a) Only a single carrier f_1 for EUT TDMA systems and on f_1 and f_2 and corresponding duplex carriers for FDMA systems.	EUT can transmit	Pass
b) All Tx windows with level $TL+UM$ except one & Rx windows with level $TL+UM+7dB$ except one, which are not the duplex mate.	Connected on the target Rx window and its duplex mate.	Pass
c) All Tx windows with level $TL+UM+7dB$ except one & Rx windows with level $TL+UM$ except one, which are not duplex mate.	Connected on the target Tx window and its duplex mate.	Pass
d) All Tx & Rx windows with level $TU+UM$, except one for Tx window & one for Rx window, which are not duplex mate.	No connection possible	Pass

12) Alternative monitoring interval

An initiating device that is prevented from monitoring during its intended transmit window due to monitoring system blocking from the transmissions of a co-located (within one meter) transmitter of the same system, may monitor the portions of the time and spectrum windows in which they intend to receive over a period of at least 10 milliseconds. The monitored time and spectrum window must total at least 50 percent of the 10 millisecond frame interval and the monitored spectrum must be within 1.25 MHz of the center frequency of channel(s) already occupied by that device or co-located co-operating devices. If the access criteria is met for the intended receive time and spectrum window under the above conditions, then transmission in the intended transmit window by the initiating device may commence.

Test procedure:

This test validates the ability of the EUT to distinguish between same-system and other-system interference for purposes of satisfying the requirement of 47CFR15.323(c) (11). Test method according to ANSI C63.17 2013 clause 8.4

- a) Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 30 dB above TL .
- b) Restrict the EUT and its companion device to operation at a single carrier f_1 for TDMA systems and on f_1 and f_2 and corresponding duplex carriers for FDMA systems. Verify that the EUT and its companion device can establish a connection.
- c) Apply interference at $TL + UM$ per carrier to the EUT on all *transmit* time/spectrum windows on the enabled carrier(s). The interference must use the same physical layer parameters (modulation, frame format, etc.) as the EUT transmissions, but with a system identifier different from that used by the EUT and the companion device. Ensure that the interference level at the companion device is at least 10 dB below TL . Apply no interference to the *receive* time/spectrum windows on the enabled carriers.
- d) Cause the EUT to attempt to establish a connection. If a connection is established, the test fails.

Test result:

Interference (Refer to ANSI C63.17 § 8.4)	Reaction of EUT	Results
a) Only a single carrier f_1 for EUT TDMA systems and one f_1 and f_2 and corresponding duplex carriers for FDMA systems.	EUT can transmit	Pass
b) Apply interference with same parameters as EUT transmissions on all Tx windows with level $TL+UM$ on the enabled carrier(s) and no interference on the Rx windows on the enabled carriers.	No connection is established	Pass

IC:

Not appropriate, as the system always monitors both the transmit and receive time/spectrum windows, it is not a co-located device.

13) Fair Access

The provisions of FCC §15.323 (c) & paragraphs 5.2 (10) or (11) shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

Test result:

The manufacturer declares that this device does not use any mechanisms as provided by FCC §15.323(c)(10) or (11) & IC RSS-213 5.2(10) and (11) to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other device.

14) Frame Repetition Stability Frame Period and Jitter

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of an intentional radiator operating in these sub-bands shall be 20 milliseconds or 10 milliseconds/X where X is a positive whole number. Each device that implements time division for the purposes of maintaining a duplex connection on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 50 parts per million (ppm). Each device which further divides access in time in order to support multiple communication links on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 10 ppm. The jitter (time-related, abrupt, spurious variations in the duration of the frame interval) introduced at the two ends of such a communication link shall not exceed 25 microseconds for any two consecutive transmissions.

Transmissions shall be continuous in every time and spectrum window during the frame period defined for the device.

Test procedure:

Measurement method according to ANSI C63.17 2013 clause 6.2.2, 6.2.3

Test result:

Frame Period and Jitter:

Max. pos. Jitter (μ s)	Max. neg. Jitter (μ s)	Frame period (ms)	Limit	
			Frame Period (ms)	Jitter (μ s)
0.13	-0.09	10.24	20 or 10/X	25

Note: X is a positive whole number.

EUT PHOTOGRAPHS

Please refer to the attachment 2401A113404E-RF External photo and 2401A113404E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2401A113404E-RF Test Setup photo.

******* END OF REPORT *******