

FCC PART 95

MEASUREMENT AND TEST REPORT

For

GOCOM Technology Co.,Ltd.

UNIT 12, 14/F, LIPPO SUN PLAZA, 28 CANTON ROAD TSIM SHA TSUI,
KOWLOON, Hong Kong, China

FCC ID: 2ARRE-2020G9

Report Type: Original Report	Product Type: walkie talkie
Report Number: RSZ200612001-00	
Report Date: 2020-07-14	
Jimmy Xiao 	
Reviewed By: RF Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "**". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
§2.1093 - RF EXPOSURE INFORMATION	9
APPLICABLE STANDARD	9
TEST RESULT	9
FCC §95.587(b)(1) – ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §2.1046 & §95.567 - RF OUTPUT POWER.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST DATA	11
FCC §2.1047 & §95.575 - MODULATION CHARACTERISTIC	12
APPLICABLE STANDARD	12
TEST PROCEDURE	12
TEST DATA	12
FCC §2.1049 & §95.573 - AUTHOURIZED BANDWIDTH AND EMISSION MASK.....	18
APPLICABLE STANDARD	18
TEST PROCEDURE	18
TEST DATA	18
FCC §2.1053 & §95.579- RADIATED SPURIOUS EMISSION	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATA	21
FCC §2.1055 (d) & §95.565 - FREQUENCY STABILITY	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATA	23

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

Product	walkie talkie
Tested Model	G9
Frequency Range	462.5500~462.7250MHz 467.5625~467.7125MHz
Transmit Power (ERP)	462.5500~462.7250MHz :30.88dBm 467.5625~467.7125MHz: 23.12dBm
Channel Spacing	12.5kHz
Modulation Technique	FM
Antenna Specification	1.5dBi
Voltage Range	DC 3*1.2V from batteries or DC 5.0V from charger by adapter
Date of Test	2020-06-22 to 2020-07-13
Sample serial number	RSZ200612001-RF-S1(Assigned by BACL, Shenzhen)
Received date	2020-06-12
Sample/EUT Status	Good condition
Adapter Information	Model:TPA-97H050055UW01 Input:100-240V~50/60Hz,0.15A Output:5.0V,550mA

Objective

This report is prepared on behalf of *GOCOM Technology Co.,Ltd.* in accordance with Part 2 and Part 95, Subpart A & Subpart B of the Federal Communication Commissions rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All tests and measurements indicated in this document were performed in accordance with Part 95 Subpart A, Subpart B of the Federal Communication Commissions rules with TIA-603-E, Land Mobile FM or PM-Communications Equipment-Measurement and Performance Standards.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 342867, the FCC Designation No. : CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

FRS Channel List

Channel No.	Channel Frequency (MHz)	Channel No.	Channel Frequency (MHz)
1	462.5625	12	467.6625
2	462.5875	13	467.6875
3	462.6125	14	467.7125
4	462.6375	15	462.5500
5	462.6625	16	462.5750
6	462.6875	17	462.6000
7	462.7125	18	462.6250
8	467.5625	19	462.6500
9	467.5875	20	462.6750
10	467.6125	21	462.7000
11	467.6375	22	462.7250


Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§2.1093	RF Exposure	Compliance
§95.587(b)(1)	Antenna Requirement	Compliance
§2.1046, §95.567	RF Output Power	Compliance
§2.1047, §95.575	Modulation Characteristic	Compliance
§2.1049, §95.573	Authorized Bandwidth & Emission Mask	Compliance
§2.1053, §95.579	Spurious Radiated Emissions	Compliance
§2.1055(d), §95.565	Frequency Stability	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017/12/22	2020/12/21
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2017/12/22	2020/12/21
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017/12/22	2020/12/21
COM-POWER	Pre-amplifier	PA-122	181919	2019/11/29	2020/11/28
Sonoma instrument	Pre-amplifier	310 N	186238	2020/4/20	2021/4/20
Agilent	MXG Vector Signal Generator	N5182B	MY53051503	2019/7/22	2020/7/21
COM-POWER	Dipole Antenna	AD-100	721027	NCR	NCR
A.H.System	Horn Antenna	SAS-200/571	135	2018/9/1	2021/8/31
R&S	EMI Test Receiver	ESR3	102455	2019/7/9	2020/7/8
Unknown	Notch Filter	SKU 5G3	ATR0205-04-13	2020/3/2	2021/3/1
UTiFLEX MICRO-COAX	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2019/11/12	2020/11/12
Ducommun Technologies	RF Cable	104PEA	218124002	2019/11/12	2020/11/12
Ducommun technologies	RF Cable	RG-214	1	2019/11/29	2020/11/28
Unknow	Signal Cable	RG-214	2	2019/11/29	2020/11/28
RF Conducted test					
HP Agilent	RF Communication test set	8920B	3325U00859	2020/1/15	2021/1/15
WEINSCHL	30dB Attenuator	53-30-43	PG633	2019/11/29	2020/11/28
HP	Microwave frequency counter	5343A	2232A00827	2019/8/29	2022/8/29
Fluke	Digital Multimeter	287	19000011	2019/7/25	2020/7/24
ESPEC	Temperature & Humidity Chamber	EL-10KA	9107726	2019/12/25	2020/12/24
Long Wei	DC Power Supply	TPR-6420D	398363	NCR	NCR
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2020/3/2	2021/3/1
Ducommun Technologies	RF Cable	RG-214	3	Each Time	

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

§2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

§2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ200612001-20A.

FCC §95.587(b)(1) – ANTENNA REQUIREMENT

Applicable Standard

According to FCC §95.587, (b) Antenna. The antenna of each FRS transmitter type must meet the following requirements.

(1) The antenna must be a non-removable integral part of the FRS transmitter type.

Antenna Connector Construction

The EUT has an integral antenna arrangement and the antenna gain is 1.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §2.1046 & §95.567 - RF OUTPUT POWER

Applicable Standard

Per FCC §2.1046, and §95.567, Each FRS transmitter type must be designed such that the effective radiated power (ERP) on channels 8 through 14 does not exceed 0.5 Watts and the ERP on channels 1 through 7 and 15 through 22 does not exceed 2.0 Watts.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the emissions were measured by the substitution.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Holland Yang on 2020-06-22.

Test Mode: Transmitting

Indicated		Table Angle Degree	Test Ant.		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBµV)		Height (m)	Polar (H/V)	Substituted level (dBm)	Cable Loss (dB)	Ant. Gain (dBd)			
462.6375MHz										
462.6375	90.8	19	2.0	H	16.0	1.32	0.0	14.68	33	18.32
462.6375	102.25	235	2.3	V	32.2	1.32	0.0	30.88	33	2.12
467.6375MHz										
467.6375	85.14	56	2.4	H	9.7	1.28	0.0	8.42	27	18.58
467.6375	96.04	100	2.0	V	24.4	1.28	0.0	23.12	27	3.88

Test Result: Compliance.

FCC §2.1047 & §95.575 - MODULATION CHARACTERISTIC

Applicable Standard

Per FCC §2.1047 and §95.575: Each FRS transmitter type must be designed such that the peak frequency deviation does not exceed 2.5 kHz, and the highest audio frequency contributing substantially to modulation must not exceed 3.125 kHz.

Test Procedure

Test Method: TIA/EIA-603-E

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Chen on 2020-06-22.


Please refer to the following tables and plots.

Test Mode: Transmitting

MODULATION LIMITING


Carrier Frequency: 462.6375MHz

Audio Frequency (Hz)	Instantaneous		Steady-state		FCC Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	1.749	0.053	1.786	0.058	2.500
400	2.053	0.073	2.058	0.071	2.500
500	2.087	0.099	2.015	0.104	2.500
600	2.204	0.111	2.256	0.114	2.500
700	1.771	0.125	1.702	0.125	2.500
800	1.801	0.142	1.848	0.135	2.500
900	2.031	0.161	2.036	0.154	2.500
1000	2.141	0.186	2.125	0.177	2.500
1200	2.137	0.223	2.128	0.215	2.500
1400	2.017	0.255	2.077	0.247	2.500
1600	1.938	0.296	1.975	0.283	2.500
1800	1.944	0.335	1.902	0.325	2.500
2000	2.004	0.365	2.029	0.338	2.500
2100	1.992	0.387	1.905	0.351	2.500
2200	2.026	0.404	2.008	0.389	2.500
2300	1.961	0.421	1.915	0.399	2.500
2400	2.007	0.438	2.032	0.452	2.500
2500	2.039	0.452	2.098	0.468	2.500
2600	1.988	0.466	1.968	0.457	2.500
2700	1.998	0.480	1.959	0.484	2.500
2800	1.975	0.494	1.928	0.495	2.500
2900	1.988	0.499	1.932	0.477	2.500
3000	1.931	0.502	1.918	0.469	2.500



Carrier Frequency: 462.6375 MHz


Audio Frequency (Hz)	Response Attenuation (dB)
300	-13.72
400	-9.17
500	-6.86
600	-5.13
700	-3.22
800	-2.23
900	-1.05
1000	0.00
1200	1.95
1400	3.44
1600	4.64
1800	5.77
2000	6.70
2100	7.20
2200	7.65
2300	7.99
2400	8.37
2500	8.66
2600	8.94
2700	9.16
2800	9.41
2900	9.55
3000	9.62



Audio frequency lows pass filter response

Carrier Frequency: 462.6375 MHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-14.2	0.0
4.0	-73.6	-12.5
5.0	-84.7	-22.2
6.0	-87.7	-30.1
7.0	-83.9	-36.8
8.0	-89.8	-42.6
9.0	-88.0	-47.7
10.0	-85.8	-52.3
15.0	-87.3	-69.9
20.0	-86.3	-82.4



FCC §2.1049 & §95.573 - AUTHORIZED BANDWIDTH AND EMISSION MASK

Applicable Standard

According to §95.573. Each FRS transmitter type must be designed such that the occupied bandwidth does not exceed 12.5 kHz.

Test Procedure

TIA-603-E, section 2.2.11

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Chen on 2020-06-22 to 2020-07-14.

Test Mode: Transmitting

Modulation	Channel Separation (kHz)	Frequency (MHz)	99% Occupied Bandwidth (kHz)	20 dB Emissions Bandwidth (kHz)
Analog	12.5	462.6375	5.288	10.256
Analog	12.5	467.6375	5.288	10.256

Emission Designator Per CFR 47 §2.201& §2.202&, $B_n = 2M + 2D$:

Emission Designator 11K0F3E In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation. $BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} \rightarrow 11K0$

F3E portion of the designator represents an FM voice transmission Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

Ref 45.5 dBm *Att 20 dB RBW 100 Hz Delta 1 [T1] -5.15 dB
 10.256410255 kHz VBW 1 kHz SWT 6 s


Offset 30.5 dB

OBW 5.288461538 kHz
 Marker 1 [T1] 3.72 dBm
 462.632451923 MHz
 Temp 1 [T1 OBW] 14.32 dBm
 462.634935897 MHz
 Temp 2 [T1 OBW] 9.68 dBm
 462.640224359 MHz

D1 31.1 dBm
 D2 5.1 dBm


Center 462.6375 MHz 5 kHz/ Span 50 kHz

Emission Mask, 462.6375 MHz




Page 19 of 24

OBW, 467.6375 MHz



Date: 14.JUL.2020 00:29:29

Emission Mask, 467.6375 MHz



Date: 3.JUL.2020 20:55:21

FCC §2.1053 & §95.579- RADIATED SPURIOUS EMISSION

Applicable Standard

FCC §2.1053 and §95.579. Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

(a) *Attenuation requirements.* The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:

(1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.

(2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.

(3) $43 + 10 \log(P)$ dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

(b) *Measurement bandwidths.* The power of unwanted emissions in the frequency bands specified in paragraphs (a)(1) and (2) of this section is measured with a reference bandwidth of 300 Hz. The power of unwanted emissions in the frequency range specified in paragraph (a)(3) is measured with a reference bandwidth of at least 30 kHz.

(c) *Measurement conditions.* The requirements in this section apply to each FRS transmitter type both with and without the connection of permitted attachments, such as an external speaker, microphone and/or power cord.

Test Procedure

The transmitter was placed on a wooden turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg(\text{TXpwr in Watts}/0.001)$ -the absolute level

Spurious attenuation limit in dB = $43 + 10 \lg_{10}(\text{power out in Watts})$

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Holland Yang and Leven Gan on 2020-06-22.

Test Mode: Transmitting

Indicated		Table Angle Degree	Test Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	Receiver Reading (dBuV)		Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd/dBi)			
462.6375MHz										
925.275	45.01	315	1.7	H	-16.0	1.02	0.0	-17.02	-13	4.02
925.275	45.85	169	2.0	V	-13.0	1.02	0.0	-14.02	-13	1.02
1387.91	76.03	261	2.0	H	-32.1	1.60	7.90	-25.80	-13	12.80
1387.91	83.92	34	1.2	V	-24.5	1.60	7.90	-18.20	-13	5.20
1850.55	70.09	70	1.4	H	-33.0	1.30	9.40	-24.90	-13	11.90
1850.55	78.51	51	1.1	V	-24.8	1.30	9.40	-16.70	-13	3.70
2313.19	54.25	37	1.2	H	-51.0	1.30	10.00	-42.30	-13	29.30
2313.19	53.19	177	1.0	V	-52.0	1.30	10.00	-43.30	-13	30.30
2775.83	62.58	296	2.4	H	-41.4	1.80	10.50	-32.70	-13	19.70
2775.83	61.18	110	2.3	V	-42.4	1.80	10.50	-33.70	-13	20.70
3238.46	61.08	235	1.8	H	-39.6	1.60	11.50	-29.70	-13	16.70
3238.46	58.54	67	2.1	V	-42.3	1.60	11.50	-32.40	-13	19.40
3701.10	65.96	1	2.4	H	-36.1	1.60	11.90	-25.80	-13	12.80
3701.10	65.86	200	1.7	V	-35.6	1.60	11.90	-25.30	-13	12.30
4163.74	70.56	265	1.2	H	-31.4	1.50	11.80	-21.10	-13	8.10
4163.74	62.13	65	2.0	V	-39.0	1.50	11.80	-28.70	-13	15.70
4626.38	59.29	198	2.3	H	-41.6	1.60	12.00	-31.20	-13	18.20
4626.38	51.05	319	1.5	V	-48.7	1.60	12.00	-38.30	-13	25.30
467.6375 MHz										
935.275	31.57	227	1.3	H	-29.5	1.02	0.0	-30.52	-13	17.52
935.275	30.86	139	1.0	V	-28.0	1.02	0.0	-29.02	-13	16.02
1402.91	61.25	245	1.1	H	-46.9	1.60	7.90	-40.60	-13	27.60
1402.91	68.82	278	1.1	V	-39.6	1.60	7.90	-33.30	-13	20.30
1870.55	45.53	358	2.3	H	-57.6	1.30	9.40	-49.50	-13	36.50
1870.55	50.72	274	1.8	V	-52.6	1.30	9.40	-44.50	-13	31.50
2338.19	48.39	282	2.2	H	-56.9	1.30	10.00	-48.20	-13	35.20
2338.19	48.06	18	2.2	V	-57.1	1.30	10.00	-48.40	-13	35.40
2805.83	44.54	79	2.5	H	-59.4	1.80	10.50	-50.70	-13	37.70
2805.83	44.25	262	1.4	V	-59.4	1.80	10.50	-50.70	-13	37.70
3273.46	45.54	353	2.0	H	-55.4	1.50	11.70	-45.20	-13	32.20
3273.46	44.28	280	2.1	V	-56.6	1.50	11.70	-46.40	-13	33.40
3741.10	45.90	261	2.1	H	-56.2	1.60	11.90	-45.90	-13	32.90
3741.10	44.87	91	1.6	V	-56.6	1.60	11.90	-46.30	-13	33.30

Note 1: The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

Note 2: Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1055 (d) & §95.565 - FREQUENCY STABILITY

Applicable Standard

According to FCC §2.1055(a) (1), the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$, and according to FCC 2.1055(d) (2), the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point which is specified by the manufacturer.

According to FCC §95.565, Each FRS transmitter type must be designed such that the carrier frequencies remain within ± 2.5 parts-per-million of the channel center frequencies specified in §95.563 during normal operating conditions.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a Frequency Counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Frequency Counter.

Frequency Stability vs. Voltage (item 1 or item 2 will be chosen according to different condition) :

☐1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

☒2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

The output frequency was recorded for each voltage.

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Chen on 2020-06-22.

Test Mode: Transmitting

FRS

Reference Frequency: 462.6375 MHz, Limit: ± 2.5 ppm			
Environment Temperature (°C)	Power Supplied (V _{DC})	Measurement Frequency (MHz)	Frequency Error (ppm)
Frequency Stability Ver. Temperature			
50	3.6	462.637456	-0.10
40	3.6	462.637461	-0.08
30	3.6	462.637463	-0.08
20	3.6	462.637466	-0.07
10	3.6	462.637469	-0.07
0	3.6	462.637476	-0.05
-10	3.6	462.637459	-0.09
-20	3.6	462.637471	-0.06
-30	3.6	462.637458	-0.09
Frequency Stability Ver. Input Voltage			
20	3.4	462.637453	-0.10
20	4.2	462.637461	-0.08

Reference Frequency: 467.6375 MHz, Limit: ± 2.5 ppm			
Environment Temperature (°C)	Power Supplied (V _{DC})	Measurement Frequency (MHz)	Frequency Error (ppm)
Frequency Stability Ver. Temperature			
50	3.6	467.637462	-0.08
40	3.6	467.637453	-0.10
30	3.6	467.637466	-0.07
20	3.6	467.637467	-0.07
10	3.6	467.637469	-0.07
0	3.6	467.637474	-0.06
-10	3.6	467.637471	-0.06
-20	3.6	463.637458	-0.09
-30	3.6	467.637460	-0.09
Frequency Stability Ver. Input Voltage			
20	3.4	467.637473	-0.06
20	4.2	467.637477	-0.05

***** END OF REPORT *****