



TEST REPORT

Report No. : **CHTEW21110222** **Report Verification:** 

Project No. : **SHT2111022701EW**

FCC ID : **2ARTX-HERO600**

Applicant's name : **LAVA International Limited**

Address : **A-56, Sector 64, Noida 201301**

Test item description : **Mobile phone**

Trade Mark : **LAVA**

Model/Type reference : **HERO 600+**

Listed Model(s) : **-**

Standard : **FCC CFR Title 47 Part 15 Subpart C Section 15.247**

Date of receipt of test sample : **Nov.18, 2021**

Date of testing : **Nov.18, 2021- Nov.25, 2021**

Date of issue : **Nov.26, 2021**

Result : **PASS**

Compiled by
(position+printed name+signature) .. : **File administrators Fanghui Zhu**

Fanghui Zhu

Supervised by
(position+printed name+signature) .. : **Project Engineer Cheng Xiao**

Cheng Xiao

Approved by
(Position+Printed name+Signature): **RF Manager Hans Hu**

Hans Hu

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address : **1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road,
Tianliao, Gongming, Shenzhen, China**

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. The test report merely correspond to the test sample.

Contents

1.	TEST STANDARDS AND REPORT VERSION	3
1.1.	Test Standards	3
1.2.	Report version	3
2.	TEST DESCRIPTION	4
3.	SUMMARY	5
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
4.	TEST CONFIGURATION	7
4.1.	Test frequency list	7
4.2.	Descriptions of Test mode	7
4.3.	Test mode	7
4.4.	Support unit used in test configuration and system	8
4.5.	Testing environmental condition	8
4.6.	Measurement uncertainty	8
4.7.	Equipment Used during the Test	9
5.	TEST CONDITIONS AND RESULTS	11
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	Peak Output Power	15
5.4.	20 dB Bandwidth	16
5.5.	99% Occupied Bandwidth	17
5.6.	Carrier Frequencies Separation	18
5.7.	Hopping Channel Number	19
5.8.	Dwell Time	20
5.9.	Duty Cycle Correction Factor (DCCF)	21
5.10.	Pseudorandom Frequency Hopping Sequence	22
5.11.	Conducted Band edge and Spurious Emission	23
5.12.	Radiated Band edge Emission	25
5.13.	Radiated Spurious Emission	27
6.	TEST SETUP PHOTOS	32
7.	EXTERANAL AND INTERNAL PHOTOS	33
8.	APPENDIX REPORT	33

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- [FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2021-11-26	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result
5.1	Antenna Requirement	15.203/15.247 (c)	PASS
5.2	AC Conducted Emission	15.207	PASS
5.3	Peak Output Power	15.247 (b)(1)	PASS
5.4	20 dB Bandwidth	15.247 (a)(1)	PASS
5.5	99% Occupied Bandwidth	-	PASS ^{*1}
5.6	Carrier Frequency Separation	15.247 (a)(1)	PASS
5.7	Hopping Channel Number	15.247 (a)(1)	PASS
5.8	Dwell Time	15.247 (a)(1)	PASS
5.9	Duty Cycle Correction Factor	-	PASS ^{*1}
5.10	Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	PASS
5.11	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS
5.12	Radiated Band Edge Emission	15.205/15.209	PASS
5.13	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS

Note:

- The measurement uncertainty is not included in the test result.
- ^{*1}: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	LAVA International Limited
Address:	A-56, Sector 64, Noida 201301
Manufacturer:	LAVA INTERNATIONAL LTD
Address:	A-154 D, Sector-63, Noida, Gautam Buddha Nagar, Uttar Pradesh, 201301
Factory:	LAVA INTERNATIONAL LTD
Address:	A-154 D, Sector-63, Noida, Gautam Buddha Nagar, Uttar Pradesh, 201301

3.2. Product Description

Name of EUT:	Mobile phone
Trade Mark:	LAVA
Model No.:	HERO 600+
Listed Model(s):	-
Power supply:	DC 3.7V for battery
Hardware version:	IL1801 PCB_V2.2 4
Software version:	Bmobile_Hero600P

3.3. Radio Specification Description

Bluetooth version:	V3.0
Support function ^{*2} :	EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Monopole Wireway Antenna
Antenna gain:	0.90 dBi

Note:

*2: only show the RF function associated with this report.

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Connect information:	Phone: 86-755-26715499 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC	762235

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Channel	Frequency (MHz)
00	2402
01	2403
⋮	⋮
39	2441
⋮	⋮
77	2479
78	2480

4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates and recorded the RF output power in the clause 5.3

Note:

- 1) The manufacturer declare that the maximum power value of the product is set as a default value in the enter test mode software.
- 2) All the test data for each data rate were verified, found 8DPSK Modulation which is worse case mode

4.3. Test mode

For RF test items:			
The engineering test program was provided and enabled to make EUT continuous transmitting.			
Test Item	Modulation / Data Rate		
	GFSK 1Mbps	$\pi/4$ DQPSK 2Mbps	8DPSK 3Mbps
Conducted test item	✓	✓	✓
Radiated test item	-	-	✓
Remark:			
– For radiated test item, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests. – The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.			

4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?					
✓ No					
Item	Equipement	Trade Name	Model No.	FCC ID	Power cord
1					
2					

4.5. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.6. Measurement uncertainty

Test Item	Measurement Uncertainty
AC Conducted Emission (150kHz~30MHz)	3.00 dB
Radiated Emission (30MHz~1000MHz)	4.36 dB
Radiated Emissions (1GHz~25GHz)	5.10 dB
Peak Output Power	0.77dB
Power Spectral Density	0.77dB
Conducted Spurious Emission	0.77dB
6dB Bandwidth	70Hz for <1GHz 130Hz for >1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.7. Equipment Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2021/9/14	2022/9/13
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2021/9/17	2022/9/16
●	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2021/9/13	2022/9/12
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLEX 142	EF-NM-BNCM-2M	2021/9/17	2022/9/16
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2022/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2021/9/14	2022/9/13
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2021/04/06	2022/04/05
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0123	VULB9163	538	2021/04/06	2022/04/05
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2021/11/5	2022/11/4
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2021/02/26	2022/02/25
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX104	501184/4	2021/02/26	2022/02/25
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2022/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2021/9/13	2022/9/12
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2020/04/01	2023/03/31
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2020/4/27	2023/4/27
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2021/11/5	2022/11/4
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2021/03/05	2022/03/04
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2021/02/26	2022/02/25
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2021/02/26	2022/02/25
●	RF Connection Cable	HUBER+SUHNER	HTWE0119-05	6m 3GHz RG Serisa	N/A	2021/02/26	2022/02/25
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2021/02/26	2022/02/25
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2021/02/26	2022/02/25
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	HTWE0242	FSV40	100048	2021/9/13	2022/9/12
●	Signal & Spectrum Analyzer	R&S	HTWE0262	FSW26	103440	2021/9/13	2022/9/12
●	Spectrum Analyzer	Agilent	HTWE0286	N9020A	MY50510187	2021/9/13	2022/9/12
●	Radio communication tester	R&S	HTWE0287	CMW500	137688-Lv	2021/9/13	2022/9/12
●	Test software	Tonscend	N/A	JS1120	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

The antenna type is a Monopole Wireway antenna, the directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

Test Line:

L

**MEASUREMENT RESULT: "GM2111225008_fin"**

11/22/2021 9:25AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.172500	48.60	10.1	65	16.2	QP	L1	GND
0.456000	39.20	10.1	57	17.6	QP	L1	GND
1.230000	29.50	10.1	56	26.5	QP	L1	GND
2.157000	28.10	10.1	56	27.9	QP	L1	GND
5.140500	24.70	10.3	60	35.3	QP	L1	GND
16.602000	27.70	10.6	60	32.3	QP	L1	GND


MEASUREMENT RESULT: "GM2111225008_fin2"

11/22/2021 9:25AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.177000	22.10	10.1	55	32.5	AV	L1	GND
0.451500	28.00	10.1	47	18.8	AV	L1	GND
1.234500	18.30	10.1	46	27.7	AV	L1	GND
2.346000	17.50	10.1	46	28.5	AV	L1	GND
5.293500	14.50	10.3	50	35.5	AV	L1	GND
19.131000	19.70	10.7	50	30.3	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM2111225009_fin"**

11/22/2021 9:27AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	48.50	10.1	66	17.5	QP	N	GND
0.451500	35.90	10.1	57	20.9	QP	N	GND
1.441500	26.30	10.1	56	29.7	QP	N	GND
2.814000	24.10	10.1	56	31.9	QP	N	GND
5.766000	21.30	10.3	60	38.7	QP	N	GND
16.422000	24.80	10.6	60	35.2	QP	N	GND

MEASUREMENT RESULT: "GM2111225009_fin2"

11/22/2021 9:27AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.172500	32.00	10.1	55	22.8	AV	N	GND
0.438000	27.90	10.1	47	19.2	AV	N	GND
1.243500	17.30	10.1	46	28.7	AV	N	GND
3.273000	10.60	10.2	46	35.4	AV	N	GND
5.523000	14.10	10.3	50	35.9	AV	N	GND
19.860000	17.40	10.7	50	32.6	AV	N	GND


5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1):

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the pathloss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ the 20 dB bandwidth of the emission being measured, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data


Please refer to appendix A on the appendix report

5.4. 20 dB Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ 1% of the 20 dB bandwidth, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data


Please refer to appendix B on the appendix report

5.5. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = channel center frequency
Span $\geq 1.5 \times \text{OBW}$
RBW = 1%~5%OBW
VBW $\geq 3 \times \text{RBW}$
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data

Please refer to appendix C on the appendix report


5.6. Carrier Frequencies Separation

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels
RBW $\geq$ 1% of the span, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.3

TEST RESULTS

☒ Passed ☐ Not Applicable

TEST Data

Please refer to appendix D on the appendix report


5.7. Hopping Channel Number

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW $\geq$ 1% of the span, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.3

TEST RESULTS

☒ Passed ☐ Not Applicable

TEST Data


Please refer to appendix E on the appendix report

5.8. Dwell Time

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW $\geq$ RBW
Sweep = as necessary to capture the entire dwell time per hopping channel,
Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.3

TEST RESULTS

☒ Passed ☐ Not Applicable

TEST Data


Please refer to appendix F on the appendix report

5.9. Duty Cycle Correction Factor (DCCF)

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW $\geq$ RBW
Sweep = as necessary to capture the entire dwell time per hopping channel,
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE:

Please refer to the clause 4.3

TEST Data

Please refer to appendix G on the appendix report

5.10. Pseudorandom Frequency Hopping Sequence


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo-randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally on the average by each transmitter.


The system receiver has input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shifts frequencies in synchronization with the transmitted signals.

5.11. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data

Please refer to appendix H on the appendix report


5.12. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement: use duty cycle correction factor method (DCCF)
 Averager level = Peak level + DCCF

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level- Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

Test channel:		CH00			Polarity			Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	40.48	27.96	5.43	37.56	36.31	74.00	-37.69	Peak
2	2390.03	54.51	27.72	5.53	37.45	50.31	74.00	-23.69	Peak

Test channel:		CH00			Polarity			Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	40.24	27.96	5.43	37.56	36.07	74.00	-37.93	Peak
2	2390.03	51.19	27.72	5.53	37.45	46.99	74.00	-27.01	Peak

Test channel:		CH78		Polarity			Horizontal	
Frequency(MHz) Reading(dBuV/m Antenna(dB Cable(dB Preamp(dB Level(dBuV/m Limit(dBuV/m Over limit Remark								
2483.50	56.55	27.43	5.64	37.26	52.36	74.00	-21.64	Peak
2483.72	69.30	27.43	5.64	37.26	65.11	74.00	-8.89	Peak
2483.72	38.43	27.43	5.64	37.26	34.24	54.00	-19.76	Average
2500.00	41.42	27.40	5.66	37.26	37.22	74.00	-36.78	Peak

Test channel:		CH78			Polarity			Vertical	
Mark	Frequency(MHz)	Reading(dBuV/m)	Antenna(dB)	Cable(dB)	Preamp(dB)	Level(dBuV/m)	Limit(dBuV/m)	Over limit	Remark
1	2483.5	68.99	27.43	5.64	37.26	64.8	74	-9.2	Peak
2	2483.5	33.93	27.43	5.64	37.26	29.74	54	-24.26	Average
3	2500	44.92	27.4	5.66	37.26	40.72	74	-33.28	Peak

5.13. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


➤ 9 kHz ~ 30 MHz



➤ 30 MHz ~ 1 GHz



➤ Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement: use duty cycle correction factor method (DCCF)

Averager level = Peak level + DCCF

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level– Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

TEST DATA FOR 9 kHz ~ 30 MHz


The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

TEST DATA FOR 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH39 which it was worst case, so only show the worst case's data on this report.

Polarization:

Horizontal


**MEASUREMENT RESULT: "GM2111236037_red"**

11/23/2021 12:00PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
51.340000	18.70	-8.8	40.0	21.3	QP	100.0	147.00	HORIZONTAL
59.100000	18.60	-9.7	40.0	21.4	QP	100.0	131.00	HORIZONTAL
103.720000	17.50	-10.3	43.5	26.0	QP	100.0	63.00	HORIZONTAL
280.260000	22.40	-7.7	46.0	23.6	QP	100.0	119.00	HORIZONTAL
524.700000	26.90	-1.0	46.0	19.1	QP	100.0	193.00	HORIZONTAL
951.500000	35.10	7.9	46.0	10.9	QP	100.0	131.00	HORIZONTAL

Polarization:

Vertical

**MEASUREMENT RESULT: "GM2111236036_red"**

11/23/2021 11:58AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
31.940000	21.00	-12.4	40.0	19.0	QP	100.0	50.00	VERTICAL
57.160000	20.40	-9.4	40.0	19.6	QP	100.0	214.00	VERTICAL
101.780000	18.10	-10.3	43.5	25.4	QP	100.0	151.00	VERTICAL
291.900000	21.40	-7.2	46.0	24.6	QP	100.0	127.00	VERTICAL
549.920000	26.90	-0.4	46.0	19.1	QP	100.0	163.00	VERTICAL
918.520000	36.00	7.7	46.0	10.0	QP	100.0	269.00	VERTICAL

TEST DATA FOR 1 GHz ~ 25 GHz

Test channel		CH00			Polarity		Horizontal		
Mark	Frequency(MHz)	Reading(dBuV/m)	Antenna(dB)	Cable(dB)	Preamp(dB)	Level(dBuV/m)	Limit(dBuV/m)	Over limit	Remark
1	1220	45.92	25.72	3.9	36.62	38.92	74	-35.08	Peak
2	2212.88	38.37	28.17	5.32	37.41	34.45	74	-39.55	Peak
3	3599.9	47.41	29.4	6.91	36.93	46.79	74	-27.21	Peak
4	9609.3	40.41	39.24	11.93	37.02	54.56	74	-19.44	Peak
5	9609.3	23.69	39.24	11.93	37.02	37.84	54	-16.16	Average

Test channel		CH00			Polarity		Vertical		
Mark	Frequency(MHz)	Reading(dBuV/m)	Antenna(dB)	Cable(dB)	Preamp(dB)	Level(dBuV/m)	Limit(dBuV/m)	Over limit	Remark
1	1220	48.37	25.72	3.9	36.62	41.37	74	-32.63	Peak
2	2242.25	38.31	28.12	5.36	37.42	34.37	74	-39.63	Peak
3	3599.99	53.98	29.4	6.91	36.93	53.36	74	-20.64	Peak
4	9609.3	42.71	39.24	11.93	37.02	56.86	74	-17.14	Peak
5	9609.3	25.99	39.24	11.93	37.02	40.14	54	-13.86	Average

Test channel		CH39			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1220.00	45.92	25.72	3.90	36.62	38.92	74.00	-35.08	Peak
2	2212.88	38.37	28.17	5.32	37.41	34.45	74.00	-39.55	Peak
3	3657.79	44.90	29.40	6.97	37.02	44.25	74.00	-29.75	Peak
4	9763.82	38.99	39.60	11.61	36.27	53.93	74.00	-20.07	Peak


Test channel		CH39			Polarity		Vertical		
Mark	Frequency(MHz)	Reading(dBuV/m)	Antenna(dB)	Cable(dB)	Preamp(dB)	Level(dBuV/m)	Limit(dBuV/m)	Over limit	Remark
1	1220	48.37	25.72	3.9	36.62	41.37	74	-32.63	Peak
2	2242.25	38.31	28.12	5.36	37.42	34.37	74	-39.63	Peak
3	3657.79	51.03	29.4	6.97	37.02	50.38	74	-23.62	Peak
4	9763.82	40.58	39.6	11.61	36.27	55.52	74	-18.48	Peak
5	9763.82	24.65	39.6	11.61	36.27	39.59	54	-14.41	Average

Test channel		CH78			Polarity		Horizontal		
Mark	Frequency(MHz)	Reading(dBuV/m)	Antenna(dB)	Cable(dB)	Preamp(dB)	Level(dBuV/m)	Limit(dBuV/m)	Over limit	Remark
1	1220	45.92	25.72	3.9	36.62	38.92	74	-35.08	Peak
2	2212.88	38.37	28.17	5.32	37.41	34.45	74	-39.55	Peak
3	3716.61	42.31	29.43	7.03	37.09	41.68	74	-32.32	Peak
4	9920.83	40.35	39.54	12	37.2	54.69	74	-19.31	Peak
5	9920.83	23.82	39.54	12	37.2	38.16	54	-15.84	Average

Test channel		CH78			Polarity		Vertical		
Mark	Frequency(MHz)	Reading(dBuV/m)	Antenna(dB)	Cable(dB)	Preamp(dB)	Level(dBuV/m)	Limit(dBuV/m)	Over limit	Remark
1	1220	48.37	25.72	3.9	36.62	41.37	74	-32.63	Peak
2	2242.25	38.31	28.12	5.36	37.42	34.37	74	-39.63	Peak
3	4960.04	41.81	31.58	8.77	35.21	46.95	74	-27.05	Peak
4	9920.83	41.97	39.54	12	37.2	56.31	74	-17.69	Peak
5	9920.83	25.44	39.54	12	37.2	39.78	54	-14.22	Average

6. TEST SETUP PHOTOS

Radiated Emission



AC Conducted Emission



7. EXTERANAL AND INTERNAL PHOTOS

Reference to the test report No. : CHTEW21110221

8. APPENDIX REPORT

APPENDIX REPORT

Project No.	SHT2111022701EW	Radio Specification	Bluetooth EDR
Test sample No.	YPHT21110227002	Model No.	HERO 600+
Start test date	2021-11-24	Finish date	2021-11-24
Temperature	23.4℃	Humidity	28%
Test Engineer	Xiaoqin Li	Auditor	Xiaodong Zhu

Appendix clause	Test item	Result
A	Peak Output Power	PASS
B	20 dB Bandwidth	PASS
C	99% Occupied Bandwidth	PASS
D	Carrier Frequencies Separation	PASS
E	Hopping Channel Number	PASS
F	Dwell Time	PASS
G	Duty Cycle Correction Factor (DCCF)	PASS
H	Band edge and Spurious Emissions(coducted)	PASS

Appendix A: Peak Output Power

Modulation type	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
GFSK	00	5.03	4.98	≤ 30.00	Pass
	39	4.05	4.02		
	78	3.07	3.04		
$\pi/4$ DQPSK	00	5.02	4..99	≤ 21.00	Pass
	39	3.85	3.79		
	78	2.55	2.50		
8DPSK	00	5.33	5.31	≤ 21.00	Pass
	39	4.20	4.16		
	78	2.86	2.87		

Modulation Type:


GFSK

CH00



Date: 24 NOV 2021 09:53:05

CH39



Date: 24 NOV 2021 10:00:45

CH78




Date: 24 NOV 2021 10:04:37

Modulation Type:


 $\pi/4$ DQPSK

CH00




Date: 24 NOV 2021 10:06:24

CH39



Date: 24 NOV 2021 10:20:11

CH78




Date: 24 NOV 2021 10:29:47

Modulation Type:


8DPSK

CH00




Date: 24 NOV 2021 10:53:00

CH39



Date: 24 NOV 2021 10:26:00

CH78



Date: 24 NOV 2021 10:41:19


Appendix B : 20 dB Bandwidth

Modulation type	Channel	20 dB Bandwidth (kHz)	Limit (kHz)	Result
GFSK	00	980.00	-	Pass
	39	932.50		
	78	927.50		
$\pi/4$ DQPSK	00	1307.50	-	Pass
	39	1302.50		
	78	1287.50		
8DPSK	00	1300.00	-	Pass
	39	1295.00		
	78	1287.50		

Modulation Type:


GFSK

CH00




Date: 24 NOV 2021 09:41:45

CH39



Date: 24 NOV 2021 09:54:38

CH78




Date: 24 NOV 2021 10:02:22

Modulation Type:


 $\pi/4$ DQPSK

CH00




Date: 24 NOV 2021 10:06:08

CH39



Date: 24 NOV 2021 10:09:55

CH78




Date: 24 NOV 2021 10:29:31

Modulation Type:


8DPSK

CH00




Date: 24 NOV 2021 10:32:44

CH39



Date: 24 NOV 2021 10:35:44




CH78







Date: 24 NOV 2021 10:41:03

Appendix C: 99% Occupied Bandwidth

Modulation type	Channel	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
GFSK	00	0.95	-	Pass
	39	0.93		
	78	0.92		
$\pi/4$ DQPSK	00	1.19	-	Pass
	39	1.18		
	78	1.17		
8DPSK	00	1.19	-	Pass
	39	1.18		
	78	1.17		

Modulation Type:	GFSK
CH00	 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 63.1 μs VBW 100 kHz Mode Auto FFT Count 300/300 1Pk View M1[1] 2.98 dBm 2.40216480 GHz 946.553446554 kHz CF 2.402 GHz 1001 pts Span 2.5 MHz Date: 24 NOV 2021 09:44:09
CH39	 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 63.1 μs VBW 100 kHz Mode Auto FFT Count 300/300 1Pk View M1[1] 2.75 dBm 2.441116480 GHz 934.065934066 kHz CF 2.441 GHz 1001 pts Span 2.5 MHz Date: 24 NOV 2021 09:54:16
CH78	 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 63.1 μs VBW 100 kHz Mode Auto FFT Count 300/300 1Pk View M1[1] 1.71 dBm 2.48016480 GHz 924.075924076 kHz CF 2.48 GHz 1001 pts Span 2.5 MHz Date: 24 NOV 2021 10:02:30

Modulation Type:	$\pi/4$ DQPSK
CH00	 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 63.1 μs VBW 100 kHz Mode Auto FFT Count 500/500 1Pk View M1[1] 1.11 dBm 2.40216480 GHz 1.100011189 MHz CF 2.402 GHz 1001 pts Span 2.5 MHz Date: 24 NOV 2021 10:06:15
CH39	 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 63.1 μs VBW 100 kHz Mode Auto FFT Count 500/500 1Pk View M1[1] -0.10 dBm 2.44116730 GHz 1.103016104 MHz CF 2.441 GHz 1001 pts Span 2.5 MHz Date: 24 NOV 2021 10:20:02
CH78	 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 63.1 μs VBW 100 kHz Mode Auto FFT Count 500/500 1Pk View M1[1] -1.47 dBm 2.48015980 GHz 1.173026174 MHz CF 2.480 GHz 1001 pts Span 2.5 MHz Date: 24 NOV 2021 10:29:39

Modulation Type:		8DPSK
CH00	 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 63.1 μs VBW 100 kHz Mode Auto FFT Count 500/500 1Pk View M1[1] 1.64 dBm 2.40215980 GHz 1.106313686 MHz CF 2.402 GHz 1001 pts Span 2.5 MHz Date: 24 NOV 2021 10:32:51	
CH39	 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 63.1 μs VBW 100 kHz Mode Auto FFT Count 500/500 1Pk View M1[1] 0.56 dBm 2.44115980 GHz 1.170821179 MHz CF 2.441 GHz 1001 pts Span 2.5 MHz Date: 24 NOV 2021 10:35:52	
CH78	 Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWI 63.1 μs VBW 100 kHz Mode Auto FFT Count 500/500 1Pk View M1[1] -0.75 dBm 2.48015980 GHz 1.173826174 MHz CF 2.48 GHz 1001 pts Span 2.5 MHz Date: 24 NOV 2021 10:41:10	

Appendix D: Carrier Frequencies Separation

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (kHz) *	Result
GFSK	39	1.00	≥980.00	Pass
π/4DQPSK	39	1.00	≥871.67	Pass
8DPSK	39	1.00	≥866.67	Pass



Note:

*: GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the appendix B.


π/4DQPSK limit = 2/3 * The maximum 20 dB Bandwidth for π/4DQPSK modulation on the appendix B.

8DPSK limit = 2/3 * The maximum 20 dB Bandwidth for 8DPSK modulation on the appendix B

GFSK

 $\pi/4$ DQPSK



8DPSK




Appendix E: Hopping Channel Number

Modulation type	Channel number	Limit	Result
GFSK	79	≥15.00	Pass
π/4DQPSK	79		
8DPSK	79		

GFSK




 $\pi/4$ DQPSK

8DPSK




Appendix F: Dwell Time


Modulation type	Packet	Burst Width [ms]	Total Hops[hop*ch]	Dwell time (Second)	Limit (Second)	Result
GFSK	DH1	0.37	316	0.12	≤ 0.40	Pass
	DH3	1.63	159	0.26		
	DH5	2.87	113	0.33		
$\pi/4$ DQPSK	2DH1	0.38	317	0.12	≤ 0.40	Pass
	2DH3	1.63	158	0.26		
	2DH5	2.88	114	0.33		
8DPSK	3DH1	0.38	313	0.12	≤ 0.40	Pass
	3DH3	1.63	161	0.26		
	3DH5	2.88	113	0.33		

Modulation Type:	GFSK
DH1 Burst width	 The spectrum plot shows a signal at 2.441 GHz. The y-axis represents power in dBm, ranging from -10 to 10. The x-axis represents time in ms, ranging from 0 to 1.0. A red line indicates a trigger level at -1.100 dBm. The plot shows a burst of signal at the start, followed by a period of low power. The signal is identified as M1[1] and D1[1]. Ref Level: 20.00 dBm Att: 30 dB RBW: 1 MHz SWT: 10 ms VBW: 3 MHz SGL TRG: VID 1AP Clw CF 2.441 GHz 8001 pts 1.0 ms/ Date: 24 NOV 2021 10:51:11
DH1 Burst number	 The spectrum plot shows a signal at 2.441 GHz. The y-axis represents power in dBm, ranging from -10 to 10. The x-axis represents time in s, ranging from 0 to 3.16. A red line indicates a trigger level at -1.100 dBm. The plot shows a burst of signal at the start, followed by a period of low power. The signal is identified as M1[1] and D1[1]. Ref Level: 20.00 dBm Att: 30 dB RBW: 500 kHz SWT: 31.6 s VBW: 3 MHz SGL TRG: VID 1AP Clw CF 2.441 GHz 30001 pts 3.16 s/ Date: 24 NOV 2021 10:51:44
DH3 Burst width	 The spectrum plot shows a signal at 2.441 GHz. The y-axis represents power in dBm, ranging from -10 to 10. The x-axis represents time in ms, ranging from 0 to 1.0. A red line indicates a trigger level at -1.200 dBm. The plot shows a burst of signal at the start, followed by a period of low power. The signal is identified as M1[1] and D1[1]. Ref Level: 20.00 dBm Att: 30 dB RBW: 1 MHz SWT: 10 ms VBW: 3 MHz SGL TRG: VID 1AP Clw CF 2.441 GHz 8001 pts 1.0 ms/ Date: 24 NOV 2021 10:53:20


DH3
Burst number






DH5
Burst width




DH5
Burst number




Modulation Type:	$\pi/4$ DQPSK
2DH1 Burst width	 The spectrum plot shows a signal at 2.441 GHz with a bandwidth of 8001 pts. The y-axis represents power in dBm, ranging from -10 to 10. The x-axis represents time in ms, ranging from 0 to 1.0. The plot shows a burst of signal at approximately 0.5 ms. The signal level is around -15.17 dBm. The plot also shows a reference level of 20.00 dBm and a noise floor of -10.00 dBm. The plot is titled 'Spectrum' and includes parameters: Ref Level 20.00 dBm, Att 30 dB, RBW 1 MHz, SWT 10 ms, VBW 3 MHz, and SGL TRG:VID. The plot is dated 24 NOV 2021 10:58:11.
2DH1 Burst number	 The spectrum plot shows a signal at 2.441 GHz with a bandwidth of 30001 pts. The y-axis represents power in dBm, ranging from -10 to 10. The x-axis represents time in s, ranging from 0 to 3.16. The plot shows a burst of signal at approximately 0.5 s. The signal level is around -15.17 dBm. The plot also shows a reference level of 20.00 dBm and a noise floor of -10.00 dBm. The plot is titled 'Spectrum' and includes parameters: Ref Level 20.00 dBm, Att 30 dB, RBW 500 kHz, SWT 31.6 s, VBW 3 MHz, and SGL TRG:VID. The plot is dated 24 NOV 2021 10:58:44.
2DH3 Burst width	 The spectrum plot shows a signal at 2.441 GHz with a bandwidth of 8001 pts. The y-axis represents power in dBm, ranging from -10 to 10. The x-axis represents time in ms, ranging from 0 to 1.0. The plot shows a burst of signal at approximately 0.5 ms. The signal level is around -20.43 dBm. The plot also shows a reference level of 20.00 dBm and a noise floor of -10.00 dBm. The plot is titled 'Spectrum' and includes parameters: Ref Level 20.00 dBm, Att 30 dB, RBW 1 MHz, SWT 10 ms, VBW 3 MHz, and SGL TRG:VID. The plot is dated 24 NOV 2021 10:59:16.

2DH3
Burst number




Date: 24 NOV 2021 10:59:49

2DH5
Burst width






Date: 24 NOV 2021 11:00:19


2DH5
Burst number



Date: 24 NOV 2021 11:00:53


Modulation Type:	8DPSK
3DH1 Burst width	 The spectrum plot shows a signal at 2.441 GHz with a bandwidth of 8001 pts. The y-axis represents power in dBm, ranging from -40 to 10. The x-axis represents time in ms, ranging from 0 to 1.0. The plot shows a burst of signal at the beginning, followed by a period of low power. The signal is labeled with M1[1] and D1[1]. The peak power is -4.72 dBm, the average power is -1.25 dBm, and the signal-to-noise ratio is 3.24 dB. The signal-to-noise ratio is also 377.50 dB. Date: 24 NOV 2021 11:04:06
3DH1 Burst number	 The spectrum plot shows a signal at 2.441 GHz with a bandwidth of 30001 pts. The y-axis represents power in dBm, ranging from -40 to 10. The x-axis represents time in s, ranging from 0 to 3.16. The plot shows a burst of signal at the beginning, followed by a period of low power. The signal is labeled with M1[1] and D1[1]. The peak power is -4.72 dBm, the average power is -1.25 dBm, and the signal-to-noise ratio is 3.24 dB. The signal-to-noise ratio is also 377.50 dB. Date: 24 NOV 2021 11:04:39
3DH3 Burst width	 The spectrum plot shows a signal at 2.441 GHz with a bandwidth of 8001 pts. The y-axis represents power in dBm, ranging from -40 to 10. The x-axis represents time in ms, ranging from 0 to 1.0. The plot shows a burst of signal at the beginning, followed by a period of low power. The signal is labeled with M1[1] and D1[1]. The peak power is -0.44 dBm, the average power is -1.25 dBm, and the signal-to-noise ratio is 8.02 dB. The signal-to-noise ratio is also 1.62750 ms. Date: 24 NOV 2021 11:05:11

3DH3
Burst number




Date: 24 NOV 2021 11:05:44

3DH5
Burst width



Date: 24 NOV 2021 11:06:37

3DH5
Burst number





Date: 24 NOV 2021 11:07:10

Appendix G: Duty Cycle Correction Factor (DCCF)**DCCF Calculate Formula**

$$\text{DCCF} = 20 * \text{Log}(\text{duty cycle}) = 20 * \text{Log}(T_{\text{on time}} / T_{\text{period}})$$



Modulation type	Test Frequency (MHz)	T _{on time} for single burst [ms]	T _{period} [ms]	Burst Quantity	DCCF [dB]
GFSK	2441	2.86	100	1	-30.87
$\pi/4$ DQPSK	2441	2.86	100	1	-30.87
8DPSK	2441	2.86	100	1	-30.87

GFSK



Ton time for single burst



Burst Quantity

 $\pi/4$ DQPSK

Ton time for single burst

Burst Quantity


8DPSK



Ton time for single burst

Burst Quantity


CH78
Hopping mode



Date: 24 NOV 2021 10:56:17


Test Item:	Band edge	Modulation type:	$\pi/4$ DQPSK
CH00 No hopping mode	<		

CH78
Hopping mode






Date: 24 NOV 2021 11:02:22


CH78
Hoppig mode




Date: 24 NOV 2021 11:08:37

Test Item:	Spurious Emission	Modulation type:	GFSK
CH00 Reference level	 Date: 24 NOV 2021 09:51:56		
CH00 30MHz~1000MHz	 Date: 24 NOV 2021 09:52:11		
CH00 1GHz~26GHz	 Date: 24 NOV 2021 09:52:26		


CH39
Reference level




CH39
30MHz~1000MHz



CH39
1GHz~26GHz




CH78
Reference level




Date: 24 NOV 2021 10:03:12

CH78
30MHz~1000MHz






Date: 24 NOV 2021 10:03:27


CH78
1GHz~26GHz




Date: 24 NOV 2021 10:03:42

Test Item:	Spurious Emission	Modulation type:	$\pi/4$ DQPSK
CH00 Reference level	 Date: 24 NOV 2021 10:08:53		
CH00 30MHz~1000MHz	 Date: 24 NOV 2021 10:09:08		
CH00 1GHz~26GHz	 Date: 24 NOV 2021 10:09:23		


CH39
Reference level




CH39
30MHz~1000MHz




CH39
1GHz~26GHz




CH78
Reference level






CH78
30MHz~1000MHz




CH78
1GHz~26GHz




Test Item:	Spurious Emission	Modulation type:	8DPSK
CH00 Reference level	 Date: 24 NOV 2021 10:34:19		
CH00 30MHz~1000MHz	 Date: 24 NOV 2021 10:34:34		
CH00 1GHz~26GHz	 Date: 24 NOV 2021 10:34:49		


CH39
Reference level




CH39
30MHz~1000MHz



CH39
1GHz~26GHz




CH78
Reference level




Date: 24 NOV 2021 10:41:59

CH78
30MHz~1000MHz



Date: 24 NOV 2021 10:42:14

CH78
1GHz~26GHz



Date: 24 NOV 2021 10:42:30

-----End of Report-----