

# TCL entertainment solutions limited

## TEST REPORT

**SCOPE OF WORK**

FCC TESTING-TS5000, TS5010, FS5000, FS5010

**REPORT NUMBER**

181205003SZN-001

**ISSUE DATE**

27 December 2018

**[REVISED DATE]**

[-----]

**PAGES**

64



**DOCUMENT CONTROL NUMBER**

FCC ID 247\_b

© 2017 INTERTEK

## **TCL entertainment solutions limited**

Application  
For  
Certification

**FCC ID: 2ARUDTS5000**

**Alto 5 2.0CH Soundbar, Alto 5+2.1CH Soundbar with wireless subwoofer, 2.0CH  
Soundbar, 2.1CH Soundbar with wireless subwoofer**

**Model: TS5000, TS5010, FS5000, FS5010**

**2.4GHz Transceiver**

Report No.: 181205003SZN-001

We hereby certify that the sample of the above item is considered to comply with the  
requirements of FCC Part 15, Subpart C for Intentional Radiator,  
mention 47 CFR [10-1-17]

**Prepared and Checked by:**

**Damon Wang**  
**Engineer**

**Approved by:**

**Kidd Yang**  
**Technical Supervisor**  
**Date: 27 December 2018**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Intertek Testing Service Shenzhen Ltd. Longhua Branch**

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen.  
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

## LIST OF EXHIBITS

### *INTRODUCTION*

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Confidentiality request
<i>EXHIBIT 10:</i>	Test Equipment List

**MEASUREMENT/TECHNICAL REPORT**

TCL entertainment solutions limited

Model: TS5000

FCC ID: 2ARUDTS5000

This report concerns (check one): Original Grant  Class I Change Equipment Type: DSS - Part 15 Spread Spectrum TransmitterDeferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes  No If yes, defer until: \_\_\_\_\_  
dateCompany Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes  No 

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-17 Edition] provision.

Report prepared by:

Damon Wang  
Intertek Testing Services Shenzhen Ltd. Longhua Branch  
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing  
Community, GuanHu Subdistrict, LongHua District, Shenzhen.  
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6661

**Table of Contents**

<b>1.0</b>	<b><u>General Description</u></b>	7
1.1	Product Description	7
1.2	Related Submittal(s) Grants	7
1.3	Test Methodology	8
1.4	Test Facility	8
<b>2.0</b>	<b><u>System Test Configuration</u></b>	10
2.1	Justification	10
2.2	EUT Exercising Software	10
2.3	Special Accessories	10
2.4	Equipment Modification	10
2.5	Measurement Uncertainty	11
2.6	Support Equipment List and Description	11
<b>3.0</b>	<b><u>Test Results</u></b>	13
3.1	Radiated Test Result	14
3.1.1	Field Strength Calculation	14
3.1.2	Radiated Emission Configuration Photograph	15
3.1.3	Radiated Emission	15
3.1.4	Transmitter Spurious Emissions (Radiated)	18
3.2	Conducted Emission at Mains Terminal	22
3.2.1	Conducted Emission Configuration Photograph	22
3.2.2	Conducted Emissions	22
3.3	Peak Power	25
3.4	20dB Bandwidth	28
3.5	Channel Number (Number of Hopping Frequencies)	30
3.6	Channel Separation (Carrier Frequency Separation)	33
3.7	Dwell Time (Time of Occupancy)	35
3.8	Band Edge	41
3.9	Transmitter Spurious Emission (Conducted)	44
<b>4.0</b>	<b><u>Equipment Photographs</u></b>	49
<b>5.0</b>	<b><u>Product Labelling</u></b>	51
<b>6.0</b>	<b><u>Technical Specifications</u></b>	53
<b>7.0</b>	<b><u>Instruction Manual</u></b>	55
<b>8.0</b>	<b><u>Miscellaneous Information</u></b>	57
8.1	Discussion of Pulse Desensitization	58
8.2	Emissions Test Procedures	59
8.3	Emissions Test Procedures (cont'd)	60
<b>9.0</b>	<b><u>Confidentiality Request</u></b>	62
<b>10.0</b>	<b><u>Test Equipment List</u></b>	64

## List of attached files

Exhibit type	File Description	filename
Test Report	Test Report	report.pdf
Operational Description	Technical Description	descri.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
External Photos	External Photo	external photos.pdf
Internal Photos	Internal Photo	internal photos.pdf
ID Label/Location Info	Label Artwork and Location	label.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Users Manual	User Manual	manual.pdf
Cover Letter	Letter of Agency	agency.pdf
Cover Letter	Confidentiality Letter	request.pdf



Total Quality. Assured.  
TEST REPORT

Intertek Report No.: 181205003SZN-001

## EXHIBIT 1

### GENERAL DESCRIPTION

## 1.0 General Description

### 1.1 Product Description

The equipment under test (EUT) is a Soundbar with Bluetooth and 2.4G transmitter functions operating in 2402-2480MHz. The EUT is powered by 100-240V~50/60Hz. For more detail information pls. refer to the user manual.

Bluetooth Version: 4.2(without BLE)

Antenna Type: Integral antenna

Antenna Gain: 1 dBi

Modulation Type: GFSK,  $\pi/4$ -DQPSK and 8-DPSK

The Model: TS5010, FS5000, FS5010 are the same as the Model: TS5000 in hardware and electrical aspect (circuitry and electrical, mechanical and physical construction). The difference in function and model number serves as packaging and marketing purpose only. Details see below.

Product name	Trade name	Model no.	Description
Alto 5 2.0CH Soundbar	TCL	TS5000	<b>Function:</b> AUX / BT / Optical / USB Playback / LED Indicator
Alto 5+2.1CH Soundbar with wireless subwoofer	TCL	TS5010	<b>Function:</b> AUX / BT / Optical / USB Playback / LED Indicator / Wireless subwoofer
2.0CH Soundbar	TCL	FS5000	Function: AUX / BT / Optical / USB Playback / LED Indicator
2.1CH Soundbar with wireless subwoofer	TCL	FS5010	Function: AUX / BT / Optical / USB Playback / LED Indicator / Wireless subwoofer

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

### 1.2 Related Submittal(s) Grants

This is an application for certification of transceiver for the soundbar which has Bluetooth function. The 2.4G transmitter function was reported in the test report: 181205003SZN-002, and Other digital functions were reported in the test report: 181205003SZN-003.

### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

### 1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

## EXHIBIT 2

### SYSTEM TEST CONFIGURATION

## 2.0 System Test Configuration

### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT was powered by 120V/60Hz during the test. Only the worst case data was reported.

All packets DH1, DH3 & DH5 mode in modulation type GFSK,  $\pi/4$ -DQPSK and 8-DPSK were tested and only the worst data was reported in this report.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit was flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

### 2.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

### 2.3 Special Accessories

No special accessory attached.

### 2.4 Equipment Modification

Any modifications installed previous to testing by TCL entertainment solutions limited will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

## 2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

## 2.6 Support Equipment List and Description

Description	Manufacturer	Model No.
iPod	Apple	A1367
USB Memory	TOSHIBA	UHYBS-004G-BL
USB Memory	SanDisk	SDCZ36-002G-P36
Audio In Cable	N/A	Unshielded, Length 120cm
Detached AC power cord	Richsound	Unshielded, Length 150cm
Optical Cable with Load	N/A	Unshielded, Length 120cm
2.5mm TV's remote control receiving extension Cable	N/A	Unshielded, Length 120cm
Dummy Load	N/A	N/A



Total Quality. Assured.  
TEST REPORT

Intertek Report No.: 181205003SZN-001

## EXHIBIT 3

### TEST RESULTS

### 3.0 Test Results

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

### 3.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

Where

FS = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

RA = Receiver Amplitude (including preamplifier) in  $\text{dB}\mu\text{V}$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Assume a receiver reading of 62.0  $\text{dB}\mu\text{V}$  is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32  $\text{dB}\mu\text{V}/\text{m}$ . This value in  $\text{dB}\mu\text{V}/\text{m}$  was converted to its corresponding level in  $\mu\text{V}/\text{m}$ .

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V}/\text{m})/20] = 39.8 \mu\text{V}/\text{m}$$

### 3.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

### 3.1.3 Radiated Emissions- FCC section 15.209

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit. Simultaneous transmission was considered.

Worst Case Radiated Emission

at 895.24 MHz

Judgement: Passed by 9.7 dB

**TEST PERSONNEL:**

*Sign on file*

Damon Wang, Engineer  
Typed/Printed Name

December 7, 2018

*Date*

Applicant: TCL entertainment solutions limited

Date of Test: December 7, 2018

Model: TS5000


Sample: 1/1

Worst-case operating Mode: BT link

Modulation type: GFSK


### ANT Polarity: Horizontal

FCC Part 15



### ANT Polarity: Vertical

FCC Part 15



Applicant: TCL entertainment solutions limited

Date of Test: December 7, 2018

Model: TS5000

Sample: 1/1

Worst-case operating Mode: BT link

Modulation type: GFSK

Table 1

**Radiated Emissions**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	61.040	31.6	20.0	10.1	21.7	40.0	-18.3
Horizontal	151.250	34.5	20.0	11.3	25.8	43.5	-17.7
Horizontal	895.240	34.6	20.0	21.7	36.3	46.0	-9.7
Vertical	39.215	33.3	20.0	10.1	23.4	40.0	-16.6
Vertical	61.040	39.3	20.0	3.1	22.4	40.0	-17.6
Vertical	150.765	27.7	20.0	21.7	29.4	43.5	-14.1

NOTES: 1. Quasi-Peak detector is used except for others stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions are below the QP limit.

## 3.1.4 Transmitter Spurious Emissions (Radiated) - FCC section 15.209

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission

at 7440.000 MHz

Judgement: Passed by 9.6 dB

***TEST PERSONNEL:***

*Sign on file*

Damon Wang, Engineer

*Typed/Printed Name*

December 7, 2018

*Date*

Applicant: TCL entertainment solutions limited

Date of Test: December 7, 2018

Model: TS5000

Sample: 1/1

Worst-case operating Mode: Transmit (2402MHz)

Modulation type: GFSK

Table 2

**Radiated Emissions**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	2402.000	107.3	36.7	28.1	98.7	--	--
Horizontal	4804.000	48.5	36.7	35.5	47.3	74.0	-26.7
Horizontal	2388.500	49.0	36.1	36.5	49.4	74.0	-24.6

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	2402.000	86.6	36.7	28.1	78.0	--	--
Horizontal	4804.000	38.8	36.7	35.5	37.6	54.0	-16.4
Horizontal	2388.500	38.3	36.1	36.5	38.7	54.0	-15.3

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and Average Measurements were made with measurement instrumentation employing an average detector function using a minimum resolution bandwidth of 1 MHz.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

Applicant: TCL entertainment solutions limited

Date of Test: December 7, 2018

Model: TS5000

Sample: 1/1

Worst-case operating Mode: Transmit (2441MHz)

Modulation type: GFSK

Table 3

**Radiated Emissions**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	4882.000	49.7	36.7	35.5	48.5	74.0	-25.5
Horizontal	7323.000	53.3	36.1	36.5	53.7	74.0	-20.3

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	4882.000	38.6	36.7	35.5	37.4	54.0	-16.6
Horizontal	7323.000	43.4	36.1	36.5	43.8	54.0	-10.2

## NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and Average Measurements were made with measurement instrumentation employing an average detector function using a minimum resolution bandwidth of 1 MHz.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

Applicant: TCL entertainment solutions limited

Date of Test: December 7, 2018

Model: TS5000

Sample: 1/1

Worst-case operating Mode: Transmit (2480MHz)

Modulation type: GFSK

Table 4

**Radiated Emissions**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	2480.000	99.4	36.7	28.1	90.8	--	--
Horizontal	4960.000	51.1	36.7	35.5	49.9	74.0	-24.1
Horizontal	7440.000	55.4	36.1	36.5	55.8	74.0	-18.2

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	2480.000	87.0	36.7	28.1	78.4	--	--
Horizontal	4960.000	42.8	36.7	35.5	41.6	54.0	-12.4
Horizontal	7440.000	44.0	36.1	36.5	44.4	54.0	-9.6

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and Average Measurements were made with measurement instrumentation employing an average detector function using a minimum resolution bandwidth of 1 MHz.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

## 3.2 Conducted Emission at Mains Terminal

### 3.2.1 Conducted Emissions Configuration Photograph

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

### 3.2.2 Conducted Emissions

Worst Case Conducted Configuration

at 0.154 MHz

Judgement: Passed by 11.7 dB margin

**TEST PERSONNEL:**

*Sign on file*

Damon Wang Engineer

*Typed/Printed Name*

December 7, 2018

*Date*

Applicant: TCL entertainment solutions limited

Date of Test: December 7, 2018

Model: TS5000


Sample: 1/1

Worst-case operating Mode: Transmit (CH00)

Modulation type: GFSK

Phase: Live

### Conducted Emission Test - FCC



**Result Table QP**

Frequency (MHz)	QuasiPeak (dB $\mu$ /V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ /V)
0.154000	53.8	9.000	L1	9.6	12.0	65.8
0.178000	49.7	9.000	L1	9.6	14.9	64.6
0.242000	43.2	9.000	L1	9.6	18.8	62.0
0.498000	33.9	9.000	L1	9.6	22.1	56.0
4.426000	25.0	9.000	L1	9.7	31.0	56.0
15.730000	28.4	9.000	L1	10.0	31.6	60.0

**Result Table AV**

Frequency (MHz)	Average (dB $\mu$ /V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ /V)
0.154000	38.3	9.000	L1	9.6	17.5	55.8
0.178000	34.9	9.000	L1	9.6	19.7	54.6
0.242000	33.0	9.000	L1	9.6	19.0	52.0
0.498000	25.4	9.000	L1	9.6	20.6	46.0
4.426000	17.7	9.000	L1	9.7	28.3	46.0
15.730000	22.5	9.000	L1	10.0	27.5	50.0

Applicant: TCL entertainment solutions limited

Date of Test: December 7, 2018

Model: TS5000


Sample: 1/1

Worst-case operating Mode: Transmit (CH00)

Modulation type: GFSK

Phase: Neutral

### Conducted Emission Test - FCC



### Result Table QP

Frequency (MHz)	QuasiPeak (dB <sub>1/2</sub> IV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB <sub>1/2</sub> IV)
0.154000	54.1	9.000	N	9.6	11.7	65.8
0.178000	49.3	9.000	N	9.6	15.3	64.6
0.238000	43.2	9.000	N	9.6	19.0	62.2
0.498000	33.5	9.000	N	9.7	22.5	56.0
4.370000	26.3	9.000	N	9.7	29.7	56.0
15.830000	30.1	9.000	N	10.0	29.9	60.0

### Result Table AV

Frequency (MHz)	Average (dB <sub>1/2</sub> IV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB <sub>1/2</sub> IV)
0.154000	38.5	9.000	N	9.6	17.3	55.8
0.178000	34.0	9.000	N	9.6	20.6	54.6
0.238000	32.2	9.000	N	9.6	20.0	52.2
0.498000	25.4	9.000	N	9.7	20.6	46.0
4.370000	19.4	9.000	N	9.7	26.6	46.0
15.830000	24.1	9.000	N	10.0	25.9	50.0

### 3.3 Peak Power

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(1).

The antenna port of the EUT was connected to the input of a spectrum analyzer. The analyzer was set for RBW > 20dB bandwidth and power was read directly in dBm.


For antenna with gains of 6dBi or less, and frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, the systems operate with an output power no greater than 125 mW.

Antenna Gain = 1dBi			
Modulation Type	Frequency (MHz)	Output Power (Peak Reading) (dBm)	Output Power (mW)
GFSK	2402	-4.01	0.397
	2441	-3.24	0.474
	2480	-3.16	0.483


Cable loss: 0.5 dB    External Attenuation: 0 dB

Modulation Type: GFSK


CH00



CH39



CH78



### 3.4 20dB Bandwidth


Maximum 20dB RF Bandwidth, FCC Rule 15.247(a) (1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.


Frequency (MHz)	20 dB Bandwidth (MHz)
2402	1.372
2441	1.376
2480	1.376

Modulation Type: 8DPSK


CH00



CH39



CH78



### 3.5 Channel Number (Number of Hopping Frequencies)

Minimum Number of Hopping Frequencies, FCC Rule 15.247(a) (1) (iii):


The RF passband of the EUT was divided into 3 approximately equal bands. With the analyzer set to MAX HOLD readings were taken for 2-3 minutes. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.



Number of hopping channels =	79
------------------------------	----

Note: In AFH mode, this device operates using 20 channels and it's satisfied the requirement of limit of minimum of 15 hopping channels.


Modulation Type: GFSK

CH00-CH78



**CH00-CH24**

**CH25-CH52**


CH53-CH78



### 3.6 Channel Separation (Carrier Frequency Separation)

Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1):


Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit:

Not less than 2/3 of 20dB bandwidth of hopping channel:  $1.376 \times 2/3 = 0.917\text{MHz}$


Minimum Channel Separation	0.9986 MHz
----------------------------	------------

Modulation Type: 8DPSK


Low Channel



## Middle Channel



## High Channel



## 3.7 Dwell Time (Time of Occupancy)

Average Channel Occupancy Time, FCC Ref: 15.247(a) (1)(iii):

The spectrum analyzer center frequency was set to one of the known hopping channels with a longer sweep time to show two successive hops on a channel; the SPAN was set to ZERO SPAN, and the TRIGGER was set to VIDEO. RBW shall be  $\leq$ channel spacing and where possible RBW should be set  $\gg 1/T$ , where T is the expected dwell time per channel. The time duration of the transmissions so captured was measured with the MARKER DELTA function.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Different modes of operation were performed and only the worst case data was reported.

Worst Test Result:

## Normal hopping mode


Modulation Type	Packet	Max Dwell Time	Limit (s)	Result
8DPSK	DH1	$0.383\text{ms} * 160 = 61.280\text{ms}$	0.4	Pass
	DH3	$1.643\text{ms} * 121 = 198.803\text{ms}$	0.4	Pass
	DH5	$2.899\text{ms} * 96 = 278.304\text{ms}$	0.4	Pass

## AFH mode:


Modulation Type	Packet	Max Dwell Time	Limit (s)	Result
8DPSK	DH1	$0.383\text{ms} * 80 = 30.64\text{ms}$	0.4	Pass
	DH3	$1.643\text{ms} * 42 = 69.01\text{ms}$	0.4	Pass
	DH5	$2.899\text{ms} * 27 = 78.27\text{ms}$	0.4	Pass

Modulation Type: 8DPSK


Packet: DH1




Number of hops (Normal hopping mode)




## Number of hops (AFH mode)




## Packet: DH3




## Number of hops (Normal hopping mode)




## Number of hops (AFH mode)




Packet: DH5



Number of hops (Normal hopping mode)



## Number of hops (AFH mode)



## 3.8 Band Edge

Out of Band Conducted Emissions, FCC Rule 15.247(d):

In any 100 KHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

Furthermore, delta measurement technique for measuring bandage emissions was shown as below:

**(i) Lower channel 2402MHz:**

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot  
= 98.7dB $\mu$ v/m-31.36dB  
= 67.34dB $\mu$ v/m


Average Resultant field strength = Fundamental emissions (Average value) – delta from the bandedge plot  
= 78.0dB $\mu$ v/m-31.36dB  
= 46.64dB $\mu$ v/m

**(ii) Upper channel 2480MHz:**


Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot  
= 90.8dB $\mu$ v/m-47.93dB  
= 42.87dB $\mu$ v/m

Average Resultant field strength = Fundamental emissions (Average value) – delta from the bandedge plot  
= 78.4dB $\mu$ v/m-47.93dB  
= 30.47dB $\mu$ v/m


The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dB $\mu$ v/m (Peak Limit) and 54dB $\mu$ v/m (Average Limit).

Modulation Type: 8DPSK  
 Single Channel



Single Channel



## Hopping



## Hopping





### 3.9 Transmitter Spurious Emissions (Conducted)

#### Out of Band Conducted Spurious Emissions, FCC Rule 15.247(d):



All spurious emission and up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

Modulation Type: GFSK



CH00



CH39



CH78



**EXHIBIT 4****EQUIPMENT PHOTOGRAPHS**

## 4.0 Equipment Photographs

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.



Total Quality. Assured.

TEST REPORT

Intertek Report No.: 181205003SZN-001

## EXHIBIT 5

### PRODUCT LABELLING

## 5.0 Product Labelling

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.



Total Quality. Assured.

TEST REPORT

Intertek Report No.: 181205003SZN-001

## EXHIBIT 6

### TECHNICAL SPECIFICATIONS

## 6.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.



Total Quality. Assured.

TEST REPORT

Intertek Report No.: 181205003SZN-001

## EXHIBIT 7

### INSTRUCTION MANUAL



Total Quality. Assured.

**TEST REPORT**

Intertek Report No.: 181205003SZN-001

**7.0 Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.



Total Quality. Assured.

TEST REPORT

Intertek Report No.: 181205003SZN-001

## EXHIBIT 8

### MISCELLANEOUS INFORMATION

## 8.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandedge, the test procedure and calculation of factor such as pulse desensitization.

### 8.1 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period ( $T_{eff}$ ) is approximately 625 $\mu$ s for Bluetooth. With a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

## 8.2 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10: 2013.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter, up to 1GHz 0.8m and above 1GHz 1.5m in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average Measurements were made with measurement instrumentation employing an average detector function using a minimum resolution bandwidth of 1 MHz.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz with RBW 9KHz used.

### 8.3 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.10: 2013.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used (RBW 3MHz used for fundamental emission).

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.



Total Quality. Assured.

TEST REPORT

Intertek Report No.: 181205003SZN-001

## EXHIBIT 9

### CONFIDENTIALITY REQUEST

## 9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.



Total Quality. Assured.

**TEST REPORT**

Intertek Report No.: 181205003SZN-001

**EXHIBIT 10**

**TEST EQUIPMENT LIST**

**10 Test Equipment List**

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	14-Sep-2018	14-Sep-2019
SZ185-01	EMI Receiver	R&S	ESCI	100547	24-Jan-2018	24-Jan-2019
SZ061-08	Horn Antenna	ETS	3115	00092346	14-Sep-2018	14-Sep-2019
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	21-May-2018	21-May-2019
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	05-Jun-2018	05-Jun-2019
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	05-Jun-2018	05-Jun-2019
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	24-Jan-2018	24-Jan-2019
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	16-Jan-2017	16-Jan-2019
SZ062-02	RF Cable	RADIALL	RG 213U	--	10-Jun-2018	10-Jun-2019
SZ062-05	RF Cable	RADIALL	0.04-26.5GHz	--	10-Jun-2018	10-Jun-2019
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	10-Jun-2018	10-Jun-2019
SZ067-04	Notch Filter	Micro-Tronics	BRM50702-02	--	05-Jun-2018	05-Jun-2019
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	26-Oct-2018	26-Oct-2019
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	26-Oct-2018	26-Oct-2019
SZ188-03	Shielding Room	ETS	RFD-100	4100	16-Jan-2017	16-Jan-2019

\*\*\*\*\* End of Report\*\*\*\*\*