

Prediction of MPE at a given distance

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

2. Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

3. Result

Mode	Frequency (MHz)	Prediction distance (cm)	Rated Peak RF power output		MPE (mW/cm ²)	Limit (mW/cm ²)	SAR Test Exclusion
			dBm	mW			
BT LE	2402-2480	20	-2.869	0.0001	0.0002	1	Yes
WIFI	2412-2462	20	12.737	0.0131	0.0049	1	Yes

Maximum Simultaneous transmission MPE Ratios for BT+WIFI:

Max MPE Ratio BT/Limit	Max MPE ratio WIFI/Limit	ΣMPE ratios	Limit	Result
0.0001	0.0131	0.0132	1	PASS

BT Antenna Gain: 1.30dBi, 1.35(numeric)

WIFI Antenna Gain:

External antenna 1, max gain 5.44dBi, 3.5(numeric)

External antenna 2, max gain 5.44dBi. 3.5(numeric)

The antenna MIMO combining gain is 8.44dBi. 6.98(numeric)

Then SAR evaluation is not required.