

RF Exposure Evaluation

FCC ID: 2ARZ3-BT-X44

1. Client Information

Applicant	:	Technaxx Deutschland GmbH & Co. KG
Address	:	Kruppstrasse 105, 60388 Frankfurt am Main, Germany
Manufacturer	:	Shenzhen Teana Technology Co.,ltd
Address	:	2nd Floor, Building 6, Nanling Village, Nanwan Street, Longgang District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Karaoke Mikrophone Fabric	
Models No.	:	BT-X44	
Model Difference	:	N/A	
Product Description	:	Operation Frequency:	Bluetooth 4.2(BT): 2402MHz~2480MHz
		RF Output Power:	GFSK:-2.358dBm π /4-DQPSK:-1.132dBm
		Antenna Gain:	0dBi PCB Antenna
Power Supply	:	DC Voltage Supply from Adapter DC Voltage supplied by Li-ion battery.	
Power Rating	:	Iutput: DC 5.0V 1A by adapter DC 3.7V by 1000mAh Li-ion battery	
Software Version	:	N/A	
Hardware Version	:	N/A	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{\text{(GHz)}}}] \leq 3.0 \text{ for 1-g SAR}$$

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{\text{(GHz)}}}] \leq 7.5.0 \text{ for 10-g SAR}$$

2. Calculation:

Test separation: 5mm						
Bluetooth Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-2.384	-3 ± 1	-2	0.631	0.196	3.0
2.441	-2.358	-3 ± 1	-2	0.631	0.197	3.0
2.480	-3.185	-3 ± 1	-2	0.631	0.199	3.0
Bluetooth Mode (π /4-DQPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-1.207	-1 ± 1	0	1.000	0.310	3.0
2.441	-1.132	-1 ± 1	0	1.000	0.312	3.0
2.480	-1.937	-1 ± 1	0	1.000	0.315	3.0

Test separation: 5mm		
The worst RF Exposure Evaluation		
Worst Calculation Value	Total Calculation Value	Threshold Value
Bluetooth Mode (π /4-DQPSK)		
0.315	0.315	3.0

The worst RF Exposure Evaluation is calculated as $0.315 / \text{cm}^2 < \text{limit } 3.0$, So standalone SAR measurements are not required.

-----END OF REPORT-----