

FCC RF Exposure

EUT Description: bebird

Model No.: bebird 1

FCC ID: 2ARZG-BEBIRD

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
$$[(\text{max power of channel, including tune - up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1 - g SAR and } \leq 7.5 \text{ for 10 - g extremity SAR,}$$

Where:

Result=P/D* \sqrt{F}

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

2.4G

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm ²)	SAR Test Exclusion
802.11b	8.53	7.6±1	8.6/7.24	5	2.249	3.0	Pass
802.11g	7.86	7±1	8/6.31	5	1.960	3.0	Pass
802.11n(HT20)	7.65	7±1	8/6.31	5	1.960	3.0	Pass
802.11n(HT40)	7.64	7±1	8/6.31	5	1.970	3.0	Pass
<p>Note:</p> <p>PK Output power= conducted power.</p> <p>Conducted power see the test report HK1812011829-E, antenna gain=1dBi</p>							

Note: Exclusion Thresholds Results=[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm