

FCC 47 CFR MPE REPORT

Shenzhen Proscenic Technology Co., Ltd

Robot Vacuum Cleaner

Model Number: D800

Additional Model: LR1, L8050, L8150, L8250, L8650, L8750, L8350,
LDS M7 PRO, LDS M8 PRO,LDS M7(MAX),LDS U6,LDS M8,LDS M8 MAX,
L8450, Lxxxx (xxxx represent number or numeric alphabetic combination)

FCC ID: 2ARZX-LDSM7PRO

Prepared for:	Shenzhen Proscenic Technology Co., Ltd
	8F, Building 5A, Tusincere Park, Intersection of Qingchun Road and Longfei
	Avenue, Longgang District, Shenzhen, Guangdong Province, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1912041
Date of Test:	Oct. 19~Dec. 05, 2019
Date of Report:	Dec. 07, 2019



Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	17.82	60.534	17 ± 1	2	1.585
	2437	19.25	84.140	19 ± 1	2	1.585
	2462	18.62	72.778	18 ± 1	2	1.585
IEEE 802.11g	2412	17.95	62.373	17 ± 1	2	1.585
	2437	18.65	73.282	18 ± 1	2	1.585
	2462	18.57	71.945	18 ± 1	2	1.585
IEEE 802.11n HT20	2412	16.39	43.551	16 ± 1	2	1.585
	2437	17.35	54.325	17 ± 1	2	1.585
	2462	17.97	62.661	17 ± 1	2	1.585
IEEE 802.11n HT40	2422	16.57	45.394	16 ± 1	2	1.585
	2437	17.22	52.723	17 ± 1	2	1.585
	2452	17.51	56.364	17 ± 1	2	1.585

3. Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	20	2	1.585	0.03153	1	Compiles
IEEE 802.11g	19	2	1.585	0.02504	1	Compiles
IEEE 802.11n HT20	18	2	1.585	0.01989	1	Compiles
IEEE 802.11n HT40	18	2	1.585	0.01989	1	Compiles

End of Test Report