



Shenzhen BCTC Testing Co., Ltd.

**FCC ID: 2AS3LX2**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT-EDR

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-1.09	0.78	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.441	-0.14	0.97	1±1	2.00	1.58	<5	0.49524	3.00	YES
	2.480	1.93	1.56	1±1	2.00	1.58	<5	0.49918	3.00	YES
Pi/4 DQPSK	2.402	-3.14	0.49	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.441	0.01	1.00	1±1	2.00	1.58	<5	0.49524	3.00	YES
	2.480	-0.26	0.94	1±1	2.00	1.58	<5	0.49918	3.00	YES
8DPSK	2.402	-2.77	0.53	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.441	0.70	1.17	1±1	2.00	1.58	<5	0.49524	3.00	YES
	2.480	0.43	1.10	1±1	2.00	1.58	<5	0.49918	3.00	YES

**Conclusion:**

For the max result :  $0.49918 \leq$  FCC Limit 3.0 for 1g SAR.