

MPE Calculation : LTE Band 48

Transmitting Mode	Transmitting configuration	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirement (mW/cm ²)
MIMO	Antenna 1 & 2 ^{Note1}	3555.00	~	3695.00	15.50	13.41	28.91	778.037	0.1548	1.000
MIMO	Antenna 3 & 4 ^{Note1}	3555.00	~	3695.00	15.50	13.41	28.91	778.037	0.1548	1.000
Uplink CA	PCC (Antenna 1 & 2) ^{Note1} , SCC (Antenna 3 & 4) ^{Note1}	3555.00	~	3695.00	18.50	13.41	31.91	1552.388	0.3089	1.000
			~							
			~							
			~							
			~							
			~							

Note 1: The transmitting antennas are cross-polarized.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 778.037 / (4 \times 20^2 \times \pi) \\
 &= 0.1548 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averaging time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC