



EMITTER

Instruction


MTR019



MTR020



MTR021



FCC Requirement

Function

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy, and if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Technical data

Function

Power input: 3Vdc with 1 CR2032

Radiated power: +6dB

Frequency: 433.92MHz±100KHz

Lifetime: >2 years

Emission distance: 80 meters outdoor, 30 meters indoor

Working temperature: 0° ~50°

Functions description

Function

1. MTR019 is a one-key transmitter.

1. MTR020 is a two-key transmitter.

1. MTR021 is a three-key transmitter.