

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR22-SRF0042-A Page (33) of (59)	 
---	--	---

Middle Channel

Port	Frequency	Pol.	Reading	Antenna Factor	Amp. + Cable	DCF	Result	Limit	Margin
	[MHz]	[V/H]	[dB(μV)]	[dB]	[dB]	[dB]	[dB(μV/m)]	[dB(μV/m)]	[dB]
Peak data									
1	2 312.13 ¹⁾	V	67.16	31.79	-45.67	-	53.28	74.00	20.72
	2 568.28	V	67.95	32.31	-45.21	-	55.05	74.00	18.95
	3 996.17 ¹⁾	V	63.66	33.40	-52.88	-	44.18	74.00	29.82
	4 880.22 ¹⁾	H	60.63	33.62	-51.54	-	42.71	74.00	31.29
	5 999.89	V	63.73	35.20	-50.98	-	47.95	74.00	26.05
	7 319.39 ¹⁾	V	63.00	35.37	-49.78	-	48.59	74.00	25.41
2	2 312.06 ¹⁾	V	66.61	31.79	-45.67	-	52.73	74.00	21.27
	2 568.36	V	68.89	32.31	-45.21	-	55.99	74.00	18.01
	4 846.23 ¹⁾	H	60.92	33.63	-51.55	-	43.00	74.00	31.00
	6 000.34	V	64.52	35.20	-50.98	-	48.74	74.00	25.26
	7 351.56 ¹⁾	H	58.52	35.36	-49.78	-	44.10	74.00	29.90
3	3 991.64 ¹⁾	H	64.88	33.39	-52.87	-	45.40	74.00	28.60
	4 880.22 ¹⁾	V	60.73	33.62	-51.54	-	42.81	74.00	31.19
	5 999.44	H	63.64	35.20	-50.98	-	47.86	74.00	26.14
	6 538.66	V	61.16	35.32	-49.77	-	46.71	74.00	27.29
	7 318.94 ¹⁾	V	61.72	35.37	-49.78	-	47.31	74.00	26.69
4	2 311.99 ¹⁾	V	67.62	31.79	-45.67	-	53.74	74.00	20.26
	2 376.00 ¹⁾	V	68.61	31.93	-45.64	-	54.90	74.00	19.10
	2 504.14	V	68.96	32.21	-45.34	-	55.83	74.00	18.17
	2 568.28	V	70.32	32.31	-45.21	-	57.42	74.00	16.58
	3 983.03 ¹⁾	H	63.39	33.39	-52.87	-	43.91	74.00	30.09
	4 147.52 ¹⁾	H	61.62	33.49	-52.63	-	42.48	74.00	31.52
	4 879.77 ¹⁾	H	65.76	33.62	-51.54	-	47.84	74.00	26.16
	5 999.89	V	63.57	35.20	-50.98	-	47.79	74.00	26.21
	7 320.75 ¹⁾	V	60.04	35.37	-49.78	-	45.63	74.00	28.37
Average Data									
1	2 312.13 ¹⁾	V	64.37	31.79	-45.67	0.23	50.72	54.00	3.28
2	2 312.06 ¹⁾	V	63.07	31.79	-45.67	0.23	49.42	54.00	4.58
3	No spurious emissions were detected within 20 dB of the limit.								
4	2 311.99 ¹⁾	V	64.62	31.79	-45.67	0.23	50.97	54.00	3.03
	2 376.00 ¹⁾	V	66.60	31.93	-45.64	0.23	53.12	54.00	0.88


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (34) of (59)



Average Data (Port 1)




Average Data (Port 2)




Average Data (Port 3)

Blank

Average Data (Port 4) _2 311 MHz



Average Data (Port 4) _2 376 MHz



Blank


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (35) of (59)




Horizontal/Vertical for 1 GHz ~ 3.5 GHz (Port 1)




Horizontal/Vertical for 3.5 GHz ~ 18 GHz (Port 1)



Horizontal/Vertical for 1 GHz ~ 3.5 GHz (Port 2)



Horizontal/Vertical for 3.5 GHz ~ 18 GHz (Port 2)




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (36) of (59)




Horizontal/Vertical for 1 GHz ~ 3.5 GHz (Port 3)




Horizontal/Vertical for 3.5 GHz ~ 18 GHz (Port 3)



Horizontal/Vertical for 1 GHz ~ 3.5 GHz (Port 4)



Horizontal/Vertical for 3.5 GHz ~ 18 GHz (Port 4)



KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR22-SRF0042-A Page (37) of (59)	 
---	--	---

High Channel

Port	Frequency	Pol.	Reading	Antenna Factor	Amp. + Cable	DCF	Result	Limit	Margin
	[MHz]	[V/H]	[dB(μV)]	[dB]	[dB]	[dB]	[dB(μV/m)]	[dB(μV/m)]	[dB]
Peak data									
1	2 351.98 ¹⁾	V	67.36	31.87	-45.65	-	53.58	74.00	20.42
	2 608.20	V	68.92	32.37	-45.14	-	56.15	74.00	17.85
	2 483.61 ¹⁾	V	49.10	32.16	-27.20	-	54.06	74.00	19.94
	3 985.30 ¹⁾	H	65.85	33.39	-52.87	-	46.37	74.00	27.63
	4 959.97 ¹⁾	V	61.16	33.61	-51.68	-	43.09	74.00	30.91
	5 999.89	V	62.73	35.20	-50.98	-	46.95	74.00	27.05
	7 440.38 ¹⁾	V	61.11	35.32	-49.78	-	46.65	74.00	27.35
2	2 352.06 ¹⁾	V	67.35	31.87	-45.65	-	53.57	74.00	20.43
	2 607.73	V	68.54	32.37	-45.14	-	55.77	74.00	18.23
	2 483.66 ¹⁾	V	52.19	32.16	-27.20	-	57.15	74.00	16.85
	3 990.28 ¹⁾	H	63.87	33.39	-52.87	-	44.39	74.00	29.61
	4 959.52 ¹⁾	V	61.26	33.61	-51.68	-	43.19	74.00	30.81
	6 000.80	V	61.74	35.20	-50.98	-	45.96	74.00	28.04
	6 551.80	H	60.46	35.32	-49.77	-	46.01	74.00	27.99
3	7 439.47 ¹⁾	V	62.11	35.32	-49.78	-	47.65	74.00	26.35
	2 493.76 ¹⁾	V	45.26	32.19	-27.23	-	50.22	74.00	23.78
	4 939.58 ¹⁾	H	60.87	33.61	-51.63	-	42.85	74.00	31.15
	5 999.89	H	63.18	35.20	-50.98	-	47.40	74.00	26.60
4	7 439.47 ¹⁾	V	59.82	35.32	-49.78	-	45.36	74.00	28.64
	2 352.05 ¹⁾	V	67.88	31.87	-45.65	-	54.10	74.00	19.90
	2 415.86	V	69.10	32.01	-45.58	-	55.53	74.00	18.47
	2 543.91	V	68.55	32.27	-45.26	-	55.56	74.00	18.44
	2 608.13	V	71.19	32.37	-45.14	-	58.42	74.00	15.58
	2 483.52 ¹⁾	V	50.20	32.16	-27.20	-	55.16	74.00	18.84
	4 960.42 ¹⁾	H	67.76	33.61	-51.68	-	49.69	74.00	24.31
	6 000.34	V	63.80	35.20	-50.98	-	48.02	74.00	25.98
4	7 440.38 ¹⁾	V	59.98	35.32	-49.78	-	45.52	74.00	28.48
Average Data									
1	2 351.98 ¹⁾	V	64.81	31.87	-45.65	0.23	51.26	54.00	2.74
	2 483.61 ¹⁾	V	35.13	32.16	-27.20	0.23	40.32	54.00	13.68
2	2 352.06 ¹⁾	V	63.59	31.87	-45.65	0.23	50.04	54.00	3.96
	2 483.66 ¹⁾	V	37.66	32.16	-27.20	0.23	42.85	54.00	11.15
3	No spurious emissions were detected within 20 dB of the limit.								
4	2 352.05 ¹⁾	V	64.93	31.87	-45.65	0.23	51.38	54.00	2.62
	2 483.52 ¹⁾	V	37.83	32.16	-27.20	0.23	43.02	54.00	10.98


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (38) of (59)



Average Data (Port 1)




Average Data (Port 2)



Average Data (Port 3)

Blank

Average Data (Port 4)




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (39) of (59)




Horizontal/Vertical for Band-edge (Port 1)




Horizontal/Vertical for Band-edge (Port 1)



Horizontal/Vertical for Band-edge (Port 2)



Horizontal/Vertical for Band-edge (Port 2)




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (40) of (59)




Horizontal/Vertical for Band-edge (Port 3)



Horizontal/Vertical for Band-edge (Port 4)



Horizontal/Vertical for Band-edge (Port 4)




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (41) of (59)




Horizontal/Vertical for 1 GHz ~ 3.5 GHz (Port 1)




Horizontal/Vertical for 3.5 GHz ~ 18 GHz (Port 1)



Horizontal/Vertical for 1 GHz ~ 3.5 GHz (Port 2)



Horizontal/Vertical for 3.5 GHz ~ 18 GHz (Port 2)




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (42) of (59)




Horizontal/Vertical for 1 GHz ~ 3.5 GHz (Port 3)




Horizontal/Vertical for 3.5 GHz ~ 18 GHz (Port 3)



Horizontal/Vertical for 1 GHz ~ 3.5 GHz (Port 4)



Horizontal/Vertical for 3.5 GHz ~ 18 GHz (Port 4)



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR22-SRF0042-A
Page (43) of (59)



Test results (Above 18 GHz) – Worst Case : 2 Mbits/s(37 Bytes) 2 480 MHz

Horizontal/Vertical for 18 GHz ~ 26.5 GHz



Note: The Worst case was based on the lowest margin condition considering Harmonic and Spurious Emission

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR22-SRF0042-A Page (44) of (59)	 
---	--	---

Simultaneous condition

802.11a (5 200 MHz) + BT_BLE(2 402 MHz)

Frequency	Pol.	Reading	Antenna Factor	Amp. + Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
1 327.42 ¹⁾	V	78.24	27.73	-47.60	-	58.37	74.00	15.63
2 529.77	V	76.47	32.25	-45.29	-	63.43	74.00	10.57
3 117.19	V	70.75	33.02	-44.56	-	59.21	74.00	14.79
3 584.73	V	68.71	33.15	-53.07	-	48.79	74.00	25.21
3 987.11 ¹⁾	V	65.89	33.39	-52.87	-	46.41	74.00	27.59
4 786.88 ¹⁾	V	65.72	33.64	-51.57	-	47.79	74.00	26.21
7 282.00 ¹⁾	H	74.02	35.39	-49.61	-	59.80	74.00	14.20
7 974.88	H	60.63	35.49	-48.89	-	47.23	74.00	26.77
8 319.88 ¹⁾	V	64.46	35.50	-49.02	-	50.94	74.00	23.06
10 397.78	H	62.57	37.24	-47.92	-	51.89	74.00	22.11
11 438.61 ¹⁾	V	65.46	38.05	-47.45	-	56.06	74.00	17.94
15 671.25 ¹⁾	H	53.79	40.64	-44.40	-	50.03	74.00	23.97
Average Data								
1 327.42	V	62.00	27.73	-47.60	0.22	42.35	54.00	11.65
7 282.00	H	64.59	35.39	-49.61	0.22	50.59	54.00	3.41
11 438.61	V	58.65	38.05	-47.45	0.22	49.47	54.00	4.53


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR22-SRF0042-A
Page (45) of (59)




Average data (1 327 MHz)



Blank

Horizontal/Vertical for 1 GHz ~ 3.5 GHz




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (46) of (59)




Average data (7 282 MHz)




Average data (11 438 MHz)






Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 5 GHz



Horizontal/Vertical for 5 GHz ~ 6.5 GHz**Horizontal/Vertical for 6.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 40 GHz**

Note: The Worst case was based on the lowest margin condition considering Harmonic and Spurious Emission.

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR22-SRF0042-A Page (48) of (59)	 
---	--	---

Simultaneous condition

802.11a (5 200 MHz) + BT_BLE(2 402 MHz)

Frequency	Pol.	Reading	Antenna Factor	Amp. + Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
1 327.42 ¹⁾	V	78.24	27.73	-47.60	-	58.37	74.00	15.63
2 529.77	V	76.47	32.25	-45.29	-	63.43	74.00	10.57
3 117.19	V	70.75	33.02	-44.56	-	59.21	74.00	14.79
3 584.73	V	68.71	33.15	-53.07	-	48.79	74.00	25.21
3 987.11 ¹⁾	V	65.89	33.39	-52.87	-	46.41	74.00	27.59
4 786.88 ¹⁾	V	65.72	33.64	-51.57	-	47.79	74.00	26.21
7 282.00 ¹⁾	H	74.02	35.39	-49.61	-	59.80	74.00	14.20
7 974.88	H	60.63	35.49	-48.89	-	47.23	74.00	26.77
8 319.88 ¹⁾	V	64.46	35.50	-49.02	-	50.94	74.00	23.06
10 397.78	H	62.57	37.24	-47.92	-	51.89	74.00	22.11
11 438.61 ¹⁾	V	65.46	38.05	-47.45	-	56.06	74.00	17.94
15 671.25 ¹⁾	H	53.79	40.64	-44.40	-	50.03	74.00	23.97
Average Data								
1 327.42	V	62.00	27.73	-47.60	0.22	42.35	54.00	11.65
7 282.00	H	64.59	35.39	-49.61	0.22	50.59	54.00	3.41
11 438.61	V	58.65	38.05	-47.45	0.22	49.47	54.00	4.53


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR22-SRF0042-A
Page (49) of (59)




Average data (1 327 MHz)



Blank

Horizontal/Vertical for 1 GHz ~ 3.5 GHz




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (50) of (59)




Average data (7 282 MHz)




Average data (11 438 MHz)






Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 5 GHz




Horizontal/Vertical for 5 GHz ~ 6.5 GHz**Horizontal/Vertical for 6.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 40 GHz**

Note: The Worst case was based on the lowest margin condition considering Harmonic and Spurious Emission.

7.5. Conducted Spurious Emission

Test setup



Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operation, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation specified in §15.209(a) is not required. In addition, radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limit : 20 dBc

Test procedure

ANSI C63.10-2013 - Section 11.11.3

KDB 558074 D01 v05 - Section 8.5

KDB 662911 D01 v02r01 – section (E)(3)(b)

Test settings

Establish an emission level by using the following procedure:

- 1) Set the center frequency and span to encompass frequency range to be measured.
- 2) Set the RBW = 100 kHz
- 3) Set the VBW $\geq [3 \times \text{RBW}]$
- 4) Detector = peak
- 5) Sweep time = auto couple
- 6) Trace mode = max hold
- 7) Allow trace to fully stabilize.
- 8) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR22-SRF0042-A
Page (53) of (59)




Test results

BLE_1 MBit/s(37 Bytes)_Port 1

Conducted band-edge / Low ch.




Conducted spurious / Low ch.




Conducted band-edge / Mid ch.

Blank


Conducted spurious / Mid ch.



Conducted band-edge / High ch.



Conducted spurious / High ch.



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR22-SRF0042-A
Page (54) of (59)




BLE 1 MBit/s(37 Bytes)_Port 2

Conducted band-edge / Low ch.




Conducted spurious / Low ch.




Conducted band-edge / Mid ch.

Blank


Conducted spurious / Mid ch.



Conducted band-edge / High ch.



Conducted spurious / High ch.



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR22-SRF0042-A
Page (55) of (59)




BLE 1 MBit/s(37 Bytes)_Port 3

Conducted band-edge / Low ch.




Conducted spurious / Low ch.




Conducted band-edge / Mid ch.

Blank


Conducted spurious / Mid ch.



Conducted band-edge / High ch.



Conducted spurious / High ch.



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR22-SRF0042-A
Page (56) of (59)




BLE_1 MBit/s(37 Bytes)_Port 4

Conducted band-edge / Low ch.




Conducted spurious / Low ch.




Conducted band-edge / Mid ch.

Blank


Conducted spurious / Mid ch.



Conducted band-edge / High ch.




Conducted spurious / High ch.



7.6. AC Conducted emission

Test setup



Limit

§15.407

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dB μ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Measurement procedure

1. The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
2. Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a spectrum analyzer or an EMI/Field Intensity Meter, to the input power source.
3. Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
4. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
5. The measurements were made with the detector set to peak amplitude within a bandwidth of 10 kHz or to quasi-peak and average within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR22-SRF0042-A
Page (58) of (59)



Test results

Worst case: BLE_1 MBit/s(37 Bytes)_Port 1 / 2 480 MHz



Final Result

--- N Phase ---									
No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	QP
1	0.17438	38.9	26.4	10.4	49.3	36.8	64.7	54.7	15.4
2	0.22596	34.5	20.9	10.2	44.7	31.1	62.6	52.6	17.9
3	0.77876	12.6	4.7	10.0	22.6	14.7	56.0	46.0	33.4
4	4.09111	24.0	17.6	10.3	34.3	27.9	56.0	46.0	21.7
5	19.81631	18.3	9.2	11.1	29.4	20.3	60.0	50.0	30.6
6	21.83844	22.9	15.0	11.1	34.0	26.1	60.0	50.0	26.0
									CAV
									[dB]
--- L1 Phase ---									
No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	QP
1	0.15601	40.9	26.8	10.5	51.4	37.3	65.7	55.7	14.3
2	0.17558	39.9	26.7	10.4	50.3	37.1	64.7	54.7	14.4
3	0.83317	11.7	4.4	10.0	21.7	14.4	56.0	46.0	34.3
4	2.82331	18.8	13.5	10.2	29.0	23.7	56.0	46.0	27.0
5	4.06947	24.1	17.8	10.3	34.4	28.1	56.0	46.0	21.6
6	21.98843	27.0	16.3	11.3	38.3	27.6	60.0	50.0	21.7
									CAV
									[dB]

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR22-SRF0042-A Page (59) of (59)	 
---	--	---

8. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSV30	100810	22.07.27
Spectrum Analyzer	R&S	FSV40	100989	22.12.21
EMI TEST RECEIVER	R&S	ESCI7	100732	23.03.04
Bi-Log Antenna	TESEQ	CBL 6112D	55545	23.01.14
Amplifier	SONOMA INSTRUMENT	310N	284608	22.08.19
ATTENUATOR	KEYSIGHT	8491B-6dB	MY39271060	23.01.14
Horn antenna	ETS.lindgren	3117	155787	22.10.05
Horn antenna	ETS.lindgren	3116	86635	22.05.17
Attenuator	API Inmet	40AH2W-10	12	22.05.11
Broadband PreAmplifier	SCHWARZBECK	BBV9718	216	22.07.27
AMPLIFIER	L-3 Narda-MITEQ	AMF-7D-01001800-22-10P	2003683	22.08.19
AMPLIFIER	L-3 Narda-MITEQ	JS44-18004000-33-8P	2000996	23.01.21
LOOP Antenna	R&S	HFH2-Z2	100355	22.08.21
Antenna Mast	Innco Systems	MA4640-XP-ET	-	-
Turn Table	Innco Systems	CO3000	1175/45850319/P	-
Antenna Mast	Innco Systems	MA4000-EP	303	-
Turn Table	Innco Systems	CO3000	1175/45850319/P	-
Highpass Filter	WT	WT-A1698-HS	WT160411001	22.05.10
TWO-LINE V - NETWORK	R&S	ENV216	101358	22.09.29
EMI TEST RECEIVER	R&S	ESCI3	100001	22.08.19
Vector Signal Generator	R&S	SMBV100A	257566	22.07.09
Signal Generator	R&S	SMB100A	176206	23.01.19
Cable Assembly	RadiAll	2301761768000PJ	1724.659	-
Cable Assembly	HUER+SUHNER	SUCOFLEX 104	MY4342/4	-
Cable Assembly	HUER+SUHNER	SUCOFLEX 102	804320/2	-

End of test report