

**HTW**

Shenzhen Huatongwei International Inspection Co.,Ltd.
Huatongwei 101, No.006, Keji south 12th Road, High-tech zone community,
Yuehai Street, Nanshan District, Shenzhen, Guangdong, China
Phone: 400-963-0755 E-mail: cs@szhtw.com.c Website: http://www.szhtw.com.cn

**CNAS**

中国认可
国际互认
检测
TESTING
CNAS L1225

TEST REPORT

For Bluetooth-LE

Report No..... : CHTW25050094



Project No : SHT2502029403W

FCC ID : 2AS8AW06LT

Applicant's name : Shenzhen Jamr Technology Co., Ltd

Address..... : A101-301, D101-201, Jamr Science & Technology Park, No. 2 Guiyuan Road, Guanlan Street, Longhua District, 518100 Shenzhen, PEOPLE'S REPUBLIC OF CHINA

Product Name..... : Blood Pressure Monitor

Trade Mark..... : -

Model No..... : W06LT

Listed Model(s) : -

Standard : **FCC CFR Title 47 Part 15 Subpart C § 15.247**

Date of receipt of test sample..... : 2025/2/18

Date of testing..... : 2025/2/18- 2025/5/27

Date of issue..... : 2025/5/28

Result..... : **Pass**

Compiled by
(Position+Printed name+Signature) : File administrator Xiaodong Zhao

Supervised by
(Position+Printed name+Signature) : Project Engineer Kiki Kong

Approved by
(Position+Printed name+Signature) : RF Manager Xu Yang

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address..... : Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China

Test Report Form No. : R0054

Test Report Form(s) Originator..... : Shenzhen Huatongwei International Inspection Co., Ltd.

Master TRF : Dated 2025-04

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. The test report merely correspond to the test sample. The authenticity of this Test Report and its contents can be verified by contacting the Laboratory, responsible for this Test Report.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
<u>4.</u>	<u>TEST CONFIGURATION</u>	<u>7</u>
4.1.	Test frequency list	7
4.2.	Descriptions of Test mode	7
4.3.	Test sample information	7
4.4.	Support unit used in test configuration and system	8
4.5.	Testing environmental condition	8
4.6.	Statement of the measurement uncertainty	8
4.7.	Equipment Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>11</u>
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	Peak Output Power	15
5.4.	Power Spectral Density	16
5.5.	6dB bandwidth	17
5.6.	99% Occupied Bandwidth	18
5.7.	Duty Cycle	19
5.8.	Conducted Band edge and Spurious Emission	20
5.9.	Radiated Band edge Emission	21
5.10.	Radiated Spurious Emission	24
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	<u>31</u>
<u>7.</u>	<u>EXTERNAL AND INTERNAL PHOTOS</u>	<u>33</u>
7.1.	External Photos	33
7.2.	Internal Photos	36
<u>8.</u>	<u>APPENDIX REPORT</u>	<u>38</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- [FCC CFR Title 47 Part 15 Subpart C § 15.247](#): Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2020](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2025-05-28	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result	Test Engineer
5.1	Antenna Requirement	15.203/15.247(c)	PASS	Jiaxing Si
5.2	AC Conducted Emission	15.207	PASS	YATING.CHEN
5.3	Peak Output Power	15.247(b)(3)	PASS	Jiaxing Si
5.4	Power Spectral Density	15.247(e)	PASS	Jiaxing Si
5.5	6dB Bandwidth	15.247(a)(2)	PASS	Jiaxing Si
5.6	99% Occupied Bandwidth	-	PASS ^{*1}	Jiaxing Si
5.7	Duty cycle	-	PASS ^{*1}	Jiaxing Si
5.8	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS	Jiaxing Si
5.9	Radiated Band Edge Emission	15.205/15.209	PASS	Yifan Wang
5.10	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS	Yifan Wang

Note:

- The measurement uncertainty is not included in the test result.
- *1: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	Shenzhen Jamr Technology Co., Ltd
Address:	A101-301, D101-201, Jamr Science & Technology Park, No. 2 Guiyuan Road, Guanlan Street, Longhua District, 518100 Shenzhen, PEOPLE'S REPUBLIC OF CHINA
Manufacturer:	Shenzhen Jamr Technology Co., Ltd
Address:	A101-301, D101-201, Jamr Science & Technology Park, No. 2 Guiyuan Road, Guanlan Street, Longhua District, 518100 Shenzhen, PEOPLE'S REPUBLIC OF CHINA
Factory:	Shenzhen Jamr Technology Co., Ltd
Address:	A101-301, D101-201, Jamr Science & Technology Park, No. 2 Guiyuan Road, Guanlan Street, Longhua District, 518100 Shenzhen, PEOPLE'S REPUBLIC OF CHINA

3.2. Product Description

Main unit information:	
Product Name:	Blood Pressure Monitor
Trade Mark:	-
Model No.:	W06LT
Listed Model(s):	-
Power supply:	DC 3.7V from Battery
Hardware version:	JMR-PCB-W06LT-AC621B-A-1.0
Software version:	V1
Accessory unit information:	
Battery information:	3.7V 300mAh 1.11Wh

3.3. Radio Specification Description

Bluetooth version:	V5.3
Support function:	BLE1M,BLE2M
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	PCB Antenna
Antenna gain:	-6.075dBi

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China	
Contact information:	<p>Tel: 400-963-0755 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn</p>	
Qualifications	Type	Accreditation Number
	FCC Registration Number	762235
	FCC Designation Number	CN1181

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Channel	Frequency (MHz)
00	2402
01	2404
..	..
19	2440
..	..
38	2478
39	2480

4.2. Descriptions of Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For Radiated spurious emissions:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

4.3. Test sample information

Test item	HTW sample no.
RF Conducted test items	Please refer to the description in the appendix report
RF Radiated test items	YPHT25020294005
EMI test items	YPHT25020294003

Note:

RF Conducted test items: Peak Output Power, Power Spectral Density, 6dB Bandwidth, 99% Occupied Bandwidth, Duty cycle, Conducted Band Edge and Spurious Emission

RF Radiated test items: Radiated Band Edge Emission, Radiated Spurious Emission

EMI test items: AC Conducted Emission

4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?			
<input checked="" type="checkbox"/> Yes			
Item	Equipment	Trade Name	Model No.
1	Adapter (Provided by the applicant)		NGE12I05

4.5. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.6. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	3.21dB
2	Peak Output Power	1.07
3	Power Spectral Density	1.07
4	6dB Bandwidth	0.002%
5	99% Occupied Bandwidth	0.002%
6	Duty cycle	-
7	Conducted Band Edge and Spurious Emission	1.68dB
8	Radiated Band Edge Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz
9	Radiated Spurious Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.7. Equipment Used during the Test

● RF Conducted test item							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	HTWE0242	FSV40	100048	2024/08/27	2025/08/26
●	Signal & Spectrum Analyzer	R&S	HTWE0262	FSW26	103440	2024/08/21	2025/08/20
●	Vector signal generator	R&S	HTWE0244	SMBV100A	260790	2025/03/13	2026/03/12
●	Test software	Tonscend	N/A	JS1120	N/A	N/A	N/A

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2024/08/12	2025/08/11
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2024/08/12	2025/08/11
●	Protection Network	SCHWARZBECK	HTWE0567	VTSD9561FN	00899	2024/08/12	2025/08/11
●	ISN	FCC	HTWE0148	FCC-TLISN-T2-02	20371	2024/08/12	2025/08/11
●	ISN	FCC	HTWE0150	FCC-TLISN-T8-02	20375	2024/08/12	2025/08/11
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated Emission – 9kHz~30MHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/04/06	2026/04/05
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2024/08/12	2025/08/11
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2024/04/08	2027/04/07
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated Emission - 30MHz~1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/04/06	2026/04/05
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2024/08/12	2025/08/11
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2023/02/22	2026/02/21
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	/	2024/05/28	2025/05/27
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	/	2025/05/26	2026/05/25
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated emission- Above 1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2023/04/17	2026/04/16
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2024/08/12	2025/08/11
●	Spectrum Analyzer	R&S	HTWE0385	N9020A	MY54486658	2024/08/12	2025/08/11
●	Horn Antenna	SCHWARZBECK	HTWE0126	BBHA 9120D	1011	2023/02/14	2026/02/13
●	Pre-Amplifier	CD	HTWE0071	PAP-0102	12004	2024/06/06	2025/06/05
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0551	SCU18F	100855	2024/06/06	2025/06/05
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

REQUIREMENT


FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

TEST RESULT

Passed Not Applicable

The antenna type is a PCB antenna, please refer to the below antenna photo.



5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.



TEST MODE


Refer to the clause 4.2

TEST RESULT


Passed Not Applicable

BLE 1M:

Test Line:	L																																																																																				
																																																																																					
Final Result																																																																																					
Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)																																																																															
<table border="1"> <tr><td>0.150000</td><td>36.64</td><td>---</td><td>66.00</td><td>29.36</td><td>L1</td><td>10.1</td></tr> <tr><td>0.158000</td><td>36.06</td><td>---</td><td>65.57</td><td>29.50</td><td>L1</td><td>10.1</td></tr> <tr><td>0.162000</td><td>---</td><td>23.09</td><td>55.36</td><td>32.27</td><td>L1</td><td>10.1</td></tr> <tr><td>0.162000</td><td>36.62</td><td>---</td><td>65.36</td><td>28.74</td><td>L1</td><td>10.1</td></tr> <tr><td>0.163500</td><td>---</td><td>23.36</td><td>55.28</td><td>31.92</td><td>L1</td><td>10.1</td></tr> <tr><td>0.171500</td><td>29.82</td><td>---</td><td>64.89</td><td>35.07</td><td>L1</td><td>10.2</td></tr> <tr><td>0.175500</td><td>29.97</td><td>---</td><td>64.70</td><td>34.73</td><td>L1</td><td>10.2</td></tr> <tr><td>0.207500</td><td>27.60</td><td>---</td><td>63.30</td><td>35.71</td><td>L1</td><td>10.2</td></tr> <tr><td>0.211500</td><td>---</td><td>19.37</td><td>53.15</td><td>33.78</td><td>L1</td><td>10.2</td></tr> <tr><td>0.375500</td><td>---</td><td>18.30</td><td>48.38</td><td>30.08</td><td>L1</td><td>10.3</td></tr> <tr><td>2.923500</td><td>---</td><td>16.09</td><td>46.00</td><td>29.91</td><td>L1</td><td>10.6</td></tr> <tr><td>3.851500</td><td>---</td><td>16.86</td><td>46.00</td><td>29.14</td><td>L1</td><td>10.6</td></tr> </table>		0.150000	36.64	---	66.00	29.36	L1	10.1	0.158000	36.06	---	65.57	29.50	L1	10.1	0.162000	---	23.09	55.36	32.27	L1	10.1	0.162000	36.62	---	65.36	28.74	L1	10.1	0.163500	---	23.36	55.28	31.92	L1	10.1	0.171500	29.82	---	64.89	35.07	L1	10.2	0.175500	29.97	---	64.70	34.73	L1	10.2	0.207500	27.60	---	63.30	35.71	L1	10.2	0.211500	---	19.37	53.15	33.78	L1	10.2	0.375500	---	18.30	48.38	30.08	L1	10.3	2.923500	---	16.09	46.00	29.91	L1	10.6	3.851500	---	16.86	46.00	29.14	L1	10.6
0.150000	36.64	---	66.00	29.36	L1	10.1																																																																															
0.158000	36.06	---	65.57	29.50	L1	10.1																																																																															
0.162000	---	23.09	55.36	32.27	L1	10.1																																																																															
0.162000	36.62	---	65.36	28.74	L1	10.1																																																																															
0.163500	---	23.36	55.28	31.92	L1	10.1																																																																															
0.171500	29.82	---	64.89	35.07	L1	10.2																																																																															
0.175500	29.97	---	64.70	34.73	L1	10.2																																																																															
0.207500	27.60	---	63.30	35.71	L1	10.2																																																																															
0.211500	---	19.37	53.15	33.78	L1	10.2																																																																															
0.375500	---	18.30	48.38	30.08	L1	10.3																																																																															
2.923500	---	16.09	46.00	29.91	L1	10.6																																																																															
3.851500	---	16.86	46.00	29.14	L1	10.6																																																																															
Test Line:	N																																																																																				
																																																																																					
Final Result																																																																																					
Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)																																																																															
<table border="1"> <tr><td>0.150000</td><td>41.83</td><td>---</td><td>66.00</td><td>24.17</td><td>N</td><td>10.1</td></tr> <tr><td>0.159500</td><td>40.54</td><td>---</td><td>65.49</td><td>24.95</td><td>N</td><td>10.1</td></tr> <tr><td>0.183500</td><td>36.92</td><td>---</td><td>64.33</td><td>27.41</td><td>N</td><td>10.2</td></tr> <tr><td>0.207500</td><td>33.70</td><td>---</td><td>63.30</td><td>29.60</td><td>N</td><td>10.2</td></tr> <tr><td>0.215500</td><td>32.97</td><td>---</td><td>62.99</td><td>30.02</td><td>N</td><td>10.2</td></tr> <tr><td>0.247500</td><td>29.31</td><td>---</td><td>61.84</td><td>32.53</td><td>N</td><td>10.2</td></tr> <tr><td>0.307500</td><td>---</td><td>23.41</td><td>50.04</td><td>26.62</td><td>N</td><td>10.2</td></tr> <tr><td>0.327500</td><td>---</td><td>24.25</td><td>49.51</td><td>25.27</td><td>N</td><td>10.2</td></tr> <tr><td>0.351500</td><td>---</td><td>24.94</td><td>48.93</td><td>23.99</td><td>N</td><td>10.2</td></tr> <tr><td>0.375500</td><td>---</td><td>25.17</td><td>48.38</td><td>23.21</td><td>N</td><td>10.2</td></tr> <tr><td>0.695500</td><td>---</td><td>16.39</td><td>46.00</td><td>29.61</td><td>N</td><td>10.2</td></tr> <tr><td>0.719500</td><td>---</td><td>14.76</td><td>46.00</td><td>31.24</td><td>N</td><td>10.2</td></tr> </table>		0.150000	41.83	---	66.00	24.17	N	10.1	0.159500	40.54	---	65.49	24.95	N	10.1	0.183500	36.92	---	64.33	27.41	N	10.2	0.207500	33.70	---	63.30	29.60	N	10.2	0.215500	32.97	---	62.99	30.02	N	10.2	0.247500	29.31	---	61.84	32.53	N	10.2	0.307500	---	23.41	50.04	26.62	N	10.2	0.327500	---	24.25	49.51	25.27	N	10.2	0.351500	---	24.94	48.93	23.99	N	10.2	0.375500	---	25.17	48.38	23.21	N	10.2	0.695500	---	16.39	46.00	29.61	N	10.2	0.719500	---	14.76	46.00	31.24	N	10.2
0.150000	41.83	---	66.00	24.17	N	10.1																																																																															
0.159500	40.54	---	65.49	24.95	N	10.1																																																																															
0.183500	36.92	---	64.33	27.41	N	10.2																																																																															
0.207500	33.70	---	63.30	29.60	N	10.2																																																																															
0.215500	32.97	---	62.99	30.02	N	10.2																																																																															
0.247500	29.31	---	61.84	32.53	N	10.2																																																																															
0.307500	---	23.41	50.04	26.62	N	10.2																																																																															
0.327500	---	24.25	49.51	25.27	N	10.2																																																																															
0.351500	---	24.94	48.93	23.99	N	10.2																																																																															
0.375500	---	25.17	48.38	23.21	N	10.2																																																																															
0.695500	---	16.39	46.00	29.61	N	10.2																																																																															
0.719500	---	14.76	46.00	31.24	N	10.2																																																																															

BLE 2M:**Final Result**

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.162000	---	16.92	55.36	38.44	L1	10.1
0.163500	34.03	---	65.28	31.25	L1	10.1
0.166000	33.03	---	65.16	32.12	L1	10.2
0.371500	---	13.28	48.47	35.19	L1	10.3
0.375500	21.44	---	58.38	36.94	L1	10.3
0.551500	---	12.38	46.00	33.62	L1	10.4
2.883500	21.58	---	56.00	34.42	L1	10.6
2.923500	---	15.85	46.00	30.15	L1	10.6
3.799500	---	17.15	46.00	28.85	L1	10.6
3.819500	23.52	---	56.00	32.48	L1	10.6
3.975500	---	16.50	46.00	29.50	L1	10.6
4.135500	20.49	---	56.00	35.51	L1	10.6

**Final Result**


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.154000	36.52	---	65.78	29.26	N	10.1
0.162000	---	22.67	55.36	32.69	N	10.1
0.162000	38.00	---	65.36	27.36	N	10.1
0.166000	---	21.51	55.16	33.65	N	10.1
0.171500	32.28	---	64.89	32.60	N	10.1
0.187500	32.82	---	64.15	31.33	N	10.2
0.195500	25.51	---	63.80	38.29	N	10.2
0.211500	27.88	---	63.15	35.27	N	10.2
0.279500	---	15.94	50.83	34.89	N	10.2
0.327500	---	14.43	49.51	35.08	N	10.2
0.347500	---	13.13	49.02	35.89	N	10.2
3.915500	---	15.09	46.00	30.91	N	10.3

5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10 and KDB 558074 D01 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

TEST MODE

Refer to the clause 4.2

TEST RESULT

Passed Not Applicable

TEST DATA

Refer to the appendix report


5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
 Center frequency=DTS channel center frequency
 Span =1.5 times the DTS bandwidth
 $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
 Sweep time = auto couple
 Detector = peak
 Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE

Refer to the clause 4.2

TEST RESULT

Passed Not Applicable

TEST DATA

Refer to the appendix report


5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
 - Center Frequency = DTS channel center frequency
 - Span=2 x DTS bandwidth
 - RBW = 100 kHz, VBW $\geq 3 \times$ RBW
 - Sweep time= auto couple
 - Detector = Peak
 - Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE

Refer to the clause 4.2

TEST RESULT

Passed Not Applicable

TEST DATA


Refer to the appendix report

5.6. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = channel center frequency
Span $\geq 1.5 \times \text{OBW}$
RBW = 1%~5%OBW
VBW $\geq 3 \times \text{RBW}$
Sweep time= auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE

Refer to the clause 4.2

TEST RESULT

Passed Not Applicable

TEST DATA


Refer to the appendix report

5.7. Duty Cycle

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span=zero span, Frequency=centered channel, RBW= 1 MHz, VBW \geq RBW
Sweep=as necessary to capture the entire dwell time,
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE

Refer to the clause 4.2

TEST DATA


Refer to the appendix report

5.8. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE

Refer to the clause 4.2

TEST RESULT

Passed Not Applicable

TEST DATA

Refer to the appendix report


5.9. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

 - VBW=10Hz, When duty cycle is no less than 98 percent
 - VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE

Refer to the clause 4.2

TEST RESULT

Passed Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level- Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

BLE 1M:

Test channel		CH00			Polarity				Horizontal	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	47.70	27.86	3.95	41.18	38.33	74.00	-35.67	Peak	
2	2390.03	50.46	27.54	4.08	41.11	40.97	74.00	-33.03	Peak	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	36.17	27.86	3.95	41.18	26.80	54.00	-27.20	Average	
2	2390.03	39.17	27.54	4.08	41.11	29.68	54.00	-24.32	Average	
Test channel		CH00			Polarity				Vertical	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	47.63	27.86	3.95	41.18	38.26	74.00	-35.74	Peak	
2	2390.03	50.48	27.54	4.08	41.11	40.99	74.00	-33.01	Peak	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	36.37	27.86	3.95	41.18	27.00	54.00	-27.00	Average	
2	2390.03	37.96	27.54	4.08	41.11	28.47	54.00	-25.53	Average	

Test channel		CH39			Polarity				Horizontal	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.50	58.28	27.33	4.18	41.04	48.75	74.00	-25.25	Peak	
2	2500.00	52.97	27.30	4.20	41.02	43.45	74.00	-30.55	Peak	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.50	41.48	27.33	4.18	41.04	31.95	54.00	-22.05	Average	
2	2500.00	44.02	27.30	4.20	41.02	34.50	54.00	-19.50	Average	
Test channel		CH39			Polarity				Vertical	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.50	58.07	27.33	4.18	41.04	48.54	74.00	-25.46	Peak	
2	2500.00	53.09	27.30	4.20	41.02	43.57	74.00	-30.43	Peak	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.50	39.55	27.33	4.18	41.04	30.02	54.00	-23.98	Average	
2	2500.00	42.28	27.30	4.20	41.02	32.76	54.00	-21.24	Average	

BLE 2M:

Test channel		CH00			Polarity				Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	47.56	27.86	3.95	41.18	38.19	74.00	-35.81	Peak	
2	2390.03	49.16	27.54	4.08	41.11	39.67	74.00	-34.33	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	36.16	27.86	3.95	41.18	26.79	54.00	-27.21	Average	
2	2390.03	39.25	27.54	4.08	41.11	29.76	54.00	-24.24	Average	
Test channel		CH00			Polarity				Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	48.06	27.86	3.95	41.18	38.69	74.00	-35.31	Peak	
2	2390.03	53.48	27.54	4.08	41.11	43.99	74.00	-30.01	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	36.64	27.86	3.95	41.18	27.27	54.00	-26.73	Average	
2	2390.03	38.07	27.54	4.08	41.11	28.58	54.00	-25.42	Average	

Test channel		CH39			Polarity				Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.50	57.43	27.33	4.18	41.04	47.90	74.00	-26.10	Peak	
2	2500.00	53.88	27.30	4.20	41.02	44.36	74.00	-29.64	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.50	44.95	27.33	4.18	41.04	35.42	54.00	-18.58	Average	
2	2500.00	43.30	27.30	4.20	41.02	33.78	54.00	-20.22	Average	
Test channel		CH39			Polarity				Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.50	51.57	27.33	4.18	41.04	42.04	74.00	-31.96	Peak	
2	2500.00	50.69	27.30	4.20	41.02	41.17	74.00	-32.83	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.50	41.04	27.33	4.18	41.04	31.51	54.00	-22.49	Average	
2	2500.00	42.07	27.30	4.20	41.02	32.55	54.00	-21.45	Average	

5.10. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



➤ Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
 If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement
 For average measurement:
 - VBW=10Hz, When duty cycle is no less than 98 percent
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE

Refer to the clause 4.2

TEST RESULT

Passed **Not Applicable**

Note:


- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level- Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.


For 9 kHz ~ 30 MHz

The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.


For 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH39 which it was worst case, so only show the worst case's data on this report.

BLE 1M:

BLE 2M:**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
41.0338	19.14	40.00	20.86	100.0	H	343.0	-9.1
54.2500	17.75	40.00	22.25	300.0	H	59.0	-8.8
308.8750	19.29	46.00	26.71	100.0	H	40.0	-6.9
523.1238	26.21	46.00	19.79	300.0	H	268.0	-1.1
623.1550	28.21	46.00	17.79	100.0	H	0.0	1.7
948.4688	41.03	46.00	4.97	100.0	H	40.0	7.5

**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
49.1575	19.87	40.00	20.13	100.0	V	329.0	-8.4
63.1013	20.67	40.00	19.33	100.0	V	24.0	-10.6
81.6525	16.69	40.00	23.31	100.0	V	24.0	-15.3
199.0225	16.56	43.50	26.94	100.0	V	123.0	-9.8
518.5163	25.48	46.00	20.52	100.0	V	92.0	-1.2
948.5900	36.80	46.00	9.20	100.0	V	339.0	7.4

For 1 GHz ~ 25 GHz**BLE 1M:**

Test channel		CH00			Polarity				Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2987.92	52.10	28.50	4.53	40.96	44.17	74.00	-29.83	Peak	
2	3993.90	47.82	29.79	5.43	40.32	42.72	74.00	-31.28	Peak	
3	4983.99	45.88	31.34	5.99	40.21	43.00	74.00	-31.00	Peak	
4	9611.66	43.46	39.12	8.60	39.82	51.36	74.00	-22.64	Peak	

Test channel		CH00			Polarity				Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2987.92	55.26	28.50	4.53	40.96	47.33	74.00	-26.67	Peak	
2	4983.99	49.60	31.34	5.99	40.21	46.72	74.00	-27.28	Peak	
3	7981.72	44.18	36.96	8.03	39.94	49.23	74.00	-24.77	Peak	
4	9611.66	42.84	39.12	8.60	39.82	50.74	74.00	-23.26	Peak	

Test channel		CH19			Polarity				Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2995.54	51.04	28.50	4.53	40.95	43.12	74.00	-30.88	Peak	
2	4983.99	48.78	31.34	5.99	40.21	45.90	74.00	-28.10	Peak	
3	7319.96	43.70	36.14	7.63	39.82	47.65	74.00	-26.35	Peak	
4	9759.59	44.42	39.30	8.60	39.85	52.47	74.00	-21.53	Peak	

Test channel		CH19			Polarity				Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2995.54	57.80	28.50	4.53	40.95	49.88	74.00	-24.12	Peak	
2	4996.69	51.89	31.39	6.00	40.20	49.08	74.00	-24.92	Peak	
3	7319.96	44.87	36.14	7.63	39.82	48.82	74.00	-25.18	Peak	
4	9759.59	44.32	39.30	8.60	39.85	52.37	74.00	-21.63	Peak	

Test channel		CH39			Polarity				Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2987.92	53.12	28.50	4.53	40.96	45.19	74.00	-28.81	Peak	
2	4983.99	46.51	31.34	5.99	40.21	43.63	74.00	-30.37	Peak	
3	7451.57	44.25	36.20	7.75	39.92	48.28	74.00	-25.72	Peak	
4	9935.05	44.68	39.30	8.60	39.89	52.69	74.00	-21.31	Peak	

Test channel		CH39			Polarity				Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	4256.33	52.74	30.03	5.79	40.47	48.09	74.00	-25.91	Peak	
2	6974.36	45.99	35.00	7.38	39.46	48.91	74.00	-25.09	Peak	
3	7451.57	46.71	36.20	7.75	39.92	50.74	74.00	-23.26	Peak	
4	9935.05	43.63	39.30	8.60	39.89	51.64	74.00	-22.36	Peak	

BLE 2M:



Test channel		CH00			Polarity				Horizontal	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2987.92	52.64	28.50	4.53	40.96	44.71	74.00	-29.29	Peak	
2	4983.99	43.48	31.34	5.99	40.21	40.60	74.00	-33.40	Peak	
3	6001.77	41.48	32.40	6.70	39.23	41.35	74.00	-32.65	Peak	
4	9611.66	44.09	39.12	8.60	39.82	51.99	74.00	-22.01	Peak	
Test channel		CH00			Polarity				Vertical	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2995.54	57.71	28.50	4.53	40.95	49.79	74.00	-24.21	Peak	
2	4809.50	50.11	31.28	5.89	40.28	47.00	74.00	-27.00	Peak	
3	4983.99	53.97	31.34	5.99	40.21	51.09	74.00	-22.91	Peak	
4	9611.66	42.55	39.12	8.60	39.82	50.45	74.00	-23.55	Peak	


Test channel		CH19			Polarity				Horizontal	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2995.54	55.11	28.50	4.53	40.95	47.19	74.00	-26.81	Peak	
2	4996.69	44.38	31.39	6.00	40.20	41.57	74.00	-32.43	Peak	
3	7301.36	45.47	36.10	7.61	39.80	49.38	74.00	-24.62	Peak	
4	9759.59	44.11	39.30	8.60	39.85	52.16	74.00	-21.84	Peak	
Test channel		CH19			Polarity				Vertical	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	4996.69	55.31	31.39	6.00	40.20	52.50	74.00	-21.50	Peak	
2	6379.86	43.95	33.32	6.89	39.20	44.96	74.00	-29.04	Peak	
3	7319.96	45.33	36.14	7.63	39.82	49.28	74.00	-24.72	Peak	
4	9759.59	43.57	39.30	8.60	39.85	51.62	74.00	-22.38	Peak	

Test channel		CH39			Polarity				Horizontal	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2987.92	51.56	28.50	4.53	40.96	43.63	74.00	-30.37	Peak	
2	3993.90	50.61	29.79	5.43	40.32	45.51	74.00	-28.49	Peak	
3	4996.69	47.90	31.39	6.00	40.20	45.09	74.00	-28.91	Peak	
4	9935.05	44.29	39.30	8.60	39.89	52.30	74.00	-21.70	Peak	
Test channel		CH39			Polarity				Vertical	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2995.54	57.53	28.50	4.53	40.95	49.61	74.00	-24.39	Peak	
2	4996.69	55.02	31.39	6.00	40.20	52.21	74.00	-21.79	Peak	
3	7451.57	46.72	36.20	7.75	39.92	50.75	74.00	-23.25	Peak	
4	9935.05	44.37	39.30	8.60	39.89	52.38	74.00	-21.62	Peak	

6. TEST SETUP PHOTOS

Radiated Emission








AC Conducted Emission




7. EXTERNAL AND INTERNAL PHOTOS



7.1. External Photos













7.2. Internal Photos







8. APPENDIX REPORT