

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a #10030 Nikko Velocitrax(#10031 Electric Orange, #10032 Neon Green) operating at 2.4G Band. The EUT can be powered by DC 6.4V (1 x 6.4V rechargeable battery). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -3.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -3.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 92.7 dBμV/m at 3m in the frequency 2440MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -2.53dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 91.6 dBμV/m at 3m in the frequency 2475MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -3.63dBm

which is within the production variation.

The maximum conducted output power specified is 0dBm= 1.000mW

The source- based time-averaging conducted output power

=1.000* Duty cycle mW < 1.000mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

= $3.0 * 5 / \sqrt{2.475}$ mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 12.464ms

Effective period of the cycle = 1.884ms

DC =1.884ms / 12.464ms =0.1512 or 15.12%