

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is an Velocitrap™ Assortment (11" / 28cm) operating at 2.4G Band. The EUT can be powered by DC 6.4V (1 x 6.4V rechargeable battery). And the RF function will be shut down and it can't transmit RF signals while charging. For more details information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -6.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -6.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 88.9dB $\mu$ V/m at 3m in the frequency 2435MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -6.33dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 88.4dB $\mu$ V/m at 3m in the frequency 2405MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -6.83dBm  
which is within the production variation.

The maximum conducted output power specified is -3.0dBm= 0.501mW

The source- based time-averaging conducted output power  
=0.501mW

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)  
= 3.0 \* 5 / sqrt (2.475) mW  
= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

---

FCC ID: 2AS9M10030NIK-TX1