

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is an 1:18 Night Mode RC Assortment (No Batteries) operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -2.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -2.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 96.0dB $\mu$ V/m at 3m in the frequency 2410MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = 0.77dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 92.1 dB $\mu$ V/m at 3m in the frequency 2470MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -3.13dBm  
which is within the production variation.

The maximum conducted output power specified is 1.0dBm= 1.259mW

The source- based time-averaging conducted output power  
=1.259mW

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)  
= 3.0 \* 5 / sqrt (2.470) mW  
= 9.54 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

---

FCC ID: 2AS9M10040NIKCOL1