

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an 1:10 Elite Trophy Trucks X2 Assortment (18" / 46cm) operating at 2.4G Band. The EUT can be powered by DC 6.0V (4 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -16.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -16.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 79.4dB μ V/m at 3m in the frequency 2420MHz

The EIRP = $[(FS^*D)^2 / 30]$ mW = -15.83dBm
which is within the production variation.

The Minimum peak radiated emission for the EUT is 76.9 dB μ V/m at 3m in the frequency 2446MHz

The EIRP = $[(FS^*D)^2 / 30]$ mW = -18.33dBm
which is within the production variation.

The maximum conducted output power specified is -13.0dBm= 0.050mW

The source- based time-averaging conducted output power
=0.050mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)
= 3.0 * 5 / sqrt (2.472) mW
= 9.54 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

FCC ID: 2AS9M19010NIKCOL1