

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-19O-RWD-039

AGR No. : A199A-269

Applicant : AMOSENSE

Address : 56 Naruteo-ro, Seocho-gu, SEOUL, South Korea

Manufacturer : AMOSENSE

Address : 56 Naruteo-ro, Seocho-gu, SEOUL, South Korea

Type of Equipment : NOVO

FCC ID. : 2AS9T-SB42SW

Model Name : SB42-SW

Multiple Model Name : N/A

Serial number : N/A

Total page of Report : 49 pages (including this page)

Date of Incoming : September 23, 2019

Date of issue : October 17, 2019

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**


This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:


Tae-Ho, Kim / Senior Manager
ONETECH Corp.

Approved by:


Ki-Hong, Nam / Chief Engineer
ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	5
2. TEST SUMMARY	6
2.1 TEST ITEMS AND RESULTS	6
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	6
2.3 RELATED SUBMITTAL(S) / GRANT(S)	6
2.4 PURPOSE OF THE TEST	6
2.5 TEST METHODOLOGY.....	6
2.6 TEST FACILITY.....	7
3. GENERAL INFORMATION.....	8
3.1 PRODUCT DESCRIPTION.....	8
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	8
4. EUT MODIFICATIONS.....	8
5. SYSTEM TEST CONFIGURATION	9
5.1 JUSTIFICATION.....	9
5.2 PERIPHERAL EQUIPMENT	9
5.3 MODE OF OPERATION DURING THE TEST	9
5.4 CONFIGURATION OF TEST SYSTEM.....	11
5.5 ANTENNA REQUIREMENT	11
6. PRELIMINARY TEST	12
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	12
6.2 GENERAL RADIATED EMISSIONS TESTS	12
7. MAXIMUM PEAK OUTPUT POWER.....	13
7.1 OPERATING ENVIRONMENT	13
7.2 TEST SET-UP	13
7.3 TEST EQUIPMENT USED	13
7.4 TEST DATA.....	14
8. BAND EDGES	16
8.1 OPERATING ENVIRONMENT	16
8.2 TEST SET-UP	16
8.3 TEST EQUIPMENT USED	16
8.4 TEST DATA.....	17

9. FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (20 DB BANDWIDTH)	21
9.1 OPERATING ENVIRONMENT	21
9.2 TEST SET-UP	21
9.3 TEST EQUIPMENT USED	21
9.4 TEST DATA	22
10. NUMBER OF HOPPING FREQUENCY	25
10.1 OPERATING ENVIRONMENT	25
10.2 TEST SET-UP	25
10.3 TEST EQUIPMENT USED	25
10.4 TEST DATA	26
11. TIME OF OCCUPANCY(DWELL TIME)	29
11.1 OPERATING ENVIRONMENT	29
11.2 TEST SET-UP	29
11.3 TEST EQUIPMENT USED	29
11.4 TEST DATA	30
12. 100 KHZ BANDWIDTH OUTSIDE THE FREQUENCY BAND	32
12.1 OPERATING ENVIRONMENT	32
12.2 TEST SET-UP FOR CONDUCTED / RADIATED MEASUREMENT	32
12.3 TEST EQUIPMENT USED	33
12.4 TEST DATA FOR CONDUCTED EMISSION	34
12.5 TEST DATA FOR TRANSMITTING MODE RADIATED EMISSION	40
12.5.1 <i>Spurious & Harmonic Radiated Emission above 1 GHz</i>	40
13. RADIATED EMISSION TEST	47
13.1 OPERATING ENVIRONMENT	47
13.2 TEST SET-UP	47
13.3 TEST EQUIPMENT USED	47
13.4 TEST DATA	48
13.4.1 <i>Test data for 30 MHz ~ 1 000 MHz</i>	48
13.4.2 <i>Test data for Below 30 MHz</i>	49
13.4.3 <i>Test data for above 1 GHz</i>	49

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-19O-RWD-039	October 17, 2019	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : AMOSENSE
Address : 56 Naruteo-ro, Seocho-gu, SEOUL, South Korea
Manufacturer : AMOSENSE
Address : 56 Naruteo-ro, Seocho-gu, SEOUL, South Korea
Factory : AMO VINA CO.,LTD
Address : Lot CN12, Khai Quang industrial Park, Khai Quang Ward, Vinh Yen City, Vinh Phuc Province, Vietnam
Contact Person : UIHAN JEONG/Research Engineer
Telephone No. : +82-010-4948-5676
FCC ID : 2AS9T-SB42SW
Model Name : SB42-SW
Brand Name : -
Serial Number : N/A
Date : October 17, 2019

EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER
E.U.T. DESCRIPTION	NOVO
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247(a)(1)(i)	20 dB Bandwidth	Met the Limit / PASS
15.247(b)(2)	Conducted Maximum Peak Output Power	Met the Limit / PASS
15.247(a)(1)	Carrier Frequency Separation	Met the Limit / PASS
15.247(a)(1)(i)	Number of Hopping Frequencies	Met the Limit / PASS
15.247(a)(1)(i)	Time of Occupancy	Met the Limit / PASS
15.247(d)	Conducted Spurious Emissions	Met the Limit / PASS
15.247(d)	Band Edge(Out of Band Emissions)	Met the Limit / PASS
15.207(a)	AC Power line Conducted Emissions	N/A (See Note)
15.247(d), 15.205, 15.209	Radiated Spurious Emissions	Met the Limit / PASS
15.247(d), 15.205, 15.209	Radiated Restricted Band Edge	Met the Limit / PASS

Note: This test is not applicable because the EUT use battery.

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247.

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-4112/ C-14617/ G-10666 / T-1842

IC (Industry Canada) – Registration No. Site# 3736A-3

-. Site Accreditation:

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The AMOSENSE, Model SB42-SW (referred to as the EUT in this report) is a NOVO. Product specification information described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	NOVO	
Temperature Range	-20 °C ~ 50 °C	
OPERATING FREQUENCY	NFC	13.56 MHz
	Sig Fox	902.137 5 MHz ~ 904.662 5 MHz
	Bluetooth LE	2 402 MHz ~ 2 480 MHz
	WLAN 2.4 GHz	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20))
MODULATION TYPE	NFC	ASK
	Sig Fox	DBPSK
	Bluetooth LE	GFSK
	WLAN 2.4 GHz	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK) 802.11g/n(HT20): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
RF OUTPUT POWER'	NFC	39.53 dBμV/m
	Sig Fox	22.26 dBm
	Bluetooth LE	-0.44 dBm
	WLAN 2.4 GHz	2.99 dBm(802.11b) 1.64 dBm(802.11g) 1.57 dBm(802.11n_HT20)
ANTENNA TYPE	NFC: FPCB Antenna Sig Fox : Chip Antenna WLAN 2.4 GHz / Bluetooth LE : Chip Antenna	
ANTENNA GAIN	WLAN 2.4 GHz / Bluetooth LE : 2.40 dBi Sig Fox : -0.59 dBi	
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	32.768 kHz, 26 MHz, 32 MHz, 50 MHz	

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	AMONSENSE	NOVO Rev04	N/A
NFC ANTENNA	N/A	ANFA150N526 NOVO	N/A

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
SB42-SW	AMONSENSE	NOVO(EUT)	-
N/A	N/A	Jig Board	EUT
Ideapad 100	LENOVO	Notebook PC	-
PA-1450-55LR	LITE-ON TECHNOLOGY	AC Adapter	-

5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting is programmed.

For final testing, the EUT was set at 902.137 5 MHz, 903.387 5 MHz, and 904.662 5 MHz to get a maximum emission levels from the EUT. The EUT was moved throughout the XY, XZ, and YZ planes and the worst case is “XZ” axis, but the worst data was recorded in this report.


-. Duty Cycle

Mode	Tx On Time [ms]	Tx Off Time [ms]	Duty Cycle [%]	Correction Factor [dB]
Sig Fox	240.0	520.0	31.58	5.01

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) * 100

Correction Factor : 10 * Log(1 / (Duty Cycle / 100))

-. Test Plot



5.4 Configuration of Test System

Line Conducted Test: It is not need to test this requirement, because the EUT shall be operated by DC battery.

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The antenna of the EUT is Chip Antenna on the main board in the EUT, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
It is not needed to test, because the power of the EUT is supplied from a DC battery.	

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

7. MAXIMUM PEAK OUTPUT POWER

7.1 Operating environment

Temperature : 24.3 °C
Relative humidity : 43.9 % R.H.

7.2 Test set-up

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For frequency hopping systems operating in the 902-928 MHz band: 1 watt (30 dBm) for systems employing at least 50 hopping channels; and, 0.25 watts (24 dBm) for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.
2. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.
3. The e.i.r.p of this module not exceed 4 W because the antenna gain not exceed not 6 dBi.



7.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 11, 2019 (1Y)

All test equipment used is calibrated on a regular basis.

7.4 Test data


-. Test Date : September 24, 2019 ~ October 15, 2019


-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	MEASURED VLAUE		LIMIT (mW)	MARGIN (dB)
		(dBm)	(mW)		
LOW	902.137 5	22.26	168.27	1 000.00	831.73
MIDDLE	903.387 5	22.23	167.11	1 000.00	832.89
HIGH	904.662 5	22.18	165.20	1 000.00	834.80




Tested by: Hyung-Kwon, Oh / Assistant Manager





Middle Channel



High Channel


8. BAND EDGES

8.1 Operating environment

Temperature : 24.3 °C
Relative humidity : 43.9 % R.H.

8.2 Test set-up

According to §15.247(d) in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.



8.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 11, 2019 (1Y)

All test equipment used is calibrated on a regular basis.

8.4 Test data

-. Test Date : September 24, 2019 ~ October 15, 2019

-. Test Result : Pass

-. Without hopping


CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dB)	LIMIT (dBc)	MARGIN (dB)
LOW	902.137 5	25.22 (22.29+2.93)	20.00	5.22
HIGH	904.662 5	70.24 (22.2+48.04)	20.00	50.24


-. With Hopping

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dB)	LIMIT (dBc)	MARGIN (dB)
LOW	902.1375	22.32 (22.29+0.03)	20.00	2.32
HIGH	904.6625	70.42 (22.29+48.13)	20.00	50.42




Tested by: Hyung-Kwon, Oh / Assistant Manager






Without hopping_High Channel_1



Without hopping_High Channel_2




9. FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (20 dB BANDWIDTH)

9.1 Operating environment

Temperature : 24.3 °C
Relative humidity : 43.9 % R.H.

9.2 Test set-up

According to §15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.



9.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 11, 2019 (1Y)

All test equipment used is calibrated on a regular basis.


9.4 Test data


-. Test Date : September 24, 2019 ~ October 15, 2019

-. Test Result : Pass


Channel Separation (kHz)	20 dB Bandwidth		Limit (kHz)	Result
	Channel	Measured Value (kHz)		
18.48	LOW	1.45	> 25 Or > 20 dB B.W. of Hopping Channel	Pass
	MIDDLE	1.45		
	HIGH	1.45		

Tested by: Hyung-Kwon, Oh / Assistant Manager






Low Channel



Middle Channel




10. NUMBER OF HOPPING FREQUENCY

10.1 Operating environment

Temperature : 24.3 °C
Relative humidity : 43.9 % R.H.

10.2 Test set-up

According to §15.247(a)(1)(i) if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 20-second period. If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 10-second period. The maximum 20 dB bandwidth of the hopping channel shall be 500 kHz..



10.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 11, 2019 (1Y)

All test equipment used is calibrated on a regular basis.

10.4 Test data


-. Test Date : September 24, 2019 ~ October 15, 2019


-. Test Result : Pass

Number of Macro Channels	One Single Macro Channel	Number of Hopping Frequencies	Limit (EA)
9	6	54.00	50.00




Tested by: Hyung-Kwon, Oh / Assistant Manager






One Single Macro Channel_1



One Single Macro Channel_2




11. TIME OF OCCUPANCY(DWELL TIME)

11.1 Operating environment

Temperature : 24.3 °C
Relative humidity : 43.9 % R.H.

11.2 Test set-up

According to §15.247(a)(1)(i) / RSS-247 5.1.3, Frequency hopping systems operating in the 902 MHz ~ 928 MHz bands. if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.



11.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 11, 2019 (1Y)

All test equipment used is calibrated on a regular basis.


11.4 Test data

-. Test Date : September 24, 2019 ~ October 15, 2019


-. Test Result : Pass

	Channel	Measured Value(ms)	Limit(ms)	Result
Pulse Time (ms)	LOW	245.00	400.00	Pass
	MIDDLE	240.00		
	HIGH	240.00		


Tested by: Hyung-Kwon, Oh / Assistant Manager



Low Channel



Middle Channel



High Channel

12. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND


12.1 Operating environment

Temperature : 24.3 °C
Relative humidity : 43.9 % R.H.

12.2 Test set-up for conducted / radiated measurement


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

- Conducted Configuration




- Radiated Configuration


1. Below 30 MHz



2. 30 MHz - 1 GHz



3. Above 1 GHz



12.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 11, 2019 (1Y)
■ - ESU	Rohde & Schwarz	EMI Test Receiver	100261	Mar. 28, 2019 (1Y)
■ - 310N	Sonoma Instrument	Pre-Amplifier	312545	Mar. 18, 2019 (1Y)
■ - BBV9718	Schwarzbeck	Amplifier	310	Mar. 28, 2019 (1Y)
■ - SCU40A	Rohde & Schwarz	Signal Conditioning unit	100436	Mar. 11, 2019 (1Y)
■ - DT3000-3t	Innco System	Turn Table	DT3000/093	N/A
■ - MA-4000XPET	Innco System	Antenna Master	MA4000/509	N/A
■ - VULB9163	Schwarzbeck	TRILOG Broadband Antenna	777	Apr. 13, 2018 (2Y)
■ - BBHA 9120D	Schwarzbeck	Horn Antenna	9120D-1366	Jul. 16, 2019 (1Y)
■ - BBHA 9170	Schwarzbeck	Horn Antenna	BBHA9170179	Jan. 16, 2019 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-003 (Rev.2)

12.4 Test data for conducted emission

-. Test Date : September 24, 2019 ~ October 15, 2019
 -. Resolution bandwidth : 100 kHz
 -. Video bandwidth : 300 kHz
 -. Detector : Peak
 -. Result : PASSED


Channel	Frequency Range	Measured Value(dBm)	Limit(dBm)	Margin(dB)
Low	Fundamental	22.28	2.28	-
	30 M ~ 1 GHz	-47.31	2.28	49.59
	1 GHz ~ 10 GHz	-7.63	2.28	9.91
Middle	Fundamental	22.24	2.24	-
	30 M ~ 1 GHz	-48.30	2.24	50.54
	1 GHz ~ 10 GHz	-7.77	2.24	10.01
High	Fundamental	22.20	2.20	-
	30 M ~ 1 GHz	-45.41	2.20	47.61
	1 GHz ~ 10 GHz	-7.86	2.20	10.06

Tabulated test data for Restricted Band


Remark: "H": Horizontal, "V": Vertical




Tested by: Hyung-Kwon, Oh / Assistant Manager




Low Channel




Middle Channel







Low Channel




Low Channel




Middle Channel



Middle Channel



High Channel



High Channel

12.5 Test data for Transmitting mode radiated emission

12.5.1 Spurious & Harmonic Radiated Emission above 1 GHz

- . Test Date : September 24, 2019 ~ October 15, 2019
- . Resolution bandwidth : 1 MHz for Peak and Average Mode
- . Video bandwidth : 3 MHz for Peak Mode(Peak Detector), 3 MHz for Average Mode(RMS Detector)
- . Frequency range : 1 GHz ~ 10.0 GHz
- . Measurement distance : 3 m
- . Duty Cycle : 31.58 %
- . Result : PASSED


Channel	Frequency (MHz)	Reading (dBuV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Correction Factor (dB)	Total (dBuV/m)	Limits (dBuV/m)	Margin (dB)
Low	1 804.245	40.24	Peak	H	24.90	1.11	-	66.25	68.20	1.95
	1 804.205	40.52	Peak	V	24.90	1.11	-	66.53	68.20	1.67
	2 706.203	28.91	Peak	H	28.00	1.08	-	57.99	74.00	16.01
	2 706.403	17.25	Average	H	28.00	1.08	5.01	51.34	54.00	2.66
	2 708.990	28.85	Peak	V	28.00	1.08	-	57.93	74.00	16.07
	2 706.403	16.91	Average	V	28.00	1.08	5.01	51.00	54.00	3.00
Middle	1 806.755	40.88	Peak	H	24.90	1.11	-	66.89	68.20	1.31
	1 806.855	39.83	Peak	V	24.90	1.11	-	65.84	68.20	2.36
	2 710.093	28.67	Peak	H	28.00	1.08	-	57.75	74.00	16.25
	2 710.163	17.11	Average	H	28.00	1.08	5.01	51.20	54.00	2.80
	2 706.357	28.49	Peak	V	28.00	1.08	-	57.57	74.00	16.43
	2 710.163	16.94	Average	V	28.00	1.08	5.01	51.03	54.00	2.97
High	1 809.335	41.22	Peak	H	24.90	1.11	-	67.23	68.20	0.97
	1 809.315	40.67	Peak	V	24.90	1.11	-	66.68	68.20	1.52
	2 713.848	28.69	Peak	H	28.00	1.08	-	57.77	74.00	16.23
	2 713.988	17.07	Average	H	28.00	1.08	5.01	51.16	54.00	2.84
	2 710.491	28.83	Peak	V	28.00	1.08	-	57.91	74.00	16.09
	2 713.978	16.96	Average	V	28.00	1.08	5.01	51.05	54.00	2.95

Tabulated test data for Restricted Band


Remark: "H": Horizontal, "V": Vertical, "*" Frequency fall in restricted band




Tested by: Hyung-Kwon, Oh / Assistant Manager




Low Channel_H




Low Channel_V




Low Channel_H




Low Channel_V




Middle Channel_H




Middle Channel_V




Middle Channel_H




Middle Channel_V




High Channel_H



High Channel_V



High Channel_H



High Channel_V

13. RADIATED EMISSION TEST

13.1 Operating environment

Temperature : 24 °C
Relative humidity : 43 % R.H.

13.2 Test set-up

The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from 9 kHz to 10.0 GHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

13.3 Test equipment used


	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 11, 2019 (1Y)
■ -	ESU	Rohde & Schwarz	EMI Test Receiver	100261	Mar. 28, 2019 (1Y)
■ -	310N	Sonoma Instrument	Pre-Amplifier	312545	Mar. 18, 2019 (1Y)
■ -	BBV9718	Schwarzbeck	Amplifier	310	Mar. 28, 2019 (1Y)
■	DT3000-3t	Innco System	Turn Table	DT3000/093	N/A
■ -	MA-4000XPET	Innco System	Antenna Master	MA4000/509	N/A
■ -	VULB9163	Schwarzbeck	TRILOG Broadband Antenna	777	Apr. 13, 2018 (2Y)
■ -	BBHA 9120D	Schwarzbeck	Horn Antenna	9120D-1366	Jul. 16, 2019 (1Y)
■ -	BBHA 9170	Schwarzbeck	Horn Antenna	BBHA9170179	Jan. 16, 2019 (1Y)

All test equipment used is calibrated on a regular basis.

13.4 Test data

13.4.1 Test data for 30 MHz ~ 1 000 MHz

- . Test Date : September 24, 2019 ~ October 15, 2019
- . Resolution bandwidth : 120 kHz
- . Frequency range : 30 MHz ~ 1 000 MHz
- . Measurement distance : 3 m



No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA TABLE [cm]	TABLE [DEG]
----- Horizontal -----										
1	81.410	33.6	8.1	2.0	33.0	10.7	40.0	29.3	300	26
2	99.840	26.4	12.5	2.3	33.0	8.2	43.5	35.3	100	231
3	181.320	33.1	9.9	3.1	33.0	13.1	43.5	30.4	400	359
4	207.510	31.4	11.0	3.3	33.0	12.7	43.5	30.8	300	0
5	249.220	28.5	12.6	3.7	32.9	11.9	46.0	34.1	100	0
6	662.436	26.4	19.8	5.9	33.3	18.8	46.0	27.2	300	0
----- Vertical -----										
7	45.520	27.1	14.5	1.5	33.1	10.0	40.0	30.0	100	359
8	381.140	34.3	15.5	4.5	33.0	21.3	46.0	24.7	200	0
9	397.630	43.2	15.8	4.6	33.1	30.5	46.0	15.5	200	165
10	540.220	35.5	18.3	5.4	33.3	25.9	46.0	20.1	200	183
11	756.523	31.1	20.7	6.4	33.2	25.0	46.0	21.0	100	359
12	864.190	33.1	21.9	6.9	32.7	29.2	46.0	16.8	100	359

Tested by: Hyung-Kwon, Oh / Assistant Manager

13.4.2 Test data for Below 30 MHz

- . Test Date : September 24, 2019 ~ October 15, 2019
- . Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)
- . Frequency range : 9 kHz ~ 30 MHz
- . Measurement distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Amp Gain	Emission Level(dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
It was not observed any emissions from the EUT.								

13.4.3 Test data for above 1 GHz

- . Test Date : September 24, 2019 ~ October 15, 2019
- . Resolution bandwidth : 1 MHz for Peak and Average Mode
- . Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode
- . Frequency range : 1 GHz ~ 10.0 GHz
- . Measurement distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Amp Gain	Emission Level(dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
It was not observed any emissions from the EUT.								


 Tested by: Hyung-Kwon, Oh / Assistant Manager