



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20190100008E-03

Applicant: Shenzhen senji technology co., LTD

Address of Applicant: Room 705, Building 2, Zhuguang Innovation and Technology Park, Taoyuan Street, Nanshan District, Shenzhen, China

Manufacturer: Shenzhen senji technology co., LTD

Address of Manufacturer: Room 705, Building 2, Zhuguang Innovation and Technology Park, Taoyuan Street, Nanshan District, Shenzhen, China

Factory: Dongguan Kailai Electronic Co., LTD

Address of Factory: No.36#Industrial Main road, 2nd District, Eastern Industrial Park, Changping Town, Dongguan City, Guangdong Province, China

Equipment Under Test (EUT):

Product: Bluetooth noise-cancelling headphones

Model No.: MU6

Brand Name: N/A

FCC ID: 2ASB2-MU6

Standards: 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2019-01-04 to 2019-01-22

Date of Issue: 2019-01-22

Test Result : PASS*

Tested By:

(Daisy Qin)

Reviewed By:

(Aaron Ma)

Approved By:

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190100008E-03	Rev.01	Initial report	2019-01-22

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT	4
3.4 GENERAL DESCRIPTION OF BLE	4
4 SAR EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 Standard Requirement.....	5
4.1.2 Limits	5
4.1.3 EUT RF Exposure.....	6

3 General Information

3.1 Client Information

Applicant:	Shenzhen senji technology co., LTD
Address of Applicant:	Room 705, Building 2, Zhuguang Innovation and Technology Park, Taoyuan Street, Nanshan District, Shenzhen, China
Manufacturer:	Shenzhen senji technology co., LTD
Address of Manufacturer:	Room 705, Building 2, Zhuguang Innovation and Technology Park, Taoyuan Street, Nanshan District, Shenzhen, China
Factory:	Dongguan Kailai Electronic Co., LTD
Address of Factory:	No.36#Industrial Main road, 2nd District, Eastern Industrial Park, Changping Town, Dongguan City, Guangdong Province, China

3.2 General Description of EUT

Product Name:	Bluetooth noise-cancelling headphones
Model No.:	MU6
Trade Mark:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Bluetooth Version:	V5.0
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Power Supply:	lithium battery:DC3.7V, Charge by DC5.0V

3.3 General Description of BT

Operation Frequency:	2402MHz~2480MHz
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Test Software of EUT:	Blue test 3 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi

3.4 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK
Transfer Rate:	1Mbps/2Mbps
Number of Channel:	40
Test Software of EUT:	Blue test 3 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)	(dBm)	(dBm)
Lowest(2402MHz)	5.570	5.0±1	6.0	3.981
Middle(2441MHz)	6.340	5.5±1	6.5	4.467
Highest(2480MHz)	7.060	6.5±1	7.5	5.623
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)	(dBm)	(dBm)
Lowest(2402MHz)	4.820	4.0±1	5.0	3.162
Middle(2441MHz)	5.980	5.0±1	6.0	3.981
Highest(2480MHz)	6.560	6.0±1	7.0	5.012
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)	(dBm)	(dBm)
Lowest(2402MHz)	5.090	4.5±1	5.5	3.548
Middle(2441MHz)	6.000	5.5±1	6.5	4.467
Highest(2480MHz)	6.590	6.0±1	7.0	5.012

Worst case: GFSK

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	5.570	5.0±1	6.0	3.981	1.23	3.0
Middle (2441MHz)	6.340	5.5±1	6.5	4.467	1.40	
Highest (2480MHz)	7.060	6.5±1	7.5	5.623	1.77	

Conclusion: the calculated value ≤3.0, SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20190100008E-01

2) For BLE
Measurement Data

GFSK(1Mbps) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)		(dBm)
Lowest(2402MHz)	5.38	4.5±1		5.5
Middle(2440MHz)	6.23	5.5±1		6.5
Highest(2480MHz)	6.97	6.0±1		7.0
				5.012

Worst case: GFSK

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	5.38	4.5±1	5.5	3.548	1.10	
Middle (2440MHz)	6.23	5.5±1	6.5	4.467	1.40	
Highest (2480MHz)	6.97	6.0±1	7.0	5.012	1.58	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20190100008E-02

BDR, EDR and BLE can not simultaneous transmitting at same time.